

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Ammonia solution 15 vol. % technical grade 150 ml ammonia solution 25 %/l in methanol

Revision: 01.10.2024

Product code: 10099

Page 1 of 16

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Ammonia solution 15 vol. % technical grade 150 ml ammonia solution 25 %/l in methanol

UFI: 62YV-N0C3-H00U-6QFR

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Reagents and laboratory chemicals

Only for laboratory and analysis purposes.

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name:	AnalytiChem GmbH	
	ACD	
Street:	Stempelstraße 6	
Place:	D-47167 Duisburg	
Telephone:	0203/5194-0	Telefax: 0203/5194-290
E-mail:	info@analytichem.de	
Contact person:	Abteilung Produktsicherheit	Telephone: 0203/5194-107/117
E-mail:	produktsicherheit@analytichem.de	
Internet:	www.analytichem.de	
Responsible Department:	Abteilung Produktsicherheit	

1.4. Emergency telephone number:

For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

Further Information

This product is a mixture. REACH Registration Number see section 3.

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No 1272/2008**

Flam. Liq. 2; H225
Acute Tox. 3; H331
Acute Tox. 3; H311
Acute Tox. 3; H301
Skin Irrit. 2; H315
Eye Dam. 1; H318
STOT SE 1; H370
Aquatic Acute 1; H400
Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements**Regulation (EC) No 1272/2008****Hazard components for labelling**

methanol

Ammonia

according to Regulation (EC) No 1907/2006

Ammonia solution 15 vol. % technical grade 150 ml ammonia solution 25 %/l in methanol

Revision: 01.10.2024

Product code: 10099

Page 2 of 16

Signal word: Danger**Pictograms:****Hazard statements**

H225	Highly flammable liquid and vapour.
H301+H311+H331	Toxic if swallowed, in contact with skin or if inhaled.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H370	Causes damage to organs.
H400	Very toxic to aquatic life.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P311	IF exposed or concerned: Call a POISON CENTER/doctor.

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Relevant ingredients**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
67-56-1	methanol			80 - < 85 %
	200-659-6	603-001-00-X	01-2119433307-44	
	Flam. Liq. 2, Acute Tox. 3, Acute Tox. 3, Acute Tox. 3, STOT SE 1; H225 H331 H311 H301 H370			
1336-21-6	Ammonia			1 - < 5 %
	215-647-6	007-001-01-2	01-2119488876-14	
	Skin Corr. 1B, Aquatic Acute 1, Aquatic Chronic 2; H314 H400 H411			

Full text of H and EUH statements: see section 16.

Ammonia solution 15 vol. % technical grade 150 ml ammonia solution 25 %/l in methanol

Revision: 01.10.2024

Product code: 10099

Page 3 of 16

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
67-56-1	200-659-6	methanol	80 - < 85 %
		inhalation: LC50 = 128,2 mg/l (vapours); inhalation: ATE = 0,5 mg/l (dusts or mists); dermal: ATE = 300 mg/kg; oral: LD50 = 6000 mg/kg STOT SE 1; H370: >= 10 - 100 STOT SE 2; H371: >= 3 - < 10	
1336-21-6	215-647-6	Ammonia	1 - < 5 %
		inhalation: LC50 = 4230 mg/l (vapours); oral: LD50 = 350 mg/kg STOT SE 3; H335: >= 5 - 100 Aquatic Acute 1; H400: M=10	

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

First aider: Pay attention to self-protection!
Remove affected person from the danger area and lay down.

After inhalation

Provide fresh air.
If breathing is irregular or stopped, administer artificial respiration.
Call a physician immediately.

After contact with skin

Wash immediately with: Water
Take off immediately all contaminated clothing and wash it before reuse.
Call a physician immediately.

After contact with eyes

After eye contact: Rinse immediately carefully and thoroughly with eye-bath or water.
Remove contact lenses, if present and easy to do. Continue rinsing.
Consult an ophthalmologist.

After ingestion

Provide fresh air.
Induce vomiting when the affected person is not unconscious.
Call a physician immediately.
Notes for the doctor : Methanol

4.2. Most important symptoms and effects, both acute and delayed

Irritant, Dizziness, Dizziness, Anaesthetic state, Agitation, Spasms, Inebriation, Vomiting, Headache, Impairment of vision
Repeated exposure may cause skin dryness or cracking.

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Water spray jet, Carbon dioxide (CO₂), Foam, Extinguishing powder.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Ammonia solution 15 vol. % technical grade 150 ml ammonia solution 25 %/l in methanol

Revision: 01.10.2024

Product code: 10099

Page 4 of 16

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Combustible liquids

Highly flammable.

Hazardous combustion products

In case of fire may be liberated:

Nitrogen oxides (NO_x)

Carbon dioxide, Carbon monoxide

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Beware of reignition.

Heating causes rise in pressure with risk of bursting.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Wear full chemical protective clothing.

In case of fire and/or explosion do not breathe fumes.

Additional information

Use water spray jet to protect personnel and to cool endangered containers.

Move undamaged containers from immediate hazard area if it can be done safely.

Suppress gases/vapours/mists with water spray jet.

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Keep away from sources of ignition - No smoking.

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

Take action to prevent static discharges.

For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Consult an expert

Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Danger of explosion

Do not allow to enter into surface water or drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Danger of explosion

6.3. Methods and material for containment and cleaning up**For containment**

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Ammonia solution 15 vol. % technical grade 150 ml ammonia solution 25 %/l in methanol

Revision: 01.10.2024

Product code: 10099

Page 5 of 16

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Keep container tightly closed.

Use personal protection equipment. Use extractor hood (laboratory).

Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges.

Vapours can form explosive mixtures with air.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

The choice of body protection depends on the concentration and quantity of hazardous substances. The chemical resistance of protective agents must be clarified with their suppliers.

Further information on handling

Take off immediately all contaminated clothing and wash it before reuse.

Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. If handled uncovered, arrangements with local exhaust ventilation have to be used.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep in a cool, well-ventilated place.

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaust at critical locations. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints on joint storage

Do not store together with: Oxidising agent. Pyrophoric or self-heating substances.
national regulations

Further information on storage conditions

Keep cool. Protect from sunlight.

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Ammonia solution 15 vol. % technical grade 150 ml ammonia solution 25 %/l in methanol

Revision: 01.10.2024

Product code: 10099

Page 6 of 16

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
7664-41-7	Ammonia, anhydrous	20	14		TWA (8 h)	
		50	36		STEL (15 min)	
67-56-1	Methyl alcohol	200	260		TWA (8 h)	

Biological limit values

CAS No	Substance	Parameter	Value	Test material	Sampling time
67-56-1	Methanol	Methanol	15 mg/L	Urine	End of shift

Ammonia solution 15 vol. % technical grade 150 ml ammonia solution 25 %/l in methanol

Revision: 01.10.2024

Product code: 10099

Page 7 of 16

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
67-56-1	methanol			
Consumer DNEL, acute		inhalation	systemic	50 mg/m ³
Worker DNEL, long-term		inhalation	systemic	260 mg/m ³
Worker DNEL, acute		inhalation	systemic	260 mg/m ³
Worker DNEL, long-term		inhalation	local	260 mg/m ³
Worker DNEL, acute		inhalation	local	260 mg/m ³
Worker DNEL, long-term		dermal	systemic	40 mg/kg bw/day
Worker DNEL, acute		dermal	systemic	40 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	50 mg/m ³
Consumer DNEL, long-term		inhalation	local	50 mg/m ³
Consumer DNEL, acute		inhalation	local	50 mg/m ³
Consumer DNEL, long-term		dermal	systemic	8 mg/kg bw/day
Consumer DNEL, acute		dermal	systemic	8 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	8 mg/kg bw/day
Consumer DNEL, acute		oral	systemic	8 mg/kg bw/day
1336-21-6	Ammonia			
Worker DNEL, long-term		inhalation	systemic	47,6 mg/m ³
Worker DNEL, acute		inhalation	systemic	47,6 mg/m ³
Worker DNEL, long-term		inhalation	local	14 mg/m ³
Worker DNEL, acute		inhalation	local	36 mg/m ³
Worker DNEL, long-term		dermal	systemic	6,8 mg/kg bw/day
Worker DNEL, acute		dermal	systemic	6,8 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	23,8 mg/m ³
Consumer DNEL, acute		inhalation	systemic	23,8 mg/m ³
Consumer DNEL, long-term		inhalation	local	2,8 mg/m ³
Consumer DNEL, acute		inhalation	local	7,2 mg/m ³
Consumer DNEL, long-term		dermal	systemic	68 mg/kg bw/day
Consumer DNEL, acute		dermal	systemic	68 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	6,8 mg/kg bw/day
Consumer DNEL, acute		oral	systemic	6,8 mg/kg bw/day

Ammonia solution 15 vol. % technical grade 150 ml ammonia solution 25 %/l in methanol

Revision: 01.10.2024

Product code: 10099

Page 8 of 16

PNEC values

CAS No	Substance	
Environmental compartment		Value
67-56-1	methanol	
Freshwater		20,8 mg/l
Freshwater (intermittent releases)		1540 mg/l
Marine water		2,08 mg/l
Freshwater sediment		77 mg/kg
Marine sediment		7,7 mg/kg
Micro-organisms in sewage treatment plants (STP)		100 mg/l
Soil		100 mg/kg
1336-21-6	Ammonia	
Freshwater		0,001 mg/l
Freshwater (intermittent releases)		0,007 mg/l
Marine water		0,001 mg/l

8.2. Exposure controls**Appropriate engineering controls**

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Do not breathe gas/fumes/vapour/spray.

Individual protection measures, such as personal protective equipment**Eye/face protection**

goggles

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact

Trade name/designation KCL 897 Butoject®

Suitable material: Butyl caoutchouc (butyl rubber) 0,3 mm

Wearing time with permanent contact: > 480 min

By short-term hand contact

Trade name/designation KCL 890 Vitoject®

Suitable material: FKM (fluoro rubber) 0,7 mm

Wearing time with occasional contact (splashes): > 120 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Ammonia solution 15 vol. % technical grade 150 ml ammonia solution 25 %/l in methanol

Revision: 01.10.2024

Product code: 10099

Page 9 of 16

sheet<(,>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing
Take off immediately all contaminated clothing and wash it before reuse.
Wear fire resistant or flame retardant clothing.
Wash hands and face before breaks and after work and take a shower if necessary.
Draw up and observe skin protection programme.

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.
The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Environmental exposure controls

Do not allow to enter into surface water or drains.
Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.
Danger of explosion

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid	
Colour:	colourless	
Odour:	characteristic	
Melting point/freezing point:		No data available
Boiling point or initial boiling point and boiling range:		>35 °C
Flammability:		not applicable
Lower explosion limits:		No data available
Upper explosion limits:		No data available
Flash point:		<21 °C
Auto-ignition temperature:		No data available
Decomposition temperature:		not determined
pH-Value:		alkaline
Viscosity / kinematic:		not determined
Solubility in other solvents		
not determined		
Partition coefficient n-octanol/water:		not determined
Vapour pressure:		No data available
Vapour pressure:		No data available
Density:		0,8229 g/cm ³
Bulk density:		No data available
Relative vapour density:		not determined

9.2. Other information**Information with regard to physical hazard classes****Explosive properties**

Vapours can form explosive mixtures with air.

Sustained combustibility:**Sustained combustibility****Self-ignition temperature****Solid:**

not applicable

Gas:

not applicable

Ammonia solution 15 vol. % technical grade 150 ml ammonia solution 25 %/l in methanol

Revision: 01.10.2024

Product code: 10099

Page 10 of 16

Oxidizing properties
not determined

Other safety characteristics

Evaporation rate:	not determined
Solvent separation test:	not determined
Solvent content:	83,15
Solid content:	not determined
Sublimation point:	No data available
Softening point:	No data available
Pour point:	No data available
No data available:	
Viscosity / dynamic:	No data available
Flow time:	not determined

Further Information

not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable.
Vapours can form explosive mixtures with air.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Oxidising agent
Risk of explosion with: Oxidizing agents, perchloric acid, perchlorates, salts of oxyhalogenic acids, chromium(VI) oxide, halogen oxides, nitrogen oxides, nonmetallic oxides, chromosulfuric acid, chlorates, hydrides, zinc diethyl, halogens, powdered magnesium, hydrogen peroxide, Nitric acid, sulphuric acid, permanganic acid, sodium hypochlorite Exothermic reaction with: acid halides, Acid anhydrides, Reducing agents, acids, Bromine, Chlorine, Chloroform, magnesium, tetrachloromethane, CYANURIC CHLORIDE Risk of ignition or formation of inflammable gases or vapours with: Fluorine, Oxides of phosphorus, Raney-nickel Generates dangerous gases or fumes in contact with: Alkaline earth metals, Alkali metals

10.4. Conditions to avoid

Vapours can form explosive mixtures with air.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

various plastics
various metals, metal alloys

10.6. Hazardous decomposition products

SECTION 5: Firefighting measures

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicokinetics, metabolism and distribution

There are no data available on the mixture itself.

Ammonia solution 15 vol. % technical grade 150 ml ammonia solution 25 %/l in methanol

Revision: 01.10.2024

Product code: 10099

Page 11 of 16

Acute toxicity

Toxic if inhaled.
Toxic in contact with skin.
Toxic if swallowed.

ATEmix calculated

ATE (oral) 120,3 mg/kg; ATE (dermal) 360,8 mg/kg; ATE (inhalation vapour) 3,610 mg/l; ATE (inhalation dust/mist) 0,6010 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
67-56-1	methanol				
	oral	LD50 6000 mg/kg	Monkey	Amer J Ophthalmol 40: 76-83 (cited in DG	Determination of the acute toxicity of t
	dermal	ATE 300 mg/kg			
	inhalation (4 h) vapour	LC50 128,2 mg/l	Rat	Study report (1980)	Study performed according to internal co
	inhalation dust/mist	ATE 0,5 mg/l			
1336-21-6	Ammonia				
	oral	LD50 350 mg/kg	Rat	Journal of Industrial Hygiene and Toxicol	OECD Guideline 401
	inhalation (1 h) vapour	LC50 4230 mg/l	Mouse	Bull. Environm. Contam. Toxicol, 1982, 2	Assessment of acute inhalation toxicity

Irritation and corrosivity

Skin corrosion/irritation: Causes skin irritation.
Serious eye damage/eye irritation: Causes serious eye damage.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.
Carcinogenicity: Based on available data, the classification criteria are not met.
Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Causes damage to organs. (methanol)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

There are no data available on the mixture itself.

Specific effects in experiment on an animal

There are no data available on the mixture itself.

Additional information on tests

There are no data available on the mixture itself.

Practical experience

There are no data available on the mixture itself.

Ammonia solution 15 vol. % technical grade 150 ml ammonia solution 25 %/l in methanol

Revision: 01.10.2024

Product code: 10099

Page 12 of 16

11.2. Information on other hazards**Endocrine disrupting properties**

There are no data available on the mixture itself.

Other information

Irritation to respiratory tract

Repeated exposure may cause skin dryness or cracking.

Causes damage to organs. Organs affected:

Liver and kidney damage, , Irreversible damage to the optic nerve.

see also Section 4

Further information

The substance has delayed effects.

Other dangerous properties cannot be excluded.

SECTION 12: Ecological information**12.1. Toxicity**

Very toxic to aquatic life.

Harmful to aquatic life with long lasting effects.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
67-56-1	methanol					
	Acute fish toxicity	LC50 15400 mg/l	96 h	Lepomis macrochirus	Bulletin of Environmental Contamination	other: EPA-660/3-75-009, 1975
	Acute algae toxicity	ErC50 ca. 22000 mg/l	96 h	Pseudokirchneriella subcapitata	Ecotoxicology and Environmental Safety 7	OECD Guideline 201
	Acute crustacea toxicity	EC50 > 10000 mg/l	48 h	Daphnia magna	Water Research 23(4): 495-499 (1989)	other: DIN 38412 Teil 11
	Fish toxicity	NOEC 446,7 mg/l	28 d	Pimephales promelas	SAR and QSAR in Environmental Research,	Calculation performed with ECOSAR
	Crustacea toxicity	NOEC 208 mg/l	21 d	Daphnia magna	OECD QSAR Toolbox Report (2013)	Toxicity of the target chemical is predi
1336-21-6	Ammonia					
	Acute fish toxicity	LC50 0,75 - 3,4 mg/l	96 h	Pimephales promelas	Trans Amer Fish Soc; 112 (5). 1983. 705-	Assessment of acute toxicity in the fath
	Acute crustacea toxicity	EC50 101 mg/l	48 h	Daphnia magna	Environ. Toxicol. Chem. 5: 443-447 (1986)	other: ASTM E729-80
	Fish toxicity	NOEC 1,2 mg/l	61 d	Oncorhynchus gorbuscha	Fish. Bull. 78(3): 641-648 (1980)	OECD Guideline 210

12.2. Persistence and degradability

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Ammonia solution 15 vol. % technical grade 150 ml ammonia solution 25 %/l in methanol

Revision: 01.10.2024

Product code: 10099

Page 13 of 16

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
67-56-1	methanol	-0,77
1336-21-6	Ammonia	-1,38

BCF

CAS No	Chemical name	BCF	Species	Source
67-56-1	methanol	1	Cyprinus carpio	Comparative Biochemi

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

There are no data available on the mixture itself.

Further information

Do not allow to enter into surface water or drains.
Avoid release to the environment.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.
Send to a physico-chemical treatment facility under observation of official regulations .
Do not allow to enter into surface water or drains.

Contaminated packaging

This material and its container must be disposed of as hazardous waste.
Handle contaminated packages in the same way as the substance itself.
The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number or ID number:	UN 1992
14.2. UN proper shipping name:	FLAMMABLE LIQUID, TOXIC, N.O.S. (methanol, Ammonia)
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3+6.1
Classification code:	FT1
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	336
Tunnel restriction code:	D/E

Inland waterways transport (ADN)

14.1. UN number or ID number:	UN 1992
--------------------------------------	---------

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Ammonia solution 15 vol. % technical grade 150 ml ammonia solution 25 %/l in methanol

Revision: 01.10.2024

Product code: 10099

Page 14 of 16

14.2. UN proper shipping name:	FLAMMABLE LIQUID, TOXIC, N.O.S. (methanol, Ammonia)
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3+6.1
Classification code:	FT1
Special Provisions:	274 802
Limited quantity:	1 L
Excepted quantity:	E2

Marine transport (IMDG)

14.1. UN number or ID number:	UN 1992
14.2. UN proper shipping name:	FLAMMABLE LIQUID, TOXIC, N.O.S. (methanol, Ammonia)
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3+6.1
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2
EmS:	F-E, S-D

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:	UN 1992
14.2. UN proper shipping name:	FLAMMABLE LIQUID, TOXIC, N.O.S. (methanol, Ammonia)
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3+6.1
Special Provisions:	A3
Limited quantity Passenger:	1 L
Passenger LQ:	Y341
Excepted quantity:	E2
IATA-packing instructions - Passenger:	352
IATA-max. quantity - Passenger:	1 L
IATA-packing instructions - Cargo:	364
IATA-max. quantity - Cargo:	60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS:	Yes
Danger releasing substance:	Ammonia

14.6. Special precautions for user

Warning: Combustible liquid. Toxic.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 69

Information according to Directive 2012/18/EU (SEVESO III): H2 ACUTE TOXIC

Additional information: P5c, E1

National regulatory information

according to Regulation (EC) No 1907/2006

Ammonia solution 15 vol. % technical grade 150 ml ammonia solution 25 %/l in methanol

Revision: 01.10.2024

Product code: 10099

Page 15 of 16

Employment restrictions:	Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.
Water hazard class (D):	2 - obviously hazardous to water
Skin resorption/Sensitization:	Permeates easily through outer skin and causes poisoning.

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 1,2,7,8,9,11,12,15.

Abbreviations and acronyms

Flam. Liq. 2: Flammable liquids, hazard category 2
Acute Tox. 3: Acute toxicity, hazard category 3
Skin Corr. 1B: Skin corrosion, sub-category 1B
Skin Irrit. 2: Skin irritation, hazard category 2
Eye Dam. 1: Serious eye damage, hazard category 1
STOT SE 1: Specific target organ toxicity - single exposure, hazard category 1
Aquatic Acute 1: Hazardous to the aquatic environment, hazard category: Acute 1
Aquatic Chronic 2: Hazardous to the aquatic environment, long-term hazard category: Chronic 2
ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service
LC50: Lethal concentration, 50%
LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Acute Tox. 3; H331	Calculation method
Acute Tox. 3; H311	Calculation method
Acute Tox. 3; H301	Calculation method
Skin Irrit. 2; H315	Calculation method
Eye Dam. 1; H318	Calculation method
STOT SE 1; H370	Calculation method
Aquatic Acute 1; H400	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H301	Toxic if swallowed.
H301+H311+H331	Toxic if swallowed, in contact with skin or if inhaled.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Ammonia solution 15 vol. % technical grade 150 ml ammonia solution 25 %/l in methanol

Revision: 01.10.2024

Product code: 10099

Page 16 of 16

H318	Causes serious eye damage.
H331	Toxic if inhaled.
H370	Causes damage to organs (eyes, central nervous system).
H370	Causes damage to organs.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Further Information

Provide appropriate information, instructions and training to users

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)