

according to Regulation (EC) No 1907/2006

Pt/Co standard reference solution color index (Hazen) 500 Hazen color standard according to EN ISO 6

Revision: 01.09.2025

Product code: 13389

Page 1 of 14

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Pt/Co standard reference solution color index (Hazen) 500 Hazen color standard according to EN ISO 6

UFI: 7H26-U165-7000-GUN0

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Reagents and laboratory chemicals
Only for laboratory and analysis purposes.

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name:	AnalytiChem GmbH	
	ACD	
Street:	Stempelstraße 6	
Place:	D-47167 Duisburg	
Telephone:	0203/5194-0	Telefax: 0203/5194-290
E-mail:	info@analytichem.de	
Contact person:	Abteilung Produktsicherheit	Telephone: 0203/5194-107/117
E-mail:	produktsicherheit@analytichem.de	
Internet:	www.analytichem.de	
Responsible Department:	Abteilung Produktsicherheit	

1.4. Emergency telephone number:

For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

Further Information

This product is a mixture. REACH Registration Number see section 3.

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No 1272/2008**

Met. Corr. 1; H290
Carc. 1B; H350i

Full text of hazard statements: see SECTION 16.

2.2. Label elements**Regulation (EC) No 1272/2008****Hazard components for labelling**

Cobalt(II) chloride hexahydrate

Signal word: Danger

Pictograms:

according to Regulation (EC) No 1907/2006

Pt/Co standard reference solution color index (Hazen) 500 Hazen color standard according to EN ISO 6

Revision: 01.09.2025

Product code: 13389

Page 2 of 14

Hazard statements

H290 May be corrosive to metals.
H350i May cause cancer by inhalation.

Precautionary statements

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P390 Absorb spillage to prevent material damage.
P405 Store locked up.

Special labelling of certain mixtures

EUH208 Contains dipotassium hexachloroplatinate. May produce an allergic reaction.
Restricted to professional users.

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Chemical characterization**

Mixtures in aqueous solution

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
7647-01-0	Hydrochloric acid			1 - < 5 %
	231-595-7	017-002-01-X	01-2119484862-27	
	Met. Corr. 1, Skin Corr. 1B, Eye Dam. 1, STOT SE 3; H290 H314 H318 H335			
16921-30-5	dipotassium hexachloroplatinate			< 1 %
	240-979-3	078-007-00-3		
	Acute Tox. 3, Eye Dam. 1, Resp. Sens. 1, Skin Sens. 1; H301 H318 H334 H317			
7791-13-1	Cobalt(II) chloride hexahydrate			< 0.1 %
	231-589-4	027-004-00-5	01-2119517584-37	
	Carc. 1B, Muta. 2, Repr. 1B, Acute Tox. 4, Resp. Sens. 1, Skin Sens. 1, Aquatic Acute 1, Aquatic Chronic 1; H350i H341 H360F H302 H334 H317 H400 H410			

Full text of H and EUH statements: see section 16.

Pt/Co standard reference solution color index (Hazen) 500 Hazen color standard according to EN ISO 6

Revision: 01.09.2025

Product code: 13389

Page 3 of 14

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
7647-01-0	231-595-7	Hydrochloric acid	1 - < 5 %
		Skin Corr. 1B; H314: >= 25 - 100 Skin Irrit. 2; H315: >= 10 - < 25 Eye Irrit. 2; H319: >= 10 - < 25 STOT SE 3; H335: >= 10 - 100	
16921-30-5	240-979-3	dipotassium hexachloroplatinate	< 1 %
		oral: LD50 = 195 mg/kg	
7791-13-1	231-589-4	Cobalt(II) chloride hexahydrate	< 0.1 %
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = 537 mg/kg Carc. 1B; H350i: >= 0,01 - 100 Aquatic Acute 1; H400: M=10 Aquatic Chronic 1; H410: M=10	

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

Self-protection of the first aider

After inhalation

Provide fresh air.

Call a physician immediately.

After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

Call a physician immediately.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Rinse mouth immediately and drink plenty of water.

Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Irritant

Allergic reactions

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

no restriction

Pt/Co standard reference solution color index (Hazen) 500 Hazen color standard according to EN ISO 6

Revision: 01.09.2025

Product code: 13389

Page 4 of 14

5.2. Special hazards arising from the substance or mixture

Non-combustible liquids
Hazardous combustion products
In case of fire may be liberated:
Hydrochloric gas
Metal oxide smoke, toxic

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.
Avoid contact with skin, eyes and clothes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.
Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Corrosive to metals.

For non-emergency personnel

Provide adequate ventilation.
Use personal protection equipment.
Avoid contact with skin, eyes and clothes.
Remove persons to safety.
Emergency procedures
Consult an expert
Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up**For containment**

Cover drains.
Prevent spread over a wide area (e.g. by containment or oil barriers).
Collect in closed and suitable containers for disposal.
Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.
Do not breathe dust/fume/gas/mist/vapours/spray.
Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7
Personal protection equipment: see section 8
Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Pt/Co standard reference solution color index (Hazen) 500 Hazen color standard according to EN ISO 6

Revision: 01.09.2025

Product code: 13389

Page 5 of 14

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used.
Read label before use. Handle and open container with care.
When using do not eat, drink, smoke, sniff. Keep container tightly closed.
Use personal protection equipment. Use extractor hood (laboratory).
Provide adequate ventilation.
Avoid contact with skin, eyes and clothes.

Advice on protection against fire and explosion

Usual measures for fire prevention.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.
The choice of body protection depends on the concentration and quantity of hazardous substances. The chemical resistance of protective agents must be clarified with their suppliers.

Further information on handling

Draw up and observe skin protection programme.
Wash hands and face before breaks and after work and take a shower if necessary.
Take off immediately all contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed.
Store in a place accessible by authorized persons only.

Hints on joint storage

national regulations

Further information on storage conditions

Unsuitable container/equipment material: Metal

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational exposure limits**

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
7647-01-0	Hydrogen chloride	5	8		TWA (8 h)	
		10	15		STEL (15 min)	

Pt/Co standard reference solution color index (Hazen) 500 Hazen color standard according to EN ISO 6

Revision: 01.09.2025

Product code: 13389

Page 6 of 14

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
7647-01-0	Hydrochloric acid			
Worker DNEL, long-term		inhalation	local	8 mg/m³
Worker DNEL, acute		inhalation	local	15 mg/m³
Consumer DNEL, long-term		inhalation	local	8 mg/m³
Consumer DNEL, acute		inhalation	local	15 mg/m³
7791-13-1	Cobalt(II) chloride hexahydrate			
Consumer DNEL, long-term		oral	systemic	0,12 mg/kg bw/dav

PNEC values

CAS No	Substance		
Environmental compartment	Value		
16921-30-5	dipotassium hexachloroplatinate		
Freshwater	0,00014 mg/l		
Freshwater (intermittent releases)	0,000205 mg/l		
Marine water	0,000017 mg/l		
Freshwater sediment	0,261 mg/kg		
Marine sediment	0,026 mg/kg		
Micro-organisms in sewage treatment plants (STP)	0,125 mg/l		
Soil	0,005 mg/kg		
7791-13-1	Cobalt(II) chloride hexahydrate		
Freshwater	0,0006 mg/l		
Marine water	0,00236 mg/l		
Freshwater sediment	9,5 mg/kg		
Marine sediment	9,5 mg/kg		
Micro-organisms in sewage treatment plants (STP)	0,37 mg/l		
Soil	10,9 mg/kg		

8.2. Exposure controls**Appropriate engineering controls**

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Suitable eye protection:
Face protection shield
goggles.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Pt/Co standard reference solution color index (Hazen) 500 Hazen color standard according to EN ISO 6

Revision: 01.09.2025

Product code: 13389

Page 7 of 14

recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact

Recommended glove articles: KCL 741 Dermatril® L

Recommended material: NBR (Nitrile rubber) 0,11 mm

Wearing time with permanent contact: > 480 min

By short-term hand contact

Recommended glove articles: KCL 741 Dermatril® L

Recommended material: NBR (Nitrile rubber) 0,11 mm

Wearing time with occasional contact (splashes): > 480 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Wear suitable protective clothing.

Protective clothing acid-resistant

Respiratory protection

Respiratory protection necessary at: aerosol or mist formation

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid	
Colour:	colourless	
Odour:	odourless	
Melting point/freezing point:		No data available
Boiling point or initial boiling point and boiling range:		No data available
Flammability:		not applicable
Lower explosion limits:		No data available
Upper explosion limits:		No data available
Flash point:		X
Auto-ignition temperature:		No data available
Decomposition temperature:		No data available
pH-Value:		acidic
Viscosity / kinematic:		No data available
Water solubility:		No data available

Pt/Co standard reference solution color index (Hazen) 500 Hazen color standard according to EN ISO 6

Revision: 01.09.2025

Product code: 13389

Page 8 of 14

Solubility in other solvents

not determined

Partition coefficient n-octanol/water:

No data available

Vapour pressure:

No data available

Vapour pressure:

No data available

Density (at 20 °C):

1,0198 g/cm³

Bulk density:

No data available

Relative vapour density:

No data available

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

No data available

Self-ignition temperature

Solid:

not applicable

Gas:

not applicable

Oxidizing properties

No data available

Other safety characteristics

Evaporation rate:

No data available

Solvent separation test:

No data available

Solvent content:

No data available

Solid content:

No data available

Sublimation point:

No data available

Softening point:

No data available

Pour point:

No data available

No data available:

Viscosity / dynamic:

No data available

Flow time:

No data available

Further Information

Corrosive to metals

SECTION 10: Stability and reactivity

10.1. Reactivity

Corrosive to metals.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

The product develops hydrogen in an aqueous solution in contact with metals.

10.4. Conditions to avoid

Heat

10.5. Incompatible materials

Keep away from: Metal.

The product develops hydrogen in an aqueous solution in contact with metals.

10.6. Hazardous decomposition products

In case of fire may be liberated:

SECTION 5: Firefighting measures

Pt/Co standard reference solution color index (Hazen) 500 Hazen color standard according to EN ISO 6

Revision: 01.09.2025

Product code: 13389

Page 9 of 14

Further information

No data available

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008****Toxicokinetics, metabolism and distribution**

There are no data available on the mixture itself.

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
16921-30-5	dipotassium hexachloroplatinate				
	oral	LD50 195 mg/kg	Rat	Study report (1995)	OECD Guideline 401
7791-13-1	Cobalt(II) chloride hexahydrate				
	oral	LD50 537 mg/kg	Rat	Revista Española de Fisiología, 39: 291	OECD Guideline 401
	dermal	LD50 > 2000 mg/kg	Rat	Study report (2007)	OECD Guideline 402

Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.
slightly irritant but not relevant for classification.**Sensitising effects**

Based on available data, the classification criteria are not met.

Contains dipotassium hexachloroplatinate. May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

May cause cancer by inhalation. (Cobalt(II) chloride hexahydrate)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

There are no data available on the mixture itself.

Additional information on tests

There are no data available on the mixture itself.

Practical experience

There are no data available on the mixture itself.

Pt/Co standard reference solution color index (Hazen) 500 Hazen color standard according to EN ISO 6

Revision: 01.09.2025

Product code: 13389

Page 10 of 14

11.2. Information on other hazards**Other information**

There are no data available on the mixture itself.

Further information

Irritant

SECTION 12: Ecological information**12.1. Toxicity**

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
7647-01-0	Hydrochloric acid					
	Acute fish toxicity	LC50 862 mg/l	96 h	Leuciscus idus		
16921-30-5	dipotassium hexachloroplatinate					
	Acute fish toxicity	LC50 76,55 mg/l	96 h	Oncorhynchus mykiss	Study report (2005)	OECD Guideline 203
	Acute algae toxicity	ErC50 1,3 mg/l	72 h	Desmodesmus subspicatus	Study report (2001)	OECD Guideline 201
	Acute crustacea toxicity	EC50 0,0608 mg/l	48 h	Daphnia magna	Study report (2005)	OECD Guideline 202
	Crustacea toxicity	NOEC 0,007 mg/l	21 d	Daphnia magna	J. Fish. Res. Bd. Canada 29: 1691-1700 (A standard guideline was not followed, b
	Acute bacteria toxicity	EC50 103 mg/l ()	3 h	activated sludge of a predominantly domestic sewage	Study report (2015)	OECD Guideline 209
7791-13-1	Cobalt(II) chloride hexahydrate					
	Acute fish toxicity	LC50 54,1 mg/l	96 h	Pimephales promelas	Study report (2009)	other: ASTM guideline
	Acute algae toxicity	ErC50 71,314 mg/l	96 h	Dunaliella tertiolecta	Study report (2010)	other: American Society for Testing and
	Acute crustacea toxicity	EC50 42,7 mg/l	48 h	Aeolosoma sp.	Study report (2008)	Newman, J.P., Jr. 1975. The effects of h
	Fish toxicity	NOEC 0,21 mg/l	34 d	Pimephales promelas	Study report (2009)	other: This study was conducted accordin
	Algae toxicity	NOEC 0,0018 mg/l	7 d	Champia parvula	Study report - model refit from original	other: EPA 821-R-02-014, Method 1009.0
	Crustacea toxicity	NOEC 0,1697 mg/l	14 d	Aeolosoma sp.	Study report (2008)	other: Newman, J.P., Jr. 1975. The effec
	Acute bacteria toxicity	EC50 120 mg/l ()	0,5 h	Activated sludge	Study report (2010)	OECD Guideline 209

12.2. Persistence and degradability

Pt/Co standard reference solution color index (Hazen) 500 Hazen color standard according to EN ISO 6

Revision: 01.09.2025

Product code: 13389

Page 11 of 14

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

BCF

CAS No	Chemical name	BCF	Species	Source
7791-13-1	Cobalt(II) chloride hexahydrate	23	Asterias rubens	Marine Pollution Bul

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Discharge into the environment must be avoided.

Harmful effect due to pH shift.

Forms corrosive mixtures with water even if diluted.

Further information

Do not empty into drains.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations.

Do not empty into drains.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number or ID number:	UN 1789
14.2. UN proper shipping name:	HYDROCHLORIC ACID
14.3. Transport hazard class(es):	8
14.4. Packing group:	III
Hazard label:	8
Classification code:	C1
Special Provisions:	520
Limited quantity:	5 L
Excepted quantity:	E1
Transport category:	3
Hazard No:	80
Tunnel restriction code:	E

Inland waterways transport (ADN)

14.1. UN number or ID number:	UN 1789
--------------------------------------	---------

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Pt/Co standard reference solution color index (Hazen) 500 Hazen color standard according to EN ISO 6

Revision: 01.09.2025

Product code: 13389

Page 12 of 14

14.2. UN proper shipping name:	HYDROCHLORIC ACID
14.3. Transport hazard class(es):	8
14.4. Packing group:	III
Hazard label:	8
Classification code:	C1
Special Provisions:	520
Limited quantity:	5 L
Excepted quantity:	E1

Marine transport (IMDG)

14.1. UN number or ID number:	UN 1789
14.2. UN proper shipping name:	HYDROCHLORIC ACID
14.3. Transport hazard class(es):	8
14.4. Packing group:	III
Hazard label:	8
Special Provisions:	223
Limited quantity:	5 L
Excepted quantity:	E1
EmS:	F-A, S-B

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:	UN 1789
14.2. UN proper shipping name:	HYDROCHLORIC ACID
14.3. Transport hazard class(es):	8
14.4. Packing group:	III
Hazard label:	8
Special Provisions:	A3 A803
Limited quantity Passenger:	1 L
Passenger LQ:	Y841
Excepted quantity:	E1
IATA-packing instructions - Passenger:	852
IATA-max. quantity - Passenger:	5 L
IATA-packing instructions - Cargo:	856
IATA-max. quantity - Cargo:	60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Authorisations (REACH, annex XIV):

Substances of very high concern, SVHC (REACH, article 59):

Cobalt(II) chloride hexahydrate

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 75

Information according to Directive 2012/18/EU (SEVESO III): Not subject to 2012/18/EU (SEVESO III)

National regulatory information

according to Regulation (EC) No 1907/2006

Pt/Co standard reference solution color index (Hazen) 500 Hazen color standard according to EN ISO 6

Revision: 01.09.2025

Product code: 13389

Page 13 of 14

Employment restrictions:	Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe employment restrictions for women of child-bearing age.
Water hazard class (D):	2 - obviously hazardous to water

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 1,9,12.

Abbreviations and acronyms

Met. Corr. 1: Corrosive to metals, hazard category 1
Acute Tox. 3: Acute toxicity, hazard category 3
Skin Corr. 1B: Skin corrosion, sub-category 1B
Eye Dam. 1: Serious eye damage, hazard category 1
Resp. Sens. 1: Respiratory sensitisation, hazard category 1
Skin Sens. 1: Skin sensitisation, hazard category 1
Muta. 2: Germ cell mutagenicity, hazard category 2
Carc. 1B: Carcinogenicity, hazard category 1B
Repr. 1B: Reproductive toxicity, hazard category 1B
STOT SE 3: Specific target organ toxicity - single exposure, hazard category 3
Aquatic Acute 1: Hazardous to the aquatic environment, hazard category: Acute 1
Aquatic Chronic 1: Hazardous to the aquatic environment, long-term hazard category: Chronic 1
ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service
LC50: Lethal concentration, 50%
LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Met. Corr. 1; H290	On basis of test data
Carc. 1B; H350i	Calculation method

Relevant H and EUH statements (number and full text)

H290	May be corrosive to metals.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H341	Suspected of causing genetic defects.
H350i	May cause cancer by inhalation.
H360F	May damage fertility.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Pt/Co standard reference solution color index (Hazen) 500 Hazen color standard according to EN ISO 6

Revision: 01.09.2025

Product code: 13389

Page 14 of 14

H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
EUH208	Contains dipotassium hexachloroplatinate. May produce an allergic reaction.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Provide appropriate information, instructions and training to users

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)