

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Buffer solution pH 10.7 67.5 g NH₄Cl + 570 ml NH₃ solution 25 %/l for complexometric titration

Revision: 07.10.2024

Product code: 17251

Page 1 of 14

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**Buffer solution pH 10.7 67.5 g NH₄Cl + 570 ml NH₃ solution 25 %/l for complexometric titration

UFI: 83SH-H1U9-3008-5845

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Reagents and laboratory chemicals

Only for laboratory and analysis purposes.

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name: AnalytiChem GmbH

ACD

Street: Stempelstraße 6

Place: D-47167 Duisburg

Telephone: 0203/5194-0

Telefax: 0203/5194-290

E-mail: info@analytichem.de

Contact person: Abteilung Produktsicherheit

Telephone: 0203/5194-107/117

E-mail: produktsicherheit@analytichem.de

Internet: www.analytichem.de

Responsible Department: Abteilung Produktsicherheit

1.4. Emergency telephone number:

For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

Further Information

This product is a mixture. REACH Registration Number see section 3.

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No 1272/2008**

Skin Corr. 1B; H314

Eye Dam. 1; H318

STOT SE 3; H335

Aquatic Acute 1; H400

Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements**Regulation (EC) No 1272/2008****Hazard components for labelling**

Ammonia

Signal word: Danger

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Buffer solution pH 10.7 67.5 g NH₄Cl + 570 ml NH₃ solution 25 %/l for complexometric titration

Revision: 07.10.2024

Product code: 17251

Page 2 of 14

Pictograms:



Hazard statements

H314	Causes severe skin burns and eye damage.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P273	Avoid release to the environment.
P280	Wear protective gloves and eye protection/face protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients**3.2. Mixtures**

Chemical characterization

Mixtures in aqueous solution

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
1336-21-6	Ammonia			10 - < 15 %
	215-647-6	007-001-01-2	01-2119488876-14	
	Skin Corr. 1B, Aquatic Acute 1, Aquatic Chronic 2; H314 H400 H411			
12125-02-9	ammonium chloride			5 - < 10 %
	235-186-4	017-014-00-8	01-2119487950-27	
	Acute Tox. 4, Eye Irrit. 2; H302 H319			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
1336-21-6	215-647-6	Ammonia	10 - < 15 %
	inhalation: LC50 = 4230 mg/l (vapours); oral: LD50 = 350 mg/kg STOT SE 3; H335: >= 5 - 100 Aquatic Acute 1; H400: M=10		
12125-02-9	235-186-4	ammonium chloride	5 - < 10 %
	dermal: LD50 = > 2000 mg/kg; oral: LD50 = 1410 mg/kg		

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Buffer solution pH 10.7 67.5 g NH₄Cl + 570 ml NH₃ solution 25 %/l for complexometric titration

Revision: 07.10.2024

Product code: 17251

Page 3 of 14

(REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

Self-protection of the first aider
Avoid contact with skin, eyes and clothes.
Take off immediately all contaminated clothing.

After inhalation

Provide fresh air.
Call a physician immediately.

After contact with skin

Wash immediately with: Water
Take off immediately all contaminated clothing and wash it before reuse.
Call a physician immediately.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.
Remove contact lenses, if present and easy to do. Continue rinsing.
Protect uninjured eye.

After ingestion

Rinse mouth immediately and drink plenty of water.
Do NOT induce vomiting.
Do not allow a neutralisation agent to be drunk.
Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Irritant
Corrosion
Cough
Dyspnoea
Gastrointestinal complaints
gastric perforation
Unconsciousness
Vomiting
Circulatory collapse
Spasms
Pulmonary oedema
Risk of serious damage to eyes.

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

no restriction

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Buffer solution pH 10.7 67.5 g NH₄Cl + 570 ml NH₃ solution 25 %/l for complexometric titration

Revision: 07.10.2024

Product code: 17251

Page 4 of 14

5.2. Special hazards arising from the substance or mixture

Non-combustible liquids
Formation of explosive mixtures with: Air
Hazardous combustion products
In case of fire may be liberated:
Nitrogen oxides (NO_x)

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.
In case of fire and/or explosion do not breathe fumes.
Avoid contact with skin, eyes and clothes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.
Move undamaged containers from immediate hazard area if it can be done safely.
Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****For non-emergency personnel**

Provide adequate ventilation.
Use personal protection equipment.
Avoid contact with skin, eyes and clothes.
Remove persons to safety.
Emergency procedures
Consult an expert
Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up**For containment**

Cover drains.
Prevent spread over a wide area (e.g. by containment or oil barriers).
Collect in closed and suitable containers for disposal.
Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.
Do not breathe dust/fume/gas/mist/vapours/spray.
Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7
Personal protection equipment: see section 8
Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

according to Regulation (EC) No 1907/2006

Buffer solution pH 10.7 67.5 g NH₄Cl + 570 ml NH₃ solution 25 %/l for complexometric titration

Revision: 07.10.2024

Product code: 17251

Page 5 of 14

Advice on safe handling

Read label before use. Handle and open container with care.
When using do not eat, drink, smoke, sniff.
Use personal protection equipment. Use extractor hood (laboratory).
Provide adequate ventilation. Do not breathe vapour/aerosol.
Avoid contact with skin, eyes and clothes.

Advice on protection against fire and explosion

Usual measures for fire prevention.
Formation of explosive mixtures with: Air

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs. Remove contaminated, saturated clothing immediately.
Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink. Avoid: aerosol or mist formation Do not breathe vapour/aerosol.

Further information on handling

Draw up and observe skin protection programme.
Wash hands and face before breaks and after work and take a shower if necessary.
Take off immediately all contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed.
Corrosive to metals.
Unsuitable container/equipment material: Metal, Light metal

Hints on joint storage

national regulations

Further information on storage conditions

Keep cool. Protect from sunlight.

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational exposure limits**

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
7664-41-7	Ammonia, anhydrous	20	14		TWA (8 h)	
		50	36		STEL (15 min)	
12125-02-9	Ammonium chloride, fume	-	10		TWA (8 h)	
		-	20		STEL (15 min)	

Buffer solution pH 10.7 67.5 g NH₄Cl + 570 ml NH₃ solution 25 %/l for complexometric titration

Revision: 07.10.2024

Product code: 17251

Page 6 of 14

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
1336-21-6	Ammonia			
Worker DNEL, long-term		inhalation	systemic	47,6 mg/m ³
Worker DNEL, acute		inhalation	systemic	47,6 mg/m ³
Worker DNEL, long-term		inhalation	local	14 mg/m ³
Worker DNEL, acute		inhalation	local	36 mg/m ³
Worker DNEL, long-term		dermal	systemic	6,8 mg/kg bw/day
Worker DNEL, acute		dermal	systemic	6,8 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	23,8 mg/m ³
Consumer DNEL, acute		inhalation	systemic	23,8 mg/m ³
Consumer DNEL, long-term		inhalation	local	2,8 mg/m ³
Consumer DNEL, acute		inhalation	local	7,2 mg/m ³
Consumer DNEL, long-term		dermal	systemic	68 mg/kg bw/day
Consumer DNEL, acute		dermal	systemic	68 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	6,8 mg/kg bw/day
Consumer DNEL, acute		oral	systemic	6,8 mg/kg bw/day
12125-02-9	ammonium chloride			
Worker DNEL, long-term		inhalation	systemic	33,5 mg/m ³
Worker DNEL, long-term		dermal	systemic	190 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	9,9 mg/m ³
Consumer DNEL, long-term		dermal	systemic	114 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	11,4 mg/kg bw/day

PNEC values

CAS No	Substance		
Environmental compartment			Value
1336-21-6	Ammonia		
Freshwater			0,001 mg/l
Freshwater (intermittent releases)			0,007 mg/l
Marine water			0,001 mg/l
12125-02-9	ammonium chloride		
Freshwater			1,2 mg/l
Freshwater (intermittent releases)			1,2 mg/l
Marine water			11,2 mg/l
Micro-organisms in sewage treatment plants (STP)			16,2 mg/l
Soil			0,163 mg/kg

8.2. Exposure controls**Appropriate engineering controls**

Technical measures and the application of suitable work processes have priority over personal protection equipment.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Buffer solution pH 10.7 67.5 g NH₄Cl + 570 ml NH₃ solution 25 %/l for complexometric titration

Revision: 07.10.2024

Product code: 17251

Page 7 of 14

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment**Eye/face protection**

goggles

Wear eye/face protection.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact

Trade name/designation: KCL 897 Butoject®

Recommended material: Butyl caoutchouc (butyl rubber) 0,3 mm

Wearing time with permanent contact: > 480 min

By short-term hand contact

Trade name/designation: KCL 730 Camatril® Velours

Recommended material: NBR (Nitrile rubber) 0,4 mm

Wearing time with occasional contact (splashes): > 120 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet (>, <) supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing.

Wash hands before breaks and after work.

The choice of body protection depends on the concentration and quantity of hazardous substances. The chemical resistance of protective agents must be clarified with their suppliers.

Respiratory protection

Respiratory protection necessary at: aerosol or mist formation

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	colourless
Odour:	stinging
Odour threshold:	No data available

Buffer solution pH 10.7 67.5 g NH₄Cl + 570 ml NH₃ solution 25 %/l for complexometric titration

Revision: 07.10.2024

Product code: 17251

Page 8 of 14

Melting point/freezing point:	No data available
Boiling point or initial boiling point and boiling range:	No data available
Flammability:	No data available
Lower explosion limits:	No data available
Upper explosion limits:	No data available
Flash point:	No data available
Auto-ignition temperature:	No data available
Decomposition temperature:	No data available
pH-Value:	10,7
Viscosity / kinematic:	No data available
Water solubility:	completely miscible
Solubility in other solvents	
No data available	
Dissolution rate:	No data available
Partition coefficient n-octanol/water:	No data available
Dispersion stability:	No data available
Vapour pressure:	No data available
Vapour pressure:	No data available
Density:	0,98 g/cm ³
Relative density:	No data available
Bulk density:	No data available
Relative vapour density:	No data available
Particle characteristics:	No data available

9.2. Other information

Information with regard to physical hazard classes

Explosive properties	
No data available	
Sustained combustibility:	No data available
Self-ignition temperature	
Solid:	No data available
Gas:	No data available
Oxidizing properties	
No data available	

Other safety characteristics

Evaporation rate:	No data available
Solvent separation test:	No data available
Solvent content:	No data available
Solid content:	No data available
Sublimation point:	No data available
Softening point:	No data available
Pour point:	No data available
No data available:	
Viscosity / dynamic:	No data available
Flow time:	No data available

Further Information

No data available

SECTION 10: Stability and reactivity

according to Regulation (EC) No 1907/2006

Buffer solution pH 10.7 67.5 g NH₄Cl + 570 ml NH₃ solution 25 %/l for complexometric titration

Revision: 07.10.2024

Product code: 17251

Page 9 of 14

10.1. Reactivity

No data available

10.2. Chemical stability

Formation of explosive mixtures with: Air

10.3. Possibility of hazardous reactions

Oxidising agent, mercury (Hg), Oxygen, Hydrogen peroxide, Acid, Chlorine, Heavy metals, Nitric acid, Bromine, Hydrogen bromide (HBr), Hydrochloric gas, Nitrogen oxides (NO_x), Hydrogen fluoride, Carbon dioxide,

10.4. Conditions to avoid

Heat

10.5. Incompatible materials

Metal, Aluminium, Lead
nickel, silver, Zinc
Copper

10.6. Hazardous decomposition products

In case of fire may be liberated:

SECTION 5: Firefighting measures

Further information

No data available

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008****Toxicokinetics, metabolism and distribution**

There are no data available on the mixture itself.

Acute toxicity

Based on available data, the classification criteria are not met.

If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects).

Mucous membrane irritation in the mouth, throat, esophagus and gastrointestinal tract.

Inhalation effect: Damage to the respiratory tract.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
1336-21-6	Ammonia				
	oral	LD50 350 mg/kg	Rat	Journal of Industrial Hygiene and Toxicology	OECD Guideline 401
	inhalation (1 h) vapour	LC50 4230 mg/l	Mouse	Bull. Environm. Contam. Toxicol, 1982, 2	Assessment of acute inhalation toxicity
12125-02-9	ammonium chloride				
	oral	LD50 1410 mg/kg	Rat	Other company data (1983)	other: not mentioned
	dermal	LD50 > 2000 mg/kg	Rat	Study report (2010)	EU Method B.3

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Buffer solution pH 10.7 67.5 g NH₄Cl + 570 ml NH₃ solution 25 %/l for complexometric titration

Revision: 07.10.2024

Product code: 17251

Page 10 of 14

Irritation and corrosivity

Skin corrosion/irritation: Causes severe skin burns and eye damage.

Serious eye damage/eye irritation: Causes serious eye damage.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation. (Ammonia)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

There are no data available on the mixture itself.

Specific effects in experiment on an animal

There are no data available on the mixture itself.

Additional information on tests

There are no data available on the mixture itself.

Practical experience

There are no data available on the mixture itself.

11.2. Information on other hazards**Endocrine disrupting properties**

There are no data available on the mixture itself.

Other information

Irritant

Corrosion

Cough

Dyspnoea

Gastrointestinal complaints

gastric perforation

Unconsciousness

Vomiting

Circulatory collapse

Spasms

Pulmonary oedema

Risk of serious damage to eyes.

Further information

Dermatitis

SECTION 12: Ecological information**12.1. Toxicity**

Very toxic to aquatic life.

Harmful to aquatic life with long lasting effects.

Buffer solution pH 10.7 67.5 g NH₄Cl + 570 ml NH₃ solution 25 %/l for complexometric titration

Revision: 07.10.2024

Product code: 17251

Page 11 of 14

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
1336-21-6	Ammonia					
	Acute fish toxicity	LC50 0,75 - 3,4 mg/l	96 h	Pimephales promelas	Trans Amer Fish Soc; 112 (5). 1983. 705-	Assessment of acute toxicity in the fath
	Acute crustacea toxicity	EC50 101 mg/l	48 h	Daphnia magna	Environ. Toxicol. Chem. 5: 443-447 (1986)	other: ASTM E729-80
	Fish toxicity	NOEC 1,2 mg/l	61 d	Oncorhynchus gorbuscha	Fish. Bull. 78(3): 641-648 (1980)	OECD Guideline 210
12125-02-9	ammonium chloride					
	Acute fish toxicity	LC50 209 mg/l	96 h	Cyprinus carpio	Indian J. Environ. Health, 17, 140-146,	other: E03-05:APHA, AWWA & WPCF
	Acute crustacea toxicity	EC50 101 mg/l	48 h	Daphnia magna	Env. Tox. Chem. 5, 443-447 (1986) (1986)	other: ASTM E729-80
	Fish toxicity	NOEC 11,8 mg/l	28 d	Pimephales promelas	Env. Tox. Chem. 5, 437-442 (1986) (1986)	other: - American Society for Testing an
	Algae toxicity	NOEC 26,8 mg/l	10 d	Navicula sp.	Mar. Biol. 43(4), 307-315, (1977) (1977)	no data
	Crustacea toxicity	NOEC 14,6 mg/l	21 d	Daphnia magna	Env. Tox. Chem. 5, 443-447 (1986) (1986)	other: not mentioned
	Acute bacteria toxicity	EC50 1618 mg/l ()	0,5 h	activated sludge, domestic	Study report (1988)	OECD Guideline 209

12.2. Persistence and degradability

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
1336-21-6	Ammonia	-1,38

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Harmful effect due to pH shift.

Forms corrosive mixtures with water even if diluted.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Buffer solution pH 10.7 67.5 g NH₄Cl + 570 ml NH₃ solution 25 %/l for complexometric titration

Revision: 07.10.2024

Product code: 17251

Page 12 of 14

Further information

Do not allow to enter into surface water or drains.
Discharge into the environment must be avoided.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.
Send to a physico-chemical treatment facility under observation of official regulations.
Do not allow to enter into surface water or drains.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.
The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number or ID number:	UN 2672
14.2. UN proper shipping name:	Ammonia solution
14.3. Transport hazard class(es):	8
14.4. Packing group:	III
Hazard label:	8
Classification code:	C5
Special Provisions:	543
Limited quantity:	5 L
Excepted quantity:	E1
Transport category:	3
Hazard No:	80
Tunnel restriction code:	E

Inland waterways transport (ADN)

14.1. UN number or ID number:	UN 2672
14.2. UN proper shipping name:	Ammonia solution
14.3. Transport hazard class(es):	8
14.4. Packing group:	III
Hazard label:	8
Classification code:	C5
Special Provisions:	543
Limited quantity:	5 L
Excepted quantity:	E1

Marine transport (IMDG)

14.1. UN number or ID number:	UN 2672
14.2. UN proper shipping name:	Ammonia solution
14.3. Transport hazard class(es):	8
14.4. Packing group:	III
Hazard label:	8
Marine pollutant:	P
Special Provisions:	-
Limited quantity:	5 L
Excepted quantity:	E1

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Buffer solution pH 10.7 67.5 g NH₄Cl + 570 ml NH₃ solution 25 %/l for complexometric titration

Revision: 07.10.2024

Product code: 17251

Page 13 of 14

EmS: F-A, S-B

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:	UN 2672
14.2. UN proper shipping name:	Ammonia solution
14.3. Transport hazard class(es):	8
14.4. Packing group:	III
Hazard label:	8
Special Provisions:	A64 A803
Limited quantity Passenger:	1 L
Passenger LQ:	Y841
Excepted quantity:	E1
IATA-packing instructions - Passenger:	852
IATA-max. quantity - Passenger:	5 L
IATA-packing instructions - Cargo:	856
IATA-max. quantity - Cargo:	60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS:	Yes
Danger releasing substance:	Ammonia

14.6. Special precautions for user

No dangerous good in sense of this transport regulation.

14.7. Maritime transport in bulk according to IMO instruments

No dangerous good in sense of this transport regulation.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**Restrictions on use (REACH, annex XVII):
Entry 3, Entry 75

Information according to Directive 2012/18/EU (SEVESO III): E1 Hazardous to the Aquatic Environment

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D): 2 - obviously hazardous to water

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 1,9,11,12.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Buffer solution pH 10.7 67.5 g NH₄Cl + 570 ml NH₃ solution 25 %/l for complexometric titration

Revision: 07.10.2024

Product code: 17251

Page 14 of 14

Abbreviations and acronyms

Acute Tox. 4: Acute toxicity, hazard category 4
Skin Corr. 1B: Skin corrosion, sub-category 1B
Eye Dam. 1: Serious eye damage, hazard category 1
Eye Irrit. 2: Eye irritation, hazard category 2
STOT SE 3: Specific target organ toxicity - single exposure, hazard category 3
Aquatic Acute 1: Hazardous to the aquatic environment, hazard category: Acute 1
Aquatic Chronic 2: Hazardous to the aquatic environment, long-term hazard category: Chronic 2

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Skin Corr. 1B; H314	Calculation method
Eye Dam. 1; H318	Calculation method
STOT SE 3; H335	Calculation method
Aquatic Acute 1; H400	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H302 Harmful if swallowed.
H314 Causes severe skin burns and eye damage.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H400 Very toxic to aquatic life.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations. Provide appropriate information, instructions and training to users

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)