

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Petroleum benzine 40/60 °C for analysis evaporation residue: < 10 ppm

Revision: 12.09.2025

Product code: 20129

Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Petroleum benzine 40/60 °C for analysis evaporation residue: < 10 ppm

REACH Registration Number: 01-2119474679-18-XXXX
CAS No: 64742-49-0
Index No: 649-328-00-1
EC No: 265-151-9

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Reagents and laboratory chemicals
Only for laboratory and analysis purposes.

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name: AnalytiChem GmbH
ACD
Street: Stempelstraße 6
Place: D-47167 Duisburg
Telephone: 0203/5194-0
Telefax: 0203/5194-290
E-mail: info@analytichem.de
Contact person: Abteilung Produktsicherheit
Telephone: 0203/5194-107/117
E-mail: produktsicherheit@analytichem.de
Internet: www.analytichem.de
Responsible Department: Abteilung Produktsicherheit

1.4. Emergency telephone number:

For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

Further Information

No data available

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No 1272/2008**

Flam. Liq. 2; H225
Skin Irrit. 2; H315
STOT SE 3; H336
Asp. Tox. 1; H304
Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

2.2. Label elements**Regulation (EC) No 1272/2008****Hazard components for labelling**

Naphtha (petroleum), hydrotreated light

Signal word: Danger

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Petroleum benzine 40/60 °C for analysis evaporation residue: < 10 ppm

Revision: 12.09.2025

Product code: 20129

Page 2 of 11

Pictograms:



Hazard statements

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H304	May be fatal if swallowed and enters airways.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P273	Avoid release to the environment.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331	Do NOT induce vomiting.
P391	Collect spillage.
P403+P235	Store in a well-ventilated place. Keep cool.

Special labelling of certain mixtures

EUH066	Repeated exposure may cause skin dryness or cracking.
--------	---

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
64742-49-0	Naphtha (petroleum), hydrotreated light			100 %
	265-151-9	649-328-00-1	01-2119474679-18	
	Flam. Liq. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H336 H304 H411 EUH066			

Full text of H and EUH statements: see section 16.

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

No data available

After inhalation

Provide fresh air.
If breathing is irregular or stopped, administer artificial respiration.
Call a physician immediately.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Petroleum benzine 40/60 °C for analysis evaporation residue: < 10 ppm

Revision: 12.09.2025

Product code: 20129

Page 3 of 11

After contact with skin

Wash immediately with: Water
Take off immediately all contaminated clothing and wash it before reuse.
Call a physician immediately.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.
Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Observe risk of aspiration if vomiting occurs.
Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Irritant
Vapours may cause drowsiness and dizziness.
Gastrointestinal complaints

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Carbon dioxide (CO₂)
Foam
Extinguishing powder
Water spray jet

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Combustible liquids
Hazardous combustion products
In case of fire may be liberated: Carbon dioxide (CO₂) Carbon monoxide
Vapours are heavier than air, spread along floors and form explosive mixtures with air.
Heating causes rise in pressure with risk of bursting.
Beware of reignition.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.
In case of fire and/or explosion do not breathe fumes.
Avoid contact with skin, eyes and clothes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.
Move undamaged containers from immediate hazard area if it can be done safely.
Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Keep away from sources of ignition - No smoking.
This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Petroleum benzine 40/60 °C for analysis evaporation residue: < 10 ppm

Revision: 12.09.2025

Product code: 20129

Page 4 of 11

paggers which have not been certified as intrinsically safe).

Take action to prevent static discharges.

For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Consult an expert

Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Danger of explosion

6.3. Methods and material for containment and cleaning up**For containment**

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Avoid exposure - obtain special instructions before use.

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Keep container tightly closed.

Use personal protection equipment. Use extractor hood (laboratory).

Provide adequate ventilation. Do not breathe vapour.

Advice on protection against fire and explosion

Take action to prevent static discharges. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs.

The choice of body protection depends on the concentration and quantity of hazardous substances. The chemical resistance of protective agents must be clarified with their suppliers.

Petroleum benzine 40/60 °C for analysis evaporation residue: < 10 ppm

Revision: 12.09.2025

Product code: 20129

Page 5 of 11

Further information on handling

Take off immediately all contaminated clothing and wash it before reuse.
Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. If handled uncovered, arrangements with local exhaust ventilation have to be used.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep in a cool, well-ventilated place.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints on joint storage

national regulations

Further information on storage conditions

Keep container tightly closed and dry.
Keep cool. Protect from sunlight.
storage temperature: < +30°C

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.2. Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.
If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment

Eye/face protection

goggles
Face protection umbrella

Hand protection

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact

Trade name/designation: KCL 890 Vitoject®
Suitable material: FKM (fluoro rubber) 0,7 mm
Wearing time with permanent contact: > 480 min

By short-term hand contact

Trade name/designation: KCL 730 Camatril® Velours
Suitable material: NBR (Nitrile rubber) 0,4 mm
Wearing time with occasional contact (splashes): > 480 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet (>, <) supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Take off immediately all contaminated clothing and wash it before reuse.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Petroleum benzine 40/60 °C for analysis evaporation residue: < 10 ppm

Revision: 12.09.2025

Product code: 20129

Page 6 of 11

Wear fire resistant or flame retardant clothing.

Wash hands and face before breaks and after work and take a shower if necessary.

Draw up and observe skin protection programme.

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Environmental exposure controls

Do not allow to enter into surface water or drains.

Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.

Danger of explosion

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid	
Colour:	colourless	
Odour:	like: Gasoline	
Melting point/freezing point:		No data available
Boiling point or initial boiling point and boiling range:		40-60 °C
Flammability:		No data available
Lower explosion limits:		1,1 vol. %
Upper explosion limits:		7,5 vol. %
Flash point:		-49 °C
Auto-ignition temperature:		280 °C
Decomposition temperature:		No data available
pH-Value:		No data available
Viscosity / kinematic:		No data available
Water solubility:		No data available
Solubility in other solvents		No data available
Partition coefficient n-octanol/water:		No data available
Vapour pressure:		No data available
Vapour pressure:		No data available
Density:		0,653 g/cm³
Bulk density:		No data available
Relative vapour density:		No data available

9.2. Other information**Information with regard to physical hazard classes****Explosive properties**

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Sustained combustibility: Sustained combustibility

Self-ignition temperature

Solid: No data available

Gas: No data available

Oxidizing properties

No data available

Other safety characteristics

Evaporation rate: No data available

Solvent separation test: No data available

Petroleum benzine 40/60 °C for analysis evaporation residue: < 10 ppm

Revision: 12.09.2025

Product code: 20129

Page 7 of 11

Solvent content:	No data available
Solid content:	No data available
Sublimation point:	No data available
Softening point:	No data available
Pour point:	No data available
Viscosity / dynamic:	No data available
Flow time:	No data available

Further Information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

Vapours may form explosive mixtures with air.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Oxidising agent

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

Plastic articles
Rubber articles

10.6. Hazardous decomposition products

SECTION 5: Firefighting measures

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

Irritation and corrosivity

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Repeated exposure may cause skin dryness or cracking.

Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Petroleum benzine 40/60 °C for analysis evaporation residue: < 10 ppm

Revision: 12.09.2025

Product code: 20129

Page 8 of 11

STOT-single exposure

May cause drowsiness or dizziness. (Naphtha (petroleum), hydrotreated light)

Organs affected: central nervous system

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

Specific effects in experiment on an animal

No data available

Additional information on tests

No data available

Practical experience

No data available

11.2. Information on other hazards**Other information**

Avoid exposure - obtain special instructions before use.

Further information

Irritant

Vapours may cause drowsiness and dizziness.

Gastrointestinal complaints

SECTION 12: Ecological information**12.1. Toxicity**

Toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Do not allow to enter into surface water or drains.

Avoid release to the environment.

Further information

No data available

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Petroleum benzine 40/60 °C for analysis evaporation residue: < 10 ppm

Revision: 12.09.2025

Product code: 20129

Page 9 of 11

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number or ID number:	UN 1268
14.2. UN proper shipping name:	PETROLEUM DISTILLATES, N.O.S.
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3
Classification code:	F1
Special Provisions:	640D ADR664
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	33
Tunnel restriction code:	D/E

Inland waterways transport (ADN)

14.1. UN number or ID number:	UN 1268
14.2. UN proper shipping name:	PETROLEUM DISTILLATES, N.O.S.
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3
Classification code:	F1
Special Provisions:	363 640D
Limited quantity:	1 L
Excepted quantity:	E2

Marine transport (IMDG)

14.1. UN number or ID number:	UN 1268
14.2. UN proper shipping name:	PETROLEUM DISTILLATES, N.O.S.
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3
Special Provisions:	-
Limited quantity:	1 L
Excepted quantity:	E2
EmS:	F-E, S-E

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:	UN 1268
14.2. UN proper shipping name:	PETROLEUM DISTILLATES, N.O.S.
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3
Special Provisions:	A3
Limited quantity Passenger:	1 L
Passenger LQ:	Y341
Excepted quantity:	E2
IATA-packing instructions - Passenger:	353
IATA-max. quantity - Passenger:	5 L

according to Regulation (EC) No 1907/2006

Petroleum benzine 40/60 °C for analysis evaporation residue: < 10 ppm

Revision: 12.09.2025

Product code: 20129

Page 10 of 11

IATA-packing instructions - Cargo:

364

IATA-max. quantity - Cargo:

60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS:

Yes

Danger releasing substance:

Naphtha (petroleum), hydrotreated light

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Information according to Directive
2012/18/EU (SEVESO III):

E2 Hazardous to the Aquatic Environment

Additional information:

P5c

National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D):

3 - highly hazardous to water

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 12.

Abbreviations and acronyms

Flam. Liq. 2: Flammable liquids, hazard category 2

Asp. Tox. 1: Aspiration hazard, hazard category 1

Skin Irrit. 2: Skin irritation, hazard category 2

STOT SE 3: Specific target organ toxicity - single exposure, hazard category 3

Aquatic Chronic 2: Hazardous to the aquatic environment, long-term hazard category: Chronic 2

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Skin Irrit. 2; H315	
STOT SE 3; H336	Calculation method
Asp. Tox. 1; H304	Calculation method
Aquatic Chronic 2; H411	Calculation method

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Petroleum benzine 40/60 °C for analysis evaporation residue: < 10 ppm

Revision: 12.09.2025

Product code: 20129

Page 11 of 11

named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

Provide appropriate information, instructions and training to users

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)