

Acetatpufferlösung zur Gesamtchlormessung nach Grundfos

Revision: 17.06.2024

Product code: 23263

Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Acetatpufferlösung zur Gesamtchlormessung nach Grundfos

UFI: 58E2-E2FW-G00G-1MG1

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Reagents and laboratory chemicals

Only for laboratory and analysis purposes.

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name: AnalytiChem GmbH

ACD

Street: Stempelstraße 6

Place: D-47167 Duisburg

Telephone: 0203/5194-0

Telefax: 0203/5194-290

E-mail: info@analytichem.de

Contact person: Abteilung Produktsicherheit

Telephone: 0203/5194-107/117

E-mail: produktsicherheit@analytichem.de

Internet: www.analytichem.de

Responsible Department: Abteilung Produktsicherheit

1.4. Emergency telephone**number:**

For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

Further Information

This product is a mixture. REACH Registration Number see section 3.

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No 1272/2008**

Skin Corr. 1B; H314

Eye Dam. 1; H318

Full text of hazard statements: see SECTION 16.

2.2. Label elements**Regulation (EC) No 1272/2008****Hazard components for labelling**

acetic acid

Signal word: Danger**Pictograms:****Hazard statements**

H314

Causes severe skin burns and eye damage.

Acetatpufferlösung zur Gesamtchlormessung nach Grundfos

Revision: 17.06.2024

Product code: 23263

Page 2 of 12

Precautionary statements

- P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER/doctor.

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Chemical characterization**

Mixtures in aqueous solution

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
64-19-7	acetic acid			50 - < 55 %
	200-580-7	607-002-00-6	01-2119475328-30	
	Flam. Liq. 3, Skin Corr. 1A, Eye Dam. 1; H226 H314 H318			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
64-19-7	200-580-7	acetic acid	50 - < 55 %
	oral: LD50 = 3310 mg/kg Skin Corr. 1A; H314: >= 90 - 100 Skin Corr. 1B; H314: >= 25 - < 90 Skin Irrit. 2; H315: >= 10 - < 25 Eye Irrit. 2; H319: >= 10 - < 25		

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

Self-protection of the first aider

After inhalation

Provide fresh air.

Call a physician immediately.

After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

Call a physician immediately.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Acetatpufferlösung zur Gesamtchlormessung nach Grundfos

Revision: 17.06.2024

Product code: 23263

Page 3 of 12

Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Rinse mouth immediately and drink plenty of water.

Do NOT induce vomiting.

Do not allow a neutralisation agent to be drunk.

Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Irritant

corrosive

Dyspnoea

Gastrointestinal complaints

Vomiting

Circulatory collapse

Corneal opacity.

Risk of serious damage to eyes.

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Combustible liquids

Hazardous combustion products

In case of fire may be liberated:

Carbon dioxide (CO₂), Carbon monoxide, Acetic acid-vapour

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Heating causes rise in pressure with risk of bursting.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

In case of fire and/or explosion do not breathe fumes.

Avoid contact with skin, eyes and clothes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Move undamaged containers from immediate hazard area if it can be done safely.

Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****For non-emergency personnel**

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Consult an expert

Acetatpufferlösung zur Gesamtchlormessung nach Grundfos

Revision: 17.06.2024

Product code: 23263

Page 4 of 12

Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up**For containment**

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Keep container tightly closed.

Use personal protection equipment. Use extractor hood (laboratory).

Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation.

Advice on protection against fire and explosion

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs.

The choice of body protection depends on the concentration and quantity of hazardous substances. The chemical resistance of protective agents must be clarified with their suppliers.

Further information on handling

Take off immediately all contaminated clothing and wash it before reuse.

Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. If handled uncovered, arrangements with local exhaust ventilation have to be used.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Store in a well-ventilated place. Keep container tightly closed.

Store in a dry place.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints on joint storage

national regulations

Further information on storage conditions

In case of warming: Vapours may form explosive mixtures with air.

Acetatpufferlösung zur Gesamtchlormessung nach Grundfos

Revision: 17.06.2024

Product code: 23263

Page 5 of 12

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational exposure limits**

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
64-19-7	Acetic acid	10	25		TWA (8 h)	
		20	50		STEL (15 min)	

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
64-19-7	acetic acid			
Worker DNEL, long-term		inhalation	local	25 mg/m ³
Worker DNEL, acute		inhalation	local	25 mg/m ³
Consumer DNEL, long-term		inhalation	local	25 mg/m ³
Consumer DNEL, acute		inhalation	local	25 mg/m ³

PNEC values

CAS No	Substance	
Environmental compartment		Value
64-19-7	acetic acid	
Freshwater		3,058 mg/l
Freshwater (intermittent releases)		30,58 mg/l
Marine water		0,306 mg/l
Freshwater sediment		11,36 mg/kg
Marine sediment		1,136 mg/kg
Micro-organisms in sewage treatment plants (STP)		85 mg/l
Soil		0,47 mg/kg

8.2. Exposure controls**Appropriate engineering controls**

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment**Eye/face protection**

goggles

Face protection umbrella

Hand protection

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact

Trade name/designation: KCL 897 Butoject®

Acetatpufferlösung zur Gesamtchlormessung nach Grundfos

Revision: 17.06.2024

Product code: 23263

Page 6 of 12

Suitable material: Butyl caoutchouc (butyl rubber) 0,3 mm
Wearing time with permanent contact: > 480 min

By short-term hand contact
Trade name/designation: KCL 890 Vitoject®
Suitable material: FKM (fluoro rubber) 0,7 mm
Wearing time with occasional contact (splashes): > 60 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Take off immediately all contaminated clothing and wash it before reuse.
Wear fire resistant or flame retardant clothing.
Wash hands and face before breaks and after work and take a shower if necessary.
Draw up and observe skin protection programme.

Respiratory protection

Respiratory protection necessary at: aerosol or mist formation
Filtering device (full mask or mouthpiece) with filter: E-(P2)
The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Environmental exposure controls

Do not allow to enter into surface water or drains.
Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.
Danger of explosion

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	colourless
Odour:	stinging
Odour threshold:	No data available
Melting point/freezing point:	~ -25 °C
Boiling point or initial boiling point and boiling range:	~102 °C
Flammability:	No data available
Lower explosion limits:	No data available
Upper explosion limits:	No data available
Flash point:	No data available
Auto-ignition temperature:	No data available
Decomposition temperature:	No data available
pH-Value:	acidic
Viscosity / kinematic:	No data available
Water solubility:	completely miscible
Solubility in other solvents	No data available
Partition coefficient n-octanol/water:	No data available
Vapour pressure:	No data available

Acetatpufferlösung zur Gesamtchlormessung nach Grundfos

Revision: 17.06.2024

Product code: 23263

Page 7 of 12

Vapour pressure:	No data available
Density:	1,12246 g/cm ³
Bulk density:	No data available
Relative vapour density:	No data available

9.2. Other information**Information with regard to physical hazard classes****Explosive properties**

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Sustained combustibility: Sustained combustibility

Self-ignition temperature

Solid: No data available

Gas: No data available

Oxidizing properties

No data available

Other safety characteristics

Evaporation rate: No data available

Solvent separation test: No data available

Solvent content: No data available

Solid content: No data available

Sublimation point: No data available

Softening point: No data available

Pour point: No data available

Viscosity / dynamic: No data available

Flow time: No data available

Further Information

May be corrosive to metals.

SECTION 10: Stability and reactivity**10.1. Reactivity**

In case of warming: Vapours may form explosive mixtures with air.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Oxidising agent

peroxides, for example hydrogen peroxide

permanganates, e.g. potassium permanganate

Oxidising agent, strong

Metal

iron and steel

Zinc

Alkali (lye)

aldehydes

Alcohols

Nitric acid

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

Metal (Formation of: Hydrogen)

Acetatpufferlösung zur Gesamtchlormessung nach Grundfos

Revision: 17.06.2024

Product code: 23263

Page 8 of 12

10.6. Hazardous decomposition products

SECTION 5: Firefighting measures

Further information

No data available

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008****Toxicokinetics, metabolism and distribution**

There are no data available on the mixture itself.

Acute toxicity

Based on available data, the classification criteria are not met.

If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects).

The substance has delayed effects.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64-19-7	acetic acid				
	oral	LD50 3310 mg/kg	Rat	J Ind Hyg Toxicol, Vol 23, PP 78-82 (194	The sodium salt of acetic acid was admin

Irritation and corrosivity

Skin corrosion/irritation: Causes severe skin burns and eye damage.

Serious eye damage/eye irritation: Causes serious eye damage.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Observe risk of aspiration if vomiting occurs.

Specific effects in experiment on an animal

There are no data available on the mixture itself.

Additional information on tests

There are no data available on the mixture itself.

Practical experience

There are no data available on the mixture itself.

11.2. Information on other hazards**Other information**

Irritant

Acetatpufferlösung zur Gesamtchlormessung nach Grundfos

Revision: 17.06.2024

Product code: 23263

Page 9 of 12

corrosive
Dyspnoea
Gastrointestinal complaints
Vomiting
Circulatory collapse
Corneal opacity.
Risk of serious damage to eyes.

Further information

May cause damage to organs.
(kidneys)

SECTION 12: Ecological information**12.1. Toxicity**

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
64-19-7	acetic acid					
	Acute fish toxicity	LC50 > 1000 mg/l	96 h	Oncorhynchus mykiss	Study report (2005)	other: SOP E257
	Acute algae toxicity	ErC50 > 1000 mg/l	72 h	Skeletonema costatum	Study report (2005)	ISO 10253
	Acute crustacea toxicity	EC50 > 1000 mg/l	48 h	Daphnia magna	Study report (1990)	OECD Guideline 202

12.2. Persistence and degradability

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
64-19-7	acetic acid	-0,17

BCF

CAS No	Chemical name	BCF	Species	Source
64-19-7	acetic acid	3,16	fish	Environ. Toxicol. Ch

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Avoid release to the environment.
Harmful effect due to pH shift.

Further information

Do not allow to enter into surface water or drains.

Acetatpufferlösung zur Gesamtchlormessung nach Grundfos

Revision: 17.06.2024

Product code: 23263

Page 10 of 12

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number or ID number:	UN 2790
14.2. UN proper shipping name:	ACETIC ACID SOLUTION
14.3. Transport hazard class(es):	8
14.4. Packing group:	III
Hazard label:	8
Classification code:	C3
Special Provisions:	597 647
Limited quantity:	5 L
Excepted quantity:	E1
Transport category:	3
Hazard No:	80
Tunnel restriction code:	E

Inland waterways transport (ADN)

14.1. UN number or ID number:	UN 2790
14.2. UN proper shipping name:	ACETIC ACID SOLUTION
14.3. Transport hazard class(es):	8
14.4. Packing group:	III
Hazard label:	8
Classification code:	C3
Special Provisions:	597 647
Limited quantity:	5 L
Excepted quantity:	E1

Marine transport (IMDG)

14.1. UN number or ID number:	UN 2790
14.2. UN proper shipping name:	ACETIC ACID SOLUTION
14.3. Transport hazard class(es):	8
14.4. Packing group:	III
Hazard label:	8
Special Provisions:	-
Limited quantity:	5 L
Excepted quantity:	E2
EmS:	F-A, S-B
Segregation group:	1 - acids

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:	UN 2790
14.2. UN proper shipping name:	ACETIC ACID SOLUTION
14.3. Transport hazard class(es):	8

Acetatpufferlösung zur Gesamtchlormessung nach Grundfos

Revision: 17.06.2024

Product code: 23263

Page 11 of 12

14.4. Packing group:

Hazard label:	III
Special Provisions:	8
Limited quantity Passenger:	A803
Passenger LQ:	1 L
Excepted quantity:	Y841
IATA-packing instructions - Passenger:	E1
IATA-max. quantity - Passenger:	852
IATA-packing instructions - Cargo:	5 L
IATA-max. quantity - Cargo:	856
	60 L

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Information according to Directive
2012/18/EU (SEVESO III):

Not subject to 2012/18/EU (SEVESO III)

National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D):

1 - slightly hazardous to water

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 1,2,6,9,12,14.

Abbreviations and acronyms

Flam. Liq. 3: Flammable liquids, hazard category 3

Skin Corr. 1A: Skin corrosion, sub-category 1A

Eye Dam. 1: Serious eye damage, hazard category 1

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Skin Corr. 1B; H314	Calculation method
Eye Dam. 1; H318	Calculation method

Relevant H and EUH statements (number and full text)

H226	Flammable liquid and vapour.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.

Further Information

Provide appropriate information, instructions and training to users

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Acetatpufferlösung zur Gesamtchlormessung nach Grundfos

Revision: 17.06.2024

Product code: 23263

Page 12 of 12

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)