

according to Regulation (EC) No 1907/2006

n-Butyl acetate > 99 % (acetic acid butylester) for analysis

Revision: 11.07.2025

Product code: 24297

Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

n-Butyl acetate > 99 % (acetic acid butylester) for analysis

REACH Registration Number: 01-2119485493-29-XXXX
CAS No: 123-86-4
Index No: 607-025-00-1
EC No: 204-658-1

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Reagents and laboratory chemicals
Only for laboratory and analysis purposes.

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name: AnalytiChem GmbH
ACD
Street: Stempelstraße 6
Place: D-47167 Duisburg
Telephone: 0203/5194-0
Telefax: 0203/5194-290
E-mail: info@analytichem.de
Contact person: Abteilung Produktsicherheit
Telephone: 0203/5194-107/117
E-mail: produktsicherheit@analytichem.de
Internet: www.analytichem.de
Responsible Department: Abteilung Produktsicherheit

1.4. Emergency telephone number:

For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

Further Information

No data available

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No 1272/2008**

Flam. Liq. 3; H226
STOT SE 3; H336

Full text of hazard statements: see SECTION 16.

2.2. Label elements**Regulation (EC) No 1272/2008**

Signal word: Warning

Pictograms:



n-Butyl acetate > 99 % (acetic acid butylester) for analysis

Revision: 11.07.2025

Product code: 24297

Page 2 of 12

Hazard statements

- H226 Flammable liquid and vapour.
H336 May cause drowsiness or dizziness.

Precautionary statements

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P312 Call a POISON CENTER/doctor if you feel unwell.
P403+P235 Store in a well-ventilated place. Keep cool.

Special labelling of certain mixtures

- EUH066 Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients**3.1. Substances**

- Sum formula: $\text{CH}_3\text{COO}(\text{CH}_2)_3\text{CH}_3$
Molecular weight: 116,16 g/mol

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
123-86-4	n-butyl acetate			100 %
	204-658-1	607-025-00-1	01-2119485493-29-XXXX	
	Flam. Liq. 3, STOT SE 3; H226 H336 EUH066			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
123-86-4	204-658-1	n-butyl acetate	100 %
	inhalation: LC50 = > 6,6 mg/l (vapours); oral: LD50 = 14130 mg/kg		

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

No data available

After inhalation

- Provide fresh air.
Call a physician immediately.

After contact with skin

- Wash immediately with: Water
Take off immediately all contaminated clothing and wash it before reuse.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

n-Butyl acetate > 99 % (acetic acid butylester) for analysis

Revision: 11.07.2025

Product code: 24297

Page 3 of 12

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water.
Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Observe risk of aspiration if vomiting occurs.
Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Vapours may cause drowsiness and dizziness.
Anaesthetic state
Has degreasing effect on the skin.

4.3. Indication of any immediate medical attention and special treatment needed

Give sodium sulfate as laxative (1 tablespoon in 1 glass of water).

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Carbon dioxide (CO₂)
Foam
Extinguishing powder

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Combustible liquids
Hazardous combustion products
In case of fire may be liberated: Carbon dioxide (CO₂) Carbon monoxide
In case of warming:
Vapours are heavier than air, spread along floors and form explosive mixtures with air.
Heating causes rise in pressure with risk of bursting.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.
In case of fire and/or explosion do not breathe fumes.
Avoid contact with skin, eyes and clothes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.
Move undamaged containers from immediate hazard area if it can be done safely.
Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Keep away from sources of ignition - No smoking.
This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).
Take action to prevent static discharges.

For non-emergency personnel

Provide adequate ventilation.
Use personal protection equipment.
Avoid contact with skin, eyes and clothes.

n-Butyl acetate > 99 % (acetic acid butylester) for analysis

Revision: 11.07.2025

Product code: 24297

Page 4 of 12

Remove persons to safety.
Emergency procedures
Consult an expert
Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.
The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.
Danger of explosion

6.3. Methods and material for containment and cleaning up**For containment**

Cover drains.
Prevent spread over a wide area (e.g. by containment or oil barriers).
Collect in closed and suitable containers for disposal.
Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.
Do not breathe dust/fume/gas/mist/vapours/spray.
Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7
Personal protection equipment: see section 8
Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Read label before use. Handle and open container with care.
When using do not eat, drink, smoke, sniff. Keep container tightly closed.
Use personal protection equipment. Use extractor hood (laboratory).
Do not breathe vapour/aerosol. Provide adequate ventilation.

Advice on protection against fire and explosion

Take action to prevent static discharges. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs.
Wash hands and face before breaks and after work and take a shower if necessary.
When using do not eat or drink.
Avoid: aerosol or mist formation Do not breathe vapour/aerosol.

Further information on handling

Take off immediately all contaminated clothing and wash it before reuse.
Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. If handled uncovered, arrangements with local exhaust ventilation have to be used.

7.2. Conditions for safe storage, including any incompatibilities

n-Butyl acetate > 99 % (acetic acid butylester) for analysis

Revision: 11.07.2025

Product code: 24297

Page 5 of 12

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

Store in a cool dry place.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Unsuitable container/equipment material: Light metal

Hints on joint storage

national regulations

Further information on storage conditions

Protect from sunlight.

minimum storage temperature +5°C

maximum storage temperature +30°C

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational exposure limits**

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
123-86-4	n-Butyl acetate	50	241		TWA (8 h)	
		150	723		STEL (15 min)	

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
123-86-4	n-butyl acetate			
Worker DNEL, long-term		inhalation	systemic	300 mg/m ³
Worker DNEL, acute		inhalation	systemic	600 mg/m ³
Worker DNEL, long-term		inhalation	local	300 mg/m ³
Worker DNEL, acute		inhalation	local	600 mg/m ³
Worker DNEL, long-term		dermal	systemic	11 mg/kg bw/day
Worker DNEL, acute		dermal	systemic	11 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	35,7 mg/m ³
Consumer DNEL, acute		inhalation	systemic	300 mg/m ³
Consumer DNEL, long-term		inhalation	local	35,7 mg/m ³
Consumer DNEL, acute		inhalation	local	300 mg/m ³
Consumer DNEL, long-term		dermal	systemic	6 mg/kg bw/day
Consumer DNEL, acute		dermal	systemic	6 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	2 mg/kg bw/day
Consumer DNEL, acute		oral	systemic	2 mg/kg bw/day

n-Butyl acetate > 99 % (acetic acid butylester) for analysis

Revision: 11.07.2025

Product code: 24297

Page 6 of 12

PNEC values

CAS No	Substance	
Environmental compartment		Value
123-86-4	n-butyl acetate	
Freshwater		0,18 mg/l
Freshwater (intermittent releases)		0,36 mg/l
Marine water		0,018 mg/l
Freshwater sediment		0,981 mg/kg
Marine sediment		0,098 mg/kg
Micro-organisms in sewage treatment plants (STP)		35,6 mg/l
Soil		0,09 mg/kg

8.2. Exposure controls**Appropriate engineering controls**

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment**Eye/face protection**

goggles

Face protection umbrella

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact

Wearing time with permanent contact : No data available

By short-term hand contact

Trade name/designation KCL 897 Butoject®

Suitable material: Butyl caoutchouc (butyl rubber) 0,3 mm

Wearing time with occasional contact (splashes): > 60 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet (>, <) supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Wear fire resistant or flame retardant clothing.

Take off immediately all contaminated clothing and wash it before reuse.

Wear suitable protective clothing. Take off immediately all contaminated clothing.

Wash hands and face before breaks and after work and take a shower if necessary.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

n-Butyl acetate > 99 % (acetic acid butylester) for analysis

Revision: 11.07.2025

Product code: 24297

Page 7 of 12

The choice of body protection depends on the concentration and quantity of hazardous substances. The chemical resistance of protective agents must be clarified with their suppliers.

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Filtering device with filter or ventilator filtering device of type: A

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Environmental exposure controls

Do not allow to enter into surface water or drains.

Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.

Danger of explosion

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	colourless
Odour:	fruity
Odour threshold:	No data available
Melting point/freezing point:	-90 °C
Boiling point or initial boiling point and boiling range:	126,2 °C
Flammability:	No data available
Lower explosion limits:	1,4 vol. %
Upper explosion limits:	7,5 vol. %
Flash point:	27 °C
Auto-ignition temperature:	370 °C
Decomposition temperature:	No data available
pH-Value (at 20 °C):	6,2 (5,3 g/l)
Viscosity / kinematic: (at 20 °C)	0,83 mm²/s
Water solubility: (at 20 °C)	5,3 g/l
Solubility in other solvents	No data available
Dissolution rate:	No data available
Partition coefficient n-octanol/water:	No data available
Dispersion stability:	No data available
Vapour pressure: (at 20 °C)	15 hPa
Vapour pressure: (at 50 °C)	63 hPa
Density (at 20 °C):	0,88 g/cm³
Bulk density:	No data available
Relative vapour density:	No data available
Particle characteristics:	No data available

9.2. Other information**Information with regard to physical hazard classes****Explosive properties**

In case of warming:

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

n-Butyl acetate > 99 % (acetic acid butylester) for analysis

Revision: 11.07.2025

Product code: 24297

Page 8 of 12

Sustained combustibility:

Sustained combustibility

Self-ignition temperature

Solid:

No data available

Gas:

No data available

Oxidizing properties

No data available

Other safety characteristics

Evaporation rate:

No data available

Solvent separation test:

No data available

Solvent content:

100%

Solid content:

No data available

Sublimation point:

No data available

Softening point:

No data available

Pour point:

No data available

Viscosity / dynamic:

0,73 mPa·s

(at 20 °C)

Flow time:

No data available

Further Information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

In case of warming:

Vapours may form explosive mixtures with air.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Oxidising agent

Alkali metals

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

rubber

Plastic articles

various plastics

10.6. Hazardous decomposition products

SECTION 5: Firefighting measures

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicokinetics, metabolism and distribution

No data available

Acute toxicity

Based on available data, the classification criteria are not met.

n-Butyl acetate > 99 % (acetic acid butylester) for analysis

Revision: 11.07.2025

Product code: 24297

Page 9 of 12

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
123-86-4	n-butyl acetate				
	oral	LD50 14130 mg/kg	Rat	Publication (1954)	acute oral toxicity test
	inhalation (4 h) vapour	LC50 > 6,6 mg/l	Rat	Study report (1988)	OECD Guideline 403

Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Repeated exposure may cause skin dryness or cracking.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (n-butyl acetate)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

No data available

Specific effects in experiment on an animal

No data available

Additional information on tests

No data available

Practical experience

No data available

11.2. Information on other hazards**Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

Other information

Pulmonary oedema

Pneumonia

Observe risk of aspiration if vomiting occurs.

Repeated exposure may cause skin dryness or cracking.

Further information

Vapours may cause drowsiness and dizziness.

Anaesthetic state

Has degreasing effect on the skin.

SECTION 12: Ecological information**12.1. Toxicity**

Based on available data, the classification criteria are not met.

n-Butyl acetate > 99 % (acetic acid butylester) for analysis

Revision: 11.07.2025

Product code: 24297

Page 10 of 12

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
123-86-4	n-butyl acetate					
	Acute fish toxicity	LC50 18 mg/l	96 h	Pimephales promelas	Publication (1984)	OECD Guideline 203
	Acute crustacea toxicity	EC50 44 mg/l	48 h	Daphnia sp.	Publication (1959)	OECD Guideline 202
	Crustacea toxicity	NOEC 23,2 mg/l	21 d	Daphnia magna	Study report (2000)	OECD Guideline 211

12.2. Persistence and degradability

98 %; 28 d; aerob

Readily biodegradable (according to OECD criteria).

12.3. Bioaccumulative potential**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
123-86-4	n-butyl acetate	200

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

This substance does not meet the PBT/vPvB criteria of REACH, annex XIII.

12.6. Endocrine disrupting properties

This substance does not have endocrine disrupting properties with respect to non-target organisms.

12.7. Other adverse effects

Avoid release to the environment.

Further information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations.

Do not empty into drains.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number or ID number:	UN 1123
14.2. UN proper shipping name:	BUTYL ACETATES
14.3. Transport hazard class(es):	3
14.4. Packing group:	III
Hazard label:	3
Classification code:	F1

Safety Data Sheet

according to Regulation (EC) No 1907/2006

n-Butyl acetate > 99 % (acetic acid butylester) for analysis

Revision: 11.07.2025

Product code: 24297

Page 11 of 12

Limited quantity: 5 L
Excepted quantity: E1
Transport category: 3
Hazard No: 30
Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1123
14.2. UN proper shipping name: BUTYL ACETATES
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3
Classification code: F1
Limited quantity: 5 L
Excepted quantity: E1

Marine transport (IMDG)

14.1. UN number or ID number: UN 1123
14.2. UN proper shipping name: BUTYL ACETATES
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3
Special Provisions: 223
Limited quantity: 5 L
Excepted quantity: E1
EmS: F-E, S-D

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1123
14.2. UN proper shipping name: BUTYL ACETATES
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3
Special Provisions: A3
Limited quantity Passenger: 10 L
Passenger LQ: Y344
Excepted quantity: E1
IATA-packing instructions - Passenger: 355
IATA-max. quantity - Passenger: 60 L
IATA-packing instructions - Cargo: 366
IATA-max. quantity - Cargo: 220 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40

Information according to Directive 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

National regulatory information

Safety Data Sheet

according to Regulation (EC) No 1907/2006

n-Butyl acetate > 99 % (acetic acid butylester) for analysis

Revision: 11.07.2025

Product code: 24297

Page 12 of 12

Employment restrictions:	Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).
Water hazard class (D):	1 - slightly hazardous to water

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 11.

Abbreviations and acronyms

Flam. Liq. 3: Flammable liquids, hazard category 3

STOT SE 3: Specific target organ toxicity - single exposure, hazard category 3

Relevant H and EUH statements (number and full text)

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

Further Information

Provide appropriate information, instructions and training to users

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.