

according to Regulation (EC) No 1907/2006

Kaliumdichromatlösung 21,35 g/l in Salpetersäure 585 ml HNO3 65%/l zur Analyse

Revision date: 11.09.2024 Product code: 25295 Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Kaliumdichromatlösung 21,35 g/l in Salpetersäure 585 ml HNO3 65%/l zur Analyse

UFI: 7Q18-W20J-V003-59K4

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name: AnalytiChem GmbH

ACD

Street: Stempelstraße 6
Place: D-47167 Duisburg

Telephone: 0203/5194-0 Telefax: 0203/5194-290

E-mail: info@analytichem.de

Contact person: Abteilung Produktsicherheit Telephone: 0203/5194-107/117

E-mail: produktsicherheit@analytichem.de

Internet: www.analytichem.de
Responsible Department: Abteilung Produktsicherheit

1.4. Emergency telephone For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire,

number: Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada:

1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls

accepted)

Further Information

This product is a mixture. REACH Registration Number see section 3.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Met. Corr. 1; H290 Acute Tox. 3; H331 Skin Corr. 1A; H314 Eye Dam. 1; H318 Resp. Sens. 1; H334 Skin Sens. 1; H317 Muta. 1B; H340 Carc. 1B; H350 Repr. 1B; H360FD STOT RE 2; H373 Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008



according to Regulation (EC) No 1907/2006

Kaliumdichromatlösung 21,35 g/l in Salpetersäure 585 ml HNO3 65%/l zur Analyse

Revision date: 11.09.2024 Product code: 25295 Page 2 of 13

Hazard components for labelling

nitric acid 43 % potassium dichromate

Signal word: Danger

Pictograms:







Hazard statements

H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H331 Toxic if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H340 May cause genetic defects.

H350 May cause cancer.

H360FD May damage fertility. May damage the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing and eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water or shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

Special labelling of certain mixtures

EUH071 Corrosive to the respiratory tract.

Restricted to professional users.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixtures in aqueous solution



according to Regulation (EC) No 1907/2006

Kaliumdichromatlösung 21,35 g/l in Salpetersäure 585 ml HNO3 65%/l zur Analyse

Revision date: 11.09.2024 Product code: 25295 Page 3 of 13

Relevant ingredients

CAS No	Chemical name		Quantity				
	EC No	Index No	REACH No				
	Classification (Regulation (EC) No	Classification (Regulation (EC) No 1272/2008)					
7697-37-2	nitric acid						
	231-714-2	007-030-00-3	01-2119487297-23				
	Ox. Liq. 3, Met. Corr. 1, Acute Tox. 3, Skin Corr. 1A; H272 H290 H331 H314 EUH071						
7778-50-9	potassium dichromate						
	231-906-6	024-002-00-6	01-2119454792-32				
	Ox. Sol. 2, Carc. 1B, Muta. 1B, Repr. 1B, Acute Tox. 2, Acute Tox. 3, Acute Tox. 4, Skin Corr. 1B, Eye Dam. 1, Resp. Sens. 1, Skin Sens. 1, STOT RE 1, Aquatic Acute 1, Aquatic Chronic 1; H272 H350 H340 H360FD H330 H301 H312 H314 H318 H334 H317 H372 H400 H410						

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity		
	Specific Conc. I	Limits, M-factors and ATE			
7697-37-2	231-714-2 nitric acid				
		: ATE 2,65 mg/l (vapours) Ox. Liq. 3; H272: >= 65 - 100 Skin Corr. 1A; H314: >= 20 tin Corr. 1B; H314: >= 5 - < 20			
7778-50-9	231-906-6	potassium dichromate	1 - < 5 %		
	inhalation: ATE = 0,5 mg/l (vapours); inhalation: ATE = 0,05 mg/l (dusts or mists); dermal: LD50 = 2000 mg/kg ; oral: LD50 = 129.5 mg/kg STOT SE 3; H335: $= 5 - 100$				

Further Information

No data available

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection! Remove affected person from the danger area and lay down.

After inhalation

Provide fresh air.

Call a physician immediately.

After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

Call a physician immediately.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Remove contact lenses, if present and easy to do. Continue rinsing.

Protect uninjured eye.

After ingestion

Rinse mouth immediately and drink plenty of water.

Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Causes burns.

Irritant

Cough

Dyspnoea



according to Regulation (EC) No 1907/2006

Kaliumdichromatlösung 21,35 g/l in Salpetersäure 585 ml HNO3 65%/l zur Analyse

Revision date: 11.09.2024 Product code: 25295 Page 4 of 13

Vomiting

Methaemoglobinaemia

Risk of serious damage to eyes.

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Non-combustible liquids

Hazardous combustion products

In case of fire may be liberated:

Nitrogen oxides (NOx)

Metal oxide smoke, toxic

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

In case of fire and/or explosion do not breathe fumes.

Avoid contact with skin, eyes and clothes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Move undamaged containers from immediate hazard area if it can be done safely.

Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Corrosive to metals.

For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Consult an expert

Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders: Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Take up carefully when dry. Take up dust-free and set down dust-free.



according to Regulation (EC) No 1907/2006

Kaliumdichromatlösung 21,35 g/l in Salpetersäure 585 ml HNO3 65%/l zur Analyse

Revision date: 11.09.2024 Product code: 25295 Page 5 of 13

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Use personal protection equipment.

Provide adequate ventilation. Avoid contact with skin, eyes and clothes.

Do not breathe vapour/aerosol. Use extractor hood (laboratory).

Advice on protection against fire and explosion

No special fire protection measures are necessary.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs. Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink. Avoid: aerosol or mist formation Do not breathe vapour/aerosol.

Further information on handling

Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary.

Take off immediately all contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaustion at critical locations. Unsuitable container/equipment material: Metal.

Hints on joint storage

national regulations

Further information on storage conditions

Keep container tightly closed.

Store in a dry place.

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
7697-37-2	Nitric acid	1	2.6		STEL (15 min)	



according to Regulation (EC) No 1907/2006

Kaliumdichromatlösung 21,35 g/l in Salpetersäure 585 ml HNO3 65%/l zur Analyse

Revision date: 11.09.2024 Product code: 25295 Page 6 of 13

PNEC values

CAS No	Substance					
Environmenta	Environmental compartment					
7778-50-9	potassium dichromate					
Freshwater						
Freshwater (intermittent releases)		0 mg/l				
Freshwater sediment		0,15 mg/kg				
Marine sediment		0,15 mg/kg				
Secondary poisoning		17000000 mg/kg				
Micro-organisms in sewage treatment plants (STP)		0,21 mg/l				
Soil 0,035						

8.2. Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment

Eye/face protection

goggles

Wear eye/face protection.

Hand protection

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact

Recommended glove articles: KCL 890 Vitoject® Recommended material: FKM (fluoro rubber) 0,7 mm Wearing time with permanent contact: > 480 min

By short-term hand contact

Recommended glove articles: KCL 897 Butoject®

Recommended material: Butyl caoutchouc (butyl rubber) 0,3 mm Wearing time with occasional contact (splashes): > 120 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing.

Wash hands before breaks and after work.

The choice of body protection depends on the concentration and quantity of hazardous substances. The chemical resistance of protective agents must be clarified with their suppliers.

Respiratory protection

Respiratory protection necessary at: aerosol or mist formation

The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Environmental exposure controls

Do not allow to enter into surface water or drains.

Print date: 07.01.2025



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Kaliumdichromatlösung 21,35 g/l in Salpetersäure 585 ml HNO3 65%/l zur Analyse

Revision date: 11.09.2024 Product code: 25295 Page 7 of 13

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid Colour: orange red Odour: like: Nitric acid Odour threshold: No data available

Melting point/freezing point: No data available Boiling point or initial boiling point and No data available

boiling range:

Flammability: not applicable Lower explosion limits: No data available Upper explosion limits: No data available Flash point: No data available Auto-ignition temperature:

No data available Decomposition temperature: pH-Value:

Viscosity / kinematic: No data available

Solubility in other solvents

not determined

Partition coefficient n-octanol/water: No data available Vapour pressure: No data available Vapour pressure: No data available Density: 1,27523 g/cm³ Bulk density: No data available Relative vapour density: No data available

9.2. Other information

Information with regard to physical hazard classes

Explosive properties No data available

Sustaining combustion: No data available

Self-ignition temperature

Solid: not applicable Gas: not applicable

Oxidizing properties Not oxidising.

Other safety characteristics

No data available Evaporation rate: No data available Solvent separation test: Solvent content: 0 0 Solid content: No data available Sublimation point: Softening point: No data available Pour point: No data available

No data available:

Viscosity / dynamic: No data available No data available Flow time:

Further Information Corrosive to metals.

SECTION 10: Stability and reactivity



according to Regulation (EC) No 1907/2006

Kaliumdichromatlösung 21,35 g/l in Salpetersäure 585 ml HNO3 65%/l zur Analyse

Revision date: 11.09.2024 Product code: 25295 Page 8 of 13

10.1. Reactivity

Corrosive to metals. Oxidising agent

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Alkali (lye)

The product develops hydrogen in an aqueous solution in contact with metals.

Amines, Ammonia, Alcohols, Alkali metals, Hydrogen peroxide

Copper, Combustible solids, Solvent, Alkaline earth metal, mercury (Hg).

10.4. Conditions to avoid

No data available

10.5. Incompatible materials

Cellulose

Metal

The product develops hydrogen in an aqueous solution in contact with metals.

10.6. Hazardous decomposition products

In case of fire may be liberated:

SECTION 5: Firefighting measures

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicocinetics, metabolism and distribution

There are no data available on the preparation/mixture itself.

Acute toxicity

Toxic if inhaled.

ATEmix calculated

ATE (oral) > 5000 mg/kg; ATE (dermal) > 5000 mg/kg; ATE (inhalation vapour) 5,330 mg/l; ATE (inhalation dust/mist) 3,704 mg/l

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
7697-37-2	nitric acid					
	inhalation vapour	ATE 2,65	mg/l			
7778-50-9	potassium dichromate					
	oral	LD50 mg/kg	129,5	Rat	Study report (1983)	OECD Guideline 401
	dermal	LD50 mg/kg	> 2000	Rabbit	Study report (1983)	OECD Guideline 402
	inhalation vapour	ATE	0,5 mg/l			
	inhalation dust/mist	ATE	0,05 mg/l			

Irritation and corrosivity



according to Regulation (EC) No 1907/2006

Kaliumdichromatlösung 21,35 g/l in Salpetersäure 585 ml HNO3 65%/l zur Analyse

Revision date: 11.09.2024 Product code: 25295 Page 9 of 13

Skin corrosion/irritation: Causes severe skin burns and eye damage.

Serious eye damage/eye irritation: Causes serious eye damage.

Corrosive to the respiratory tract.

Following ingestion Gastric perforation

Mucous membrane irritation in the mouth, throat, esophagus and gastrointestinal tract.

Irritating to respiratory system.

Pulmonary oedema

see also Section 4

Sensitising effects

May cause allergy or asthma symptoms or breathing difficulties if inhaled. (potassium dichromate)

May cause an allergic skin reaction. (potassium dichromate)

Carcinogenic/mutagenic/toxic effects for reproduction

May cause genetic defects. (potassium dichromate)

May cause cancer. (potassium dichromate)

May damage fertility. May damage the unborn child. (potassium dichromate)

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (potassium dichromate)

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

There are no data available on the preparation/mixture itself.

Additional information on tests

There are no data available on the preparation/mixture itself.

Practical experience

There are no data available on the preparation/mixture itself.

11.2. Information on other hazards

Other information

Causes burns.

Irritant

Cough

Dyspnoea

Vomiting

Methaemoglobinaemia

Risk of serious damage to eyes.

Further information

There are no data available on the preparation/mixture itself.

SECTION 12: Ecological information

12.1. Toxicity

Harmful to aquatic life with long lasting effects.

There are no data available on the mixture itself.



according to Regulation (EC) No 1907/2006

Kaliumdichromatlösung 21,35 g/l in Salpetersäure 585 ml HNO3 65%/l zur Analyse

Revision date: 11.09.2024 Product code: 25295 Page 10 of 13

CAS No	Chemical name							
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method	
7697-37-2	nitric acid							
	Acute fish toxicity	LC50 mg/l	1559	96 h	Topeka shiner	Environmental Toxicology and Chemistry,	other: ASTM E729-26	
	Fish toxicity	NOEC	268 mg/l		juvenile Topeka shiner and with juvenile Fathead m	Study report (2009)	Growth tests estimated the test chemical	
	Algae toxicity	NOEC mg/l	> 419	· ·	several benthic diatoms; see results	Marine Biology 43:307-315 (1977)	Ten cultures of benthic diatoms were iso	
	Acute bacteria toxicity	EC50 mg/l ()	> 1000	3 h	Activated sludge	Study report (2008)	OECD Guideline 209	

12.2. Persistence and degradability

The methods for determining the biological degradability are not applicable to inorganic substances.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Discharge into the environment must be avoided.

Harmful effect due to pH shift.

Forms corrosive mixtures with water even if diluted.

Further information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations.

Do not empty into drains.

Contaminated packaging

This material and its container must be disposed of as hazardous waste. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 2031
14.2. UN proper shipping name: NITRIC ACID

14.3. Transport hazard class(es):814.4. Packing group:IIHazard label:8



according to Regulation (EC) No 1907/2006

Kaliumdichromatlösung 21,35 g/l in Salpetersäure 585 ml HNO3 65%/l zur Analyse

Revision date: 11.09.2024 Product code: 25295 Page 11 of 13

Classification code:

Limited quantity:

Excepted quantity:

Transport category:

Hazard No:

Tunnel restriction code:

C1

Limited quantity:

E2

Racepted quantity:

E3

Racepted quantity:

E4

Racepted quantity:

E5

Racepted quantity:

E6

Racepted quantity:

E7

Racepted quantity:

E8

Racepted quantity:

Racepted quantity:

E8

Racepted quantity:

Racepted quantity:

Racepted quantity:

E8

Racepted quantity:

Racepte

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 2031
14.2. UN proper shipping name: NITRIC ACID

14.3. Transport hazard class(es):814.4. Packing group:IIHazard label:8Classification code:C1Limited quantity:1 LExcepted quantity:E2

Marine transport (IMDG)

14.1. UN number or ID number: UN 2031
14.2. UN proper shipping name: NITRIC ACID

14.3. Transport hazard class(es):814.4. Packing group:IIHazard label:8Special Provisions:-Limited quantity:1 LExcepted quantity:E2EmS:F-A, S-B

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 2031
14.2. UN proper shipping name: NITRIC ACID

14.3. Transport hazard class(es):814.4. Packing group:IIHazard label:8Special Provisions:A212Limited quantity Passenger:ForbiddenPassenger LQ:ForbiddenExcepted quantity:E0

IATA-packing instructions - Passenger: Forbidden
IATA-max. quantity - Passenger: Forbidden
IATA-packing instructions - Cargo: 855
IATA-max. quantity - Cargo: 30 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No.

14.6. Special precautions for user

Warning: strongly corrosive.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Authorisations (REACH, annex XIV):

potassium dichromate



according to Regulation (EC) No 1907/2006

Kaliumdichromatlösung 21,35 g/l in Salpetersäure 585 ml HNO3 65%/l zur Analyse

Revision date: 11.09.2024 Product code: 25295 Page 12 of 13

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28, Entry 75

Information according to Directive

H2 ACUTE TOXIC

2012/18/EU (SEVESO III):

Marketing and use of explosives precursors (Regulation (EU) 2019/1148):

Acquisition, introduction, possession or use of this product by the general public is restricted by Regulation (EU) 2019/1148. All suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point.

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe employment restrictions for women of

child-bearing age.

Water hazard class (D): 3 - highly hazardous to water

Skin resorption/Sensitization: Causes allergic hypersensitivity reactions.

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1,2,9,11,12.

Abbreviations and acronyms

Ox. Liq: Oxidising liquid Ox. Sol: Oxidising solid

Met. Corr: Substance or mixture corrosive to metals

Acute Tox: Acute toxicity Skin Corr: Skin corrosion Eye Dam: Eye damage

Resp. Sens: Respiratory sensitisation

Skin Sens: Skin sensitisation Muta: Germ cell mutagenicity

Carc: Carcinogenicity
Repr: Reproductive toxicity

STOT RE: Specific target organ toxicity - repeated exposure

Aquatic Acute: Acute aquatic hazard Aquatic Chronic: Chronic aquatic hazard

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%



according to Regulation (EC) No 1907/2006

Kaliumdichromatlösung 21,35 g/l in Salpetersäure 585 ml HNO3 65%/l zur Analyse

Revision date: 11.09.2024 Product code: 25295 Page 13 of 13

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Met. Corr. 1; H290	On basis of test data
Acute Tox. 3; H331	Calculation method
Skin Corr. 1A; H314	Calculation method
Eye Dam. 1; H318	Calculation method
Resp. Sens. 1; H334	Calculation method
Skin Sens. 1; H317	Calculation method
Muta. 1B; H340	Calculation method
Carc. 1B; H350	Calculation method
Repr. 1B; H360FD	Calculation method
STOT RE 2; H373	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

veie vai	iit ii aiiu Luii stat	ements (number and run text)
H27	72	May intensify fire; oxidiser.
H29	90	May be corrosive to metals.
H30)1	Toxic if swallowed.
H31	12	Harmful in contact with skin.
H31	14	Causes severe skin burns and eye damage.
H31	17	May cause an allergic skin reaction.
H31	18	Causes serious eye damage.
H33	30	Fatal if inhaled.
H33	31	Toxic if inhaled.
H33	34	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H34	10	May cause genetic defects.
H35	50	May cause cancer.
H36	30FD	May damage fertility. May damage the unborn child.
H37	7 2	Causes damage to organs through prolonged or repeated exposure.
H37	73	May cause damage to organs through prolonged or repeated exposure.
H40	00	Very toxic to aquatic life.
H41	10	Very toxic to aquatic life with long lasting effects.
H41	12	Harmful to aquatic life with long lasting effects.
EUI	H071	Corrosive to the respiratory tract.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)