

# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

# Potassium hydroxide solution (0.5 mol/l) in ethanol 10 % R Reag. Ph. Eur., chapter 4.1.1

Revision: 07.12.2023 Product code: 26768 Page 1 of 13

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Potassium hydroxide solution (0.5 mol/l) in ethanol 10 % R Reag. Ph. Eur., chapter 4.1.1

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Reagents and laboratory chemicals

Only for laboratory and analysis purposes.

#### Uses advised against

Do not use for private purposes (household).

### 1.3. Details of the supplier of the safety data sheet

Company name: AnalytiChem GmbH

ACD

Street: Stempelstraße 6
Place: D-47167 Duisburg

Telephone: 0203/5194-0 Telefax: 0203/5194-290

E-mail: info@analytichem.de

Contact person: Abteilung Produktsicherheit Telephone: 0203/5194-107/117

E-mail: produktsicherheit@analytichem.de

Internet: www.analytichem.de

Responsible Department: Abteilung Produktsicherheit

1.4. Emergency telephone For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada:

Exposure, of Accident Call Childriff Co Day of Night Within Ook and Callada.

1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls

accepted)

#### **Further Information**

This product is a mixture. REACH Registration Number see section 3.

### **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

## Regulation (EC) No 1272/2008

Flam. Liq. 3; H226 Met. Corr. 1; H290 Skin Corr. 1B; H314 Eye Dam. 1; H318

Full text of hazard statements: see SECTION 16.

### 2.2. Label elements

## Regulation (EC) No 1272/2008

## Hazard components for labelling

potassium hydroxide

Signal word: Danger

Pictograms:







# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

# Potassium hydroxide solution (0.5 mol/l) in ethanol 10 % R Reag. Ph. Eur., chapter 4.1.1

Revision: 07.12.2023 Product code: 26768 Page 2 of 13

#### **Hazard statements**

H226 Flammable liquid and vapour. H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

### **Precautionary statements**

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water

or shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

### 2.3. Other hazards

No information available.

# **SECTION 3: Composition/information on ingredients**

### 3.2. Mixtures

### Relevant ingredients

CAS No	Chemical name	Chemical name			
	EC No	Index No	REACH No		
	Classification (Regulation	n (EC) No 1272/2008)	·		
64-17-5	ethanol			5 - < 10 %	
	200-578-6	603-002-00-5	01-2119457610-43		
	Flam. Liq. 2, Eye Irrit. 2; H225 H319				
1310-58-3	potassium hydroxide	potassium hydroxide			
	215-181-3	019-002-00-8	01-2119487136-33		
Met. Corr. 1, Acute Tox. 4, Skin Corr. 1A, Eye Dam. 1; H290 H302 H314 H318			H302 H314 H318		

Full text of H and EUH statements: see section 16.

## Specific Conc. Limits, M-factors and ATE

	I=		
CAS No	EC No	Chemical name	Quantity
	Specific Conc. I	Limits, M-factors and ATE	
64-17-5	200-578-6	ethanol	5 - < 10 %
	inhalation: LC5	0 = 124,7 mg/l (vapours); oral: LD50 = 10470 mg/kg	
1310-58-3	215-181-3	potassium hydroxide	2 - < 5 %
	l l	33 mg/kg Skin Corr. 1A; H314: >= 5 - 100 Skin Corr. 1B; H314: >= 2 - < 5 Skin = 0,5 - < 2 Eye Irrit. 2; H319: >= 0,5 - < 2	

# **Further Information**

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

# **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

### **General information**

No data available

### After inhalation

Provide fresh air.



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

# Potassium hydroxide solution (0.5 mol/l) in ethanol 10 % R Reag. Ph. Eur., chapter 4.1.1

Revision: 07.12.2023 Product code: 26768 Page 3 of 13

Call a physician immediately.

### After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

Call a physician immediately.

### After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Remove contact lenses, if present and easy to do. Continue rinsing. Protect uninjured eye.

#### After ingestion

Rinse mouth immediately and drink plenty of water.

Do NOT induce vomiting.

Do not allow a neutralisation agent to be drunk.

Call a physician immediately.

## 4.2. Most important symptoms and effects, both acute and delayed

corrosive

Irritant

Cough

Dyspnoea

Dizziness

The product causes narcotic-like effects.

Inebriation

Vomiting

Risk of serious damage to eyes.

Corneal opacity.

#### 4.3. Indication of any immediate medical attention and special treatment needed

No data available

## **SECTION 5: Firefighting measures**

# 5.1. Extinguishing media

# Suitable extinguishing media

Water spray jet, Carbon dioxide (CO2), Foam, Extinguishing powder.

# Unsuitable extinguishing media

no restriction

### 5.2. Special hazards arising from the substance or mixture

Combustible liquid.

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Hazardous combustion products

In case of fire may be liberated:

Carbon dioxide (CO2), Carbon monoxide

## 5.3. Advice for firefighters

Remove persons to safety. Do not inhale explosion and combustion gases.

Avoid contact with skin, eyes and clothes.

In case of fire: Wear self-contained breathing apparatus.

Use water spray jet to protect personnel and to cool endangered containers.

## **Additional information**

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Suppress gases/vapours/mists with water spray jet.

Move undamaged containers from immediate hazard area if it can be done safely.



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

# Potassium hydroxide solution (0.5 mol/l) in ethanol 10 % R Reag. Ph. Eur., chapter 4.1.1

Revision: 07.12.2023 Product code: 26768 Page 4 of 13

# **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

#### General advice

Keep away from sources of ignition - No smoking.

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

Take action to prevent static discharges.

Corrosive to metals.

### For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

**Emergency procedures** 

Consult an expert

Do not breathe dust/fume/gas/mist/vapours/spray.

#### For emergency responders

Precautionary statements For emergency responders: Personal protection equipment: see section 8

#### 6.2. Environmental precautions

Do not allow to enter into surface water or drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Danger of explosion

#### 6.3. Methods and material for containment and cleaning up

#### For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

#### For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

#### Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

# 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

## **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

# Advice on safe handling

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Keep container tightly closed.

Use personal protection equipment. Use extractor hood (laboratory).

Do not breathe vapour/aerosol. Provide adequate ventilation.



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

## Potassium hydroxide solution (0.5 mol/l) in ethanol 10 % R Reag. Ph. Eur., chapter 4.1.1

Revision: 07.12.2023 Product code: 26768 Page 5 of 13

## Advice on protection against fire and explosion

Take action to prevent static discharges. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

### Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink. The choice of body protection depends on the concentration and quantity of hazardous substances. The chemical resistance of protective agents must be clarified with their suppliers.

#### Further information on handling

Take off immediately all contaminated clothing and wash it before reuse.

Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

#### Hints on joint storage

Do not store together with: Oxidising agent. Pyrophoric or self-heating substances. national regulations

## Further information on storage conditions

Vapours may form explosive mixtures with air.

#### 7.3. Specific end use(s)

Laboratory use Laboratory chemical

## **SECTION 8: Exposure controls/personal protection**

## 8.1. Control parameters

## Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
64-17-5	Ethyl alcohol	1000	-		STEL (15 min)	
1310-58-3	Potassium hydroxide	-	2		STEL (15 min)	

# **DNEL/DMEL values**

CAS No	Substance				
DNEL type		Exposure route	Effect	Value	
64-17-5	ethanol				
Worker DNE	L, long-term	inhalation	systemic	950 mg/m³	
Worker DNEL, long-term		dermal	systemic	343 mg/kg bw/day	
Consumer DNEL, long-term		inhalation	systemic	114 mg/m³	
Consumer DNEL, long-term		dermal	systemic	206 mg/kg bw/day	
Consumer D	NEL, long-term	oral	systemic	87 mg/kg bw/day	
1310-58-3 potassium hydroxide					
Worker DNEL, long-term inhalation			local	1 mg/m³	
Consumer D	NEL, long-term	inhalation	local	1 mg/m³	



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

## Potassium hydroxide solution (0.5 mol/l) in ethanol 10 % R Reag. Ph. Eur., chapter 4.1.1

Revision: 07.12.2023 Product code: 26768 Page 6 of 13

#### **PNEC values**

CAS No	Substance	
Environmenta	I compartment	Value
64-17-5	ethanol	
Freshwater		0,96 mg/l
Freshwater (intermittent releases) 2,75 m		2,75 mg/l
Marine water		0,79 mg/l
Freshwater sediment		3,6 mg/kg
Marine sediment		2,9 mg/kg
Secondary poisoning		380 mg/kg
Micro-organisms in sewage treatment plants (STP) 58		580 mg/l
Soil		0,63 mg/kg

#### 8.2. Exposure controls

## Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

#### Individual protection measures, such as personal protective equipment

#### Eve/face protection

Suitable eye protection: goggles.

# **Hand protection**

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact

Recommended glove articles: KCL 897 Butoject®
Suitable material: Butyl caoutchouc (butyl rubber) 0,3 mm
Wearing time with permanent contact: > 480 min

By short-term hand contact

Recommended glove articles KCL 720 Camapren®

Suitable material: CR (polychloroprene, chloroprene rubber) 0,65 mm

Wearing time with occasional contact (splashes): > 60 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

## Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing

### Respiratory protection

Respiratory protection necessary at: aerosol or mist formation

The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

# **Environmental exposure controls**

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

# Potassium hydroxide solution (0.5 mol/l) in ethanol 10 % R Reag. Ph. Eur., chapter 4.1.1

Revision: 07.12.2023 Product code: 26768 Page 7 of 13

Danger of explosion

## **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state:

Colour:

Odour:

Odour threshold:

Liquid

clear / yellow

like: Ethanol

No data available

Melting point/freezing point:

Boiling point or initial boiling point and

No data available

No data available

boiling range:

not applicable Flammability: No data available Lower explosion limits: Upper explosion limits: No data available 47 °C Flash point: Auto-ignition temperature: No data available No data available Decomposition temperature: alkaline pH-Value: No data available Viscosity / kinematic: Soluble in: Water Water solubility:

Solubility in other solvents

not determined

Dissolution rate: No data available No data available Partition coefficient n-octanol/water: No data available Dispersion stability: No data available Vapour pressure: No data available Vapour pressure: 1.00615 a/cm<sup>3</sup> Density: No data available Relative density: No data available Bulk density: Relative vapour density: not determined No data available Particle characteristics:

# 9.2. Other information

# Information with regard to physical hazard classes

Explosive properties

Vapours can form explosive mixtures with air.

Sustained combustibility: No data available

Self-ignition temperature

Solid: not applicable
Gas: not applicable

Oxidizing properties Not oxidising.

## Other safety characteristics

Evaporation rate:

Solvent separation test:

No data available
Solvent content:

No data available
Solid content:

No data available
Sublimation point:

No data available
Softening point:

No data available
Pour point:

No data available



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

## Potassium hydroxide solution (0.5 mol/l) in ethanol 10 % R Reag. Ph. Eur., chapter 4.1.1

Revision: 07.12.2023 Product code: 26768 Page 8 of 13

No data available:

Viscosity / dynamic:

Flow time:

No data available

No data available

**Further Information** 

May be corrosive to metals.

# **SECTION 10: Stability and reactivity**

## 10.1. Reactivity

Vapours can form explosive mixtures with air.

May be corrosive to metals.

### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

### 10.3. Possibility of hazardous reactions

Oxidising agent, Hydrogen peroxide, Nitric acid, Alkali metals, Alkaline earth metal

Chlorine, Fluorine, silver, permanganates, e.g. potassium permanganate

#### 10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

## 10.5. Incompatible materials

Glass

Plastic articles

Metal

## 10.6. Hazardous decomposition products

Hazardous combustion products

In case of fire may be liberated: Carbon dioxide (CO2), Carbon monoxide

## **Further information**

No data available

## **SECTION 11: Toxicological information**

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

# Toxicocinetics, metabolism and distribution

There are no data available on the mixture itself.

#### **Acute toxicity**

Based on available data, the classification criteria are not met.

If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects).

Mucous membrane irritation in the mouth, throat, esophagus and gastrointestinal tract.

Inhalation effect: Damage to the respiratory tract.

Resorption (by inhalation)

## **ATEmix calculated**

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

# Potassium hydroxide solution (0.5 mol/l) in ethanol 10 % R Reag. Ph. Eur., chapter 4.1.1

Revision: 07.12.2023 Product code: 26768 Page 9 of 13

CAS No	Chemical name						
	Exposure route	Dose		Species	Source	Method	
64-17-5	ethanol						
	oral	LD50 mg/kg	10470	Rat	Study report (1976)	OECD Guideline 401	
	inhalation (4 h) vapour	LC50 mg/l	124,7	Rat	Study report (1980)	OECD Guideline 403	
1310-58-3	potassium hydroxide						
	oral	LD50 mg/kg	333		Fund. Appl. Toxicol., 8, 97-100 (1987)	OECD Guideline 425	

## Irritation and corrosivity

Skin corrosion/irritation: Causes severe skin burns and eye damage.

Serious eye damage/eye irritation: Causes serious eye damage.

Risk of serious damage to eyes.

#### Sensitising effects

Based on available data, the classification criteria are not met.

#### Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

### STOT-single exposure

Based on available data, the classification criteria are not met.

## STOT-repeated exposure

Based on available data, the classification criteria are not met.

# **Aspiration hazard**

Based on available data, the classification criteria are not met.

Observe risk of aspiration if vomiting occurs.

#### Information on likely routes of exposure

There are no data available on the mixture itself.

### Specific effects in experiment on an animal

There are no data available on the mixture itself.

### Additional information on tests

There are no data available on the mixture itself.

## **Practical experience**

There are no data available on the mixture itself.

## 11.2. Information on other hazards

## **Endocrine disrupting properties**

There are no data available on the mixture itself.

## Other information

corrosive

Irritant

Cough

Dyspnoea

Dizziness

The product causes narcotic-like effects.

Inebriation

Vomiting

Risk of serious damage to eyes.



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

# Potassium hydroxide solution (0.5 mol/l) in ethanol 10 % R Reag. Ph. Eur., chapter 4.1.1

Revision: 07.12.2023 Product code: 26768 Page 10 of 13

Corneal opacity.

### **Further information**

Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).

# **SECTION 12: Ecological information**

## 12.1. Toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h]   [d]	Species	Source	Method
64-17-5	ethanol						
	Acute fish toxicity	LC50 mg/l	15400	96 h	Lepomis macrochirus	Bulletin of Environmental Contamination	other: EPA-660/3-75-00 9, 1975
	Acute algae toxicity	ErC50 22000 mg/l	ca.	96 h	Pseudokirchneriella subcapitata	Ecotoxicology and Environmental Safety 7	OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	> 10000	48 h	Daphnia magna	Water Research 23(4): 495-499 (1989)	other: DIN 38412 Teil 11
	Algae toxicity	NOEC mg/l	5400	5 d	Skeletonema costatum	Environ Toxicol Chem 8(5):451-455. (1989	Study to determine the sensitivity of a
	Crustacea toxicity	NOEC	2 mg/l	10 d	Ceriodaphnia dubia	Arch Environ Contam Toxicol 20(2):211-21	Follows the basic methodology for the th

# 12.2. Persistence and degradability

There are no data available on the mixture itself.

## 12.3. Bioaccumulative potential

There are no data available on the mixture itself.

# Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
64-17-5	ethanol	-0,77

## **BCF**

CAS No	Chemical name	BCF	Species	Source
64-17-5	ethanol	1	Cyprinus carpio	Comparative Biochemi

# 12.4. Mobility in soil

There are no data available on the mixture itself.

### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

## 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

# 12.7. Other adverse effects

Do not allow to enter into surface water or drains.



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

# Potassium hydroxide solution (0.5 mol/l) in ethanol 10 % R Reag. Ph. Eur., chapter 4.1.1

Revision: 07.12.2023 Product code: 26768 Page 11 of 13

#### **Further information**

Avoid release to the environment.

## **SECTION 13: Disposal considerations**

## 13.1. Waste treatment methods

#### Disposal recommendations

Do not allow to enter into surface water or drains.

Send to a physico-chemical treatment facility under observation of official regulations.

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

### Contaminated packaging

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

Handle contaminated packages in the same way as the substance itself.

## **SECTION 14: Transport information**

444 LIN	number or ID number:	UN 2920
14.1. UN	number or ID number:	UN 2920

14.2. UN proper shipping name: CORROSIVE LIQUID, FLAMMABLE, N.O.S. (potassium hydroxide,

ethanol)

14.3. Transport hazard class(es): 8 Ш 14.4. Packing group: Hazard label: 8+3 CF1 Classification code: **Special Provisions:** 274 1 L Limited quantity: F2 Excepted quantity: Transport category: 2 Hazard No: 83

Inland waterways transport (ADN)

Tunnel restriction code:

14.1. UN number or ID number: UN 2920

14.2. UN proper shipping name: CORROSIVE LIQUID, FLAMMABLE, N.O.S. (potassium hydroxide,

ethanol)

D/E

14.3. Transport hazard class(es):814.4. Packing group:IIHazard label:8+3Classification code:CF1Special Provisions:274Limited quantity:1 LExcepted quantity:E2

Marine transport (IMDG)

14.1. UN number or ID number: UN 2920

**14.2. UN proper shipping name:** CORROSIVE LIQUID, FLAMMABLE, N.O.S. (potassium hydroxide,

ethanol)

14.3. Transport hazard class(es):814.4. Packing group:IIHazard label:8+3Special Provisions:274Limited quantity:1 LExcepted quantity:E2



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

# Potassium hydroxide solution (0.5 mol/l) in ethanol 10 % R Reag. Ph. Eur., chapter 4.1.1

Revision: 07.12.2023 Product code: 26768 Page 12 of 13

EmS: F-E, S-C

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 2920

**14.2. UN proper shipping name:** CORROSIVE LIQUID, FLAMMABLE, N.O.S. (potassium hydroxide,

ethanol)

14.3. Transport hazard class(es):814.4. Packing group:IIHazard label:8+3Limited quantity Passenger:0.5 LPassenger LQ:Y840Excepted quantity:E2

IATA-packing instructions - Passenger:851IATA-max. quantity - Passenger:1 LIATA-packing instructions - Cargo:855IATA-max. quantity - Cargo:30 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: Combustible liquid.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

# **SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **EU** regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Information according to Directive

2012/18/EU (SEVESO III):

P5c FLAMMABLE LIQUIDS

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

### **SECTION 16: Other information**

#### Changes

This data sheet contains changes from the previous version in section(s): 2,4,5,8,9,10,11,12,13,14,15.



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

# Potassium hydroxide solution (0.5 mol/l) in ethanol 10 % R Reag. Ph. Eur., chapter 4.1.1

Revision: 07.12.2023 Product code: 26768 Page 13 of 13

#### Abbreviations and acronyms

Met. Corr. 1: Corrosive to metals, hazard category 1 Flam. Liq. 2: Flammable liquids, hazard category 2 Acute Tox. 4: Acute toxicity, hazard category 4 Skin Corr. 1A: Skin corrosion, sub-category 1A Eye Dam. 1: Serious eye damage, hazard category 1

Eye Irrit. 2: Eye irritation, hazard category 2

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

### Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 3; H226	On basis of test data
Met. Corr. 1; H290	On basis of test data
Skin Corr. 1B; H314	Calculation method
Eye Dam. 1; H318	Calculation method

## Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H290	May be corrosive to metals.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.

### **Further Information**

Provide appropriate information, instructions and training to users

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)