

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Ätzlösung für Titan-Alloys (PW4000 Engine Mounts) 200 ml HNO₃ 69% + 20 ml HF 49%/l

Revision date: 10.12.2024

Product code: 27159

Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Ätzlösung für Titan-Alloys (PW4000 Engine Mounts) 200 ml HNO₃ 69% + 20 ml HF 49%/l

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name:	AnalytiChem GmbH	
	ACD	
Street:	Stempelstraße 6	
Place:	D-47167 Duisburg	
Telephone:	0203/5194-0	Telefax: 0203/5194-290
E-mail:	info@analytichem.de	
Contact person:	Abteilung Produktsicherheit	Telephone: 0203/5194-107/117
E-mail:	produktsicherheit@analytichem.de	
Internet:	www.analytichem.de	
Responsible Department:	Abteilung Produktsicherheit	

1.4. Emergency telephone number:

For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

Further Information

This product is a mixture. REACH Registration Number see section 3.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Met. Corr. 1; H290
Acute Tox. 2; H330
Acute Tox. 3; H301
Acute Tox. 3; H311
Skin Corr. 1A; H314
Eye Dam. 1; H318

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

nitric acid 18,29 %
hydrofluoric acid 1,1 %

Signal word: Danger

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Ätzlösung für Titan-Alloys (PW4000 Engine Mounts) 200 ml HNO₃ 69% + 20 ml HF 49%/l

Revision date: 10.12.2024

Product code: 27159

Page 2 of 13

Pictograms:



Hazard statements

- H290 May be corrosive to metals.
H301+H311 Toxic if swallowed or in contact with skin.
H330 Fatal if inhaled.
H314 Causes severe skin burns and eye damage.

Precautionary statements

- P260
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Special labelling of certain mixtures

- EUH071 Corrosive to the respiratory tract.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixtures in aqueous solution

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
7697-37-2	nitric acid			15 - < 20 %
	231-714-2	007-030-00-3	01-2119487297-23	
	Ox. Liq. 3, Met. Corr. 1, Acute Tox. 3, Skin Corr. 1A; H272 H290 H331 H314 EUH071			
7664-39-3	hydrofluoric acid ... %			1 - < 5 %
	231-634-8	009-003-00-1		
	Acute Tox. 1, Acute Tox. 2, Acute Tox. 2, Skin Corr. 1A; H310 H330 H300 H314			

Full text of H and EUH statements: see section 16.

Ätzlösung für Titan-Alloys (PW4000 Engine Mounts) 200 ml HNO₃ 69% + 20 ml HF 49%/l

Revision date: 10.12.2024

Product code: 27159

Page 3 of 13

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
7697-37-2	231-714-2	nitric acid	15 - < 20 %
		inhalation: ATE 2,65 mg/l (vapours) Ox. Liq. 3; H272: >= 65 - 100 Skin Corr. 1A; H314: >= 20 - 100 Skin Corr. 1B; H314: >= 5 - < 20	
7664-39-3	231-634-8	hydrofluoric acid ... %	1 - < 5 %
		inhalation: ATE = 0,5 mg/l (vapours); inhalation: ATE = 0,05 mg/l (dusts or mists); inhalation: LC50 = 2240 ppm (gases); dermal: ATE = 5 mg/kg; oral: ATE = 5 mg/kg Skin Corr. 1A; H314: >= 7 - 100 Skin Corr. 1B; H314: >= 1 - < 7 Eye Irrit. 2; H319: >= 0,1 - < 1	

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection! Remove affected person from the danger area and lay down.

After inhalation

Provide fresh air.

If breathing is irregular or stopped, administer artificial respiration.

Call a physician immediately.

After contact with skin

Rinse with plenty of water for at least 10 minutes. Immediately remove contaminated clothes. Apply calcium gluconate gel (preparation: boil 5 g of calcium gluconate in 85 ml of hot distilled water, add 10 g glycerol. Allow 5 g of Carmellose-sodium to swell in the hot solution. Stable for 6 months, store in a cool place) and massage into the skin until the pain subsides, in between rinse with water and apply fresh gel. Continue gel therapy for another 15 minutes after the pain has subsided. If no calcium gluconate gel is available, apply several dressings thoroughly moistened with 20 % calcium gluconate solution. Medical advice absolutely required!

Wash immediately with: Water

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Remove contact lenses, if present and easy to do. Continue rinsing.

Protect uninjured eye.

After ingestion

Rinse mouth immediately and drink plenty of water.

Do NOT induce vomiting. Do not allow a neutralisation agent to be drunk.

Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Causes burns.

Irritant

Cough

Dyspnoea

Vomiting

Methaemoglobinaemia

Risk of serious damage to eyes.

4.3. Indication of any immediate medical attention and special treatment needed

It is recommended to consult a doctor with experience in the treatment of lesions caused by hydrofluoric acid

No data available

Ätzlösung für Titan-Alloys (PW4000 Engine Mounts) 200 ml HNO₃ 69% + 20 ml HF 49%/l

Revision date: 10.12.2024

Product code: 27159

Page 4 of 13

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Non-combustible liquids

Hazardous combustion products

In case of fire may be liberated:

Nitrogen oxides (NO_x)

Hydrogen fluoride

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

In case of fire and/or explosion do not breathe fumes.

Avoid contact with skin, eyes and clothes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Move undamaged containers from immediate hazard area if it can be done safely.

Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Corrosive to metals.

For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Consult an expert

Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Ätzlösung für Titan-Alloys (PW4000 Engine Mounts) 200 ml HNO₃ 69% + 20 ml HF 49%/l

Revision date: 10.12.2024

Product code: 27159

Page 5 of 13

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Use personal protection equipment.

Provide adequate ventilation. Avoid contact with skin, eyes and clothes.

Do not breathe vapour/aerosol. Use extractor hood (laboratory).

Advice on protection against fire and explosion

No special fire protection measures are necessary.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs. Remove contaminated, saturated clothing immediately.

Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink. Avoid: aerosol or mist formation Do not breathe vapour/aerosol.

Further information on handling

Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary.

Take off immediately all contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaust at critical locations. Unsuitable container/equipment material:

Metal, Glass

Hints on joint storage

national regulations

Further information on storage conditions

Store in a well-ventilated place. Keep container tightly closed.

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
7664-39-3	Hydrogen fluoride (as F)	1.8	1.5		TWA (8 h)	
		3	2.5		STEL (15 min)	
7697-37-2	Nitric acid	1	2.6		STEL (15 min)	

Biological limit values

CAS No	Substance	Parameter	Value	Test material	Sampling time
7664-39-3	Hydrogen fluoride	Fluoride	2 mg/L	Urine	Prior to shift

Ätzlösung für Titan-Alloys (PW4000 Engine Mounts) 200 ml HNO₃ 69% + 20 ml HF 49%/l

Revision date: 10.12.2024

Product code: 27159

Page 6 of 13

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
7664-39-3	hydrofluoric acid ... %			
Worker DNEL, long-term		inhalation	systemic	1,5 mg/m ³
Worker DNEL, acute		inhalation	systemic	2,5 mg/m ³
Worker DNEL, long-term		inhalation	local	1,5 mg/m ³
Worker DNEL, acute		inhalation	local	2,5 mg/m ³
Consumer DNEL, long-term		inhalation	systemic	0,03 mg/m ³
Consumer DNEL, acute		inhalation	systemic	0,03 mg/m ³
Consumer DNEL, long-term		inhalation	local	0,2 mg/m ³
Consumer DNEL, acute		inhalation	local	1,25 mg/m ³
Consumer DNEL, long-term		oral	systemic	0,01 mg/kg bw/day
Consumer DNEL, acute		oral	systemic	0,01 mg/kg bw/day

PNEC values

CAS No	Substance	Value
7664-39-3	hydrofluoric acid ... %	
Freshwater		0,89 mg/l
Marine water		0,089 mg/l
Freshwater sediment		3,38 mg/kg
Marine sediment		0,338 mg/kg
Micro-organisms in sewage treatment plants (STP)		51 mg/l
Soil		10,6 mg/kg

8.2. Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment

Eye/face protection

goggles

Wear eye/face protection.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Ätzlösung für Titan-Alloys (PW4000 Engine Mounts) 200 ml HNO₃ 69% + 20 ml HF 49%/l

Revision date: 10.12.2024

Product code: 27159

Page 7 of 13

Trade name/designation: KCL 897 Butoject®
Recommended material: Butyl caoutchouc (butyl rubber) 0,3 mm
Wearing time with permanent contact: > 480 min

By short-term hand contact

Trade name/designation: KCL 720 Camapren®
Recommended material: CR (polychloroprene, chloroprene rubber) 0,65 mm
Wearing time with occasional contact (splashes): > 240 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing.

Wash hands before breaks and after work.

The choice of body protection depends on the concentration and quantity of hazardous substances. The chemical resistance of protective agents must be clarified with their suppliers.

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	colourless
Odour:	stinging
Odour threshold:	No data available
Melting point/freezing point:	No data available
Boiling point or initial boiling point and boiling range:	No data available
Flammability:	not applicable
Lower explosion limits:	No data available
Upper explosion limits:	No data available
Flash point:	No data available
Auto-ignition temperature:	No data available
Decomposition temperature:	not determined
pH-Value:	acidic
Viscosity / kinematic:	No data available
Solubility in other solvents	
not determined	
Partition coefficient n-octanol/water:	No data available
Vapour pressure:	No data available
Vapour pressure:	No data available
Density:	1,18042 g/cm ³
Bulk density:	No data available
Relative vapour density:	No data available

9.2. Other information

Ätzlösung für Titan-Alloys (PW4000 Engine Mounts) 200 ml HNO₃ 69% + 20 ml HF 49%/l

Revision date: 10.12.2024

Product code: 27159

Page 8 of 13

Information with regard to physical hazard classes

Explosive properties

No data available

Sustaining combustion:

No data available

Self-ignition temperature

Solid:

not applicable

Gas:

not applicable

Oxidizing properties

Not oxidising.

Other safety characteristics

Evaporation rate:

No data available

Solvent separation test:

No data available

Solvent content:

0

Solid content:

0

Sublimation point:

No data available

Softening point:

No data available

Pour point:

No data available

No data available:

Viscosity / dynamic:

No data available

Flow time:

No data available

Further Information

Corrosive to metals.

SECTION 10: Stability and reactivity

10.1. Reactivity

Corrosive to metals.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Alkali (lye)

The product develops hydrogen in an aqueous solution in contact with metals.

Amines, Ammonia, Alcohols, Alkali metals, Hydrogen peroxide

Copper, Combustible solids, Solvent, Alkaline earth metal, mercury (Hg).

10.4. Conditions to avoid

No data available

10.5. Incompatible materials

Cellulose

Glass

Metal

The product develops hydrogen in an aqueous solution in contact with metals.

10.6. Hazardous decomposition products

In case of fire may be liberated:

SECTION 5: Firefighting measures

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Ätzlösung für Titan-Alloys (PW4000 Engine Mounts) 200 ml HNO₃ 69% + 20 ml HF 49%/l

Revision date: 10.12.2024

Product code: 27159

Page 9 of 13

Toxicokinetics, metabolism and distribution

There are no data available on the preparation/mixture itself.

Acute toxicity

Fatal if inhaled.

Toxic if swallowed.

Toxic in contact with skin.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
7697-37-2	nitric acid				
	inhalation vapour	ATE 2,65 mg/l			
7664-39-3	hydrofluoric acid ... %				
	oral	ATE 5 mg/kg			
	dermal	ATE 5 mg/kg			
	inhalation vapour	ATE 0,5 mg/l			
	inhalation dust/mist	ATE 0,05 mg/l			
	inhalation (1 h) gas	LC50 2240 ppm	Rat	Study report (1990)	OECD Guideline 403

Irritation and corrosivity

Skin corrosion/irritation: Causes severe skin burns and eye damage.

Serious eye damage/eye irritation: Causes serious eye damage.

Corrosive to the respiratory tract.

Following ingestion Gastric perforation

Mucous membrane irritation in the mouth, throat, esophagus and gastrointestinal tract.

Irritating to respiratory system.

Pulmonary oedema

see also Section 4

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

There are no data available on the preparation/mixture itself.

Additional information on tests

There are no data available on the preparation/mixture itself.

Practical experience

There are no data available on the preparation/mixture itself.

11.2. Information on other hazards

Other information

There are no data available on the preparation/mixture itself.

Ätzlösung für Titan-Alloys (PW4000 Engine Mounts) 200 ml HNO₃ 69% + 20 ml HF 49%/l

Revision date: 10.12.2024

Product code: 27159

Page 10 of 13

Further information

There are no data available on the preparation/mixture itself.

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
7697-37-2	nitric acid					
	Acute fish toxicity	LC50 1559 mg/l	96 h	Topeka shiner	Environmental Toxicology and Chemistry,	other: ASTM E729-26
	Fish toxicity	NOEC 268 mg/l	30 d	juvenile Topeka shiner and with juvenile Fathead m	Study report (2009)	Growth tests estimated the test chemical
	Algae toxicity	NOEC > 419 mg/l	10 d	several benthic diatoms; see results	Marine Biology 43:307-315 (1977)	Ten cultures of benthic diatoms were iso
	Acute bacteria toxicity	EC50 > 1000 mg/l ()	3 h	Activated sludge	Study report (2008)	OECD Guideline 209
7664-39-3	hydrofluoric acid ... %					
	Acute fish toxicity	LC50 299 mg/l	96 h	Salmo trutta	REACH Registration Dossier	other: U.S Environmental Protection Agen
	Acute algae toxicity	ErC50 43 mg/l	96 h	various algae species	REACH Registration Dossier	Methods not detailed in the review.
	Crustacea toxicity	NOEC 3,7 mg/l	21 d	Daphnia magna	REACH Registration Dossier	The publication is a review article of v
	Acute bacteria toxicity	EC50 2930 mg/l ()	3 h	Activated sludge	REACH Registration Dossier	ISO 8192

12.2. Persistence and degradability

The product has not been tested.

12.3. Bioaccumulative potential

The product has not been tested.

BCF

CAS No	Chemical name	BCF	Species	Source
7664-39-3	hydrofluoric acid ... %	53 - 58	not specified	REACH Registration D

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Harmful effect due to pH shift.

Forms corrosive mixtures with water even if diluted.

Ätzlösung für Titan-Alloys (PW4000 Engine Mounts) 200 ml HNO₃ 69% + 20 ml HF 49%/l

Revision date: 10.12.2024

Product code: 27159

Page 11 of 13

Further information

Do not allow to enter into surface water or drains.
Discharge into the environment must be avoided.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.
Send to a physico-chemical treatment facility under observation of official regulations.
Do not empty into drains.

Contaminated packaging

This material and its container must be disposed of as hazardous waste. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:	UN 2922
14.2. UN proper shipping name:	CORROSIVE LIQUID, TOXIC, N.O.S. (nitric acid, Hydrofluoric acid)
14.3. Transport hazard class(es):	8
14.4. Packing group:	II
Hazard label:	8+6.1
Classification code:	CT1
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	86
Tunnel restriction code:	E

Inland waterways transport (ADN)

14.1. UN number or ID number:	UN 2922
14.2. UN proper shipping name:	CORROSIVE LIQUID, TOXIC, N.O.S. (nitric acid, Hydrofluoric acid)
14.3. Transport hazard class(es):	8
14.4. Packing group:	II
Hazard label:	8+6.1
Classification code:	CT1
Special Provisions:	274 802
Limited quantity:	1 L
Excepted quantity:	E2

Marine transport (IMDG)

14.1. UN number or ID number:	UN 2922
14.2. UN proper shipping name:	CORROSIVE LIQUID, TOXIC, N.O.S. (nitric acid, Hydrofluoric acid)
14.3. Transport hazard class(es):	8
14.4. Packing group:	II
Hazard label:	8+6.1
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2
EmS:	F-A, S-B

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:	UN 2922
14.2. UN proper shipping name:	CORROSIVE LIQUID, TOXIC, N.O.S. (nitric acid, Hydrofluoric acid)

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Ätzlösung für Titan-Alloys (PW4000 Engine Mounts) 200 ml HNO₃ 69% + 20 ml HF 49%/l

Revision date: 10.12.2024

Product code: 27159

Page 12 of 13

14.3. Transport hazard class(es):	8
14.4. Packing group:	II
Hazard label:	8+6.1
Special Provisions:	A3 A803
Limited quantity Passenger:	0.5 L
Passenger LQ:	Y840
Excepted quantity:	E2
IATA-packing instructions - Passenger:	851
IATA-max. quantity - Passenger:	1 L
IATA-packing instructions - Cargo:	855
IATA-max. quantity - Cargo:	30 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: Toxic. strongly corrosive.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3

Marketing and use of explosives precursors (Regulation (EU) 2019/1148):

Acquisition, introduction, possession or use of this product by the general public is restricted by Regulation (EU) 2019/1148. All suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point.

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D): 1 - slightly hazardous to water

Skin resorption/Sensitization: Permeates easily through outer skin and causes poisoning.

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 9,12.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Ätzlösung für Titan-Alloys (PW4000 Engine Mounts) 200 ml HNO₃ 69% + 20 ml HF 49%/l

Revision date: 10.12.2024

Product code: 27159

Page 13 of 13

Abbreviations and acronyms

Ox. Liq: Oxidising liquid
Met. Corr: Substance or mixture corrosive to metals
Acute Tox: Acute toxicity
Skin Corr: Skin corrosion
Eye Dam: Eye damage
ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service
LC50: Lethal concentration, 50%
LD50: Lethal dose, 50%

Relevant H and EUH statements (number and full text)

H272	May intensify fire; oxidiser.
H290	May be corrosive to metals.
H300	Fatal if swallowed.
H301	Toxic if swallowed.
H301+H311	Toxic if swallowed or in contact with skin.
H310	Fatal in contact with skin.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
EUH071	Corrosive to the respiratory tract.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)