

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### **Toluene / ethanol mixture mixed 1:1 volumetrically for the determination of the acid value and acidi**

Revision date: 20.03.2024

Product code: 27956

Page 1 of 14

#### **SECTION 1: Identification of the substance/mixture and of the company/undertaking**

##### **1.1. Product identifier**

Toluene / ethanol mixture mixed 1:1 volumetrically for the determination of the acid value and acidi

UFI: C5EG-Q2PW-V00Y-DQ6T

##### **1.2. Relevant identified uses of the substance or mixture and uses advised against**

###### **Use of the substance/mixture**

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

###### **Uses advised against**

Do not use for private purposes (household).

##### **1.3. Details of the supplier of the safety data sheet**

Company name:	AnalytiChem GmbH	
	ACD	
Street:	Stempelstraße 6	
Place:	D-47167 Duisburg	
Telephone:	0203/5194-0	Telefax: 0203/5194-290
E-mail:	info@analytichem.de	
Contact person:	Abteilung Produktsicherheit	Telephone: 0203/5194-107/117
E-mail:	produktsicherheit@analytichem.de	
Internet:	www.analytichem.de	
Responsible Department:	Abteilung Produktsicherheit	

##### **1.4. Emergency telephone number:**

For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

##### **Further Information**

This product is a mixture. REACH Registration Number see section 3.

#### **SECTION 2: Hazards identification**

##### **2.1. Classification of the substance or mixture**

###### **Regulation (EC) No 1272/2008**

Flam. Liq. 2; H225

Asp. Tox. 1; H304

Skin Irrit. 2; H315

Repr. 2; H361d

STOT SE 3; H336

STOT RE 2; H373

Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

##### **2.2. Label elements**

###### **Regulation (EC) No 1272/2008**

###### **Hazard components for labelling**

toluene

**Signal word:** Danger

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Toluene / ethanol mixture mixed 1:1 volumetrically for the determination of the acid value and acidi

Revision date: 20.03.2024

Product code: 27956

Page 2 of 14

#### Pictograms:



#### Hazard statements

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

#### Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe mist/vapours/spray.
P280	Wear protective gloves/protective clothing and eye protection/face protection.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331	Do NOT induce vomiting.
P403+P235	Store in a well-ventilated place. Keep cool.

#### 2.3. Other hazards

No information available.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

##### Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
108-88-3	toluene			50 - < 55 %
	203-625-9	601-021-00-3	01-2119471310-51	
	Flam. Liq. 2, Repr. 2, Skin Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1, Aquatic Chronic 3; H225 H361d H315 H336 H373 H304 H412			
64-17-5	ethanol			45 - < 50 %
	200-578-6	603-002-00-5	01-2119457610-43	
	Flam. Liq. 2, Eye Irrit. 2; H225 H319			

Full text of H and EUH statements: see section 16.

#### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
108-88-3	203-625-9	toluene	50 - < 55 %
		inhalation: LC50 = 28,1 mg/l (vapours); dermal: LD50 = > 5000 mg/kg; oral: LD50 = 5580 mg/kg	
64-17-5	200-578-6	ethanol	45 - < 50 %
		inhalation: LC50 = 124,7 mg/l (vapours); oral: LD50 = 10470 mg/kg Eye Irrit. 2; H319: >= 50 - 100	

#### Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### **Toluene / ethanol mixture mixed 1:1 volumetrically for the determination of the acid value and acidi**

Revision date: 20.03.2024

Product code: 27956

Page 3 of 14

(REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

#### **SECTION 4: First aid measures**

##### **4.1. Description of first aid measures**

###### **General information**

No data available

###### **After inhalation**

Provide fresh air.

If breathing is irregular or stopped, administer artificial respiration.

Call a physician immediately.

###### **After contact with skin**

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

Call a physician immediately.

###### **After contact with eyes**

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Remove contact lenses, if present and easy to do. Continue rinsing.

###### **After ingestion**

Observe risk of aspiration if vomiting occurs.

Call a physician immediately.

##### **4.2. Most important symptoms and effects, both acute and delayed**

Irritant

Vapours may cause drowsiness and dizziness.

##### **4.3. Indication of any immediate medical attention and special treatment needed**

No data available

#### **SECTION 5: Firefighting measures**

##### **5.1. Extinguishing media**

###### **Suitable extinguishing media**

Water spray jet, Carbon dioxide (CO<sub>2</sub>), Foam, Extinguishing powder.

###### **Unsuitable extinguishing media**

no restriction

##### **5.2. Special hazards arising from the substance or mixture**

Combustible liquids

Hazardous combustion products

In case of fire may be liberated:

Carbon dioxide (CO<sub>2</sub>), Carbon monoxide

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Heating causes rise in pressure with risk of bursting.

Beware of reignition.

##### **5.3. Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus.

In case of fire and/or explosion do not breathe fumes.

Avoid contact with skin, eyes and clothes.

###### **Additional information**

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Move undamaged containers from immediate hazard area if it can be done safely.

Use water spray jet to protect personnel and to cool endangered containers.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### **Toluene / ethanol mixture mixed 1:1 volumetrically for the determination of the acid value and acidi**

Revision date: 20.03.2024

Product code: 27956

Page 4 of 14

## **SECTION 6: Accidental release measures**

### **6.1. Personal precautions, protective equipment and emergency procedures**

#### **General advice**

Keep away from sources of ignition - No smoking.

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

Take action to prevent static discharges.

#### **For non-emergency personnel**

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Consult an expert

Do not breathe dust/fume/gas/mist/vapours/spray.

#### **For emergency responders**

Precautionary statements For emergency responders : Personal protection equipment: see section 8

### **6.2. Environmental precautions**

Do not allow to enter into surface water or drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Danger of explosion

### **6.3. Methods and material for containment and cleaning up**

#### **For containment**

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

#### **For cleaning up**

Clean contaminated articles and floor according to the environmental legislation.

#### **Other information**

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

### **6.4. Reference to other sections**

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

## **SECTION 7: Handling and storage**

### **7.1. Precautions for safe handling**

#### **Advice on safe handling**

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Keep container tightly closed.

Use personal protection equipment. Use extractor hood (laboratory).

Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation.

#### **Advice on protection against fire and explosion**

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Toluene / ethanol mixture mixed 1:1 volumetrically for the determination of the acid value and acidi

Revision date: 20.03.2024

Product code: 27956

Page 5 of 14

Vapours can form explosive mixtures with air.

#### Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs.

The choice of body protection depends on the concentration and quantity of hazardous substances. The chemical resistance of protective agents must be clarified with their suppliers.

#### Further information on handling

Take off immediately all contaminated clothing and wash it before reuse.

Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. If handled uncovered, arrangements with local exhaust ventilation have to be used.

Store in a place accessible by authorized persons only.

#### 7.2. Conditions for safe storage, including any incompatibilities

##### Requirements for storage rooms and vessels

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaust at critical locations. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

##### Hints on joint storage

national regulations

##### Further information on storage conditions

Keep cool. Protect from sunlight.

#### 7.3. Specific end use(s)

Laboratory chemicals

## SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### Occupational exposure limits

CAS No	Substance	ppm	mg/m <sup>3</sup>	fib/cm <sup>3</sup>	Category	Origin
64-17-5	Ethyl alcohol	1000	-		STEL (15 min)	
108-88-3	Toluene	50	192		TWA (8 h)	
		100	384		STEL (15 min)	

##### Biological limit values

CAS No	Substance	Parameter	Value	Test material	Sampling time
108-88-3	Toluene	Toluene	0.02 mg/L	Blood	Prior to last shift of workweek

**Toluene / ethanol mixture mixed 1:1 volumetrically for the determination of the acid value and acidi**

Revision date: 20.03.2024

Product code: 27956

Page 6 of 14

**DNEL/DMEL values**

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
108-88-3	toluene			
Worker DNEL, long-term		inhalation	systemic	192 mg/m <sup>3</sup>
Worker DNEL, acute		inhalation	systemic	384 mg/m <sup>3</sup>
Worker DNEL, long-term		inhalation	local	192 mg/m <sup>3</sup>
Worker DNEL, acute		inhalation	local	384 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	384 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	56,5 mg/m <sup>3</sup>
Consumer DNEL, acute		inhalation	systemic	226 mg/m <sup>3</sup>
Consumer DNEL, long-term		inhalation	local	56,5 mg/m <sup>3</sup>
Consumer DNEL, acute		inhalation	local	226 mg/m <sup>3</sup>
Consumer DNEL, long-term		dermal	systemic	226 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	8,13 mg/kg bw/day
64-17-5	ethanol			
Worker DNEL, long-term		inhalation	systemic	950 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	343 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	114 mg/m <sup>3</sup>
Consumer DNEL, long-term		dermal	systemic	206 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	87 mg/kg bw/day

**PNEC values**

CAS No	Substance		
Environmental compartment			Value
108-88-3	toluene		
Freshwater			0,68 mg/l
Freshwater (intermittent releases)			0,68 mg/l
Marine water			0,68 mg/l
Freshwater sediment			16,39 mg/kg
Marine sediment			16,39 mg/kg
Micro-organisms in sewage treatment plants (STP)			13,61 mg/l
Soil			2,89 mg/kg
64-17-5	ethanol		
Freshwater			0,96 mg/l
Freshwater (intermittent releases)			2,75 mg/l
Marine water			0,79 mg/l
Freshwater sediment			3,6 mg/kg
Marine sediment			2,9 mg/kg
Secondary poisoning			380 mg/kg
Micro-organisms in sewage treatment plants (STP)			580 mg/l
Soil			0,63 mg/kg

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Toluene / ethanol mixture mixed 1:1 volumetrically for the determination of the acid value and acidi

Revision date: 20.03.2024

Product code: 27956

Page 7 of 14

#### 8.2. Exposure controls

##### Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

##### Individual protection measures, such as personal protective equipment

##### Eye/face protection

goggles

Face protection umbrella

##### Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: [vertrieb@kcl.de](mailto:vertrieb@kcl.de) With specification (test according to EN374):

By long-term hand contact

Trade name/designation: KCL 890 Vitoject®

Suitable material: FKM (fluoro rubber) 0,7 mm

Wearing time with permanent contact: > 480 min

By short-term hand contact

Trade name/designation: KCL 890 Vitoject®

Suitable material: FKM (fluoro rubber) 0,7 mm

Wearing time with occasional contact (splashes): > 480 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: [www.kcl.de](http://www.kcl.de)).

##### Skin protection

Take off immediately all contaminated clothing and wash it before reuse.

Wear fire resistant or flame retardant clothing.

Wash hands and face before breaks and after work and take a shower if necessary.

Draw up and observe skin protection programme.

##### Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

##### Environmental exposure controls

Do not allow to enter into surface water or drains.

Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.

Danger of explosion

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:

Liquid

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Toluene / ethanol mixture mixed 1:1 volumetrically for the determination of the acid value and acids

Revision date: 20.03.2024

Product code: 27956

Page 8 of 14

Colour:	colourless	
Odour:	characteristic	
Odour threshold:	No data available	
Melting point/freezing point:		not determined
Boiling point or initial boiling point and boiling range:		?
Flammability:		not applicable
Lower explosion limits:		not determined
Upper explosion limits:		not determined
Flash point:		<12 °C
Auto-ignition temperature:		No data available
Decomposition temperature:		not determined
pH-Value:		not determined
Viscosity / kinematic:		No data available
Water solubility:		No
Solubility in other solvents		not determined
Partition coefficient n-octanol/water:		not determined
Vapour pressure:		No data available
Vapour pressure:		No data available
Density:		0,83530 g/cm <sup>3</sup>
Bulk density:		No data available
Relative vapour density:		not determined

#### 9.2. Other information

##### Information with regard to physical hazard classes

###### Explosive properties

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

###### Self-ignition temperature

Solid:

not applicable

Gas:

not applicable

###### Oxidizing properties

Not oxidising.

##### Other safety characteristics

###### Evaporation rate:

not determined

###### Solvent separation test:

No data available

###### Solvent content:

No data available

###### Solid content:

0

###### Sublimation point:

No data available

###### Softening point:

No data available

###### Pour point:

No data available

###### Viscosity / dynamic:

No data available

###### Flow time:

No data available

##### Further Information

No data available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Highly flammable.

### 10.2. Chemical stability

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Toluene / ethanol mixture mixed 1:1 volumetrically for the determination of the acid value and acids

Revision date: 20.03.2024

Product code: 27956

Page 9 of 14

The product is stable under storage at normal ambient temperatures.

#### 10.3. Possibility of hazardous reactions

Oxidising agent

#### 10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

#### 10.5. Incompatible materials

various plastics

#### 10.6. Hazardous decomposition products

SECTION 5: Firefighting measures

#### Further information

No data available

### SECTION 11: Toxicological information

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

##### Toxicokinetics, metabolism and distribution

There are no data available on the mixture itself.

##### Acute toxicity

Based on available data, the classification criteria are not met.

##### ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
108-88-3	toluene				
	oral	LD50 5580 mg/kg	Rat	Toxicology 4, 5-15 (1975)	EU Method B.1
	dermal	LD50 > 5000 mg/kg	Rabbit	American Industrial Hygiene Association	Study investigated mortality in groups o
	inhalation (4 h) vapour	LC50 28,1 mg/l	Rat	Study report (1980)	OECD Guideline 403
64-17-5	ethanol				
	oral	LD50 10470 mg/kg	Rat	Study report (1976)	OECD Guideline 401
	inhalation (4 h) vapour	LC50 124,7 mg/l	Rat	Study report (1980)	OECD Guideline 403

##### Irritation and corrosivity

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

##### Sensitising effects

Based on available data, the classification criteria are not met.

##### Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of damaging the unborn child. (toluene)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

##### STOT-single exposure

May cause drowsiness or dizziness. (toluene)

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### **Toluene / ethanol mixture mixed 1:1 volumetrically for the determination of the acid value and acidi**

Revision date: 20.03.2024

Product code: 27956

Page 10 of 14

#### **STOT-repeated exposure**

May cause damage to organs through prolonged or repeated exposure. (toluene)

#### **Aspiration hazard**

May be fatal if swallowed and enters airways.

#### **Specific effects in experiment on an animal**

There are no data available on the mixture itself.

#### **Additional information on tests**

There are no data available on the mixture itself.

#### **Practical experience**

There are no data available on the mixture itself.

#### **11.2. Information on other hazards**

##### **Other information**

There are no data available on the mixture itself.

##### **Further information**

There are no data available on the mixture itself.

### **SECTION 12: Ecological information**

#### **12.1. Toxicity**

Harmful to aquatic life with long lasting effects.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Toluene / ethanol mixture mixed 1:1 volumetrically for the determination of the acid value and acidi

Revision date: 20.03.2024

Product code: 27956

Page 11 of 14

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
108-88-3	toluene					
	Acute fish toxicity	LC50 5,5 mg/l	96 h	Oncorhynchus kisutch	Transactions A. Fish. Soc. 110, 430-436.	Fry were exposed to toluene in a flow th
	Acute algae toxicity	ErC50 mg/l > 433	96 h	Pseudokirchneriella subcapitata	REACH Registration Dossier	Method: other
	Acute crustacea toxicity	EC50 mg/l 11,5	48 h	Daphnia magna	REACH Registration Dossier	Method: other
	Fish toxicity	NOEC mg/l 1,39	40 d	Oncorhynchus kisutch	Transactions A. Fish. Soc. 110, 430-436.	Fry were exposed to toluene in a flow th
	Algae toxicity	NOEC mg/l > 400	7 d	Scenedesmus quadricauda	REACH Registration Dossier	Method: other
	Crustacea toxicity	NOEC mg/l 0,74	7 d	Ceriodaphnia dubia	Ecotoxicol. Environ. Saf. 39, 136-146. (	other: US EPA 600/4-91-003
64-17-5	ethanol					
	Acute fish toxicity	LC50 mg/l 15400	96 h	Lepomis macrochirus	Bulletin of Environmental Contamination	other: EPA-660/3-75-00 9, 1975
	Acute algae toxicity	ErC50 ca. 22000 mg/l	96 h	Pseudokirchneriella subcapitata	Ecotoxicology and Environmental Safety 7	OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l > 10000	48 h	Daphnia magna	Water Research 23(4): 495-499 (1989)	other: DIN 38412 Teil 11
	Algae toxicity	NOEC mg/l 5400	5 d	Skeletonema costatum	Environ Toxicol Chem 8(5):451-455. (1989)	Study to determine the sensitivity of a
	Crustacea toxicity	NOEC 2 mg/l	10 d	Ceriodaphnia dubia	Arch Environ Contam Toxicol 20(2):211-21	Follows the basic methodology for the th

#### 12.2. Persistence and degradability

There are no data available on the mixture itself.

#### 12.3. Bioaccumulative potential

There are no data available on the mixture itself.

#### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
108-88-3	toluene	2,73
64-17-5	ethanol	-0,77

#### BCF

CAS No	Chemical name	BCF	Species	Source
108-88-3	toluene	90	Leuciscus idus melanotus	Chemosphere 14 (10).
64-17-5	ethanol	1	Cyprinus carpio	Comparative Biochemi

**Toluene / ethanol mixture mixed 1:1 volumetrically for the determination of the acid value and acidi**

Revision date: 20.03.2024

Product code: 27956

Page 12 of 14

**12.4. Mobility in soil**

There are no data available on the mixture itself.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

No data available

**12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**12.7. Other adverse effects**

Do not allow to enter into surface water or drains.

**Further information**

Avoid release to the environment.

**SECTION 13: Disposal considerations**

**13.1. Waste treatment methods**

**Disposal recommendations**

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations.

Do not empty into drains.

**Contaminated packaging**

This material and its container must be disposed of as hazardous waste. Handle contaminated packages in the same way as the substance itself.

**SECTION 14: Transport information**

**Land transport (ADR/RID)**

<b>14.1. UN number or ID number:</b>	UN 1993
<b>14.2. UN proper shipping name:</b>	FLAMMABLE LIQUID, N.O.S. (toluene, ethanol; ethyl alcohol)
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3
Classification code:	F1
Special Provisions:	274 601 640D
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	33
Tunnel restriction code:	D/E

**Inland waterways transport (ADN)**

<b>14.1. UN number or ID number:</b>	UN 1993
<b>14.2. UN proper shipping name:</b>	FLAMMABLE LIQUID, N.O.S. (toluene, ethanol; ethyl alcohol)
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3
Classification code:	F1
Special Provisions:	274 601 640D
Limited quantity:	1 L
Excepted quantity:	E2

**Marine transport (IMDG)**

<b>14.1. UN number or ID number:</b>	UN 1993
--------------------------------------	---------

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Toluene / ethanol mixture mixed 1:1 volumetrically for the determination of the acid value and acidi

Revision date: 20.03.2024

Product code: 27956

Page 13 of 14

<b>14.2. UN proper shipping name:</b>	FLAMMABLE LIQUID, N.O.S. (toluene, ethanol; ethyl alcohol)
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2
EmS:	F-E, S-E

#### Air transport (ICAO-TI/IATA-DGR)

<b>14.1. UN number or ID number:</b>	UN 1993
<b>14.2. UN proper shipping name:</b>	FLAMMABLE LIQUID, N.O.S. (toluene, ethanol; ethyl alcohol)
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3
Special Provisions:	A3
Limited quantity Passenger:	1 L
Passenger LQ:	Y341
Excepted quantity:	E2
IATA-packing instructions - Passenger:	353
IATA-max. quantity - Passenger:	5 L
IATA-packing instructions - Cargo:	364
IATA-max. quantity - Cargo:	60 L

#### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

#### 14.6. Special precautions for user

Warning: Combustible liquid.

#### 14.7. Maritime transport in bulk according to IMO instruments

not applicable

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 48

##### National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D):

3 - highly hazardous to water

#### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

### SECTION 16: Other information

#### Changes

This data sheet contains changes from the previous version in section(s): 1,9,12.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Toluene / ethanol mixture mixed 1:1 volumetrically for the determination of the acid value and acidi

Revision date: 20.03.2024

Product code: 27956

Page 14 of 14

#### Abbreviations and acronyms

Flam. Liq: Flammable liquid  
Asp. Tox: Aspiration hazard  
Skin Irrit: Skin irritation  
Eye Irrit: Eye irritation  
Repr: Reproductive toxicity  
STOT SE: Specific target organ toxicity - single exposure  
STOT RE: Specific target organ toxicity - repeated exposure  
Aquatic Chronic: Chronic aquatic hazard  
ADR: Accord européen sur le transport des marchandises dangereuses par Route  
(European Agreement concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
GHS: Globally Harmonized System of Classification and Labelling of Chemicals  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service  
LC50: Lethal concentration, 50%  
LD50: Lethal dose, 50%

#### Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Asp. Tox. 1; H304	Calculation method
Skin Irrit. 2; H315	Calculation method
Repr. 2; H361d	Calculation method
STOT SE 3; H336	Calculation method
STOT RE 2; H373	Calculation method
Aquatic Chronic 3; H412	Calculation method

#### Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.  
H361d Suspected of damaging the unborn child.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H412 Harmful to aquatic life with long lasting effects.

#### Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*