

according to Regulation (EC) No 1907/2006

V2A-Stahl-Ätzung Komponenten-Mischung reinst Produkt ohne Salzsäure

Revision date: 12.09.2023 Product code: 29222 Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

V2A-Stahl-Ätzung Komponenten-Mischung reinst Produkt ohne Salzsäure

UFI: HUWK-G2HG-N00G-UVXG

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name: AnalytiChem GmbH

ACD

Street: Stempelstraße 6
Place: D-47167 Duisburg

Telephone: 0203/5194-0 Telefax: 0203/5194-290

E-mail: info@analytichem.de

Contact person: Abteilung Produktsicherheit Telephone: 0203/5194-107/117

E-mail: produktsicherheit@analytichem.de

Internet: www.analytichem.de
Responsible Department: Abteilung Produktsicherheit

1.4. Emergency telephone For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire,

number: Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada:

1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls

accepted)

Further Information

This product is a mixture. REACH Registration Number see section 3.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Met. Corr. 1; H290 Acute Tox. 1; H310 Acute Tox. 2; H300 Acute Tox. 2; H330 Skin Corr. 1A; H314 Eye Dam. 1; H318

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

nitric acid 20 % hydrofluoric acid 16 %

Signal word: Danger



according to Regulation (EC) No 1907/2006

V2A-Stahl-Ätzung Komponenten-Mischung reinst Produkt ohne Salzsäure

Revision date: 12.09.2023 Product code: 29222 Page 2 of 13

Pictograms:





Hazard statements

H290 May be corrosive to metals.

H300+H310+H330 Fatal if swallowed, in contact with skin or if inhaled. H314 Causes severe skin burns and eye damage.

Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water or shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixtures in aqueous solution

Relevant ingredients

CAS No	Chemical name					
	EC No	Index No	REACH No			
	Classification (Regulation					
7697-37-2	nitric acid					
	231-714-2	007-030-00-3	01-2119487297-23			
	Ox. Liq. 3, Met. Corr. 1,	Acute Tox. 3, Skin Corr. 1A; H272 H	290 H331 H314 EUH071			
7664-39-3	hydrofluoric acid %	15 - < 20 %				
	231-634-8	009-003-00-1				
	Acute Tox. 1, Acute Tox H318					

Full text of H and EUH statements: see section 16.

Specific Conc. Limits. M-factors and ATE

CAS No	EC No	Chemical name	Quantity		
	Specific Conc.	Limits, M-factors and ATE			
7697-37-2	231-714-2	nitric acid	15 - < 20 %		
	inhalation: ATE 2,65 mg/l (vapours) Ox. Liq. 3; H272: >= 65 - 100 Skin Corr. 1A; H314: >= 20 - 100 Skin Corr. 1B; H314: >= 5 - < 20				
7664-39-3	231-634-8	hydrofluoric acid %	15 - < 20 %		
	inhalation: ATE = 0,5 mg/l (vapours); inhalation: ATE = 0,05 mg/l (dusts or mists); inhalation: LC50 = 2240 ppm (gases); dermal: ATE = 5 mg/kg; oral: ATE = 5 mg/kg Skin Corr. 1A; H314: >= 7 - 100 Skin Corr. 1B; H314: >= 1 - < 7 Eye Irrit. 2; H319: >= 0,1 - < 1				



according to Regulation (EC) No 1907/2006

V2A-Stahl-Ätzung Komponenten-Mischung reinst Produkt ohne Salzsäure

Revision date: 12.09.2023 Product code: 29222 Page 3 of 13

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection!

fast help required

After inhalation

Provide fresh air.

If breathing is irregular or stopped, administer artificial respiration.

Call a physician immediately.

After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

Call a physician immediately.

Rinse with plenty of water for at least 10 minutes. Immediately remove contaminated clothes. Apply calcium gluconate gel (preparation: boil 5 g of calcium gluconate in 85 ml of hot distilled water, add 10 g glycerol. Allow 5 g of Carmellose-sodium to swell in the hot solution. Stable for 6 months, store in a cool place) and massage into the skin until the pain subsides, in between rinse with water and apply fresh gel. Continue gel therapy for another 15 minutes after the pain has subsided. If no calcium gluconate gel is available, apply several dressings thoroughly moistened with 20 % calcium gluconate solution. Medical advice absolutely required!

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Rinse mouth immediately and drink plenty of water.

Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Causes burns.

Irritant

Cough

Dyspnoea

Vomiting

Methaemoglobinaemia

Risk of serious damage to eyes.

4.3. Indication of any immediate medical attention and special treatment needed

It is recommended to consult a doctor with experience in the treatment of lesions caused by hydrofluoric acid

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Non-combustible liquids

Hazardous combustion products



according to Regulation (EC) No 1907/2006

V2A-Stahl-Ätzung Komponenten-Mischung reinst Produkt ohne Salzsäure

Revision date: 12.09.2023 Product code: 29222 Page 4 of 13

In case of fire may be liberated:

Nitrogen oxides (NOx)

Hydrogen fluoride

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Move undamaged containers from immediate hazard area if it can be done safely.

Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Corrosive to metals.

For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Consult an expert

Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders: Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Use personal protection equipment.

Provide adequate ventilation. Avoid contact with skin, eyes and clothes.

Do not breathe vapour/aerosol. Use extractor hood (laboratory).



according to Regulation (EC) No 1907/2006

V2A-Stahl-Ätzung Komponenten-Mischung reinst Produkt ohne Salzsäure

Revision date: 12.09.2023 Product code: 29222 Page 5 of 13

Advice on protection against fire and explosion

No special fire protection measures are necessary.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs. Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink. Avoid: aerosol or mist formation Do not breathe vapour/aerosol.

Further information on handling

Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary.

Take off immediately all contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaustion at critical locations. Unsuitable container/equipment material: Metal. Glass

Hints on joint storage

national regulations

Further information on storage conditions

Keep container tightly closed.

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
7664-39-3	Hydrogen fluoride (as F)	1.8	1.5		TWA (8 h)	
		3	2.5		STEL (15 min)	•
7697-37-2	Nitric acid	1	2.6		STEL (15 min)	

Biological limit values

CAS No	Substance	Parameter	Value	Test material	Sampling time
7664-39-3	Hydrogen fluoride	Fluoride	2 mg/L	Urine	Prior to shift



according to Regulation (EC) No 1907/2006

V2A-Stahl-Ätzung Komponenten-Mischung reinst Produkt ohne Salzsäure

Revision date: 12.09.2023 Product code: 29222 Page 6 of 13

DNEL/DMEL values

CAS No	Substance					
DNEL type		Exposure route	Effect	Value		
7664-39-3	hydrofluoric acid %					
Worker DNEI	., long-term	inhalation	systemic	1,5 mg/m³		
Worker DNEI	_, acute	inhalation	systemic	2,5 mg/m³		
Worker DNEI	_, long-term	inhalation	local	1,5 mg/m³		
Worker DNEI	Worker DNEL, acute		local	2,5 mg/m³		
Consumer Di	NEL, long-term	inhalation	systemic	0,03 mg/m³		
Consumer Di	NEL, acute	inhalation	systemic	0,03 mg/m³		
Consumer Di	NEL, long-term	inhalation	local	0,2 mg/m³		
Consumer Di	NEL, acute	inhalation	local	1,25 mg/m³		
Consumer DNEL, long-term		oral	systemic	0,01 mg/kg bw/day		
Consumer Di	Consumer DNEL, acute		systemic	0,01 mg/kg bw/day		

PNEC values

CAS No	Substance				
Environmental compartment Vs					
7664-39-3	hydrofluoric acid %				
Freshwater		0,89 mg/l			
Marine water	0,089 mg/l				
Freshwater sediment 3,38 mg/k					
Marine sedim	0,338 mg/kg				
Micro-organisms in sewage treatment plants (STP)		51 mg/l			
Soil		10,6 mg/kg			

8.2. Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment

Eye/face protection

goggles

Wear eye/face protection.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact



according to Regulation (EC) No 1907/2006

V2A-Stahl-Ätzung Komponenten-Mischung reinst Produkt ohne Salzsäure

Product code: 29222 Revision date: 12.09.2023 Page 7 of 13

Trade name/designation: KCL 720 Camapren®

Recommended material: CR (polychloroprene, chloroprene rubber) 0,65 mm

Wearing time with permanent contact: > 480 min

By short-term hand contact

Trade name/designation: KCL 720 Camapren®

Recommended material: CR (polychloroprene, chloroprene rubber) 0,65 mm

Wearing time with occasional contact (splashes): > 480 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing.

Wash hands before breaks and after work.

The choice of body protection depends on the concentration and quantity of hazardous substances. The chemical resistance of protective agents must be clarified with their suppliers.

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid Colour: colourless Odour: stinging

Odour threshold: No data available

Melting point/freezing point: No data available Boiling point or initial boiling point and No data available

boiling range:

Flammability: not applicable

not applicable

Lower explosion limits: not determined Upper explosion limits: not determined

Flash point: Χ

Auto-ignition temperature: No data available Decomposition temperature: not determined pH-Value:

Viscosity / kinematic: No data available

Solubility in other solvents

not determined

Dissolution rate: No data available Partition coefficient n-octanol/water: not determined Dispersion stability: No data available Vapour pressure: No data available Vapour pressure: No data available 1,1583 g/cm³ Density:



according to Regulation (EC) No 1907/2006

V2A-Stahl-Ätzung Komponenten-Mischung reinst Produkt ohne Salzsäure

Revision date: 12.09.2023 Product code: 29222 Page 8 of 13

Bulk density:

Relative vapour density:

Particle characteristics:

No data available

No data available

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

No data available

Sustaining combustion: No data available

Self-ignition temperature

Solid: not applicable
Gas: not applicable

Oxidizing properties Not oxidising.

Other safety characteristics

Evaporation rate: not determined Solvent separation test: No data available Solvent content: 0 Solid content: 0 Sublimation point: No data available Softening point: No data available Pour point: No data available No data available

No data available:

Viscosity / dynamic: No data available Flow time: No data available

Further Information
Corrosive to metals.

SECTION 10: Stability and reactivity

10.1. Reactivity

Corrosive to metals. Glass

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Alkali (lye)

The product develops hydrogen in an aqueous solution in contact with metals.

Amines, Ammonia, Alcohols, Alkali metals, Hydrogen peroxide

Copper, Combustible solids, Solvent, Alkaline earth metal, mercury (Hg).

10.4. Conditions to avoid

none

10.5. Incompatible materials

Cellulose

Metal

Glass

The product develops hydrogen in an aqueous solution in contact with metals.

10.6. Hazardous decomposition products

In case of fire may be liberated: SECTION 5: Firefighting measures

Further information

No data available



according to Regulation (EC) No 1907/2006

V2A-Stahl-Ätzung Komponenten-Mischung reinst Produkt ohne Salzsäure

Revision date: 12.09.2023 Product code: 29222 Page 9 of 13

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicocinetics, metabolism and distribution

There are no data available on the preparation/mixture itself.

Acute toxicity

Fatal in contact with skin.

Fatal if swallowed.

Fatal if inhaled.

CAS No	Chemical name								
	Exposure route	Dose		Species	Source	Method			
7697-37-2	nitric acid								
	inhalation vapour	ATE 2,6	65 mg/l						
7664-39-3	hydrofluoric acid %	hydrofluoric acid %							
	oral	ATE	5 mg/kg						
	dermal	ATE	5 mg/kg						
	inhalation vapour	ATE	0,5 mg/l						
	inhalation dust/mist	ATE	0,05 mg/l						
	inhalation (1 h) gas	LC50 ppm	2240	Rat	Study report (1990)	OECD Guideline 403			

Irritation and corrosivity

Skin corrosion/irritation: Causes severe skin burns and eye damage.

Serious eye damage/eye irritation: Causes serious eye damage.

Following ingestion Gastric perforation

Mucous membrane irritation in the mouth, throat, esophagus and gastrointestinal tract.

Irritating to respiratory system.

Pulmonary oedema see also Section 4

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

There are no data available on the preparation/mixture itself.

Additional information on tests

There are no data available on the preparation/mixture itself.

Practical experience

There are no data available on the preparation/mixture itself.

11.2. Information on other hazards



according to Regulation (EC) No 1907/2006

V2A-Stahl-Ätzung Komponenten-Mischung reinst Produkt ohne Salzsäure

Revision date: 12.09.2023 Product code: 29222 Page 10 of 13

Other information

There are no data available on the preparation/mixture itself.

Further information

There are no data available on the preparation/mixture itself.

SECTION 12: Ecological information

12.1. Toxicity

There are no data available on the preparation/mixture itself.

CAS No	Chemical name								
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method		
7697-37-2	nitric acid								
	Acute fish toxicity	LC50 mg/l	1559	96 h	Topeka shiner	Environmental Toxicology and Chemistry,	other: ASTM E729-26		
	Fish toxicity	NOEC	268 mg/l	30 d	juvenile Topeka shiner and with juvenile Fathead m	Study report (2009)	Growth tests estimated the test chemical		
	Algae toxicity	NOEC mg/l	> 419	10 d	several benthic diatoms; see results	Marine Biology 43:307-315 (1977)	Ten cultures of benthic diatoms were iso		
	Acute bacteria toxicity	EC50 mg/l ()	> 1000	3 h	Activated sludge	Study report (2008)	OECD Guideline 209		
7664-39-3	hydrofluoric acid %								
	Acute fish toxicity	LC50	299 mg/l	96 h	Salmo trutta	REACh Registration Dossier	other: U.S Environmental Protection Agen		
	Acute algae toxicity	ErC50	43 mg/l	96 h	various algae species	REACh Registration Dossier	Methods not detailed in the review.		
	Crustacea toxicity	NOEC	3,7 mg/l	21 d	Daphnia magna	REACh Registration Dossier	The publication is a review article of v		
	Acute bacteria toxicity	EC50 mg/l ()	2930	3 h	Activated sludge	REACh Registration Dossier	ISO 8192		

12.2. Persistence and degradability

There are no data available on the preparation/mixture itself.

12.3. Bioaccumulative potential

There are no data available on the preparation/mixture itself.

BCF

CAS No	Chemical name	BCF	Species	Source
7664-39-3	hydrofluoric acid %	53 - 58	not specified	REACh Registration D

12.4. Mobility in soil

There are no data available on the preparation/mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

There are no data available on the preparation/mixture itself.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.



according to Regulation (EC) No 1907/2006

V2A-Stahl-Ätzung Komponenten-Mischung reinst Produkt ohne Salzsäure

Revision date: 12.09.2023 Product code: 29222 Page 11 of 13

12.7. Other adverse effects

Harmful effect due to pH shift.

Forms corrosive mixtures with water even if diluted.

Further information

Do not allow to enter into surface water or drains.

Discharge into the environment must be avoided.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations.

Do not empty into drains.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

Dispose of waste according to "Kreislaufwirtschafts- und Abfallgesetz (KrW-/AbfG)".

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 3289

14.2. UN proper shipping name: TOXIC LIQUID, CORROSIVE, INORGANIC, N.O.S. (Hydrofluoric acid,

nitric acid)

6.1

14.3. Transport hazard class(es):

14.4. Packing group:IIHazard label:6.1+8

Classification code: TC3
Special Provisions: 274
Limited quantity: 100 mL
Excepted quantity: E4
Transport category: 2
Hazard No: 68
Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 3289

14.2. UN proper shipping name: TOXIC LIQUID, CORROSIVE, INORGANIC, N.O.S. (Hydrofluoric acid,

nitric acid)

6.1

14.3. Transport hazard class(es):

14.4. Packing group:

Hazard label: 6.1+8
Classification code: TC3
Special Provisions: 274 802
Limited quantity: 100 mL
Excepted quantity: E4

Marine transport (IMDG)

14.1. UN number or ID number: UN 3289

14.2. UN proper shipping name: TOXIC LIQUID, CORROSIVE, INORGANIC, N.O.S. (Hydrofluoric acid,

nitric acid)

14.3. Transport hazard class(es): 6.1
14.4. Packing group:



according to Regulation (EC) No 1907/2006

V2A-Stahl-Ätzung Komponenten-Mischung reinst Produkt ohne Salzsäure

Revision date: 12.09.2023 Product code: 29222 Page 12 of 13

Hazard label: 6.1+8
Special Provisions: 274
Limited quantity: 100 mL
Excepted quantity: E4
EmS: F-A, S-B

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 3289

14.2. UN proper shipping name: TOXIC LIQUID, CORROSIVE, INORGANIC, N.O.S. (Hydrofluoric acid,

nitric acid)

14.3. Transport hazard class(es):6.114.4. Packing group:IIHazard label:6.1+8Special Provisions:A4 A137Limited quantity Passenger:0.5 LPassenger LQ:Y640Excepted quantity:E4

IATA-packing instructions - Passenger: 653
IATA-max. quantity - Passenger: 1 L
IATA-packing instructions - Cargo: 660
IATA-max. quantity - Cargo: 30 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: Toxic. strongly corrosive.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3

Marketing and use of explosives precursors (Regulation (EU) 2019/1148):

Acquisition, introduction, possession or use of this product by the general public is restricted by Regulation (EU) 2019/1148. All suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point.

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.

Water hazard class (D): 2 - obviously hazardous to water

Skin resorption/Sensitization: Permeates easily through outer skin and causes poisoning.

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1,2,4,5,6,7,8,9,10,11,12,13,14,16.



according to Regulation (EC) No 1907/2006

V2A-Stahl-Ätzung Komponenten-Mischung reinst Produkt ohne Salzsäure

Revision date: 12.09.2023 Product code: 29222 Page 13 of 13

Abbreviations and acronyms

Ox. Liq: Oxidising liquid

Met. Corr: Substance or mixture corrosive to metals

Acute Tox: Acute toxicity Skin Corr: Skin corrosion Eye Dam: Eye damage

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Relevant H and EUH statements (number and full text)

H272 May intensify fire; oxidiser. H290 May be corrosive to metals.

H300 Fatal if swallowed.

H300+H310+H330 Fatal if swallowed, in contact with skin or if inhaled.

H310 Fatal in contact with skin.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.

H330 Fatal if inhaled. H331 Toxic if inhaled.

EUH071 Corrosive to the respiratory tract.

Further Information

Provide appropriate information, instructions and training to users

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)