

Natriumaluminat-Lösung min. 10 %(m/m) Al zur Wasseraufbereitung

Revision: 23.04.2024

Product code: 31606

Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Natriumaluminat-Lösung min. 10 %(m/m) Al zur Wasseraufbereitung

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Reagents and laboratory chemicals
Only for laboratory and analysis purposes.

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name:	AnalytiChem GmbH	
	ACD	
Street:	Stempelstraße 6	
Place:	D-47167 Duisburg	
Telephone:	0203/5194-0	Telefax: 0203/5194-290
E-mail:	info@analytichem.de	
Contact person:	Abteilung Produktsicherheit	Telephone: 0203/5194-107/117
E-mail:	produktsicherheit@analytichem.de	
Internet:	www.analytichem.de	
Responsible Department:	Abteilung Produktsicherheit	

1.4. Emergency telephone number:

For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

Further Information

This product is a mixture. REACH Registration Number see section 3.

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No 1272/2008**

Met. Corr. 1; H290
Skin Corr. 1A; H314
Eye Dam. 1; H318

Full text of hazard statements: see SECTION 16.

2.2. Label elements**Regulation (EC) No 1272/2008****Hazard components for labelling**
sodium aluminate**Signal word:** Danger**Pictograms:****Hazard statements**

H290 May be corrosive to metals.

according to Regulation (EC) No 1907/2006

Natriumaluminat-Lösung min. 10 %(m/m) Al zur Wasseraufbereitung

Revision: 23.04.2024

Product code: 31606

Page 2 of 11

H314 Causes severe skin burns and eye damage.

Precautionary statements

P234 Keep only in original packaging.
P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P363 Wash contaminated clothing before reuse.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P310 Immediately call a POISON CENTER/doctor.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER/doctor.
P390 Absorb spillage to prevent material damage.
P405 Store locked up.
P406 Store in a corrosion-resistant container with a resistant inner liner.

Special labelling of certain mixtures

EUH071 Corrosive to the respiratory tract.

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Chemical characterization**

Mixtures in aqueous solution

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
1302-42-7	sodium aluminate			35 - < 40 %
	215-100-1		01-2119519249-35	
	Met. Corr. 1, Skin Corr. 1A, Eye Dam. 1; H290 H314 H318 EUH071			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
1302-42-7	215-100-1	sodium aluminate	35 - < 40 %
	inhalation: LC50 = > 5,09 mg/l (dusts or mists); oral: LD50 = > 2000 mg/kg		

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

Take off immediately all contaminated clothing.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Natriumaluminat-Lösung min. 10 %(m/m) Al zur Wasseraufbereitung

Revision: 23.04.2024

Product code: 31606

Page 3 of 11

After inhalation

Provide fresh air.
Call a physician immediately.

After contact with skin

Wash immediately with: Water
Take off immediately all contaminated clothing and wash it before reuse.
Call a physician immediately.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.
Remove contact lenses, if present and easy to do. Continue rinsing.
Protect uninjured eye.

After ingestion

Never give anything by mouth to an unconscious person or a person with cramps.
Rinse mouth immediately and drink plenty of water.
Do not allow a neutralisation agent to be drunk. Do NOT induce vomiting.
Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Irritant — skin irritation and eye damage
Causes burns.

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Non-combustible liquids
Hazardous combustion products

5.3. Advice for firefighters

Do not inhale explosion and combustion gases.
Avoid contact with skin, eyes and clothes.
In case of fire: Wear self-contained breathing apparatus.

Additional information

Suppress gases/vapours/mists with water spray jet.
Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.
Move undamaged containers from immediate hazard area if it can be done safely.
Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Corrosive to metals.

For non-emergency personnel

Provide adequate ventilation.

Natriumaluminat-Lösung min. 10 %(m/m) Al zur Wasseraufbereitung

Revision: 23.04.2024

Product code: 31606

Page 4 of 11

Use personal protection equipment.
Avoid contact with skin, eyes and clothes.
Remove persons to safety.
Emergency procedures
Consult an expert
Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up**For containment**

Cover drains.
Prevent spread over a wide area (e.g. by containment or oil barriers).
Collect in closed and suitable containers for disposal.
Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.
Do not breathe dust/fume/gas/mist/vapours/spray.
Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7
Personal protection equipment: see section 8
Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Read label before use. Handle and open container with care.
When using do not eat, drink, smoke, sniff. Keep container tightly closed.
Use personal protection equipment. Use extractor hood (laboratory).
Provide adequate ventilation.
Avoid contact with skin, eyes and clothes.

Advice on protection against fire and explosion

Usual measures for fire prevention.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs. Make available sufficient washing facilities
Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

Further information on handling

Draw up and observe skin protection programme.
Wash hands and face before breaks and after work and take a shower if necessary.
Take off immediately all contaminated clothing and wash it before reuse.
If handled uncovered, arrangements with local exhaust ventilation have to be used.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Store in a well-ventilated place. Keep container tightly closed.

Natriumaluminat-Lösung min. 10 %(m/m) Al zur Wasseraufbereitung

Revision: 23.04.2024

Product code: 31606

Page 5 of 11

Corrosive to metals.

Hints on joint storage

national regulations

Further information on storage conditions

Store in a dry place.

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****PNEC values**

CAS No	Substance	
	Environmental compartment	Value
1302-42-7	sodium aluminate	
	Freshwater	0,014 mg/l
	Freshwater (intermittent releases)	0,0043 mg/l
	Marine water	0,0014 mg/l
	Micro-organisms in sewage treatment plants (STP)	10 mg/l

8.2. Exposure controls**Appropriate engineering controls**

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Do not breathe gas/fumes/vapour/spray.

Individual protection measures, such as personal protective equipment**Eye/face protection**

goggles

Wear eye protection/face protection.

Hand protection

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

KCL 741 Dermatril® L

NBR (Nitrile rubber) 0,11mm

Wearing time with permanent contact: >480min

KCL 741 Dermatril® L

NBR (Nitrile rubber) 0,11mm

Wearing time with occasional contact (splashes): >480min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Wear suitable protective clothing.

Take off immediately all contaminated clothing.

Natriumaluminat-Lösung min. 10 %(m/m) Al zur Wasseraufbereitung

Revision: 23.04.2024

Product code: 31606

Page 6 of 11

Wash hands before breaks and after work.

The choice of body protection depends on the concentration and quantity of hazardous substances. The chemical resistance of protective agents must be clarified with their suppliers.

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid	
Colour:	yellow	
Odour:	odourless	
Melting point/freezing point:		No data available
Boiling point or initial boiling point and boiling range:		115 °C
Flammability:		No data available
Lower explosion limits:		No data available
Upper explosion limits:		No data available
Flash point:		No data available
Auto-ignition temperature:		No data available
Decomposition temperature:		No data available
pH-Value:		alkaline
Viscosity / kinematic:		No data available
Water solubility:		No data available
Solubility in other solvents		
No data available		
Partition coefficient n-octanol/water:		No data available
Vapour pressure:		No data available
Vapour pressure:		No data available
Density:		1,45 g/cm ³
Bulk density:		No data available
Relative vapour density:		No data available

9.2. Other information**Information with regard to physical hazard classes**

Explosive properties

 No data available

Sustained combustibility:

No data available

Self-ignition temperature

 Solid:

No data available

 Gas:

No data available

Oxidizing properties

 No data available

Other safety characteristics

Evaporation rate:

No data available

Solvent separation test:

No data available

Solvent content:

0

Solid content:

0

Natriumaluminat-Lösung min. 10 %(m/m) Al zur Wasseraufbereitung

Revision: 23.04.2024

Product code: 31606

Page 7 of 11

Sublimation point: No data available
Softening point: No data available
Pour point: No data available
No data available:
Viscosity / dynamic: No data available
Flow time: No data available

Further Information

No data available

SECTION 10: Stability and reactivity**10.1. Reactivity**

Corrosive to metals.

10.2. Chemical stability

No data available

10.3. Possibility of hazardous reactions

Acid

10.4. Conditions to avoid

No data available

10.5. Incompatible materials

Metal
various metals, metal alloys

10.6. Hazardous decomposition products

No data available

Further information

No data available

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity**

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
1302-42-7	sodium aluminate				
	oral	LD50 > 2000 mg/kg	Rat	Mutation Research 676(1-2):41-47 (2009)	OECD Guideline 420
	inhalation (4 h) dust/mist	LC50 > 5,09 mg/l	Rat	Study report (1990)	OECD Guideline 403

Irritation and corrosivity

Skin corrosion/irritation: Causes severe skin burns and eye damage.
Serious eye damage/eye irritation: Causes serious eye damage.
Corrosive to the respiratory tract.

Sensitising effects

Based on available data, the classification criteria are not met.

Natriumaluminat-Lösung min. 10 %(m/m) Al zur Wasseraufbereitung

Revision: 23.04.2024

Product code: 31606

Page 8 of 11

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

No data available

Additional information on tests

No data available

Practical experience

No data available

11.2. Information on other hazards**Other information**

No data available

Further information

Mucous membrane irritation in the mouth, throat, esophagus and gastrointestinal tract.

Irritating to respiratory system.

Corrosive to the respiratory tract.

SECTION 12: Ecological information**12.1. Toxicity**

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
1302-42-7	sodium aluminate					
	Acute fish toxicity	LC50 > 100 mg/l	96 h	Salmo trutta	Study report (1996)	OECD Guideline 203
	Acute algae toxicity	ErC50 1,282 mg/l	72 h	Pseudokirchneriella subcapitata	Study report (2010)	OECD Guideline 201
	Acute crustacea toxicity	EC50 0,7208 - 0,7878 mg/l	48 h	Daphnia magna	Study report (2009)	other: method 2021.0 D. magna acute toxi
	Fish toxicity	NOEC 1,49 mg/l	16 d	Oncorhynchus mykiss	Canadian Journal of Fisheries and Aquati	Determination of the effects of humic ac
	Crustacea toxicity	NOEC 0,6 mg/l	21 d	Daphnia magna	Study report (2010)	OECD Guideline 211
	Acute bacteria toxicity	EC50 > 100 mg/l ()	3 h	activated sludge of a predominantly domestic sewage	Study report (2010)	OECD Guideline 209

12.3. Bioaccumulative potential

Natriumaluminat-Lösung min. 10 %(m/m) Al zur Wasseraufbereitung

Revision: 23.04.2024

Product code: 31606

Page 9 of 11

BCF

CAS No	Chemical name	BCF	Species	Source
1302-42-7	sodium aluminate	215	Salvelinus fontinalis	Environmental Toxico

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Harmful effect due to pH shift.

Further information

Do not allow to enter into surface water or drains.

Discharge into the environment must be avoided.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Dispose of waste according to applicable legislation.

Do not allow to enter into surface water or drains.

Contaminated packaging

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number or ID number:	UN 1819
14.2. UN proper shipping name:	SODIUM ALUMINATE SOLUTION
14.3. Transport hazard class(es):	8
14.4. Packing group:	II
Hazard label:	8
Classification code:	C5
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	80
Tunnel restriction code:	E

Inland waterways transport (ADN)

14.1. UN number or ID number:	UN 1819
14.2. UN proper shipping name:	SODIUM ALUMINATE SOLUTION
14.3. Transport hazard class(es):	8
14.4. Packing group:	II
Hazard label:	8
Classification code:	C5
Limited quantity:	1 L
Excepted quantity:	E2

Marine transport (IMDG)

14.1. UN number or ID number:	UN 1819
--------------------------------------	---------

Natriumaluminat-Lösung min. 10 %(m/m) Al zur Wasseraufbereitung

Revision: 23.04.2024

Product code: 31606

Page 10 of 11

14.2. UN proper shipping name:	SODIUM ALUMINATE SOLUTION
14.3. Transport hazard class(es):	8
14.4. Packing group:	II
Hazard label:	8
Special Provisions:	-
Limited quantity:	1 L
Excepted quantity:	E2
EmS:	F-A, S-B

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:	UN 1819
14.2. UN proper shipping name:	SODIUM ALUMINATE SOLUTION
14.3. Transport hazard class(es):	8
14.4. Packing group:	II
Hazard label:	8
Special Provisions:	A3 A803
Limited quantity Passenger:	0.5 L
Passenger LQ:	Y840
Excepted quantity:	E2
IATA-packing instructions - Passenger:	851
IATA-max. quantity - Passenger:	1 L
IATA-packing instructions - Cargo:	855
IATA-max. quantity - Cargo:	30 L

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):
Entry 3

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).
Water hazard class (D): 1 - slightly hazardous to water

SECTION 16: Other information**Abbreviations and acronyms**

Met. Corr. 1: Corrosive to metals, hazard category 1
Skin Corr. 1A: Skin corrosion, sub-category 1A
Eye Dam. 1: Serious eye damage, hazard category 1

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Met. Corr. 1; H290	On basis of test data
Skin Corr. 1A; H314	Calculation method
Eye Dam. 1; H318	Calculation method

Relevant H and EUH statements (number and full text)

H290 May be corrosive to metals.
H314 Causes severe skin burns and eye damage.
H318 Causes serious eye damage.
EUH071 Corrosive to the respiratory tract.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Natriumaluminat-Lösung min. 10 %(m/m) Al zur Wasseraufbereitung

Revision: 23.04.2024

Product code: 31606

Page 11 of 11

Further Information

Provide appropriate information, instructions and training to users

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)