

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Multielement-Standardlösung "Öko 500" 19 Elemente in Salpetersäure 2 mol/l

Revision: 23.05.2024

Product code: 33357

Page 1 of 18

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Multielement-Standardlösung "Öko 500" 19 Elemente in Salpetersäure 2 mol/l

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Reagents and laboratory chemicals
Only for laboratory and analysis purposes.

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name:	AnalytiChem GmbH	
	ACD	
Street:	Stempelstraße 6	
Place:	D-47167 Duisburg	
Telephone:	0203/5194-0	Telefax: 0203/5194-290
E-mail:	info@analytichem.de	
Contact person:	Abteilung Produktsicherheit	Telephone: 0203/5194-107/117
E-mail:	produktsicherheit@analytichem.de	
Internet:	www.analytichem.de	
Responsible Department:	Abteilung Produktsicherheit	

1.4. Emergency telephone number:

For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

Further Information

This product is a mixture. REACH Registration Number see section 3.

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No 1272/2008**

Met. Corr. 1; H290
Carc. 1A; H350
Acute Tox. 4; H332
Skin Corr. 1B; H314
Eye Dam. 1; H318
Skin Sens. 1; H317
STOT RE 2; H373
Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements**Regulation (EC) No 1272/2008****Hazard components for labelling**

nitric acid
arsenic acid and its salts with the exception of those specified elsewhere in this Annex
nickel dinitrate
cobalt dinitrate

Signal word: Danger

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Multielement-Standardlösung "Öko 500" 19 Elemente in Salpetersäure 2 mol/l

Revision: 23.05.2024

Product code: 33357

Page 2 of 18

Pictograms:



Hazard statements

H290	May be corrosive to metals.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H332	Harmful if inhaled.
H350	May cause cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.

Special labelling of certain mixtures

EUH071	Corrosive to the respiratory tract. Restricted to professional users.
--------	--

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixtures in aqueous solution

according to Regulation (EC) No 1907/2006

Multielement-Standardlösung "Öko 500" 19 Elemente in Salpetersäure 2 mol/l

Revision: 23.05.2024

Product code: 33357

Page 3 of 18

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
7697-37-2	nitric acid			10 - < 15 %
	231-714-2	007-030-00-3	01-2119487297-23	
	Ox. Liq. 3, Met. Corr. 1, Acute Tox. 3, Skin Corr. 1A, Eye Dam. 1; H272 H290 H331 H314 H318 EUH071			
10043-35-3	boric acid			< 1 %
	233-139-2	005-007-00-2	01-2119486683-25	
	Repr. 1B; H360FD			
10031-43-3	Copper(II) nitrate trihydrate			< 1 %
			01-2119969290-34	
	Ox. Sol. 2, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, Aquatic Acute 1, Aquatic Chronic 1; H272 H302 H315 H319 H400 H410			
-	arsenic acid and its salts with the exception of those specified elsewhere in this Annex			< 1 %
	-	033-005-00-1		
	Carc. 1A, Acute Tox. 3, Acute Tox. 3, Aquatic Acute 1, Aquatic Chronic 1; H350 H331 H301 H400 H410			
13138-45-9	nickel dinitrate			< 1 %
	236-068-5	028-012-00-1	01-2119492333-38	
	Ox. Sol. 2, Carc. 1A, Muta. 2, Repr. 1B, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Dam. 1, Resp. Sens. 1, Skin Sens. 1, STOT RE 1, Aquatic Acute 1, Aquatic Chronic 1; H272 H350i H341 H360D H332 H302 H315 H318 H334 H317 H372 H400 H410			
10141-05-6	cobalt dinitrate			< 0.1 %
	233-402-1	027-009-00-2		
	Carc. 1B, Muta. 2, Repr. 1B, Resp. Sens. 1, Skin Sens. 1, Aquatic Acute 1, Aquatic Chronic 1; H350i H341 H360F H334 H317 H400 H410			
10325-94-7	cadmium nitrate; cadmium dinitrate			< 0.1 %
	233-710-6	048-014-00-6		
	Carc. 1B, Muta. 1B, Repr. 1B, Acute Tox. 4, Acute Tox. 4, Acute Tox. 4, STOT RE 1, Aquatic Acute 1, Aquatic Chronic 1; H350 H340 H360 H332 H312 H302 H372 H400 H410			

Full text of H and EUH statements: see section 16.

Multielement-Standardlösung "Öko 500" 19 Elemente in Salpetersäure 2 mol/l

Revision: 23.05.2024

Product code: 33357

Page 4 of 18

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
7697-37-2	231-714-2	nitric acid	10 - < 15 %
		inhalation: ATE 2,65 mg/l (vapours) Ox. Liq. 3; H272: >= 65 - 100 Skin Corr. 1A; H314: >= 20 - 100 Skin Corr. 1B; H314: >= 5 - < 20	
10043-35-3	233-139-2	boric acid	< 1 %
		inhalation: LC50 = > 2,12 mg/l (dusts or mists); dermal: LD50 = > 2000 mg/kg; oral: LD50 = 3450 mg/kg	
10031-43-3		Copper(II) nitrate trihydrate	< 1 %
		oral: ATE = 500 mg/kg	
-	-	arsenic acid and its salts with the exception of those specified elsewhere in this Annex	< 1 %
		inhalation: ATE = 3 mg/l (vapours); inhalation: ATE = 0,5 mg/l (dusts or mists); oral: ATE = 100 mg/kg	
13138-45-9	236-068-5	nickel dinitrate	< 1 %
		inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); oral: LD50 = 361,9 mg/kg Skin Irrit. 2; H315: >= 20 - 100 Skin Sens. 1; H317: >= 0,01 - 100 STOT RE 1; H372: >= 1 - 100 STOT RE 2; H373: >= 0,1 - < 1 Aquatic Acute 1; H400: M=1 Aquatic Chronic 1; H410: M=1	
10141-05-6	233-402-1	cobalt dinitrate	< 0.1 %
		Carc. 1B; H350i: >= 0,01 - 100 Aquatic Acute 1; H400: M=10 Aquatic Chronic 1; H410: M=10	
10325-94-7	233-710-6	cadmium nitrate; cadmium dinitrate	< 0.1 %
		inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: ATE = 1100 mg/kg; oral: ATE = 500 mg/kg Carc. 1B; H350: >= 0,01 - 100	

Further Information

No data available

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

First aider: Pay attention to self-protection!

After inhalation

Provide fresh air.

Call a physician immediately.

After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

Call a physician immediately.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Remove contact lenses, if present and easy to do. Continue rinsing.

Protect uninjured eye.

After ingestion

Rinse mouth immediately and drink plenty of water.

Do NOT induce vomiting. Do not allow a neutralisation agent to be drunk.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Multielement-Standardlösung "Öko 500" 19 Elemente in Salpetersäure 2 mol/l

Revision: 23.05.2024

Product code: 33357

Page 5 of 18

Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Causes burns.
Irritant
Cough
Dyspnoea
Vomiting
Methaemoglobinaemia
Risk of serious damage to eyes.
Allergic reactions

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Non-combustible liquids
Hazardous combustion products
In case of fire may be liberated:
Nitrogen oxides (NO_x)
Metal oxide smoke, toxic

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.
In case of fire and/or explosion do not breathe fumes.
Avoid contact with skin, eyes and clothes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.
Move undamaged containers from immediate hazard area if it can be done safely.
Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Corrosive to metals.

For non-emergency personnel

Provide adequate ventilation.
Use personal protection equipment.
Avoid contact with skin, eyes and clothes.
Remove persons to safety.
Emergency procedures
Consult an expert
Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

Multielement-Standardlösung "Öko 500" 19 Elemente in Salpetersäure 2 mol/l

Revision: 23.05.2024

Product code: 33357

Page 6 of 18

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up**For containment**

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Use personal protection equipment.

Provide adequate ventilation. Avoid contact with skin, eyes and clothes.

Do not breathe vapour/aerosol. Use extractor hood (laboratory).

Advice on protection against fire and explosion

Usual measures for fire prevention.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs. Remove contaminated, saturated clothing immediately.

Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink. Avoid: aerosol or mist formation Do not breathe vapour/aerosol.

Further information on handling

Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary.

Take off immediately all contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Corrosive to metals.

Unsuitable container/equipment material: Metal

The product develops hydrogen in an aqueous solution in contact with metals.

Hints on joint storage

national regulations

Further information on storage conditions

Keep container tightly closed.

Store in a place accessible by authorized persons only.

7.3. Specific end use(s)

according to Regulation (EC) No 1907/2006

Multielement-Standardlösung "Öko 500" 19 Elemente in Salpetersäure 2 mol/l

Revision: 23.05.2024

Product code: 33357

Page 7 of 18

Laboratory chemicals

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational exposure limits**

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
10043-35-3	Borate compounds inorganic: boric acid	-	2		TWA (8 h)	
7697-37-2	Nitric acid	1	2.6		STEL (15 min)	

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
10043-35-3	boric acid			
Worker DNEL, long-term		inhalation	systemic	8,3 mg/m³
Worker DNEL, long-term		dermal	systemic	392 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	4,15 mg/m³
Consumer DNEL, long-term		dermal	systemic	196 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	0,98 mg/kg bw/day
Consumer DNEL, acute		oral	systemic	0,98 mg/kg bw/day
13138-45-9	nickel dinitrate			
Consumer DNEL, acute		oral	systemic	0,012 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	0,02 mg/kg bw/day
Worker DNEL, acute		inhalation	systemic	104 mg/m³
Worker DNEL, acute		inhalation	local	1,6 mg/m³
Consumer DNEL, acute		inhalation	systemic	8,8 mg/m³
Consumer DNEL, acute		inhalation	local	0,1 mg/m³

Multielement-Standardlösung "Öko 500" 19 Elemente in Salpetersäure 2 mol/l

Revision: 23.05.2024

Product code: 33357

Page 8 of 18

PNEC values

CAS No	Substance	
Environmental compartment		Value
10043-35-3	boric acid	
Freshwater		2,9 mg/l
Freshwater (intermittent releases)		13,7 mg/l
Marine water		2,9 mg/l
Micro-organisms in sewage treatment plants (STP)		10 mg/l
Soil		5,7 mg/kg
10031-43-3	Copper(II) nitrate trihydrate	
Freshwater		0,0078 mg/l
Marine water		0,0052 mg/l
Freshwater sediment		87 mg/kg
Marine sediment		676 mg/kg
Micro-organisms in sewage treatment plants (STP)		0,23 mg/l
Soil		65 mg/kg
13138-45-9	nickel dinitrate	
Freshwater		0,0071 mg/l
Freshwater (intermittent releases)		0 mg/l
Marine water		0,0086 mg/l
Freshwater sediment		109 mg/kg
Marine sediment		109 mg/kg
Secondary poisoning		0,12 mg/kg
Micro-organisms in sewage treatment plants (STP)		0,33 mg/l
Soil		29,9 mg/kg

8.2. Exposure controls**Appropriate engineering controls**

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment**Eye/face protection**

goggles

Wear eye/face protection.

Hand protection

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact

Recommended glove articles: KCL 741 Dermatrill® L

Recommended material: NBR (Nitrile rubber) 0,11 mm

Wearing time with permanent contact: > 480 min

By short-term hand contact

Recommended glove articles: KCL 741 Dermatrill® L

Recommended material: NBR (Nitrile rubber) 0,11mm

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Multielement-Standardlösung "Öko 500" 19 Elemente in Salpetersäure 2 mol/l

Revision: 23.05.2024

Product code: 33357

Page 9 of 18

Wearing time with occasional contact (splashes): > 480 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet <(>, <)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing.

Wash hands before breaks and after work.

The choice of body protection depends on the concentration and quantity of hazardous substances. The chemical resistance of protective agents must be clarified with their suppliers.

Respiratory protection

Respiratory protection necessary at: aerosol or mist formation

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid	
Colour:	clear	
Odour:	like: Nitric acid	
Odour threshold:	No data available	
Melting point/freezing point:		No data available
Boiling point or initial boiling point and boiling range:		No data available
Flammability:		No data available
Lower explosion limits:		No data available
Upper explosion limits:		No data available
Flash point:		No data available
Auto-ignition temperature:		No data available
Decomposition temperature:		No data available
pH-Value:		acidic
Viscosity / kinematic:		No data available
Water solubility:		completely miscible
Solubility in other solvents		
No data available		
Partition coefficient n-octanol/water:		No data available
Vapour pressure:		No data available
Vapour pressure:		No data available
Density:		No data available
Bulk density:		No data available
Relative vapour density:		No data available

9.2. Other information**Information with regard to physical hazard classes**

Explosive properties

 No data available

Sustained combustibility:

No data available

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Multiement-Standardlösung "Öko 500" 19 Elemente in Salpetersäure 2 mol/l

Revision: 23.05.2024

Product code: 33357

Page 10 of 18

Self-ignition temperature

Solid:

No data available

Gas:

No data available

Oxidizing properties

Oxidizing

Other safety characteristics

Evaporation rate:

No data available

Solvent separation test:

No data available

Solvent content:

0

Solid content:

0

Sublimation point:

No data available

Softening point:

No data available

Pour point:

No data available

No data available:

Viscosity / dynamic:

No data available

Flow time:

No data available

Further Information

Corrosive to metals.

SECTION 10: Stability and reactivity

10.1. Reactivity

Corrosive to metals.

Oxidising agent

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Alkali (lye)

The product develops hydrogen in an aqueous solution in contact with metals.

Amines, Ammonia, Alcohols, Alkali metals, Hydrogen peroxide

Copper, Combustible solids, Solvent, Alkaline earth metal, mercury (Hg).

10.4. Conditions to avoid

No data available

10.5. Incompatible materials

Cellulose

Metal

The product develops hydrogen in an aqueous solution in contact with metals.

10.6. Hazardous decomposition products

In case of fire may be liberated:

SECTION 5: Firefighting measures

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicokinetics, metabolism and distribution

There are no data available on the mixture itself.

Acute toxicity

Harmful if inhaled.

Multielement-Standardlösung "Öko 500" 19 Elemente in Salpetersäure 2 mol/l

Revision: 23.05.2024

Product code: 33357

Page 11 of 18

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) 4,235 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
7697-37-2	nitric acid				
	inhalation vapour	ATE 2,65 mg/l			
10043-35-3	boric acid				
	oral	LD50 3450 mg/kg	Rat	Toxicology and Applied Pharmacology 23:	other: No data
	dermal	LD50 > 2000 mg/kg	Rabbit	Study report (1982)	other: FIFRA
	inhalation (4 h) dust/mist	LC50 > 2,12 mg/l	Rat	Study report (1997)	OECD Guideline 403
10031-43-3	Copper(II) nitrate trihydrate				
	oral	ATE 500 mg/kg			
-	arsenic acid and its salts with the exception of those specified elsewhere in this Annex				
	oral	ATE 100 mg/kg			
	inhalation vapour	ATE 3 mg/l			
	inhalation dust/mist	ATE 0,5 mg/l			
13138-45-9	nickel dinitrate				
	oral	LD50 361,9 mg/kg	Rat	Regul Toxicol and Pharmacol (doi.org/10.	OECD Guideline 425
	inhalation vapour	ATE 11 mg/l			
	inhalation dust/mist	ATE 1,5 mg/l			
10325-94-7	cadmium nitrate; cadmium dinitrate				
	oral	ATE 500 mg/kg			
	dermal	ATE 1100 mg/kg			
	inhalation vapour	ATE 11 mg/l			
	inhalation dust/mist	ATE 1,5 mg/l			

Irritation and corrosivity

Skin corrosion/irritation: Causes severe skin burns and eye damage.

Serious eye damage/eye irritation: Causes serious eye damage.

Corrosive to the respiratory tract.

Following ingestion Gastric perforation

Mucous membrane irritation in the mouth, throat, esophagus and gastrointestinal tract.

Irritating to respiratory system.

Pulmonary oedema

see also Section 4

Sensitising effects

May cause an allergic skin reaction. (nickel dinitrate; cobalt dinitrate)

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Multielement-Standardlösung "Öko 500" 19 Elemente in Salpetersäure 2 mol/l

Revision: 23.05.2024

Product code: 33357

Page 12 of 18

Carcinogenic/mutagenic/toxic effects for reproduction

May cause cancer. (arsenic acid and its salts with the exception of those specified elsewhere in this Annex ; nickel dinitrate; cobalt dinitrate; cadmium nitrate; cadmium dinitrate)
Germ cell mutagenicity: Based on available data, the classification criteria are not met.
Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (nickel dinitrate)

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

There are no data available on the mixture itself.

Additional information on tests

There are no data available on the mixture itself.

Practical experience

There are no data available on the mixture itself.

11.2. Information on other hazards**Other information**

There are no data available on the mixture itself.

Further information

There are no data available on the mixture itself.

SECTION 12: Ecological information**12.1. Toxicity**

Harmful to aquatic life with long lasting effects.

Multielement-Standardlösung "Öko 500" 19 Elemente in Salpetersäure 2 mol/l

Revision: 23.05.2024

Product code: 33357

Page 13 of 18

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
7697-37-2	nitric acid					
	Acute fish toxicity	LC50 1559 mg/l	96 h	Topeka shiner	Environmental Toxicology and Chemistry,	other: ASTM E729-26
	Fish toxicity	NOEC 268 mg/l	30 d	juvenile Topeka shiner and with juvenile Fathead m	Study report (2009)	Growth tests estimated the test chemical
	Algae toxicity	NOEC > 419 mg/l	10 d	several benthic diatoms; see results	Marine Biology 43:307-315 (1977)	Ten cultures of benthic diatoms were iso
	Acute bacteria toxicity	EC50 > 1000 mg/l ()	3 h	Activated sludge	Study report (2008)	OECD Guideline 209
10043-35-3	boric acid					
	Acute fish toxicity	LC50 79,7 mg/l	96 h	Pimephales promelas	Study report (2010)	other: ASTM E729-95 Standard Guide for C
	Acute algae toxicity	ErC50 66 mg/l	72 h	Phaeodactylum tricornutum	Study report (2011)	ISO 10253
	Acute crustacea toxicity	EC50 109 mg/l	48 h	Ceriodaphnia dubia	Study report (2010)	other: ASTM E729-95 Standard Guide for C
	Fish toxicity	NOEC 11,2 mg/l	32 d	Pimephales promelas	Study report (2010)	other: ASTM E1241-05 Standard Guide for
	Algae toxicity	NOEC 17,5 mg/l	3 d	Pseudokirchneriella subcapitata	Study report (2000)	OECD Guideline 201
	Crustacea toxicity	NOEC 25,9 mg/l	42 d	other aquatic crustacea: Hyalella azteca	Study report (2010)	other: US EPA 2000 Methods for assessing
	Acute bacteria toxicity	EC50 > 10000 mg/l ()	3 h	activated sludge of a predominantly domestic sewage	Study report (2001)	OECD Guideline 209
10031-43-3	Copper(II) nitrate trihydrate					
	Acute fish toxicity	LC50 0,193 mg/l	96 h	Pimephales promelas	Study report (1996)	measurements were conducted by standard
	Acute algae toxicity	ErC50 0,152 mg/l	72 h	Pseudokirchneriella subcapitata	Publication (2005)	OECD Guideline 201
	Acute crustacea toxicity	EC50 0,007 mg/l	48 h	Daphnia magna	Study report (1978)	- Test were conducted on Daphnia magna t
	Fish toxicity	NOEC 0,123 mg/l	12 d	Atherinops affinis	Mar. Environ. Res. 31: 17-35 (1991)	Three tests are reported, designed to de

Multielement-Standardlösung "Öko 500" 19 Elemente in Salpetersäure 2 mol/l

Revision: 23.05.2024

Product code: 33357

Page 14 of 18

	Algae toxicity	NOEC mg/l	0,0102	19 d	other aquatic plant: giant kelp <i>Macrocystis</i> <i>pyrife</i>	Mar. Ecol. Prog. Ser. 68: 147 - 156 (199)	Tests were conducted to determine the ef
	Crustacea toxicity	NOEC mg/l	0,033	14 d	<i>Penaeus</i> <i>mergulus</i> and <i>Penaeus monodon</i>	Bull. Environ. Contain. Toxicol. (1995)	The effects of dissolved copper on the g
13138-45-9	nickel dinitrate						
	Acute fish toxicity	LC50 mg/l	15,3	96 h	<i>Oncorhynchus mykiss</i>	Aquatic Toxicology 63 (2003) 65-82 (2003)	other: not reported
	Acute algae toxicity	ErC50 mg/l	0,237	72 h	<i>Ankistrodesmus</i> <i>falcatus</i>	Publication (2009)	OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	0,2663	48 h	<i>Ceriodaphnia dubia</i>	Study report (2004)	other: American society of testing and m
	Fish toxicity	NOEC mg/l	0,057	32 d	<i>Pimephales</i> <i>promelas</i>	Water Resources Research Institute. Kent	other: ASTM 1980, E-729
	Algae toxicity	NOEC	0,6 mg/l	14 d	<i>Anabaena cylindrica</i>	Environ. Pollut. (Series A). 25(4):241-2	other: not reported
	Crustacea toxicity	NOEC mg/l	0,04	42 d	<i>Daphnia magna</i>	Wat. Res. 24(7):845-852 (1990)	Chronic exposure to sublethal concentrat
	Acute bacteria toxicity	EC50	33 mg/l ()	0,5 h	Activated sludge	Journal of Hazardous Materials. B139:332	ISO 8192

12.2. Persistence and degradability

The methods for determining the biological degradability are not applicable to inorganic substances.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
10043-35-3	boric acid	-1,09

BCF

CAS No	Chemical name	BCF	Species	Source
10043-35-3	boric acid	0,558	<i>Oncorhynchus nerka</i>	Water Research Vol.
10031-43-3	Copper(II) nitrate trihydrate	0,02 - 20	<i>Crangon crangon</i>	Symp. Biologica. Hun
13138-45-9	nickel dinitrate	23	<i>Spirodela polyrhiza</i>	Ecotoxicology and en

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Multielement-Standardlösung "Öko 500" 19 Elemente in Salpetersäure 2 mol/l

Revision: 23.05.2024

Product code: 33357

Page 15 of 18

Discharge into the environment must be avoided.
Harmful effect due to pH shift.
Forms corrosive mixtures with water even if diluted.

Further information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.
Send to a physico-chemical treatment facility under observation of official regulations.
Do not empty into drains.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.
The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number or ID number:	UN 2031
14.2. UN proper shipping name:	NITRIC ACID
14.3. Transport hazard class(es):	8
14.4. Packing group:	II
Hazard label:	8
Classification code:	C1
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	80
Tunnel restriction code:	E

Inland waterways transport (ADN)

14.1. UN number or ID number:	UN 2031
14.2. UN proper shipping name:	NITRIC ACID
14.3. Transport hazard class(es):	8
14.4. Packing group:	II
Hazard label:	8
Classification code:	C1
Limited quantity:	1 L
Excepted quantity:	E2

Marine transport (IMDG)

14.1. UN number or ID number:	UN 2031
14.2. UN proper shipping name:	NITRIC ACID
14.3. Transport hazard class(es):	8
14.4. Packing group:	II
Hazard label:	8
Special Provisions:	-
Limited quantity:	1 L
Excepted quantity:	E2
EmS:	F-A, S-B

Air transport (ICAO-TI/IATA-DGR)

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Multielement-Standardlösung "Öko 500" 19 Elemente in Salpetersäure 2 mol/l

Revision: 23.05.2024

Product code: 33357

Page 16 of 18

14.1. UN number or ID number:	UN 2031
14.2. UN proper shipping name:	NITRIC ACID
14.3. Transport hazard class(es):	8
14.4. Packing group:	II
Hazard label:	8
Special Provisions:	A212
Limited quantity Passenger:	Forbidden
Passenger LQ:	Forbidden
Excepted quantity:	E0
IATA-packing instructions - Passenger:	Forbidden
IATA-max. quantity - Passenger:	Forbidden
IATA-packing instructions - Cargo:	855
IATA-max. quantity - Cargo:	30 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Authorisations (REACH, annex XIV):

arsenic acid and its salts with the exception of those specified elsewhere in this Annex

Substances of very high concern, SVHC (REACH, article 59):

boric acid; cobalt dinitrate; cadmium nitrate; cadmium dinitrate

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 23, Entry 27, Entry 28, Entry 30, Entry 75

Marketing and use of explosives precursors (Regulation (EU) 2019/1148):

Acquisition, introduction, possession or use of this product by the general public is restricted by Regulation (EU) 2019/1148. All suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point.

National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe employment restrictions for women of child-bearing age.

Water hazard class (D):

3 - highly hazardous to water

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 2,3,4,5,7,9,11,12,13,14,15.

Multielement-Standardlösung "Öko 500" 19 Elemente in Salpetersäure 2 mol/l

Revision: 23.05.2024

Product code: 33357

Page 17 of 18

Abbreviations and acronyms

Ox. Liq. 3: Oxidising liquids, hazard category 3
Ox. Sol. 2: Oxidising solids, hazard category 2
Met. Corr. 1: Corrosive to metals, hazard category 1
Acute Tox. 3: Acute toxicity, hazard category 3
Skin Corr. 1A: Skin corrosion, sub-category 1A
Skin Irrit. 2: Skin irritation, hazard category 2
Eye Dam. 1: Serious eye damage, hazard category 1
Eye Irrit. 2: Eye irritation, hazard category 2
Resp. Sens. 1: Respiratory sensitisation, hazard category 1
Skin Sens. 1: Skin sensitisation, hazard category 1
Muta. 1B: Germ cell mutagenicity, hazard category 1B
Carc. 1A: Carcinogenicity, hazard category 1A
Repr. 1B: Reproductive toxicity, hazard category 1B
STOT RE 1: Specific target organ toxicity - repeated exposure, hazard category 1
Aquatic Acute 1: Hazardous to the aquatic environment, hazard category: Acute 1
Aquatic Chronic 1: Hazardous to the aquatic environment, long-term hazard category: Chronic 1

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Met. Corr. 1; H290	On basis of test data
Carc. 1A; H350	Calculation method
Acute Tox. 4; H332	Calculation method
Skin Corr. 1B; H314	Calculation method
Eye Dam. 1; H318	Calculation method
Skin Sens. 1; H317	Calculation method
STOT RE 2; H373	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H272 May intensify fire; oxidiser.
H290 May be corrosive to metals.
H301 Toxic if swallowed.
H302 Harmful if swallowed.
H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H331 Toxic if inhaled.
H332 Harmful if inhaled.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H340 May cause genetic defects.
H341 Suspected of causing genetic defects.
H350 May cause cancer.
H350i May cause cancer by inhalation.
H360 May damage fertility or the unborn child.
H360D May damage the unborn child.
H360F May damage fertility.
H360FD May damage fertility. May damage the unborn child.
H372 Causes damage to organs through prolonged or repeated exposure.
H373 May cause damage to organs through prolonged or repeated exposure.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Multielement-Standardlösung "Öko 500" 19 Elemente in Salpetersäure 2 mol/l

Revision: 23.05.2024

Product code: 33357

Page 18 of 18

H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations. Provide appropriate information, instructions and training to users

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)