Print date: 25.09.2025



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Multi-element standard solution 27 elements each 500 mg/l in nitric acid 2 mol/l

Revision: 28.11.2024 Product code: 34043 Page 1 of 19

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Multi-element standard solution 27 elements each 500 mg/l in nitric acid 2 mol/l

UFI: RR81-K33A-800A-VP8H

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Reagents and laboratory chemicals

Only for laboratory and analysis purposes.

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name: AnalytiChem GmbH

ACD

Street: Stempelstraße 6
Place: D-47167 Duisburg

Telephone: 0203/5194-0 Telefax: 0203/5194-290

E-mail: info@analytichem.de

Contact person: Abteilung Produktsicherheit Telephone: 0203/5194-107/117

E-mail: produktsicherheit@analytichem.de

Internet: www.analytichem.de

Responsible Department: Abteilung Produktsicherheit

1.4. Emergency telephone For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire,

<u>number:</u> Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada:

1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls

accepted)

Further Information

This product is a mixture. REACH Registration Number see section 3.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Met. Corr. 1; H290 Carc. 1A; H350 Acute Tox. 4; H332 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1; H317 STOT RE 2; H373 Aquatic Acute 1; H400 Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008



according to Regulation (EC) No 1907/2006

Multi-element standard solution 27 elements each 500 mg/l in nitric acid 2 mol/l

Revision: 28.11.2024 Product code: 34043 Page 2 of 19

Hazard components for labelling

nitric acid

beryllium nitrate

arsenic acid and it salts with the exception of those specified elsewhere in this Annex

nickel dinitrate cobalt dinitrate

cadmium nitrate; cadmium dinitrate

Signal word: Danger

Pictograms:









Hazard statements

H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H332 Harmful if inhaled. H350 May cause cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water

or shower

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

Special labelling of certain mixtures

EUH071 Corrosive to the respiratory tract.

Restricted to professional users.

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixtures in aqueous solution



according to Regulation (EC) No 1907/2006

Multi-element standard solution 27 elements each 500 mg/l in nitric acid 2 mol/l

Revision: 28.11.2024 Product code: 34043 Page 3 of 19

Relevant ingredients

CAS No	Chemical name			Quantity	
	EC No	Index No	REACH No		
	Classification (Regulation (EC	i) No 1272/2008)	·		
7697-37-2	nitric acid			10 - < 15 %	
	231-714-2	007-030-00-3	01-2119487297-23		
	Ox. Liq. 3, Met. Corr. 1, Acute EUH071	Tox. 3, Skin Corr. 1A, Eye Dan	n. 1; H272 H290 H331 H314 H318		
-	beryllium compounds with the specified elsewhere in this An	exception of aluminium berylliunex	m silicates, and with those	< 1 %	
	-	004-002-00-2			
	•	Tox. 3, Skin Irrit. 2, Eye Irrit. 2, 0 H301 H315 H319 H317 H335	Skin Sens. 1, STOT SE 3, STOT RE 1, H372 H411		
10031-43-3	Copper(II) nitrate trihydrate			< 1 %	
			01-2119969290-34		
	Ox. Sol. 2, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, Aquatic Acute 1, Aquatic Chronic 1; H272 H302 H315 H319 H400 H410				
-	arsenic acid and it salts with t	ne exception of those specified	elsewhere in this Annex	< 1 %	
	-	033-005-00-1			
	Carc. 1A, Acute Tox. 3, Acute H410	Tox. 3, Aquatic Acute 1, Aquatic	Chronic 1; H350 H331 H301 H400		
13138-45-9	nickel dinitrate			< 1 %	
	236-068-5	028-012-00-1	01-2119492333-38		
		RE 1, Aquatic Acute 1, Aquatic	ox. 4, Skin Irrit. 2, Eye Dam. 1, Resp. Chronic 1; H272 H350i H341 H360D		
10141-05-6	cobalt dinitrate			< 1 %	
	233-402-1	027-009-00-2			
	Carc. 1B, Muta. 2, Repr. 1B, Resp. Sens. 1, Skin Sens. 1, Aquatic Acute 1, Aquatic Chronic 1; H350i H341 H360F H334 H317 H400 H410				
7803-55-6	ammonium trioxovanadate			< 1 %	
	232-261-3				
	Repr. 2, Acute Tox. 3, Acute T H319 H372 H411	ox. 4, Eye Irrit. 2, STOT RE 1, A	Aquatic Chronic 2; H361d H301 H332		
10325-94-7	cadmium nitrate; cadmium dir	itrate		< 0.1 %	
	233-710-6	048-014-00-6			
	· _ · _ · _ · _ · _ ·	Acute Tox. 4, Acute Tox. 4, Acu 0 H360 H332 H312 H302 H372	ute Tox. 4, STOT RE 1, Aquatic Acute 1, H400 H410		
7761-88-8	silver nitrate			< 0.1 %	
	231-853-9	047-001-00-2	01-2119513705-43		
	Ox. Sol. 2, Met. Corr. 1, Skin H290 H314 H318 H400 H410		cute 1, Aquatic Chronic 1; H272		

Full text of H and EUH statements: see section 16.



according to Regulation (EC) No 1907/2006

Multi-element standard solution 27 elements each 500 mg/l in nitric acid 2 mol/l

Revision: 28.11.2024 Product code: 34043 Page 4 of 19

Specific Conc. Limits, M-factors and ATE

CAS No	EC No Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE	
7697-37-2	231-714-2 nitric acid	10 - < 15 %
	inhalation: ATE 2,65 mg/l (vapours) Ox. Liq. 3; H272: >= 65 - 100 Skin Corr. 1A; H314: >= 20 100 Skin Corr. 1B; H314: >= 5 - < 20) -
	- beryllium compounds with the exception of aluminium beryllium silicates, and with those specified elsewhere in this Annex	< 1 %
	inhalation: ATE = 0,5 mg/l (vapours); inhalation: ATE = 0,05 mg/l (dusts or mists); oral: ATE = 100 mg/kg	
10031-43-3	Copper(II) nitrate trihydrate	< 1 %
	oral: ATE = 500 mg/kg	
-	- arsenic acid and it salts with the exception of those specified elsewhere in this Annex	< 1 %
	inhalation: ATE = 3 mg/l (vapours); inhalation: ATE = 0,5 mg/l (dusts or mists); oral: ATE = 100 mg/kg	
13138-45-9	236-068-5 nickel dinitrate	< 1 %
	inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); oral: LD50 = 361,9 mg/kg Skin Irrit. 2; H315: >= 20 - 100 Skin Sens. 1; H317: >= 0,01 - 100 STOT RE 1; H372: >= 1 - 100 STOT RE 2; H373: >= 0,1 - < 1 Aquatic Acute 1; H400: M=1 Aquatic Chronic 1; H410: M=1	
10141-05-6	233-402-1 cobalt dinitrate	< 1 %
	Carc. 1B; H350i: >= 0,01 - 100 Aquatic Acute 1; H400: M=10 Aquatic Chronic 1; H410: M=10	
7803-55-6	232-261-3 ammonium trioxovanadate	< 1 %
	inhalation: ATE = 11 mg/l (vapours); inhalation: LC50 = 2,61 mg/l (dusts or mists); dermal: LD50 = > 2500 mg/kg; oral: LD50 = 218,1 mg/kg	
10325-94-7	233-710-6 cadmium nitrate; cadmium dinitrate	< 0.1 %
	inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: ATE = 1100 mg/kg; oral: ATE = 500 mg/kg	
7761-88-8	231-853-9 silver nitrate	< 0.1 %
	dermal: LD50 = > 348 mg/kg; oral: LD50 = > 2000 mg/kg Aquatic Acute 1; H400: M=1000 Aquatic Chronic 1; H410: M=100	

Further Information

No data available

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection!

After inhalation

Provide fresh air.

Call a physician immediately.

After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

Call a physician immediately.

Print date: 25 09 2025



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Multi-element standard solution 27 elements each 500 mg/l in nitric acid 2 mol/l

Revision: 28.11.2024 Product code: 34043 Page 5 of 19

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Remove contact lenses, if present and easy to do. Continue rinsing.

Protect uninjured eye.

After ingestion

Rinse mouth immediately and drink plenty of water.

Do NOT induce vomiting. Do not allow a neutralisation agent to be drunk.

Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Causes burns.

Irritant

Cough

Dyspnoea

Vomiting

Methaemoglobinaemia

Risk of serious damage to eyes.

Allergic reactions

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Non-combustible liquids

Hazardous combustion products

In case of fire may be liberated:

Nitrogen oxides (NOx)

Metal oxide smoke, toxic

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

In case of fire and/or explosion do not breathe fumes.

Avoid contact with skin, eyes and clothes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Move undamaged containers from immediate hazard area if it can be done safely.

Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Do not breathe vapour/aerosol. Corrosive to metals.

For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Print date: 25 09 2025



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Multi-element standard solution 27 elements each 500 mg/l in nitric acid 2 mol/l

Revision: 28.11.2024 Product code: 34043 Page 6 of 19

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Consult an expert

Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders: Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Use personal protection equipment.

Provide adequate ventilation. Avoid contact with skin, eyes and clothes.

Do not breathe vapour/aerosol. Use extractor hood (laboratory).

Advice on protection against fire and explosion

Usual measures for fire prevention.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs. Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink. Avoid: aerosol or mist formation Do not breathe vapour/aerosol.

Further information on handling

Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary.

Take off immediately all contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Corrosive to metals.

Unsuitable container/equipment material: Metal

The product develops hydrogen in an aqueous solution in contact with metals.



according to Regulation (EC) No 1907/2006

Multi-element standard solution 27 elements each 500 mg/l in nitric acid 2 mol/l

Revision: 28.11.2024 Product code: 34043 Page 7 of 19

Hints on joint storage

national regulations

Further information on storage conditions

Keep container tightly closed.

Store in a place accessible by authorized persons only.

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
7697-37-2	Nitric acid	1	2.6		STEL (15 min)	

DNEL/DMEL values

CAS No	Substance					
DNEL type		Exposure route	Effect	Value		
13138-45-9	nickel dinitrate	nickel dinitrate				
Consumer DN	EL, acute	oral	systemic	0,012 mg/kg bw/day		
Consumer DN	EL, long-term	oral	systemic	0,02 mg/kg bw/day		
Worker DNEL,	acute	inhalation	systemic	104 mg/m³		
Worker DNEL,	acute	inhalation	local	1,6 mg/m³		
Consumer DN	EL, acute	inhalation	systemic	8,8 mg/m³		
Consumer DN	EL, acute	inhalation	local	0,1 mg/m³		
7803-55-6	ammonium trioxovanadate					
Worker DNEL,	long-term	inhalation	systemic	0,64 mg/m³		
Worker DNEL,	long-term	inhalation	local	0,18 mg/m³		
Worker DNEL,	acute	inhalation	local	0,92 mg/m³		
Consumer DN	EL, long-term	inhalation	systemic	0,18 mg/m³		
Consumer DN	EL, long-term	inhalation	local	0,11 mg/m³		
Consumer DN	EL, acute	inhalation	local	0,57 mg/m³		
Consumer DN	EL, long-term	oral	systemic	0,18 mg/kg bw/day		
Consumer DN	EL, acute	oral	systemic	0,92 mg/kg bw/day		
7761-88-8	silver nitrate					
Worker DNEL,	long-term	inhalation	systemic	0,016 mg/m³		
Consumer DN	EL, long-term	inhalation	systemic	0,006 mg/m³		
Consumer DN	EL, long-term	oral	systemic	0,02 mg/kg bw/day		

Print date: 25.09.2025



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Multi-element standard solution 27 elements each 500 mg/l in nitric acid 2 mol/l

Revision: 28.11.2024 Product code: 34043 Page 8 of 19

PNEC values

CAS No	Substance	
Environmenta	al compartment	Value
10031-43-3	Copper(II) nitrate trihydrate	
Freshwater	<u> </u>	0,0078 mg/l
Marine water		0,0052 mg/l
Freshwater se	ediment	87 mg/kg
Marine sedim	ent	676 mg/kg
Micro-organis	ms in sewage treatment plants (STP)	0,23 mg/l
Soil		65 mg/kg
13138-45-9	nickel dinitrate	
Freshwater		0,0071 mg/l
Freshwater (in	ntermittent releases)	0 mg/l
Marine water		0,0086 mg/l
Freshwater se	ediment	109 mg/kg
Marine sedim	ent	109 mg/kg
Secondary po	pisoning	0,12 mg/kg
Micro-organis	ms in sewage treatment plants (STP)	0,33 mg/l
Soil		29,9 mg/kg
7803-55-6	ammonium trioxovanadate	
Freshwater		0,0076 mg/l
Freshwater (iı	ntermittent releases)	0,00693 mg/l
Marine water		0,0025 mg/l
Freshwater se	ediment	240 mg/kg
Marine sedim	ent	79 mg/kg
Secondary po	bisoning	0,167 mg/kg
Micro-organis	ms in sewage treatment plants (STP)	0,45 mg/l
Soil		7,2 mg/kg
7761-88-8	silver nitrate	
Freshwater		0,00004 mg/l
Marine water		0,00086 mg/l
Freshwater se	ediment	438,13 mg/kg
Marine sedim	ent	438,13 mg/kg
Micro-organis	ms in sewage treatment plants (STP)	0,025 mg/l
Soil		1,41 mg/kg

8.2. Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment

Eye/face protection

goggles

Wear eye/face protection.



according to Regulation (EC) No 1907/2006

Multi-element standard solution 27 elements each 500 mg/l in nitric acid 2 mol/l

Revision: 28.11.2024 Product code: 34043 Page 9 of 19

Hand protection

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact

Recommended glove articles: KCL 741 Dermatril® L Recommended material: NBR (Nitrile rubber) 0,11 mm Wearing time with permanent contact: > 480 min

By short-term hand contact

Recommended glove articles: KCL 741 Dermatril® L Recommended material: NBR (Nitrile rubber) 0,11mm Wearing time with occasional contact (splashes): > 480 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing.

Wash hands before breaks and after work.

The choice of body protection depends on the concentration and quantity of hazardous substances. The chemical resistance of protective agents must be clarified with their suppliers.

Respiratory protection

Respiratory protection necessary at: aerosol or mist formation

The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Thermal hazards

No data available

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid Colour: clear

Odour: like: Nitric acid
Odour threshold: No data available

Melting point/freezing point:

Boiling point or initial boiling point and

No data available

No data available

boiling range:

No data available Flammability: Lower explosion limits: No data available No data available Upper explosion limits: No data available Flash point: No data available Auto-ignition temperature: No data available Decomposition temperature: acidic pH-Value: No data available Viscosity / kinematic:



according to Regulation (EC) No 1907/2006

Multi-element standard solution 27 elements each 500 mg/l in nitric acid 2 mol/l

Revision: 28.11.2024 Product code: 34043 Page 10 of 19

completely miscible Water solubility:

Solubility in other solvents

No data available

No data available Dissolution rate: No data available Partition coefficient n-octanol/water: No data available Dispersion stability: No data available Vapour pressure: Vapour pressure: No data available No data available Density: No data available Bulk density: No data available Relative vapour density:

9.2. Other information

Information with regard to physical hazard classes

Explosive properties No data available

No data available Sustained combustibility:

Self-ignition temperature

No data available Solid: No data available Gas:

Oxidizing properties No data available

Other safety characteristics

No data available Evaporation rate: No data available Solvent separation test: Solvent content: 0 Solid content: No data available Sublimation point: No data available Softening point: No data available Pour point:

No data available:

Viscosity / dynamic: No data available No data available Flow time:

Further Information

Corrosive to metals.

SECTION 10: Stability and reactivity

10.1. Reactivity

Corrosive to metals.

Oxidising agent

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Alkali (lye)

The product develops hydrogen in an aqueous solution in contact with metals.

Amines, Ammonia, Alcohols, Alkali metals, Hydrogen peroxide

Copper, Combustible solids, Solvent, Alkaline earth metal, mercury (Hg).

10.4. Conditions to avoid

No data available

Print date: 25.09.2025



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Multi-element standard solution 27 elements each 500 mg/l in nitric acid 2 mol/l

Revision: 28.11.2024 Product code: 34043 Page 11 of 19

10.5. Incompatible materials

Cellulose

Metal

The product develops hydrogen in an aqueous solution in contact with metals.

10.6. Hazardous decomposition products

In case of fire may be liberated: SECTION 5: Firefighting measures

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicocinetics, metabolism and distribution

There are no data available on the mixture itself.

Acute toxicity

Harmful if inhaled.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) 15,48 mg/l; ATE (inhalation dust/mist) > 5 mg/l



according to Regulation (EC) No 1907/2006

Multi-element standard solution 27 elements each 500 mg/l in nitric acid 2 mol/l

Revision: 28.11.2024 Product code: 34043 Page 12 of 19

CAS No	Chemical name									
	Exposure route	Dose		Species	Source	Method				
7697-37-2	nitric acid									
	inhalation vapour	ATE 2,65	mg/l							
-	beryllium compounds with the exception of aluminium beryllium silicates, and with those specified elsewhere in this Annex									
	oral	ATE mg/kg	100							
	inhalation vapour	ATE	0,5 mg/l							
	inhalation dust/mist	ATE	0,05 mg/l							
10031-43-3	Copper(II) nitrate trihyd	Irate								
	oral	ATE mg/kg	500							
-	arsenic acid and it salts	with the exce	eption of thos	e specified elsewhe	ere in this Annex					
	oral	ATE mg/kg	100							
	inhalation vapour	ATE	3 mg/l							
	inhalation dust/mist	ATE	0,5 mg/l							
13138-45-9	nickel dinitrate									
	oral	LD50 mg/kg	361,9	Rat	Regul Toxicol and Pharmacol (doi.org/10.	OECD Guideline 425				
	inhalation vapour	ATE	11 mg/l							
	inhalation dust/mist	ATE	1,5 mg/l							
7803-55-6	ammonium trioxovanac	ammonium trioxovanadate								
	oral	LD50 mg/kg	218,1	Rat	Study report (1992)	OECD Guideline 401				
	dermal	LD50 mg/kg	> 2500	Rat	Study report (1992)	OECD Guideline 402				
	inhalation vapour	ATE	11 mg/l							
	inhalation (4 h) dust/mist	LC50	2,61 mg/l	Rat	Study report (1992)	OECD Guideline 403				
10325-94-7	cadmium nitrate; cadm	ium dinitrate								
	oral	ATE mg/kg	500							
	dermal	ATE mg/kg	1100							
	inhalation vapour	ATE	11 mg/l							
	inhalation dust/mist	ATE	1,5 mg/l							
7761-88-8	silver nitrate									
	oral	LD50 mg/kg	> 2000	Rat	Study report (1993)	OECD Guideline 401				
	dermal	LD50 mg/kg	> 348	Guinea pig	J. Vet. Med. Sci.73: 1417 - 1423. (2011)	OECD Guideline 434				

Print date: 25 09 2025



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Multi-element standard solution 27 elements each 500 mg/l in nitric acid 2 mol/l

Revision: 28.11.2024 Product code: 34043 Page 13 of 19

Irritation and corrosivity

Skin corrosion/irritation: Causes severe skin burns and eye damage.

Serious eye damage/eye irritation: Causes serious eye damage.

Corrosive to the respiratory tract.

Following ingestion Gastric perforation

Mucous membrane irritation in the mouth, throat, esophagus and gastrointestinal tract.

Irritating to respiratory system.

Pulmonary oedema

see also Section 4

Sensitising effects

May cause an allergic skin reaction. (beryllium compounds with the exception of aluminium beryllium silicates, and with those specified elsewhere in this Annex; nickel dinitrate; cobalt dinitrate)

Carcinogenic/mutagenic/toxic effects for reproduction

May cause cancer. (beryllium compounds with the exception of aluminium beryllium silicates, and with those specified elsewhere in this Annex; arsenic acid and it salts with the exception of those specified elsewhere in this Annex; nickel dinitrate; cobalt dinitrate; cadmium nitrate; cadmium dinitrate)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (nickel dinitrate)

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

There are no data available on the mixture itself.

Specific effects in experiment on an animal

There are no data available on the mixture itself.

Additional information on tests

There are no data available on the mixture itself.

Practical experience

There are no data available on the mixture itself.

11.2. Information on other hazards

Endocrine disrupting properties

There are no data available on the mixture itself.

Other information

There are no data available on the mixture itself.

Further information

There are no data available on the mixture itself.

SECTION 12: Ecological information

12.1. Toxicity

Very toxic to aquatic life.

Toxic to aquatic life with long lasting effects.



according to Regulation (EC) No 1907/2006

Multi-element standard solution 27 elements each 500 mg/l in nitric acid 2 mol/l

Revision: 28.11.2024 Product code: 34043 Page 14 of 19

CAS No	Chemical name								
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method		
697-37-2	nitric acid								
	Acute fish toxicity	LC50 mg/l	1559	96 h	Topeka shiner	Environmental Toxicology and Chemistry,	other: ASTM E729-26		
	Fish toxicity	NOEC	268 mg/l	30 d	juvenile Topeka shiner and with juvenile Fathead m	Study report (2009)	Growth tests estimated the tes chemical		
	Algae toxicity	NOEC mg/l	> 419	10 d	several benthic diatoms; see results	Marine Biology 43:307-315 (1977)	Ten cultures of benthic diatoms were iso		
	Acute bacteria toxicity	EC50 mg/l ()	> 1000	3 h	Activated sludge	Study report (2008)	OECD Guideline 209		
0031-43-3	Copper(II) nitrate trihydra	te							
	Acute fish toxicity	LC50 mg/l	0,193	96 h	Pimephales promelas	Study report (1996)	measurements were conducted by standard		
	Acute algae toxicity	ErC50 mg/l	0,152	72 h	Pseudokirchneriella subcapitata	Publication (2005)	OECD Guideline 201		
	Acute crustacea toxicity	EC50 mg/l	0,007	48 h	Daphnia magna	Study report (1978)	- Test were conducted on Daphnia magna t		
	Fish toxicity	NOEC mg/l	0,123	12 d	Atherinops affinis	Mar. Environ. Res. 31: 17-35 (1991)	Three tests are reported, designed to de		
	Algae toxicity	NOEC mg/l	0,0102	19 d	other aquatic plant: giant kelp Macrocystis pyrife	Mar. Ecol. Prog. Ser. 68: 147 - 156 (199	Tests were conducted to determine the ef		
	Crustacea toxicity	NOEC mg/l	0,033	14 d	Penaeus mergulensis and Penaeus monodon	Bull. Environ. Contain. Toxicol. (1995)	The effects of dissolved copper on the g		
13138-45-9	nickel dinitrate								
	Acute fish toxicity	LC50 mg/l	15,3	96 h	Oncorhynchus mykiss	Aquatic Toxicology 63 (2003) 65-82 (2003	other: not reported		
	Acute algae toxicity	ErC50 mg/l	0,237	72 h	Ankistrodesmus falcatus	Publication (2009)	OECD Guideline 201		
	Acute crustacea toxicity	EC50 mg/l	0,2663	48 h	Ceriodaphnia dubia	Study report (2004)	other: American society of testing and m		
	Fish toxicity	NOEC mg/l	0,057		Pimephales promelas	Water Resources Research Institute. Kent	other: ASTM 1980, E-729		
	Algae toxicity	NOEC	0,6 mg/l	14 d	Anabaena cylindrica	Environ. Pollut. (Series A). 25(4):241-2	other: not reported		
	Crustacea toxicity	NOEC mg/l	0,04	42 d	Daphnia magna	Wat. Res. 24(7):845-852 (1990)	Chronic exposure to sublethal concentrat		



according to Regulation (EC) No 1907/2006

Multi-element standard solution 27 elements each 500 mg/l in nitric acid 2 mol/l

Revision: 28.11.2024 Product code: 34043 Page 15 of 19

	Acute bacteria toxicity	EC50	33 mg/l (0,5 h	Activated sludge	Journal of Hazardous Materials. B139:332	ISO 8192
7803-55-6	ammonium trioxovanadat	е					
	Acute fish toxicity	LC50 mg/l	3,17	96 h	Gasterosteus aculeatus	Environmental Toxicology 20:18–22. (2005	EPA OPPTS 850.1075
	Acute algae toxicity	ErC50 mg/l	2,907	72 h	Desmodesmus subspicatus	Study report (1999)	OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	1,52	48 h	Daphnia magna	Study report (1978)	48h mortality test with daphnids
	Fish toxicity	NOEC mg/l	>= 0,48	28 d	Jordanella floridae	Water Research 13:905-910. (1979)	Different groups of fish were continuous
	Crustacea toxicity	NOEC mg/l	1,344	23 d	Daphnia magna	Bulletin of Environmental Contamination	other: 84/449/EEC: given by the Commissi
	Acute bacteria toxicity	EC50 mg/l ()	> 100	3 h	activated sludge of a predominantly domestic sewag	Study report (2010)	OECD Guideline 209
7761-88-8	silver nitrate						
	Acute fish toxicity	LC50 mg/l	0,0012	96 h	Pimephales promelas	Environmental Toxicology and Chemistry.	A guideline was not specified. The test
	Acute algae toxicity	ErC50 mg/l	0,0099	96 h	Pseudokirchneriella subcapitata	Environmental Science and Technology. 44	eline: U.S. Environmental Protection Age
	Acute crustacea toxicity	EC50 mg/l	0,00022	48 h	Daphnia magna	Environmental Toxicology and Chemistry.	The protective effect of reactive sulphi
	Fish toxicity	NOEC 0,00125 n	> ng/l	73 d	Oncorhynchus mykiss	Environmental Toxicology and Chemistry 2	other: ASTM 1241-98
	Algae toxicity	NOEC mg/l	0,0012	14 d	Champia parvula	in Bishop WE, Cardwell RD Heidolph BB (E	The toxicity tests lasted 11 days for th
	Crustacea toxicity	NOEC mg/l	0,00031	20 d	Isonychia bicolour	Environmental Toxicology and Chemistry.	20 day sublethal effects on representati

12.2. Persistence and degradability

The methods for determining the biological degradability are not applicable to inorganic substances.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.



according to Regulation (EC) No 1907/2006

Multi-element standard solution 27 elements each 500 mg/l in nitric acid 2 mol/l

Revision: 28.11.2024 Product code: 34043 Page 16 of 19

BCF

CAS No	Chemical name	BCF	Species	Source
10031-43-3	Copper(II) nitrate trihydrate	0,02 - 20	Crangon crangon	Symp. Biologica. Hun
13138-45-9	nickel dinitrate	23	Spirodela polyrhiza	Ecotoxicology and en
7803-55-6	ammonium trioxovanadate	< 0,036	Lactuca sativa	Study report (2003)
7761-88-8	silver nitrate	70	Cyprinus carpio	Water, Air and Soil

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Discharge into the environment must be avoided.

Harmful effect due to pH shift.

Forms corrosive mixtures with water even if diluted.

Further information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations.

Do not empty into drains.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 3264

14.2. UN proper shipping name: CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (nitric acid)

14.3. Transport hazard class(es): П 14.4. Packing group: 8 Hazard label: Classification code: C₁ 274 **Special Provisions:** 1 I Limited quantity: F2 Excepted quantity: Transport category: 80 Hazard No: F Tunnel restriction code:

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 3264

14.2. UN proper shipping name: CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (nitric acid)



according to Regulation (EC) No 1907/2006

Multi-element standard solution 27 elements each 500 mg/l in nitric acid 2 mol/l

Revision: 28.11.2024 Product code: 34043 Page 17 of 19

14.3. Transport hazard class(es):814.4. Packing group:IIHazard label:8Classification code:C1Special Provisions:274Limited quantity:1 LExcepted quantity:E2

Marine transport (IMDG)

14.1. UN number or ID number: UN 3264

14.2. UN proper shipping name: CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (nitric acid)

14.3. Transport hazard class(es): 8 Ш 14.4. Packing group: 8 Hazard label: 274 **Special Provisions:** Limited quantity: 1 L E2 Excepted quantity: F-A, S-B EmS: 1 - acids Segregation group:

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 3264

14.2. UN proper shipping name: CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (nitric acid)

14.3. Transport hazard class(es):814.4. Packing group:IIHazard label:8Special Provisions:A3 A803Limited quantity Passenger:0.5 LPassenger LQ:Y840Excepted quantity:E2

IATA-packing instructions - Passenger:851IATA-max. quantity - Passenger:1 LIATA-packing instructions - Cargo:855IATA-max. quantity - Cargo:30 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes

Danger releasing substance: silver nitrate

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Authorisations (REACH, annex XIV):

arsenic acid and it salts with the exception of those specified elsewhere in this Annex

Substances of very high concern, SVHC (REACH, article 59):

cobalt dinitrate; cadmium nitrate; cadmium dinitrate

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 23, Entry 27, Entry 28, Entry 65, Entry 75

Information according to Directive E1 Hazardous to the Aquatic Environment

2012/18/EU (SEVESO III):

Marketing and use of explosives precursors (Regulation (EU) 2019/1148):



according to Regulation (EC) No 1907/2006

Multi-element standard solution 27 elements each 500 mg/l in nitric acid 2 mol/l

Revision: 28.11.2024 Product code: 34043 Page 18 of 19

Acquisition, introduction, possession or use of this product by the general public is restricted by Regulation (EU) 2019/1148. All suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point.

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe employment restrictions for women of

child-bearing age.

Water hazard class (D): 3 - highly hazardous to water

SECTION 16: Other information

Abbreviations and acronyms

Ox. Liq. 3: Oxidising liquids, hazard category 3

Ox. Sol. 2: Oxidising solids, hazard category 2

Met. Corr. 1: Corrosive to metals, hazard category 1

Acute Tox. 2: Acute toxicity, hazard category 2

Skin Corr. 1A: Skin corrosion, sub-category 1A

Skin Irrit. 2: Skin irritation, hazard category 2

Eye Dam. 1: Serious eye damage, hazard category 1

Eye Irrit. 2: Eye irritation, hazard category 2

Resp. Sens. 1: Respiratory sensitisation, hazard category 1

Skin Sens. 1: Skin sensitisation, hazard category 1

Muta. 1B: Germ cell mutagenicity, hazard category 1B

Carc. 1A: Carcinogenicity, hazard category 1A

Repr. 1B: Reproductive toxicity, hazard category 1B

STOT SE 3: Specific target organ toxicity - single exposure, hazard category 3

STOT RE 1: Specific target organ toxicity - repeated exposure, hazard category 1

Aquatic Acute 1: Hazardous to the aquatic environment, hazard category: Acute 1

Aquatic Chronic 1: Hazardous to the aquatic environment, long-term hazard category: Chronic 1

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Met. Corr. 1; H290	On basis of test data
Carc. 1A; H350	Calculation method
Acute Tox. 4; H332	Calculation method
Skin Corr. 1B; H314	Calculation method
Eye Dam. 1; H318	Calculation method
Skin Sens. 1; H317	Calculation method
STOT RE 2; H373	Calculation method
Aquatic Acute 1; H400	Calculation method
Aquatic Chronic 2; H411	Calculation method

Relevant H and EUH statements (number and full text)

H272	May intensify fire; oxidiser.
H290	May be corrosive to metals.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.

H315 Causes skin irritation.



according to Regulation (EC) No 1907/2006

M	ulti-element standard solution 27 elements each 500 mg/l in nitric acid 2 mol/l	
Revision: 28.11.20	Product code: 34043	Page 19 of 19
H317	May cause an allergic skin reaction.	
H318	Causes serious eye damage.	
H319	Causes serious eye irritation.	
H330	Fatal if inhaled.	
H331	Toxic if inhaled.	
H332	Harmful if inhaled.	
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.	
H335	May cause respiratory irritation.	
H340	May cause genetic defects.	
H341	Suspected of causing genetic defects.	
H350	May cause cancer.	
H350i	May cause cancer by inhalation.	
H360	May damage fertility or the unborn child.	
H360D	May damage the unborn child.	
H360F	May damage fertility.	
H361d	Suspected of damaging the unborn child.	
H372	Causes damage to organs through prolonged or repeated exposure.	
H373	May cause damage to organs through prolonged or repeated exposure.	
H400	Very toxic to aquatic life.	
H410	Very toxic to aquatic life with long lasting effects.	
H411	Toxic to aquatic life with long lasting effects.	
EUH071	Corrosive to the respiratory tract.	

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

Provide appropriate information, instructions and training to users

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)