

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Multielement-Standard "Hoch-2" 19 Elemente mit 60 ml/l Salpetersäure 70% + 3 ml/l Flusssäure 40%

Revision: 19.02.2025 Product code: 34344 Page 1 of 19

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Multielement-Standard "Hoch-2" 19 Elemente mit 60 ml/l Salpetersäure 70% + 3 ml/l Flusssäure 40%

UFI: 7K32-W3UT-F009-YENX

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Reagents and laboratory chemicals

Only for laboratory and analysis purposes.

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name: AnalytiChem GmbH

ACD

Street: Stempelstraße 6
Place: D-47167 Duisburg

Telephone: 0203/5194-0 Telefax: 0203/5194-290

E-mail: info@analytichem.de

Contact person: Abteilung Produktsicherheit Telephone: 0203/5194-107/117

E-mail: produktsicherheit@analytichem.de

Internet: www.analytichem.de

Responsible Department: Abteilung Produktsicherheit

1.4. Emergency telephone For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire,

number: Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada:

1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls

accepted)

Further Information

This product is a mixture. REACH Registration Number see section 3.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Met. Corr. 1; H290 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1; H317

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

nitric acid Hydrofluoric acid nickel dinitrate

Signal word: Danger



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Multielement-Standard "Hoch-2" 19 Elemente mit 60 ml/l Salpetersäure 70% + 3 ml/l Flusssäure 40%

Revision: 19.02.2025 Product code: 34344 Page 2 of 19

Pictograms:





Hazard statements

H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water

or shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

Special labelling of certain mixtures

EUH071 Corrosive to the respiratory tract.

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixtures in aqueous solution



according to Regulation (EC) No 1907/2006

Multielement-Standard "Hoch-2" 19 Elemente mit 60 ml/l Salpetersäure 70% + 3 ml/l Flusssäure 40%

Revision: 19.02.2025 Product code: 34344 Page 3 of 19

Relevant ingredients

CAS No	Chemical name					
	EC No	Index No	REACH No			
	Classification (Regulation (EC)	No 1272/2008)				
7697-37-2	nitric acid			5 - < 10 %		
	231-714-2	007-030-00-3	01-2119487297-23			
	Ox. Liq. 3, Met. Corr. 1, Acute 1 EUH071					
7647-14-5	sodium chloride			< 1 %		
	231-598-3		01-2119485491-33			
7664-39-3	hydrofluoric acid %	< 1 %				
	231-634-8	009-003-00-1				
	Acute Tox. 1, Acute Tox. 2, Acu	ite Tox. 2, Skin Corr. 1A, Eye	Dam. 1; H310 H330 H300 H314 H318			
10043-35-3	boric acid	< 1 %				
	233-139-2	005-007-00-2	01-2119486683-25			
	Repr. 1B; H360FD					
13138-45-9	nickel dinitrate	< 0.1 %				
	236-068-5	028-012-00-1	01-2119492333-38			
		E 1, Aquatic Acute 1, Aquatic	Tox. 4, Skin Irrit. 2, Eye Dam. 1, Resp. Chronic 1; H272 H350i H341 H360D			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. I	Limits, M-factors and ATE	
7697-37-2	231-714-2	nitric acid	5 - < 10 %
	1	2,65 mg/l (vapours) Ox. Liq. 3; H272: >= 65 - 100 Skin Corr. 1A; H314: >= 20 - 1B; H314: >= 5 - < 20	
7647-14-5	231-598-3	sodium chloride	< 1 %
	dermal: LD50 =	= > 10000 mg/kg; oral: LD50 = 3550 mg/kg	
7664-39-3	231-634-8	hydrofluoric acid %	< 1 %
	LC50 = 2240 pp	= 0,5 mg/l (vapours); inhalation: ATE = 0,05 mg/l (dusts or mists); inhalation: om (gases); dermal: ATE = 5 mg/kg; oral: ATE = 5 mg/kg	
10043-35-3	233-139-2	boric acid	< 1 %
	inhalation: LC5 3450 mg/kg	60 = > 2,12 mg/l (dusts or mists); dermal: LD50 = > 2000 mg/kg; oral: LD50 =	
13138-45-9	236-068-5	nickel dinitrate	< 0.1 %
	361,9 mg/kg S		

Further Information

No data available



according to Regulation (EC) No 1907/2006

Multielement-Standard "Hoch-2" 19 Elemente mit 60 ml/l Salpetersäure 70% + 3 ml/l Flusssäure 40%

Revision: 19.02.2025 Product code: 34344 Page 4 of 19

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection!

After inhalation

Provide fresh air.

Call a physician immediately.

After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

Call a physician immediately.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Remove contact lenses, if present and easy to do. Continue rinsing.

Protect uninjured eye.

After inaestion

Rinse mouth immediately and drink plenty of water.

Do NOT induce vomiting. Do not allow a neutralisation agent to be drunk.

Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Causes burns.

Irritant

Cough

Dyspnoea

Vomiting

Methaemoglobinaemia

Risk of serious damage to eyes.

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Non-combustible liquids

Hazardous combustion products

In case of fire may be liberated:

Nitrogen oxides (NOx)

Hydrogen fluoride

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

In case of fire and/or explosion do not breathe fumes.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Multielement-Standard "Hoch-2" 19 Elemente mit 60 ml/l Salpetersäure 70% + 3 ml/l Flusssäure 40%

Revision: 19.02.2025 Product code: 34344 Page 5 of 19

Avoid contact with skin, eyes and clothes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Move undamaged containers from immediate hazard area if it can be done safely.

Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Do not breathe vapour/aerosol. Corrosive to metals.

For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Consult an expert

Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders: Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Collect in closed and suitable containers for disposal.

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Use personal protection equipment.

Provide adequate ventilation. Avoid contact with skin, eyes and clothes.

Do not breathe vapour/aerosol. Use extractor hood (laboratory).

Advice on protection against fire and explosion

Usual measures for fire prevention.



according to Regulation (EC) No 1907/2006

Multielement-Standard "Hoch-2" 19 Elemente mit 60 ml/l Salpetersäure 70% + 3 ml/l Flusssäure 40%

Revision: 19.02.2025 Product code: 34344 Page 6 of 19

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs. Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink. Avoid: aerosol or mist formation Do not breathe vapour/aerosol.

Further information on handling

Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary.

Take off immediately all contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Corrosive to metals.

Unsuitable container/equipment material: Metal, Glass

The product develops hydrogen in an aqueous solution in contact with metals.

Hints on joint storage

national regulations

Further information on storage conditions

Keep container tightly closed.

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
10043-35-3	Borate compounds inorganic: boric acid	-	2		TWA (8 h)	
7664-39-3	Hydrogen fluoride (as F)	1.8	1.5		TWA (8 h)	
		3	2.5		STEL (15 min)	
7697-37-2	Nitric acid	1	2.6		STEL (15 min)	

Biological limit values

CAS No	Substance	Parameter	Value	Test material	Sampling time
7664-39-3	Hydrogen fluoride	Fluoride	2 mg/L	Urine	Prior to shift



according to Regulation (EC) No 1907/2006

Multielement-Standard "Hoch-2" 19 Elemente mit 60 ml/l Salpetersäure 70% + 3 ml/l Flusssäure 40%

Revision: 19.02.2025 Product code: 34344 Page 7 of 19

DNEL/DMEL values

CAS No Substance			
DNEL type	Exposure route	Effect	Value
7647-14-5 sodium chloride			
Consumer DNEL, long-term	dermal	systemic	126,65 mg/kg bw/day
Consumer DNEL, acute	dermal	systemic	126,65 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	126,65 mg/kg bw/day
Consumer DNEL, acute	oral	systemic	126,65 mg/kg bw/day
Worker DNEL, long-term	inhalation	systemic	2068,62 mg/m ³
Worker DNEL, acute	inhalation	systemic	2068,62 mg/m ³
Worker DNEL, acute	dermal	systemic	295,52 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	443,28 mg/m³
Consumer DNEL, acute	inhalation	systemic	443,28 mg/m³
Worker DNEL, long-term	dermal	systemic	295,52 mg/kg bw/day
7664-39-3 hydrofluoric acid %			
Worker DNEL, long-term	inhalation	systemic	1,5 mg/m³
Worker DNEL, acute	inhalation	systemic	2,5 mg/m³
Worker DNEL, long-term	inhalation	local	1,5 mg/m³
Worker DNEL, acute	inhalation	local	2,5 mg/m³
Consumer DNEL, long-term	inhalation	systemic	0,03 mg/m³
Consumer DNEL, acute	inhalation	systemic	0,03 mg/m³
Consumer DNEL, long-term	inhalation	local	0,2 mg/m³
Consumer DNEL, acute	inhalation	local	1,25 mg/m³
Consumer DNEL, long-term	oral	systemic	0,01 mg/kg bw/day
Consumer DNEL, acute	oral	systemic	0,01 mg/kg bw/day
10043-35-3 boric acid			
Worker DNEL, long-term	inhalation	systemic	8,3 mg/m³
Worker DNEL, long-term	dermal	systemic	392 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	4,15 mg/m³
Consumer DNEL, long-term	dermal	systemic	196 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	0,98 mg/kg bw/day
Consumer DNEL, acute	oral	systemic	0,98 mg/kg bw/day
13138-45-9 nickel dinitrate			
Consumer DNEL, acute	oral	systemic	0,012 mg/kg bw/day



according to Regulation (EC) No 1907/2006

Multielement-Standard "Hoch-2" 19 Elemente mit 60 ml/l Salpetersäure 70% + 3 ml/l Flusssäure 40%

Revision: 19.02.2025 Product code: 34344 Page 8 of 19

Consumer DNEL, long-term	oral	systemic	0,02 mg/kg bw/day
Worker DNEL, acute	inhalation	systemic	104 mg/m³
Worker DNEL, acute	inhalation	local	1,6 mg/m³
Consumer DNEL, acute	inhalation	systemic	8,8 mg/m³
Consumer DNEL, acute	inhalation	local	0,1 mg/m³

PNEC values

CAS No	Substance		
Environmenta	al compartment	Value	
7647-14-5	sodium chloride		
Freshwater		5 mg/l	
Micro-organisms in sewage treatment plants (STP)			
Soil		4,86 mg/kg	
7664-39-3	hydrofluoric acid %		
Freshwater		0,89 mg/l	
Marine water		0,089 mg/l	
Freshwater se	ediment	3,38 mg/kg	
Marine sedim	ent	0,338 mg/kg	
Micro-organis	ms in sewage treatment plants (STP)	51 mg/l	
Soil		10,6 mg/kg	
10043-35-3	boric acid		
Freshwater		2,9 mg/l	
Freshwater (in	ntermittent releases)	13,7 mg/l	
Marine water		2,9 mg/l	
Micro-organis	ms in sewage treatment plants (STP)	10 mg/l	
Soil		5,7 mg/kg	
13138-45-9	nickel dinitrate		
Freshwater		0,0071 mg/l	
Freshwater (i	ntermittent releases)	0 mg/l	
Marine water	0,0086 mg/l		
Freshwater se	109 mg/kg		
Marine sedim	109 mg/kg		
Secondary po	0,12 mg/kg		
Micro-organis	ms in sewage treatment plants (STP)	0,33 mg/l	
Soil		29,9 mg/kg	

8.2. Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment

Eye/face protection

goggles



according to Regulation (EC) No 1907/2006

Multielement-Standard "Hoch-2" 19 Elemente mit 60 ml/l Salpetersäure 70% + 3 ml/l Flusssäure 40%

Revision: 19.02.2025 Product code: 34344 Page 9 of 19

Wear eye/face protection.

Hand protection

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact

Recommended glove articles: KCL 741 Dermatril® L Recommended material: NBR (Nitrile rubber) 0,11 mm Wearing time with permanent contact: > 480 min

By short-term hand contact

Recommended glove articles: KCL 741 Dermatril® L Recommended material: NBR (Nitrile rubber) 0,11mm Wearing time with occasional contact (splashes): > 480 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing.

Wash hands before breaks and after work.

The choice of body protection depends on the concentration and quantity of hazardous substances. The chemical resistance of protective agents must be clarified with their suppliers.

Respiratory protection

Respiratory protection necessary at: aerosol or mist formation

The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Thermal hazards

No data available

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:

Colour:

Odour:

Odour:

Odour threshold:

Liquid

colourless

like: Nitric acid

No data available

Melting point/freezing point:

Boiling point or initial boiling point and

No data available

No data available

boiling range:

Flammability:

Lower explosion limits:

Upper explosion limits:

No data available

Upper explosion limits:

No data available

Flash point:

No data available

Auto-ignition temperature:

No data available

Decomposition temperature:

No data available



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Multielement-Standard "Hoch-2" 19 Elemente mit 60 ml/l Salpetersäure 70% + 3 ml/l Flusssäure 40%

Revision: 19.02.2025 Product code: 34344 Page 10 of 19

pH-Value: acidic Viscosity / kinematic: No data available Water solubility: completely miscible

Solubility in other solvents

No data available

No data available Dissolution rate: Partition coefficient n-octanol/water: No data available No data available Dispersion stability: No data available Vapour pressure: No data available Vapour pressure: Density: No data available No data available Relative density: No data available Bulk density: No data available Relative vapour density: No data available Particle characteristics:

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

No data available

Sustained combustibility: No data available

Self-ignition temperature

Solid: No data available
Gas: No data available

Oxidizing properties
Oxidising agent

Other safety characteristics

Evaporation rate:

Solvent separation test:

No data available

Solvent content:

Solid content:

Sublimation point:

No data available

Softening point:

No data available

Pour point:

No data available

No data available:

Viscosity / dynamic:

No data available

Viscosity / dynamic:

Flow time:

No data available

No data available

Further Information
Corrosive to metals.

SECTION 10: Stability and reactivity

10.1. Reactivity

Corrosive to metals.
Oxidising agent

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Alkali (lye)

The product develops hydrogen in an aqueous solution in contact with metals.



according to Regulation (EC) No 1907/2006

Multielement-Standard "Hoch-2" 19 Elemente mit 60 ml/l Salpetersäure 70% + 3 ml/l Flusssäure 40%

Revision: 19.02.2025 Product code: 34344 Page 11 of 19

Amines, Ammonia, Alcohols, Alkali metals, Hydrogen peroxide

Copper, Combustible solids, Solvent, Alkaline earth metal, mercury (Hg).

10.4. Conditions to avoid

No data available

10.5. Incompatible materials

Cellulose

Metal

Glass

The product develops hydrogen in an aqueous solution in contact with metals.

10.6. Hazardous decomposition products

In case of fire may be liberated:

SECTION 5: Firefighting measures

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicocinetics, metabolism and distribution

There are no data available on the mixture itself.

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 12.5 mg/l



according to Regulation (EC) No 1907/2006

Multielement-Standard "Hoch-2" 19 Elemente mit 60 ml/l Salpetersäure 70% + 3 ml/l Flusssäure 40%

Revision: 19.02.2025 Product code: 34344 Page 12 of 19

CAS No	Chemical name									
	Exposure route	Dose		Species	Source	Method				
7697-37-2	nitric acid	nitric acid								
	inhalation vapour	ATE 2,65	mg/l							
7647-14-5	sodium chloride									
	oral	LD50 mg/kg	3550	Rat	Study report	The study methodology followed appeared				
	dermal	LD50 mg/kg	> 10000	Rabbit	Study report	The study methology followed appeared to				
7664-39-3	hydrofluoric acid %									
	oral	ATE	5 mg/kg							
	dermal	ATE	5 mg/kg							
	inhalation vapour	ATE	0,5 mg/l							
	inhalation dust/mist	ATE	0,05 mg/l							
	inhalation (1 h) gas	LC50 ppm	2240	Rat	Study report (1990)	OECD Guideline 403				
10043-35-3	boric acid									
	oral	LD50 mg/kg	3450	Rat	Toxicology and Applied Pharmacology 23:	other: No data				
	dermal	LD50 mg/kg	> 2000	Rabbit	Study report (1982)	other: FIFRA				
	inhalation (4 h) dust/mist	LC50 mg/l	> 2,12	Rat	Study report (1997)	OECD Guideline 403				
13138-45-9	nickel dinitrate									
	oral	LD50 mg/kg	361,9	Rat	Regul Toxicol and Pharmacol (doi.org/10.	OECD Guideline 425				
	inhalation vapour	ATE	11 mg/l							
	inhalation dust/mist	ATE	1,5 mg/l							

Irritation and corrosivity

Skin corrosion/irritation: Causes severe skin burns and eye damage.

Serious eye damage/eye irritation: Causes serious eye damage.

Corrosive to the respiratory tract.

Following ingestion Gastric perforation

Mucous membrane irritation in the mouth, throat, esophagus and gastrointestinal tract.

Irritating to respiratory system.

Pulmonary oedema

see also Section 4

Sensitising effects

May cause an allergic skin reaction. (nickel dinitrate)

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Multielement-Standard "Hoch-2" 19 Elemente mit 60 ml/l Salpetersäure 70% + 3 ml/l Flusssäure 40%

Revision: 19.02.2025 Product code: 34344 Page 13 of 19

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

There are no data available on the mixture itself.

Specific effects in experiment on an animal

There are no data available on the mixture itself.

Additional information on tests

There are no data available on the mixture itself.

Practical experience

There are no data available on the mixture itself.

11.2. Information on other hazards

Endocrine disrupting properties

There are no data available on the mixture itself.

Other information

There are no data available on the mixture itself.

Further information

There are no data available on the mixture itself.

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.



according to Regulation (EC) No 1907/2006

Multielement-Standard "Hoch-2" 19 Elemente mit 60 ml/l Salpetersäure 70% + 3 ml/l Flusssäure 40%

Revision: 19.02.2025 Product code: 34344 Page 14 of 19

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method
7697-37-2	nitric acid						
	Acute fish toxicity	LC50 mg/l	1559	96 h	Topeka shiner	Environmental Toxicology and Chemistry,	other: ASTM E729-26
	Fish toxicity	NOEC	268 mg/l	30 d	juvenile Topeka shiner and with juvenile Fathead m	Study report (2009)	Growth tests estimated the test chemical
	Algae toxicity	NOEC mg/l	> 419	10 d	several benthic diatoms; see results	Marine Biology 43:307-315 (1977)	Ten cultures of benthic diatoms were iso
	Acute bacteria toxicity	EC50 mg/l ()	> 1000	3 h	Activated sludge	Study report (2008)	OECD Guideline 209
647-14-5	sodium chloride						
	Acute fish toxicity	LC50 mg/l	5840	96 h	Lepomis macrochirus	Study report (1985)	other: ASTM E729
	Acute crustacea toxicity	EC50 mg/l	4136	48 h	Daphnia magna	J. fish. Res. Bd. Canada, 29: 1691-1700.	OECD Guideline 202
	Fish toxicity	NOEC	252 mg/l	33 d	Pimephales promelas	Study report (1985)	OECD Guideline 210
	Crustacea toxicity	NOEC	314 mg/l	21 d	Daphnia pulex	Memorandum of agreement No. 5429, Kentuc	OECD Guideline 211
7664-39-3	hydrofluoric acid %						·
	Acute fish toxicity	LC50	299 mg/l	96 h	Salmo trutta	REACh Registration Dossier	other: U.S Environmental Protection Agen
	Acute algae toxicity	ErC50	43 mg/l	96 h	various algae species	REACh Registration Dossier	Methods not detailed in the review.
	Crustacea toxicity	NOEC	3,7 mg/l	21 d	Daphnia magna	REACh Registration Dossier	The publication is a review article of v
	Acute bacteria toxicity	EC50 mg/l ()	2930	3 h	Activated sludge	REACh Registration Dossier	ISO 8192
10043-35-3	boric acid						
	Acute fish toxicity	LC50 mg/l	79,7	96 h	Pimephales promelas	Study report (2010)	other: ASTM E729-95 Standard Guide for C
	Acute algae toxicity	ErC50	66 mg/l	72 h	Phaeodactylum tricornutum	Study report (2011)	ISO 10253
	Acute crustacea toxicity	EC50	109 mg/l	48 h	Ceriodaphnia dubia	Study report (2010)	other: ASTM E729-95 Standard Guide for C



according to Regulation (EC) No 1907/2006

Multielement-Standard "Hoch-2" 19 Elemente mit 60 ml/l Salpetersäure 70% + 3 ml/l Flusssäure 40%

Revision: 19.02.2025 Product code: 34344 Page 15 of 19

	Fish toxicity	NOEC	11,2 mg/l	32 d	Pimephales promelas	Study report (2010)	other: ASTM E1241-05 Standard Guide for
	Algae toxicity	NOEC mg/l	17,5	3 d	Pseudokirchneriella subcapitata	Study report (2000)	OECD Guideline 201
	Crustacea toxicity	NOEC mg/l	25,9	42 d	other aquatic crustacea: Hyalella azteca	Study report (2010)	other: US EPA 2000 Methods for assessing
	Acute bacteria toxicity	EC50 mg/l ()	> 10000	3 h	activated sludge of a predominantly domestic sewag	Study report (2001)	OECD Guideline 209
13138-45-9	nickel dinitrate						
	Acute fish toxicity	LC50 mg/l	15,3	96 h	Oncorhynchus mykiss	Aquatic Toxicology 63 (2003) 65-82 (2003	other: not reported
	Acute algae toxicity	ErC50 mg/l	0,237	72 h	Ankistrodesmus falcatus	Publication (2009)	OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	0,2663	48 h	Ceriodaphnia dubia	Study report (2004)	other: American society of testing and m
	Fish toxicity	NOEC mg/l	0,057	32 d	Pimephales promelas	Water Resources Research Institute. Kent	other: ASTM 1980, E-729
	Algae toxicity	NOEC	0,6 mg/l	14 d	Anabaena cylindrica	Environ. Pollut. (Series A). 25(4):241-2	other: not reported
	Crustacea toxicity	NOEC mg/l	0,04	42 d	Daphnia magna	Wat. Res. 24(7):845-852 (1990)	Chronic exposure to sublethal concentrat
	Acute bacteria toxicity	EC50)	33 mg/l (0,5 h	Activated sludge	Journal of Hazardous Materials. B139:332	ISO 8192

12.2. Persistence and degradability

The methods for determining the biological degradability are not applicable to inorganic substances.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
10043-35-3	boric acid	-1,09

BCF

CAS No	Chemical name	BCF	Species	Source
7664-39-3	hydrofluoric acid %	53 - 58	not specified	REACh Registration D
10043-35-3	boric acid	0,558	Oncorhynchus nerka	Water Research Vol.
13138-45-9	nickel dinitrate	23	Spirodela polyrhiza	Ecotoxicology and en



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Multielement-Standard "Hoch-2" 19 Elemente mit 60 ml/l Salpetersäure 70% + 3 ml/l Flusssäure 40%

Revision: 19.02.2025 Product code: 34344 Page 16 of 19

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Discharge into the environment must be avoided.

Harmful effect due to pH shift.

Forms corrosive mixtures with water even if diluted.

Further information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

UN 2031

UN 2031

Send to a physico-chemical treatment facility under observation of official regulations.

Do not empty into drains.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

SECTION 14: Transport information

14.1. UN number or ID number:

Land transport (ADR/RID)

14.2. UN proper shipping name:	NITRIC ACID
14.3. Transport hazard class(es):	8
14.4. Packing group:	II
Hazard label:	8
Classification code:	C1
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	80
Tunnel restriction code:	Е

Inland waterways transport (ADN) 14.1. UN number or ID number:

14.2. UN proper shipping name:	NITRIC ACID
14.3. Transport hazard class(es):	8
14.4. Packing group:	II
Hazard label:	8

Classification code: C1
Limited quantity: 1 L
Excepted quantity: E2

Marine transport (IMDG)



according to Regulation (EC) No 1907/2006

Multielement-Standard "Hoch-2" 19 Elemente mit 60 ml/l Salpetersäure 70% + 3 ml/l Flusssäure 40%

Revision: 19.02.2025 Product code: 34344 Page 17 of 19

14.1. UN number or ID number: UN 2031
14.2. UN proper shipping name: NITRIC ACID

14.3. Transport hazard class(es):814.4. Packing group:IIHazard label:8Special Provisions:-Limited quantity:1 LExcepted quantity:E2EmS:F-A, S-BSegregation group:1 - acids

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:UN 203114.2. UN proper shipping name:NITRIC ACID

14.3. Transport hazard class(es):814.4. Packing group:IIHazard label:8Special Provisions:A212Limited quantity Passenger:ForbiddenPassenger LQ:ForbiddenExcepted quantity:E0

IATA-packing instructions - Passenger: Forbidden
IATA-max. quantity - Passenger: Forbidden
IATA-packing instructions - Cargo: 855
IATA-max. quantity - Cargo: 30 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Authorisations (REACH, annex XIV):

Substances of very high concern, SVHC (REACH, article 59):

boric acid

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 27, Entry 30, Entry 65, Entry 75

Marketing and use of explosives precursors (Regulation (EU) 2019/1148):

Acquisition, introduction, possession or use of this product by the general public is restricted by Regulation (EU) 2019/1148. All suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point.

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1,2,3,5,7,9,10,11,15.



according to Regulation (EC) No 1907/2006

Multielement-Standard "Hoch-2" 19 Elemente mit 60 ml/l Salpetersäure 70% + 3 ml/l Flusssäure 40%

Revision: 19.02.2025 Product code: 34344 Page 18 of 19

Abbreviations and acronyms

Ox. Liq. 3: Oxidising liquids, hazard category 3
Ox. Sol. 2: Oxidising solids, hazard category 2
Met. Corr. 1: Corrosive to metals, hazard category 1
Acute Tox. 1: Acute toxicity, hazard category 1
Skin Corr. 1A: Skin corrosion, sub-category 1A
Skin Irrit. 2: Skin irritation, hazard category 2

Eye Dam. 1: Serious eye damage, hazard category 1 Resp. Sens. 1: Respiratory sensitisation, hazard category 1

Skin Sens. 1: Skin sensitisation, hazard category 1 Muta. 2: Germ cell mutagenicity, hazard category 2 Carc. 1A: Carcinogenicity, hazard category 1A Repr. 1B: Reproductive toxicity, hazard category 1B

STOT RE 1: Specific target organ toxicity - repeated exposure, hazard category 1 Aquatic Acute 1: Hazardous to the aquatic environment, hazard category: Acute 1

Aquatic Chronic 1: Hazardous to the aquatic environment, long-term hazard category: Chronic 1

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Met. Corr. 1; H290	On basis of test data
Skin Corr. 1B; H314	Calculation method
Eye Dam. 1; H318	Calculation method
Skin Sens. 1; H317	Calculation method

Relevant H and EUH statements (number and full text)

ievanit ii and Eon sta	atements (number and run text)
H272	May intensify fire; oxidiser.
H290	May be corrosive to metals.
H300	Fatal if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H341	Suspected of causing genetic defects.
H350i	May cause cancer by inhalation.
H360D	May damage the unborn child.
H360FD	May damage fertility. May damage the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.
rthor Information	

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.



according to Regulation (EC) No 1907/2006

Multielement-Standard "Hoch-2" 19 Elemente mit 60 ml/l Salpetersäure 70% + 3 ml/l Flusssäure 40%

Revision: 19.02.2025 Product code: 34344 Page 19 of 19

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

Provide appropriate information, instructions and training to users

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)