

according to Regulation (EC) No 1907/2006

## Flusssäure 40 % VLSI

Revision: 26.06.2024 Product code: 34806 Page 1 of 14

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Flusssäure 40 % VLSI

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Reagents and laboratory chemicals

Only for laboratory and analysis purposes.

#### Uses advised against

Do not use for private purposes (household).

### 1.3. Details of the supplier of the safety data sheet

Company name: AnalytiChem GmbH

ACD

Street: Stempelstraße 6
Place: D-47167 Duisburg

Telephone: 0203/5194-0 Telefax: 0203/5194-290

E-mail: info@analytichem.de

Contact person: Abteilung Produktsicherheit Telephone: 0203/5194-107/117

E-mail: produktsicherheit@analytichem.de

Internet: www.analytichem.de

Responsible Department: Abteilung Produktsicherheit

1.4. Emergency telephone For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire,

<u>number:</u> Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada:

1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls

accepted)

#### **Further Information**

This product is a mixture. REACH Registration Number see section 3.

## **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

## Regulation (EC) No 1272/2008

Acute Tox. 1; H310 Acute Tox. 2; H330 Acute Tox. 2; H300 Skin Corr. 1A; H314 Eye Dam. 1; H318

Full text of hazard statements: see SECTION 16.

## 2.2. Label elements

## Regulation (EC) No 1272/2008

# Hazard components for labelling

hydrofluoric acid 40 %

Signal word: Danger

Pictograms:







according to Regulation (EC) No 1907/2006

### Flusssäure 40 % VLSI

Revision: 26.06.2024 Product code: 34806 Page 2 of 14

#### **Hazard statements**

H300+H310+H330 Fatal if swallowed, in contact with skin or if inhaled. H314 Causes severe skin burns and eye damage.

## **Precautionary statements**

P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P262 Do not get in eyes, on skin, or on clothing.
P264 Wash hands and face thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P310 Immediately call a POISON CENTER/doctor.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

### Additional advice on labelling

No information available.

#### 2.3. Other hazards

No data available

## **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

#### Chemical characterization

Mixtures in aqueous solution

### Relevant ingredients

CAS No	Chemical name	Chemical name			
	EC No	EC No Index No REACH No			
	Classification (Regulation (EC) No 1272/2008)				
7664-39-3	Hydrofluoric acid %	Hydrofluoric acid %			
	231-634-8	009-003-00-1	01-2119458860-33		
	Acute Tox. 1, Acute Tox. 2, Acute Tox. 2, Skin Corr. 1A, Eye Dam. 1; H310 H330 H300 H314 H318				

Full text of H and EUH statements: see section 16.

## Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. L	imits, M-factors and ATE	
7664-39-3	231-634-8	Hydrofluoric acid %	40 - < 45 %
	LC50 = 2240 pp	= 0,5 mg/l (vapours); inhalation: ATE = 0,05 mg/l (dusts or mists); inhalation: om (gases); dermal: ATE = 5 mg/kg; oral: ATE = 5 mg/kg Skin Corr. 1A; H314: in Corr. 1B; H314: >= 1 - < 7 Eye Irrit. 2; H319: >= 0,1 - < 1	

## **Further Information**

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

## **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

#### **General information**

First aider: Pay attention to self-protection! Remove affected person from the danger area and lay down.

Call a physician immediately.

fast help required

#### After inhalation

Provide fresh air.



according to Regulation (EC) No 1907/2006

## Flusssäure 40 % VLSI

Revision: 26.06.2024 Product code: 34806 Page 3 of 14

If breathing is irregular or stopped, administer artificial respiration.

Call a physician immediately.

#### After contact with skin

Rinse with plenty of water for at least 10 minutes. Immediately remove contaminated clothes. Apply calcium gluconate gel (preparation: boil 5 g of calcium gluconate in 85 ml of hot distilled water, add 10 g glycerol. Allow 5 g of Carmellose-sodium to swell in the hot solution. Stable for 6 months, store in a cool place) and massage into the skin until the pain subsides, in between rinse with water and apply fresh gel. Continue gel therapy for another 15 minutes after the pain has subsided. If no calcium gluconate gel is available, apply several dressings thoroughly moistened with 20 % calcium gluconate solution. Medical advice absolutely required!

#### After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Remove contact lenses, if present and easy to do. Continue rinsing. Protect uninjured eye.

#### After ingestion

Never give anything by mouth to an unconscious person or a person with cramps.

Rinse mouth immediately and drink plenty of water.

Adverse human health effects and symptoms:

Gastric perforation

Remove casualty to fresh air and keep warm and at rest.

Call a physician immediately.

## 4.2. Most important symptoms and effects, both acute and delayed

Irritant

Causes burns.

Cough

Dyspnoea

Risk of serious damage to eyes.

Gastric perforation

Circulatory collapse

Pulmonary oedema

Vomiting

seizures

Pneumonia

## 4.3. Indication of any immediate medical attention and special treatment needed

It is recommended to consult a doctor with experience in the treatment of lesions caused by hydrofluoric acid

## **SECTION 5: Firefighting measures**

## 5.1. Extinguishing media

### Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

#### Unsuitable extinguishing media

no restriction

# 5.2. Special hazards arising from the substance or mixture

Non-combustible liquids

Hazardous combustion products

In case of fire may be liberated: Hydrogen fluoride

### 5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit. In case of fire and/or explosion do not breathe fumes. Use water spray jet to protect personnel and to cool endangered containers.



according to Regulation (EC) No 1907/2006

## Flusssäure 40 % VLSI

Revision: 26.06.2024 Product code: 34806 Page 4 of 14

# Additional information

Suppress gases/vapours/mists with water spray jet.

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Move undamaged containers from immediate hazard area if it can be done safely.

#### **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

#### General advice

Do not breathe vapour/aerosol. Avoid contact with skin, eyes and clothes.

### For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

**Emergency procedures** 

Consult an expert

Do not breathe dust/fume/gas/mist/vapours/spray.

### For emergency responders

Precautionary statements For emergency responders: Personal protection equipment: see section 8

#### 6.2. Environmental precautions

Do not allow to enter into surface water or drains.

## 6.3. Methods and material for containment and cleaning up

### For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

#### For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

## Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

## 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

## **SECTION 7: Handling and storage**

# 7.1. Precautions for safe handling

#### Advice on safe handling

Avoid exposure - obtain special instructions before use.

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Keep container tightly closed.

Use personal protection equipment. Use extractor hood (laboratory).

Provide adequate ventilation.

Avoid contact with skin, eyes and clothes.

## Advice on protection against fire and explosion

Usual measures for fire prevention.



according to Regulation (EC) No 1907/2006

## Flusssäure 40 % VLSI

Revision: 26.06.2024 Product code: 34806 Page 5 of 14

## Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs. Make available sufficient washing facilities
Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash
hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

#### Further information on handling

Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary.

Take off immediately all contaminated clothing and wash it before reuse.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

## 7.2. Conditions for safe storage, including any incompatibilities

## Requirements for storage rooms and vessels

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaustion at critical locations. storage temperature +5°C - +30°C

## Hints on joint storage

national regulations

### Further information on storage conditions

Store in a dry place.

Suitable container/equipment material: plastic

Unsuitable container/equipment material: Metal, Glass

### 7.3. Specific end use(s)

Laboratory chemicals

## **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

### Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
7664-39-3	Hydrogen fluoride (as F)	1.8	1.5		TWA (8 h)	
		3	2.5		STEL (15 min)	

## **Biological limit values**

CAS No	Substance	Parameter	Value	Test material	Sampling time
7664-39-3	Hydrogen fluoride	Fluoride	3 mg/L	Urine	End of shift



according to Regulation (EC) No 1907/2006

# Flusssäure 40 % VLSI

Revision: 26.06.2024 Product code: 34806 Page 6 of 14

### **DNEL/DMEL values**

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
7664-39-3	Hydrofluoric acid %			
Worker DNE	L, long-term	inhalation	systemic	1,5 mg/m³
Worker DNE	L, acute	inhalation	systemic	2,5 mg/m³
Worker DNE	L, long-term	inhalation	local	1,5 mg/m³
Worker DNE	L, acute	inhalation	local	2,5 mg/m³
Consumer D	NEL, long-term	inhalation	systemic	0,03 mg/m³
Consumer D	NEL, acute	inhalation	systemic	0,03 mg/m³
Consumer D	NEL, long-term	inhalation	local	0,2 mg/m³
Consumer D	NEL, acute	inhalation	local	1,25 mg/m³
Consumer D	NEL, long-term	oral	systemic	0,01 mg/kg bw/day
Consumer D	NEL, acute	oral	systemic	0,01 mg/kg bw/day

## **PNEC values**

CAS No	Substance		
Environmenta	al compartment	Value	
7664-39-3	7664-39-3 Hydrofluoric acid %		
Freshwater		0,89 mg/l	
Marine water		0,089 mg/l	
Freshwater sediment		3,38 mg/kg	
Marine sediment		0,338 mg/kg	
Micro-organisms in sewage treatment plants (STP)		51 mg/l	
Soil		10,6 mg/kg	

# 8.2. Exposure controls

## Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Technical measures and the application of suitable work processes have priority over personal protection equipment.

# Individual protection measures, such as personal protective equipment

# Eye/face protection

Suitable eye protection:

goggles

Face protection umbrella

## **Hand protection**

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact

Trade name/designation KCL 897 Butoject®

Recommended material: Butyl caoutchouc (butyl rubber)

Thickness of the glove material 0,3 mm



according to Regulation (EC) No 1907/2006

## Flusssäure 40 % VLSI

Revision: 26.06.2024 Product code: 34806 Page 7 of 14

Wearing time with permanent contact > 480 min

By short-term hand contact

Trade name/designation KCL 720 Camapren®

Recommended material: CR (polychloroprene, chloroprene rubber)

Thickness of the glove material 0,65 mm

Wearing time with occasional contact (splashes): > 480 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

#### Skin protection

Wear suitable protective clothing.

Take off immediately all contaminated clothing.

Wash hands before breaks and after work.

The choice of body protection depends on the concentration and quantity of hazardous substances. The chemical resistance of protective agents must be clarified with their suppliers.

### Respiratory protection

Respiratory protection necessary at: aerosol or mist formation

The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

### Thermal hazards

No data available

### **Environmental exposure controls**

Do not allow to enter into surface water or drains.

# **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Physical state: Liquid
Colour: colourless
Odour: stinging

Odour threshold: No data available

Melting point/freezing point:  $\sim$  -44 °C Boiling point or initial boiling point and  $\sim$  112 °C

boiling range:

Flammability: not applicable
Lower explosion limits: No data available
Upper explosion limits: No data available
Flash point: X
Auto-ignition temperature: No data available
Decomposition temperature: No data available
pH-Value: acidic
Viscosity / kinematic: No data available

Viscosity / kinematic:

Water solubility:

No data available
Soluble in: Water

Solubility in other solvents

not determined

Dissolution rate: No data available



according to Regulation (EC) No 1907/2006

### Flusssäure 40 % VLSI

Revision: 26.06.2024 Product code: 34806 Page 8 of 14

No data available Partition coefficient n-octanol/water: No data available Dispersion stability: No data available Vapour pressure: No data available Vapour pressure: Density (at 20 °C): 1.13 a/cm<sup>3</sup> Relative density: No data available No data available Bulk density: No data available Relative vapour density: No data available Particle characteristics:

## 9.2. Other information

## Information with regard to physical hazard classes

Explosive properties

No data available

Sustained combustibility:

No data available

Self-ignition temperature

Solid: not applicable
Gas: not applicable

Oxidizing properties Not oxidising.

## Other safety characteristics

Evaporation rate:

Solvent separation test:

Solvent content:

Solid content:

Sublimation point:

Softening point:

No data available

No data available:

Viscosity / dynamic: No data available Flow time: No data available

Further Information
No data available

# **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

No data available

## 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

## 10.3. Possibility of hazardous reactions

Alkali metals

Fluorine

permanganates, e.g. potassium permanganate

Alkali (lye) Metal

Nitric acid

Acetic anhydride

Ammonia (NH3)

sulphuric acid

Sodium and potassium hydroxide



according to Regulation (EC) No 1907/2006

### Flusssäure 40 % VLSI

Revision: 26.06.2024 Product code: 34806 Page 9 of 14

(HF) Danger of inflammation or formation of inflammatory gases or vapours with: alkali metals, fluorine, organic substances, vinyl acetate. Explosive danger with: potassium permanganate, alkali hydroxides, strong bases, fluorides, potassium, metals, sodium, methanesulfonic acid, nitric acid, with glycerin. Exothermic reaction with: acetic anhydride, ammonia, ammonium hydroxide, sodium hydroxide, oleum, phosphorus oxides, silicon compounds, ethylamine, sulphuric acid, bismuth acid.

### 10.4. Conditions to avoid

Radiant heat.

### 10.5. Incompatible materials

Metal

Glass

The product develops hydrogen in an aqueous solution in contact with metals.

### 10.6. Hazardous decomposition products

In case of fire:

SECTION 5: Firefighting measures

#### **Further information**

No data available

# **SECTION 11: Toxicological information**

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

## Toxicocinetics, metabolism and distribution

Avoid exposure - obtain special instructions before use.

### **Acute toxicity**

Fatal in contact with skin.

Fatal if inhaled.

Fatal if swallowed.

If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects).

Causes poorly healing wounds.

Irritant

Causes burns.

Cough

Dyspnoea

Risk of serious damage to eyes.

Gastric perforation

Circulatory collapse

Pulmonary oedema

Vomiting

seizures

Pneumonia

## **ATEmix** calculated

ATE (oral) 12,50 mg/kg; ATE (dermal) 12,50 mg/kg; ATE (inhalation vapour) 1,250 mg/l; ATE (inhalation dust/mist) 0,1250 mg/l



according to Regulation (EC) No 1907/2006

## Flusssäure 40 % VLSI

Revision: 26.06.2024 Product code: 34806 Page 10 of 14

CAS No	Chemical name							
	Exposure route	Dose		Species	Source	Method		
7664-39-3	Hydrofluoric acid %							
	oral	ATE	5 mg/kg					
	dermal	ATE	5 mg/kg					
	inhalation vapour	ATE	0,5 mg/l					
	inhalation dust/mist	ATE	0,05 mg/l					
	inhalation (1 h) gas	LC50	2240	Rat	Study report (1990)	OECD Guideline 403		
		ppm						

### Irritation and corrosivity

Skin corrosion/irritation: Causes severe skin burns and eye damage.

Serious eye damage/eye irritation: Causes serious eye damage.

## Sensitising effects

Based on available data, the classification criteria are not met.

#### Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

#### STOT-single exposure

Based on available data, the classification criteria are not met.

### STOT-repeated exposure

Based on available data, the classification criteria are not met.

## **Aspiration hazard**

Based on available data, the classification criteria are not met.

## Information on likely routes of exposure

No data available

## Specific effects in experiment on an animal

No data available

## Additional information on tests

No data available

## **Practical experience**

No data available

## 11.2. Information on other hazards

## **Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

## Other information

No data available

# **Further information**

Following ingestion gastric perforation

Liver and kidney damage

Risk of serious damage to eyes.

Resorption (oral)

Resorption (by inhalation)

Resorption (dermal)

The substance has delayed effects.

Other dangerous properties cannot be excluded.



according to Regulation (EC) No 1907/2006

## Flusssäure 40 % VLSI

Revision: 26.06.2024 Product code: 34806 Page 11 of 14

## **SECTION 12: Ecological information**

### 12.1. Toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h]   [d]	Species	Source	Method
7664-39-3	Hydrofluoric acid %						
	Acute fish toxicity	LC50	299 mg/l	96 h	Salmo trutta	REACh Registration Dossier	other: U.S Environmental Protection Agen
	Acute algae toxicity	ErC50	43 mg/l	96 h	various algae species	REACh Registration Dossier	Methods not detailed in the review.
	Crustacea toxicity	NOEC	3,7 mg/l	21 d	Daphnia magna	REACh Registration Dossier	The publication is a review article of v
	Acute bacteria toxicity	EC50 mg/l ( )	2930	3 h	Activated sludge	REACh Registration Dossier	ISO 8192

## 12.2. Persistence and degradability

No information available.

## 12.3. Bioaccumulative potential

No information available.

## BCF

CAS No	Chemical name	BCF	Species	Source
7664-39-3	Hydrofluoric acid %	53 - 58	not specified	REACh Registration D

## 12.4. Mobility in soil

No information available.

## 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

### 12.7. Other adverse effects

No information available.

## **Further information**

Avoid release to the environment.

Do not allow to enter into surface water or drains.

Do not allow to enter into soil/subsoil.

Harmful effect due to pH shift.

Forms corrosive mixtures with water even if diluted.

## **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

#### **Disposal recommendations**

Send to a physico-chemical treatment facility under observation of official regulations.

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.



according to Regulation (EC) No 1907/2006

### Flusssäure 40 % VLSI

Revision: 26.06.2024 Product code: 34806 Page 12 of 14

Do not allow to enter into surface water or drains.

### Contaminated packaging

This material and its container must be disposed of as hazardous waste.

Handle contaminated packages in the same way as the substance itself.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

# **SECTION 14: Transport information**

# Land transport (ADR/RID)

**14.1. UN number or ID number:** UN 1790

14.2. UN proper shipping name: Hydrofluoric acid

14.3. Transport hazard class(es): П 14.4. Packing group: 8+6.1 Hazard label: CT1 Classification code: 1 I Limited quantity: E2 Excepted quantity: 2 Transport category: 86 Hazard No: Ε Tunnel restriction code:

#### Inland waterways transport (ADN)

**14.1. UN number or ID number:** UN 1790

14.2. UN proper shipping name: Hydrofluoric acid

14.3. Transport hazard class(es):814.4. Packing group:IIHazard label:8+6.1Classification code:CT1Special Provisions:802Limited quantity:1 LExcepted quantity:E2

### Marine transport (IMDG)

**14.1. UN number or ID number:** UN 1790

14.2. UN proper shipping name: Hydrofluoric acid

14.3. Transport hazard class(es):814.4. Packing group:IIHazard label:8+6.1Special Provisions:-Limited quantity:1 LExcepted quantity:E2EmS:F-A, S-B

## Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1790

**14.2. UN proper shipping name:** Hydrofluoric acid

14.3. Transport hazard class(es):814.4. Packing group:IIHazard label:8+6.1Limited quantity Passenger:0.5 LPassenger LQ:Y840Excepted quantity:E2

IATA-packing instructions - Passenger: 851
IATA-max. quantity - Passenger: 1 L



according to Regulation (EC) No 1907/2006

### Flusssäure 40 % VLSI

Revision: 26.06.2024 Product code: 34806 Page 13 of 14

IATA-packing instructions - Cargo: 855
IATA-max. quantity - Cargo: 30 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: Toxic. strongly corrosive.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

## **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **EU** regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 75

Information according to Directive

2012/18/EU (SEVESO III):

H1 ACUTE TOXIC

**National regulatory information** 

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.

Water hazard class (D): 2 - obviously hazardous to water

Skin resorption/Sensitization: Permeates easily through outer skin and causes poisoning.

## **SECTION 16: Other information**

### Abbreviations and acronyms

Acute Tox. 1: Acute toxicity, hazard category 1 Skin Corr. 1A: Skin corrosion, sub-category 1A Eye Dam. 1: Serious eye damage, hazard category 1

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

## Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Acute Tox. 1; H310	Calculation method
Acute Tox. 2; H330	Calculation method
Acute Tox. 2; H300	Calculation method
Skin Corr. 1A; H314	Calculation method
Eye Dam. 1; H318	Calculation method

### Relevant H and EUH statements (number and full text)

H300 Fatal if swallowed.



according to Regulation (EC) No 1907/2006

	Flusssäure 40 % VLSI	
Revision: 26.06.2024	Product code: 34806	Page 14 of 14

H300+H310+H330 Fatal if swallowed, in contact with skin or if inhaled.

H310 Fatal in contact with skin.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.

H330 Fatal if inhaled.

#### **Further Information**

Provide appropriate information, instructions and training to users

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)