

according to Regulation (EC) No 1907/2006

Acetic acid 97.5% ± 0.4% (m/m)

Revision: 17.03.2025 Product code: AC12.01795 Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Acetic acid 97.5% ± 0.4% (m/m)

UFI: 2NW3-E3K1-F00F-XC62

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Reagents and laboratory chemicals

Only for laboratory and analysis purposes.

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Details of the supplier of the safety data sheet

Company name: AnalytiChem Services, Unipessoal, Lda

Street: Rua de Júlio Dinis 676 7º Place: P-4050-320 Porto +351 226002917 Telephone: info@analvtichem.com F-mail: SDS service department Contact person: E-mail: SDS@analytichem.com Internet: www.analytichem.com SDS service department Responsible Department:

Supplier or manufacturer details

Company name: AnalytiChem GmbH Street: Stempelstraße 6 Place: D-47167 Duisburg Telephone: 0203/5194-0

E-mail: info@analytichem.de

Contact person: SDS service department

SDS@analytichem.com

E-mail: SDS@analytichem.com www.analytichem.de

Responsible Department: AnalytiChem:

EU-Belgium: AnalytiChem Belgium, Industriezone "De Arend" 2, 8210 Zedelgem,

Telefax: 0203/5194-290

Belgium, +32 50 28 83 20

EU-Germany: AnalytiChem Germany, Stempelstrasse 6, 47167 Duisburg,

Germany, +49 203 51 94 - 200

EU-Netherlands: AnalytiChem Netherlands, Communicatieweg 7, 3641 SG

Mijdrecht, The Netherlands, +31 297 286848

UK: AnalytiChem UK, Unit 7 Launton Business Center, Murdock Road, Bicester,

OX26 4XB, England, +44 1869 355 500

USA: AnalytiChem USA, 227 China Road, Winslow, Maine, 04901, United States,

+1 800-244-8378

Canada: AnalytiChem Canada, 21800 Clark Graham Avenue, Baie d'Urfe, H9X

4B6, Canada, +1 514-457-0701

Australia: ORE Research & Exploration Pty Ltd, 37A Hosie Street, Bayswater

North, 3153, Australia, +61 3 9729 0333

1.4. Emergency telephone

number:

+353 1 901 4670 (CHEMTREC)



according to Regulation (EC) No 1907/2006

Acetic acid 97.5% ± 0.4% (m/m)

Revision: 17.03.2025 Product code: AC12.01795 Page 2 of 12

Further Information

This product is a mixture. REACH Registration Number see section 3.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Flam. Liq. 3; H226 Skin Corr. 1A; H314 Eye Dam. 1; H318

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

acetic acid

Signal word: Danger

Pictograms:





Hazard statements

H226 Flammable liquid and vapour.

H314 Causes severe skin burns and eye damage.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P260 Do not breathe mist/vapours/spray.

P280 Wear protective gloves/protective clothing and eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water

or shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Relevant ingredients

CAS No	Chemical name	Chemical name				
	EC No	Index No	REACH No			
	Classification (Regulation	Classification (Regulation (EC) No 1272/2008)				
64-19-7	acetic acid	acetic acid				
	200-580-7	607-002-00-6	01-2119475328-30			
	Flam. Liq. 3, Skin Corr. 1A, Eye Dam. 1; H226 H314 H318					

Full text of H and EUH statements: see section 16.



according to Regulation (EC) No 1907/2006

Acetic acid 97.5% ± 0.4% (m/m)

Revision: 17.03.2025 Product code: AC12.01795 Page 3 of 12

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity	
	Specific Conc. L	imits, M-factors and ATE		
64-19-7	200-580-7	acetic acid	95 - < 100 %	
	oral: LD50 = 3310 mg/kg Skin Corr. 1A; H314: >= 90 - 100 Skin Corr. 1B; H314: >= 25 - < 90 Skin Irrit. 2; H315: >= 10 - < 25 Eye Irrit. 2; H319: >= 10 - < 25			

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Self-protection of the first aider

After inhalation

Provide fresh air.

Call a physician immediately.

After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

Call a physician immediately.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Rinse mouth immediately and drink plenty of water.

Do NOT induce vomiting.

Do not allow a neutralisation agent to be drunk.

Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Irritant

corrosive

Dyspnoea

Gastrointestinal complaints

Vomiting

Circulatory collapse

Corneal opacity.

Risk of serious damage to eyes.

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

no restriction



according to Regulation (EC) No 1907/2006

Acetic acid 97.5% ± 0.4% (m/m)

Revision: 17.03.2025 Product code: AC12.01795 Page 4 of 12

5.2. Special hazards arising from the substance or mixture

Combustible liquids

Hazardous combustion products

In case of fire may be liberated:

Carbon dioxide (CO2) Carbon monoxide

Acetic acid vapour

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Heating causes rise in pressure with risk of bursting.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

In case of fire and/or explosion do not breathe fumes.

Avoid contact with skin, eyes and clothes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Move undamaged containers from immediate hazard area if it can be done safely.

Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Keep away from sources of ignition - No smoking.

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

Take action to prevent static discharges.

For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Consult an expert

Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders: Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Danger of explosion

6.3. Methods and material for containment and cleaning up

For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.



according to Regulation (EC) No 1907/2006

Acetic acid 97.5% ± 0.4% (m/m)

Revision: 17.03.2025 Product code: AC12.01795 Page 5 of 12

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Keep container tightly closed.

Use personal protection equipment. Use extractor hood (laboratory).

Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation.

Advice on protection against fire and explosion

Take action to prevent static discharges. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs.

The choice of body protection depends on the concentration and quantity of hazardous substances. The chemical resistance of protective agents must be clarified with their suppliers.

Further information on handling

Take off immediately all contaminated clothing and wash it before reuse.

Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. If handled uncovered, arrangements with local exhaust ventilation have to be used.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Store in a well-ventilated place. Keep container tightly closed.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints on joint storage

national regulations

Further information on storage conditions

Store in a dry place.

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
64-19-7	Acetic acid	10	25		TWA (8 h)	
		20	50		STEL (15 min)	



according to Regulation (EC) No 1907/2006

Acetic acid 97.5% ± 0.4% (m/m)

Revision: 17.03.2025 Product code: AC12.01795 Page 6 of 12

DNEL/DMEL values

CAS No	Substance					
DNEL type		Exposure route	Effect	Value		
64-19-7	acetic acid					
Worker DNEL, long-term		inhalation	local	25 mg/m³		
Worker DNEL, acute		inhalation	local	25 mg/m³		
Consumer DNEL, long-term		inhalation	local	25 mg/m³		
Consumer DNEL, acute		inhalation	local	25 mg/m³		

PNEC values

CAS No	Substance			
Environmen	Environmental compartment V			
64-19-7	acetic acid			
Freshwater		3,058 mg/l		
Freshwater (intermittent releases)		30,58 mg/l		
Marine water		0,306 mg/l		
Freshwater sediment		11,36 mg/kg		
Marine sediment		1,136 mg/kg		
Micro-organisms in sewage treatment plants (STP)		85 mg/l		
Soil	0,47 mg/kg			

8.2. Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment

Eye/face protection

goggles

Face protection umbrella

Hand protection

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact

Trade name/designation KCL 897 Butoject®

Suitable material: Butyl caoutchouc (butyl rubber) 0,3 mm

Wearing time with permanent contact: > 480 min

By short-term hand contact

Trade name/designation KCL 897 Butoject®

Suitable material: Butyl caoutchouc (butyl rubber) 0,3 mm Wearing time with occasional contact (splashes): > 480 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).



according to Regulation (EC) No 1907/2006

Acetic acid 97.5% ± 0.4% (m/m)

Revision: 17.03.2025 Product code: AC12.01795 Page 7 of 12

Skin protection

Take off immediately all contaminated clothing and wash it before reuse.

Wear fire resistant or flame retardant clothing.

Wash hands and face before breaks and after work and take a shower if necessary.

Draw up and observe skin protection programme.

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Filtering device (full mask or mouthpiece) with filter: E-(P2)

The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Thermal hazards

No data available

Environmental exposure controls

Do not allow to enter into surface water or drains.

Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.

Danger of explosion

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid
Colour: colourless
Odour: stinging

Odour threshold: No data available

Melting point/freezing point: 17 °C Boiling point or initial boiling point and 116-118 °C

boiling range:

No data available Flammability: Lower explosion limits: 4 vol. % Upper explosion limits: 19,9 vol. % Flash point: 39 °C 463 °C Auto-ignition temperature: No data available Decomposition temperature: acidic pH-Value (at 20 °C): Viscosity / kinematic: 1,17 mm²/s

(at 20 °C)

Water solubility: 602,9 g/l

(at 25 °C)

Solubility in other solvents

No data available

Dissolution rate:

Partition coefficient n-octanol/water:

Dispersion stability:

Vapour pressure:

No data available

No data available

No data available

No data available

(at 20 °C)

Vapour pressure:No data availableRelative density:No data availableBulk density:No data availableRelative vapour density:No data available

9.2. Other information

Information with regard to physical hazard classes



according to Regulation (EC) No 1907/2006

Acetic acid 97.5% ± 0.4% (m/m)

Revision: 17.03.2025 Product code: AC12.01795 Page 8 of 12

Explosive properties

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Sustained combustibility: Sustained combustibility

Self-ignition temperature

Solid: No data available
Gas: No data available

Oxidizing properties

No data available

Other safety characteristics

Evaporation rate:

Solvent separation test:

No data available
Solid content:

No data available
Sublimation point:

No data available
Softening point:

No data available
Pour point:

No data available

(at 20 °C)

Flow time: No data available

Further Information
No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

In case of warming: Vapours may form explosive mixtures with air.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Oxidising agent

peroxides, for example hydrogen peroxide

permanganates, e.g. potassium permanganate

Oxidising agent, strong

Metal

iron and steel

Zinc

Alkali (lye)

aldehydes

Alcohols

Nitric acid

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

Metal

10.6. Hazardous decomposition products

SECTION 5: Firefighting measures

Further information

No data available

SECTION 11: Toxicological information



according to Regulation (EC) No 1907/2006

Acetic acid 97.5% ± 0.4% (m/m)

Revision: 17.03.2025 Product code: AC12.01795 Page 9 of 12

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects).

The substance has delayed effects.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name						
	Exposure route	Dose		Species	Source	Method	
64-19-7	acetic acid						
		LD50 mg/kg	3310		23, PP 78-82 (194	The sodium salt of acetic acid was admin	

Irritation and corrosivity

Skin corrosion/irritation: Causes severe skin burns and eye damage.

Serious eye damage/eye irritation: Causes serious eye damage.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

No data available

Specific effects in experiment on an animal

No data available

Additional information on tests

No data available

Practical experience

No data available

11.2. Information on other hazards

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

Other information

Irritant

corrosive

Dyspnoea

Gastrointestinal complaints

Vomiting



according to Regulation (EC) No 1907/2006

Acetic acid 97.5% ± 0.4% (m/m)

Revision: 17.03.2025 Product code: AC12.01795 Page 10 of 12

Circulatory collapse

Corneal opacity.
Risk of serious damage to eyes.

Further information

Damage to: kidneys

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method
64-19-7	acetic acid						
	Acute fish toxicity	LC50 mg/l	> 1000	96 h	Oncorhynchus mykiss	Study report (2005)	other: SOP E257
	Acute algae toxicity	ErC50 mg/l	> 1000		Skeletonema costatum	Study report (2005)	ISO 10253
	Acute crustacea toxicity	EC50 mg/l	> 1000	48 h	Daphnia magna	Study report (1990)	OECD Guideline 202

12.2. Persistence and degradability

99 %; 30 d

Readily biodegradable (according to OECD criteria).

12.3. Bioaccumulative potential

No indication of bioaccumulation potential.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
64-19-7	acetic acid	-0,17
BCF		

CAS No	Chemical name	BCF	Species	Source
64-19-7	acetic acid	3,16	fish	Environ. Toxicol. Ch

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Do not allow to enter into surface water or drains.

Avoid release to the environment.

Harmful effect due to pH shift.

Further information

No data available

SECTION 13: Disposal considerations

13.1. Waste treatment methods



according to Regulation (EC) No 1907/2006

Acetic acid 97.5% ± 0.4% (m/m)

Revision: 17.03.2025 Product code: AC12.01795 Page 11 of 12

Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 2789

14.2. UN proper shipping name: ACETIC ACID SOLUTION

14.3. Transport hazard class(es): Ш 14.4. Packing group: Hazard label: 8+3 CF1 Classification code: Limited quantity: 1 L Excepted quantity: E2 2 Transport category: Hazard No: 83 D/E Tunnel restriction code:

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 2789

14.2. UN proper shipping name: ACETIC ACID SOLUTION

14.3. Transport hazard class(es):814.4. Packing group:IIHazard label:8+3Classification code:CF1Limited quantity:1 LExcepted quantity:E2

Marine transport (IMDG)

14.1. UN number or ID number: UN 2789

14.2. UN proper shipping name: ACETIC ACID SOLUTION

14.3. Transport hazard class(es):814.4. Packing group:IIHazard label:8+3Special Provisions:-Limited quantity:1 LExcepted quantity:E2EmS:F-E, S-CSegregation group:1 - acids

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 2789

14.2. UN proper shipping name: ACETIC ACID SOLUTION

14.3. Transport hazard class(es):814.4. Packing group:IIHazard label:8+3Limited quantity Passenger:0.5 LPassenger LQ:Y840Excepted quantity:E2

IATA-packing instructions - Passenger: 851



according to Regulation (EC) No 1907/2006

Acetic acid 97.5% ± 0.4% (m/m)

Revision: 17.03.2025 Product code: AC12.01795 Page 12 of 12

IATA-max. quantity - Passenger: 1 L
IATA-packing instructions - Cargo: 855
IATA-max. quantity - Cargo: 30 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Information according to Directive

2012/18/EU (SEVESO III):

P5c FLAMMABLE LIQUIDS

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

SECTION 16: Other information

Abbreviations and acronyms

Flam. Liq. 3: Flammable liquids, hazard category 3 Skin Corr. 1A: Skin corrosion, sub-category 1A Eye Dam. 1: Serious eye damage, hazard category 1

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

	- 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1						
Classification	Classification procedure						
Flam. Liq. 3; H226	On basis of test data						
Skin Corr. 1A; H314	Calculation method						
Eye Dam. 1; H318	Calculation method						

Relevant H and EUH statements (number and full text)

H226 Flammable liquid and vapour.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.

Further Information

Provide appropriate information, instructions and training to users

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)