

**Potassium hydroxide 0.1 mol/l in Methano**

Revision: 07.03.2024

Product code: AC15.00468

Page 1 of 16

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Potassium hydroxide 0.1 mol/l in Methano

UFI: MKTF-H0J1-W004-SHUU

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

Reagents and laboratory chemicals

Only for laboratory and analysis purposes.

**Uses advised against**

Do not use for private purposes (household).

**1.3. Details of the supplier of the safety data sheet****Details of the supplier of the safety data sheet**

Company name: AnalytiChem Services, Unipessoal, Lda  
Street: Rua de Júlio Dinis 676 7º  
Place: N-4050-320 Porto  
Telephone: +351 226002917  
E-mail: info@analytichem.com  
Contact person: SDS service department  
E-mail: SDS@analytichem.com  
Internet: www.analytichem.com  
Responsible Department: SDS service department

**Supplier or manufacturer details**

Company name: AnalytiChem Belgium NV  
Street: Industriezone "De Arend" 2  
Place: B-8210 Zedelgem  
Telephone: +32 50 28 83 20  
E-mail: info.be@analytichem.com  
Contact person: SDS service department  
E-mail: SDS@analytichem.com  
Responsible Department: AnalytiChem  
EU-Belgium: AnalytiChem Belgium, Industriezone "De Arend" 2, 8210 Zedelgem, Belgium, +32 50 28 83 20  
EU-Germany: AnalytiChem Germany, Stempelstrasse 6, 47167 Duisburg, Germany, +49 203 51 94 – 200  
EU-Netherlands: AnalytiChem Netherlands, Communicatieweg 7, 3641 SG Mijdrecht, The Netherlands, +31 297 286848  
UK: AnalytiChem UK, Unit 7 Launton Business Center, Murdock Road, Bicester, OX26 4XB, England, +44 1869 355 500  
USA: AnalytiChem USA, 227 China Road, Winslow, Maine, 04901, United States, +1 800-244-8378  
Canada: AnalytiChem Canada, 21800 Clark Graham Avenue, Baie d'Urfe, H9X 4B6, Canada, +1 514-457-0701  
Australia: ORE Research & Exploration Pty Ltd, 37A Hosie Street, Bayswater North, 3153, Australia, +61 3 9729 0333

**1.4. Emergency telephone****number:**

+44 20 3807 3798 (CHEMTREC)

**Further Information**

inapplicable, this product is a mixture REACH registration number see section 3

**Potassium hydroxide 0.1 mol/l in Methano**

Revision: 07.03.2024

Product code: AC15.00468

Page 2 of 16

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Regulation (EC) No 1272/2008**

Flam. Liq. 2; H225

Met. Corr. 1; H290

Acute Tox. 3; H331

Acute Tox. 3; H311

Acute Tox. 3; H301

Skin Irrit. 2; H315

Eye Irrit. 2; H319

STOT SE 1; H370

Full text of hazard statements: see SECTION 16.

**2.2. Label elements****Regulation (EC) No 1272/2008****Hazard components for labelling**

methanol

potassium hydroxide

**Signal word:** Danger**Pictograms:****Hazard statements**

H225 Highly flammable liquid and vapour.

H290 May be corrosive to metals.

H301+H311+H331 Toxic if swallowed, in contact with skin or if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H370 Causes damage to organs.

**Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P240 Ground and bond container and receiving equipment.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P302+P352 IF ON SKIN: Wash with plenty of water and soap.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P311 IF exposed or concerned: Call a POISON CENTER/doctor.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

**2.3. Other hazards**

No data available

**SECTION 3: Composition/information on ingredients****3.2. Mixtures**

## Potassium hydroxide 0.1 mol/l in Methano

Revision: 07.03.2024

Product code: AC15.00468

Page 3 of 16

## Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
67-56-1	methanol			85 - < 90 %
	200-659-6	603-001-00-X	01-2119433307-44	
	Flam. Liq. 2, Acute Tox. 3, Acute Tox. 3, Acute Tox. 3, STOT SE 1; H225 H331 H311 H301 H370			
1310-58-3	potassium hydroxide			< 1 %
	215-181-3	019-002-00-8	01-2119487136-33	
	Met. Corr. 1, Acute Tox. 4, Skin Corr. 1A, Eye Dam. 1; H290 H302 H314 H318			

Full text of H and EUH statements: see section 16.

## Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
67-56-1	200-659-6	methanol	85 - < 90 %
	inhalation: LC50 = 128,2 mg/l (vapours); inhalation: ATE = 0,5 mg/l (dusts or mists); dermal: ATE = 300 mg/kg; oral: LD50 = 6000 mg/kg STOT SE 1; H370: >= 10 - 100 STOT SE 2; H371: >= 3 - < 10		
1310-58-3	215-181-3	potassium hydroxide	< 1 %
	oral: LD50 = 333 mg/kg Skin Corr. 1A; H314: >= 5 - 100 Skin Corr. 1B; H314: >= 2 - < 5 Skin Irrit. 2; H315: >= 0,5 - < 2 Eye Irrit. 2; H319: >= 0,5 - < 2		

## Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

## SECTION 4: First aid measures

## 4.1. Description of first aid measures

## General information

First aider: Pay attention to self-protection!

## After inhalation

Provide fresh air.  
If breathing is irregular or stopped, administer artificial respiration.  
Call a physician immediately.

## After contact with skin

Wash immediately with: Water  
Take off immediately all contaminated clothing and wash it before reuse.  
Call a physician immediately.

## After contact with eyes

After eye contact: Rinse immediately carefully and thoroughly with eye-bath or water.  
Remove contact lenses, if present and easy to do. Continue rinsing.  
Consult an ophthalmologist.

## After ingestion

Provide fresh air.  
Do not allow a neutralisation agent to be drunk.  
Call a physician immediately.  
Notes for the doctor : Methanol

**Potassium hydroxide 0.1 mol/l in Methano**

Revision: 07.03.2024

Product code: AC15.00468

Page 4 of 16

**4.2. Most important symptoms and effects, both acute and delayed**

Irritant, Dizziness, Dizziness  
Anaesthetic state, Agitation, Spasms  
Inebriation, Vomiting, Headache  
Impairment of vision, Dyspnoea, Cough  
Repeated exposure may cause skin dryness or cracking.  
Risk of serious damage to eyes.  
Circulatory collapse, Corneal opacity.

**4.3. Indication of any immediate medical attention and special treatment needed**

Notes for the doctor : Methanol

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**

Carbon dioxide (CO2)  
Foam  
Extinguishing powder

**Unsuitable extinguishing media**

no restriction

**5.2. Special hazards arising from the substance or mixture**

Combustible liquids  
Vapours are heavier than air, spread along floors and form explosive mixtures with air.  
Hazardous combustion products  
In case of fire may be liberated: Carbon dioxide, Carbon monoxide  
Beware of reignition.  
Heating causes rise in pressure with risk of bursting.

**5.3. Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus.  
Wear full chemical protective clothing.  
In case of fire and/or explosion do not breathe fumes.

**Additional information**

Use water spray jet to protect personnel and to cool endangered containers.  
Move undamaged containers from immediate hazard area if it can be done safely.  
Suppress gases/vapours/mists with water spray jet.  
Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Keep away from sources of ignition - No smoking.  
This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).  
Take action to prevent static discharges.  
Corrosive to metals.

**For non-emergency personnel**

Provide adequate ventilation.  
Use personal protection equipment.  
Avoid contact with skin, eyes and clothes.

**Potassium hydroxide 0.1 mol/l in Methano**

Revision: 07.03.2024

Product code: AC15.00468

Page 5 of 16

Remove persons to safety.  
Emergency procedures  
Consult an expert  
Do not breathe dust/fume/gas/mist/vapours/spray.

**For emergency responders**

Precautionary statements For emergency responders : Personal protection equipment: see section 8

**6.2. Environmental precautions**

Do not allow uncontrolled discharge of product into the environment. Danger of explosion  
Do not allow to enter into surface water or drains.  
The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.  
Danger of explosion

**6.3. Methods and material for containment and cleaning up****For containment**

Cover drains.  
Prevent spread over a wide area (e.g. by containment or oil barriers).  
Collect in closed and suitable containers for disposal.  
Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

**For cleaning up**

Clean contaminated articles and floor according to the environmental legislation.

**Other information**

Provide adequate ventilation.  
Do not breathe dust/fume/gas/mist/vapours/spray.  
Wear breathing apparatus if exposed to vapours/dusts/aerosols.

**6.4. Reference to other sections**

Safe handling: see section 7  
Personal protection equipment: see section 8  
Disposal: see section 13

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

Avoid exposure - obtain special instructions before use.  
If handled uncovered, arrangements with local exhaust ventilation have to be used.  
Read label before use. Handle and open container with care.  
When using do not eat, drink, smoke, sniff. Keep container tightly closed.  
Use personal protection equipment. Use extractor hood (laboratory).  
Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation.

**Advice on protection against fire and explosion**

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges.  
Vapours can form explosive mixtures with air.

**Advice on general occupational hygiene**

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.  
The choice of body protection depends on the concentration and quantity of hazardous substances. The chemical resistance of protective agents must be clarified with their suppliers.

**Further information on handling**

Take off immediately all contaminated clothing and wash it before reuse.  
Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. If handled uncovered, arrangements with local exhaust ventilation have to be used.

**Potassium hydroxide 0.1 mol/l in Methano**

Revision: 07.03.2024

Product code: AC15.00468

Page 6 of 16

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Keep in a cool, well-ventilated place.

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaustion at critical locations. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Unsuitable container/equipment material: Aluminium, tin, zinc

**Hints on joint storage**

Do not store together with: Oxidising agent. Pyrophoric or self-heating substances.

Take national regulations into account.

**Further information on storage conditions**

Keep cool. Protect from sunlight.

storage temperature +15°C - +25°C

**7.3. Specific end use(s)**

Laboratory chemicals

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
67-56-1	Methanol	200	266		TWA (8 h)	WEL
		250	333		STEL (15 min)	WEL
1310-58-3	Potassium hydroxide	-	2		STEL (15 min)	WEL

## Potassium hydroxide 0.1 mol/l in Methano

Revision: 07.03.2024

Product code: AC15.00468

Page 7 of 16

## DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
67-56-1	methanol			
Consumer DNEL, acute		inhalation	systemic	50 mg/m <sup>3</sup>
Worker DNEL, long-term		inhalation	systemic	260 mg/m <sup>3</sup>
Worker DNEL, acute		inhalation	systemic	260 mg/m <sup>3</sup>
Worker DNEL, long-term		inhalation	local	260 mg/m <sup>3</sup>
Worker DNEL, acute		inhalation	local	260 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	40 mg/kg bw/day
Worker DNEL, acute		dermal	systemic	40 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	50 mg/m <sup>3</sup>
Consumer DNEL, long-term		inhalation	local	50 mg/m <sup>3</sup>
Consumer DNEL, acute		inhalation	local	50 mg/m <sup>3</sup>
Consumer DNEL, long-term		dermal	systemic	8 mg/kg bw/day
Consumer DNEL, acute		dermal	systemic	8 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	8 mg/kg bw/day
Consumer DNEL, acute		oral	systemic	8 mg/kg bw/day
1310-58-3	potassium hydroxide			
Worker DNEL, long-term		inhalation	local	1 mg/m <sup>3</sup>
Consumer DNEL, long-term		inhalation	local	1 mg/m <sup>3</sup>

## PNEC values

CAS No	Substance		
Environmental compartment		Value	
67-56-1	methanol		
Freshwater		20,8 mg/l	
Freshwater (intermittent releases)		1540 mg/l	
Marine water		2,08 mg/l	
Freshwater sediment		77 mg/kg	
Marine sediment		7,7 mg/kg	
Micro-organisms in sewage treatment plants (STP)		100 mg/l	
Soil		100 mg/kg	

**8.2. Exposure controls****Appropriate engineering controls**

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Do not breathe vapour/aerosol.

**Individual protection measures, such as personal protective equipment****Eye/face protection**

goggles

**Hand protection**

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the

**Potassium hydroxide 0.1 mol/l in Methano**

Revision: 07.03.2024

Product code: AC15.00468

Page 8 of 16

specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Suitable examples are gloves of KCL GmbH, D-36124 Eichenzell, e-mail: vertrieb@kcl.de with the following specification (test according to EN 374):

By long-term hand contact

Recommended glove articles KCL 897 Butoject®

Suitable material: Butyl caoutchouc (butyl rubber) 0,3 mm

Wearing time with permanent contact: > 480 min

By short-term hand contact

Recommended glove articles KCL 890 Vitoject®

Suitable material: FKM (fluoro rubber) 0,7 mm

Wearing time with occasional contact (splashes): > 120 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: [www.kcl.de](http://www.kcl.de)).

**Skin protection**

Flame-retardant protective clothing. Wear anti-static footwear and clothing

Take off immediately all contaminated clothing and wash it before reuse.

Wear fire resistant or flame retardant clothing.

Wash hands and face before breaks and after work and take a shower if necessary.

Draw up and observe skin protection programme.

**Respiratory protection**

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

**Environmental exposure controls**

Do not allow to enter into surface water or drains.

Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	colourless
Odour:	like: Methanol
Odour threshold:	No data available
Melting point/freezing point:	No data available
Boiling point or initial boiling point and boiling range:	~64 °C
Flammability:	not applicable
Lower explosion limits:	5,5 vol. %
Upper explosion limits:	44 vol. %
Flash point:	~11 °C
Auto-ignition temperature:	455 °C

**Potassium hydroxide 0.1 mol/l in Methano**

Revision: 07.03.2024

Product code: AC15.00468

Page 9 of 16

Decomposition temperature:	not determined
pH-Value:	13
Viscosity / kinematic:	not determined
Water solubility:	Soluble in: Water
Solubility in other solvents	
not determined	
Dissolution rate:	No data available
Partition coefficient n-octanol/water:	not determined
Dispersion stability:	No data available
Vapour pressure:	No data available
Vapour pressure:	No data available
Density:	0,8107 g/cm <sup>3</sup>
Bulk density:	No data available
Relative vapour density:	not determined
Particle characteristics:	No data available

**9.2. Other information****Information with regard to physical hazard classes****Explosive properties**

Vapours can form explosive mixtures with air.

**Sustained combustibility:**

Sustained combustibility

**Self-ignition temperature**

Solid:

not applicable

Gas:

not applicable

**Oxidizing properties**

not determined

**Other safety characteristics****Evaporation rate:**

not determined

**Solvent separation test:**

not determined

**Solvent content:**

No data available

**Solid content:**

not determined

**Sublimation point:**

No data available

**Softening point:**

No data available

**Pour point:**

No data available

**No data available:****Viscosity / dynamic:**

No data available

**Flow time:**

not determined

**Further Information**

May be corrosive to metals.

**SECTION 10: Stability and reactivity****10.1. Reactivity**

Highly flammable.

Vapours can form explosive mixtures with air.

May be corrosive to metals.

**10.2. Chemical stability**

The product is stable under storage at normal ambient temperatures.

**10.3. Possibility of hazardous reactions**

Oxidising agent, Hydrogen peroxide, Acid halides

Reducing agent, Acid, Alkaline earth metal, Alkali metals

**Potassium hydroxide 0.1 mol/l in Methano**

Revision: 07.03.2024

Product code: AC15.00468

Page 10 of 16

Risk of explosion with: Oxidizing agents, perchloric acid, perchlorates, salts of oxyhalogenic acids, chromium(VI) oxide, halogen oxides, nitrogen oxides, nonmetallic oxides, chromosulfuric acid, chlorates, hydrides, zinc diethyl, halogens, powdered magnesium, hydrogen peroxide, Nitric acid, sulphuric acid, permanganic acid, sodium hypochlorite Exothermic reaction with: acid halides, Acid anhydrides, Reducing agents, acids, Bromine, Chlorine, Chloroform, magnesium, tetrachloromethane, CYANURIC CHLORIDE Risk of ignition or formation of inflammable gases or vapours with: Fluorine, Oxides of phosphorus, Raney-nickel Generates dangerous gases or fumes in contact with: Alkaline earth metals, Alkali metals

**10.4. Conditions to avoid**

Vapours can form explosive mixtures with air.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**10.5. Incompatible materials**

Plastic articles

Glass

metals (including their alloys)

**10.6. Hazardous decomposition products**

in case of fire, see:

SECTION 5: Firefighting measures

**Further information**

No data available

**SECTION 11: Toxicological information****11.1. Information on hazard classes****Toxicokinetics, metabolism and distribution**

Avoid exposure - obtain special instructions before use.

**Acute toxicity**

Toxic if inhaled.

Toxic in contact with skin.

Toxic if swallowed.

Mucous membrane irritation in the mouth, throat, esophagus and gastrointestinal tract.

Inhalation effect: Damage to the respiratory tract.

Resorption (oral)

Resorption (by inhalation)

Resorption (dermal)

**ATEmix calculated**

ATE (oral) 115,4 mg/kg; ATE (dermal) 354,4 mg/kg; ATE (inhalation vapour) 3,540 mg/l; ATE (inhalation dust/mist) 0,5910 mg/l

## Potassium hydroxide 0.1 mol/l in Methano

Revision: 07.03.2024

Product code: AC15.00468

Page 11 of 16

CAS No	Chemical name					
	Exposure route	Dose	Species	Source	Method	
67-56-1	methanol					
	oral	LD50 mg/kg	6000	Monkey	Amer J Ophthalmol 40: 76-83 (cited in DG)	Determination of the acute toxicity of t
	dermal	ATE mg/kg	300			
	inhalation (4 h) vapour	LC50 mg/l	128,2	Rat	Study report (1980)	Study performed according to internal co
	inhalation dust/mist	ATE	0,5 mg/l			
1310-58-3	potassium hydroxide					
	oral	LD50 mg/kg	333	Rat	Fund. Appl. Toxicol., 8, 97-100 (1987)	OECD Guideline 425

**Irritation and corrosivity**

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Causes serious eye irritation.

Corneal opacity.

**Sensitising effects**

Based on available data, the classification criteria are not met.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

**STOT-single exposure**

Causes damage to organs. (methanol)

eyes

Liver and kidney damage

Irreversible damage to the optic nerve.

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Information on likely routes of exposure**

There are no data available on the mixture itself.

**Specific effects in experiment on an animal**

There are no data available on the mixture itself.

**Additional information on tests**

There are no data available on the mixture itself.

**Practical experience**

There are no data available on the mixture itself.

**11.2. Information on other hazards****Endocrine disrupting properties**

There are no data available on the mixture itself.

**Other information**

Irritant, Dizziness, Dizziness

Anaesthetic state, Agitation, Spasms

## Potassium hydroxide 0.1 mol/l in Methano

Revision: 07.03.2024

Product code: AC15.00468

Page 12 of 16

Inebriation, Vomiting, Headache  
 Impairment of vision, Dyspnoea, Cough  
 Repeated exposure may cause skin dryness or cracking.  
 Risk of serious damage to eyes.  
 Circulatory collapse, Corneal opacity.

**Further information**

Do not empty into drains.  
 Discharge into the environment must be avoided.  
 Symptoms may be delayed.  
 Other dangerous properties can not be excluded.

**SECTION 12: Ecological information****12.1. Toxicity**

Based on available data, the classification criteria are not met.

CAS No	Chemical name	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
67-56-1	methanol						
	Acute fish toxicity	LC50 15400 mg/l	96 h		Lepomis macrochirus	Bulletin of Environmental Contamination	other: EPA-660/3-75-00 9, 1975
	Acute algae toxicity	ErC50 ca. 22000 mg/l	96 h		Pseudokirchneriella subcapitata	Ecotoxicology and Environmental Safety 7	OECD Guideline 201
	Acute crustacea toxicity	EC50 > 10000 mg/l	48 h		Daphnia magna	Water Research 23(4): 495-499 (1989)	other: DIN 38412 Teil 11
	Fish toxicity	NOEC 446,7 mg/l	28 d		Pimephales promelas	SAR and QSAR in Environmental Research,	Calculation performed with ECOSAR
	Crustacea toxicity	NOEC 208 mg/l	21 d		Daphnia magna	OECD QSAR Toolbox Report (2013)	Toxicity of the target chemical is predi

**12.2. Persistence and degradability**

There are no data available on the mixture itself.

**12.3. Bioaccumulative potential**

There are no data available on the mixture itself.

**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
67-56-1	methanol	-0,77

**BCF**

CAS No	Chemical name	BCF	Species	Source
67-56-1	methanol	1	Cyprinus carpio	Comparative Biochemi

**12.4. Mobility in soil**

There are no data available on the mixture itself.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

**Potassium hydroxide 0.1 mol/l in Methano**

Revision: 07.03.2024

Product code: AC15.00468

Page 13 of 16

**12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**12.7. Other adverse effects**

No data available

**Further information**

Do not allow to enter into surface water or drains.

Avoid release to the environment.

**SECTION 13: Disposal considerations****13.1. Waste treatment methods****Disposal recommendations**

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations .

Do not allow to enter into surface water or drains.

**Contaminated packaging**

This material and its container must be disposed of as hazardous waste.

Handle contaminated packages in the same way as the substance itself.

The waste code has to be identified in agreement with the disposal company or the competent authority.

**SECTION 14: Transport information****Land transport (ADR/RID)****14.1. UN number or ID number:**

UN 3286

**14.2. UN proper shipping name:**

FLAMMABLE LIQUID, TOXIC, CORROSIVE, N.O.S. (methanol, potassium hydroxide)

**14.3. Transport hazard class(es):**

3

**14.4. Packing group:**

II

Hazard label:

3+6.1+8

Classification code:

FTC

Special Provisions:

274

Limited quantity:

1 L

Excepted quantity:

E2

Transport category:

2

Hazard No:

368

Tunnel restriction code:

D/E

**Inland waterways transport (ADN)****14.1. UN number or ID number:**

UN 3286

**14.2. UN proper shipping name:**

FLAMMABLE LIQUID, TOXIC, CORROSIVE, N.O.S. (methanol, potassium hydroxide)

**14.3. Transport hazard class(es):**

3

**14.4. Packing group:**

II

Hazard label:

3+6.1+8

Classification code:

FTC

Special Provisions:

274 802

Limited quantity:

1 L

Excepted quantity:

E2

**Marine transport (IMDG)****14.1. UN number or ID number:**

UN 3286

**14.2. UN proper shipping name:**

FLAMMABLE LIQUID, TOXIC, CORROSIVE, N.O.S. (methanol, potassium hydroxide)

## Potassium hydroxide 0.1 mol/l in Methano

Revision: 07.03.2024

Product code: AC15.00468

Page 14 of 16

<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3+6.1+8
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2
EmS:	F-E, S-C
<b>Air transport (ICAO-TI/IATA-DGR)</b>	
<b>14.1. UN number or ID number:</b>	UN 3286
<b>14.2. UN proper shipping name:</b>	FLAMMABLE LIQUID, TOXIC, CORROSIVE, N.O.S. (methanol, potassium hydroxide)
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3+6.1+8
Limited quantity Passenger:	0.5 L
Passenger LQ:	Y340
Excepted quantity:	E2
IATA-packing instructions - Passenger:	352
IATA-max. quantity - Passenger:	1 L
IATA-packing instructions - Cargo:	363
IATA-max. quantity - Cargo:	5 L

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

**14.6. Special precautions for user**

Warning: Combustible liquid. Toxic.

**14.7. Maritime transport in bulk according to IMO instruments**

not applicable

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 69, Entry 75

Information according to Directive 2012/18/EU (SEVESO III):

H2 ACUTE TOXIC

Additional information:

P5c

**National regulatory information**

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D):

2 - obviously hazardous to water

Skin resorption/Sensitization:

Permeates easily through outer skin and causes poisoning.

**SECTION 16: Other information****Changes**

This data sheet contains changes from the previous version in section(s): 1,9,11,12,13.

## Potassium hydroxide 0.1 mol/l in Methano

Revision: 07.03.2024

Product code: AC15.00468

Page 15 of 16

## Abbreviations and acronyms

Met. Corr. 1: Corrosive to metals, hazard category 1  
Flam. Liq. 2: Flammable liquids, hazard category 2  
Acute Tox. 3: Acute toxicity, hazard category 3  
Acute Tox. 4: Acute toxicity, hazard category 4  
Skin Corr. 1A: Skin corrosion, sub-category 1A  
Skin Irrit. 2: Skin irritation, hazard category 2  
Eye Dam. 1: Serious eye damage, hazard category 1  
Eye Irrit. 2: Eye irritation, hazard category 2  
STOT SE 1: Specific target organ toxicity - single exposure, hazard category 1  
ADR: Accord européen sur le transport des marchandises dangereuses par Route  
(European Agreement concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
GHS: Globally Harmonized System of Classification and Labelling of Chemicals  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service  
LC50: Lethal concentration, 50%  
LD50: Lethal dose, 50%

## Classification for mixtures and used evaluation method

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Met. Corr. 1; H290	On basis of test data
Acute Tox. 3; H331	Calculation method
Acute Tox. 3; H311	Calculation method
Acute Tox. 3; H301	Calculation method
Skin Irrit. 2; H315	
Eye Irrit. 2; H319	
STOT SE 1; H370	Calculation method

## Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.  
H290 May be corrosive to metals.  
H301 Toxic if swallowed.  
H301+H311+H331 Toxic if swallowed, in contact with skin or if inhaled.  
H302 Harmful if swallowed.  
H311 Toxic in contact with skin.  
H314 Causes severe skin burns and eye damage.  
H315 Causes skin irritation.  
H318 Causes serious eye damage.  
H319 Causes serious eye irritation.  
H331 Toxic if inhaled.  
H370 Causes damage to organs (eyes, central nervous system).  
H370 Causes damage to organs.

## Further Information

Provide appropriate information, instructions and training to users

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing,

**Potassium hydroxide 0.1 mol/l in Methano**

Revision: 07.03.2024

Product code: AC15.00468

Page 16 of 16

the information on this safety data sheet is not necessarily valid for the new made-up material.

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*