

according to Regulation (EC) No 1907/2006

Sodium methanolate 0.1 mol/l

Revision: 15.09.2025 Product code: AC15.00958 Page 1 of 17

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Sodium methanolate 0.1 mol/l

UFI: 1TA7-U20A-R00W-G7YP

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Reagents and laboratory chemicals

Only for laboratory and analysis purposes.

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Details of the supplier of the safety data sheet

Company name: AnalytiChem Services, Unipessoal, Lda

Street: Rua de Júlio Dinis 676 7º Place: P-4050-320 Porto +351 226002917 Telephone: info@analvtichem.com F-mail: SDS service department Contact person: E-mail: SDS@analytichem.com Internet: www.analytichem.com SDS service department Responsible Department:

Supplier or manufacturer details

Company name: AnalytiChem GmbH Street: Stempelstraße 6 Place: D-47167 Duisburg

Telephone: 0203/5194-0 Telefax: 0203/5194-290

E-mail: info@analytichem.de
Contact person: SDS service department
E-mail: SDS@analytichem.com
Internet: www.analytichem.de
Responsible Department: AnalytiChem:

EU-Belgium: AnalytiChem Belgium, Industriezone "De Arend" 2, 8210 Zedelgem,

Belgium, +32 50 28 83 20

EU-Germany: AnalytiChem Germany, Stempelstrasse 6, 47167 Duisburg,

Germany, +49 203 51 94 - 200

EU-Netherlands: AnalytiChem Netherlands, Communicatieweg 7, 3641 SG

Mijdrecht, The Netherlands, +31 297 286848

UK: AnalytiChem UK, Unit 7 Launton Business Center, Murdock Road, Bicester,

OX26 4XB, England, +44 1869 355 500

USA: AnalytiChem USA, 227 China Road, Winslow, Maine, 04901, United States,

+1 800-244-8378

Canada: AnalytiChem Canada, 21800 Clark Graham Avenue, Baie d'Urfe, H9X

4B6, Canada, +1 514-457-0701

Australia: ORE Research & Exploration Pty Ltd, 37A Hosie Street, Bayswater

North, 3153, Australia, +61 3 9729 0333

1.4. Emergency telephone

number:

+353 1 901 4670 (CHEMTREC)



according to Regulation (EC) No 1907/2006

Sodium methanolate 0.1 mol/l

Revision: 15.09.2025 Product code: AC15.00958 Page 2 of 17

Further Information

This product is a mixture. REACH Registration Number see section 3.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Flam. Liq. 2; H225 Repr. 2; H361d Acute Tox. 4; H332 Acute Tox. 4; H312 Acute Tox. 4; H302 Skin Irrit. 2; H315 STOT SE 1; H370 H336 STOT RE 2; H373 Asp. Tox. 1; H304 Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

toluene methanol

Signal word: Danger

Pictograms:







Hazard statements

H225 Highly flammable liquid and vapour.

H302+H312+H332 Harmful if swallowed, in contact with skin or if inhaled.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.H361d Suspected of damaging the unborn child.

H370 Causes damage to organs.

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P260 Do not breathe mist/vapours/spray.

P308+P311 IF exposed or concerned: Call a POISON CENTER/doctor.

P310 Immediately call a POISON CENTER/doctor.

P331 Do NOT induce vomiting.

P403+P235 Store in a well-ventilated place. Keep cool.

2.3. Other hazards

No data available



according to Regulation (EC) No 1907/2006

Sodium methanolate 0.1 mol/l

Revision: 15.09.2025 Product code: AC15.00958 Page 3 of 17

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Relevant ingredients

CAS No	Chemical name			Quantity	
	EC No	Index No	ndex No REACH No		
	Classification (Regulation (EC) No 1272/2008)				
108-88-3	toluene				
	203-625-9	601-021-00-3	01-2119471310-51		
	Flam. Liq. 2, Repr. 2, Skin Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1, Aquatic Chronic 3; H225 H361d H315 H336 H373 H304 H412				
67-56-1	methanol			15 - < 20 %	
	200-659-6	603-001-00-X	01-2119433307-44		
	Flam. Liq. 2, Acute Tox. 3, Acute Tox. 3, Acute Tox. 3, STOT SE 1; H225 H331 H311 H301 H370				

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity			
	Specific Conc. Limits, M-factors and ATE					
108-88-3	203-625-9	toluene	80 - < 85 %			
	inhalation: LC50 = 28,1 mg/l (vapours); dermal: LD50 = > 5000 mg/kg; oral: LD50 = 5580 mg/kg					
67-56-1	200-659-6	6 methanol				
	inhalation: LC50 = 128,2 mg/l (vapours); inhalation: ATE = 0,5 mg/l (dusts or mists); dermal: ATE = 300 mg/kg; oral: LD50 = 6000 mg/kg STOT SE 1; H370: >= 10 - 100 STOT SE 2; H371: >= 3 - < 10					

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Self-protection of the first aider

After inhalation

Provide fresh air.

If breathing is irregular or stopped, administer artificial respiration.

Call a physician immediately.

After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

Call a physician immediately.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Observe risk of aspiration if vomiting occurs.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Sodium methanolate 0.1 mol/l

Revision: 15.09.2025 Product code: AC15.00958 Page 4 of 17

Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Irritant, Headache

Dizziness, Dizziness

Vomiting, Inebriation

Spasms, Circulatory collapse

Respiratory complaints, Dyspnoea

Unconsciousness

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam.

Extinguishing powder

Carbon dioxide (CO2)

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Combustible liquids

Beware of reignition.

Hazardous combustion products

In case of fire may be liberated:

Carbon dioxide (CO2), Carbon monoxide

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Heating causes rise in pressure with risk of bursting.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

In case of fire and/or explosion do not breathe fumes.

Avoid contact with skin, eyes and clothes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Move undamaged containers from immediate hazard area if it can be done safely.

Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Keep away from sources of ignition - No smoking.

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

Take action to prevent static discharges.

For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Sodium methanolate 0.1 mol/l

Revision: 15.09.2025 Product code: AC15.00958 Page 5 of 17

Emergency procedures

Consult an expert

Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders: Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Danger of explosion

6.3. Methods and material for containment and cleaning up

For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Avoid exposure - obtain special instructions before use.

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Keep container tightly closed.

Use personal protection equipment. Use extractor hood (laboratory).

Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation.

Advice on protection against fire and explosion

Take action to prevent static discharges. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs.

Draw up and observe skin protection programme.

The choice of body protection depends on the concentration and quantity of hazardous substances. The chemical resistance of protective agents must be clarified with their suppliers.

Further information on handling

Take off immediately all contaminated clothing and wash it before reuse .

Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. If handled uncovered, arrangements with local exhaust ventilation have to be used. Store in a place accessible by authorized persons only.

Otore in a place accessible by authorized persons only.

7.2. Conditions for safe storage, including any incompatibilities



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Sodium methanolate 0.1 mol/l

Revision: 15.09.2025 Product code: AC15.00958 Page 6 of 17

Requirements for storage rooms and vessels

Keep in a cool, well-ventilated place.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Keep container tightly closed.

Hints on joint storage

national regulations

Further information on storage conditions

Keep cool. Protect from sunlight.

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
67-56-1	Methyl alcohol	200	260		TWA (8 h)	
108-88-3	Toluene	50	192		TWA (8 h)	
		100	384		STEL (15 min)	

Biological limit values

CAS No	Substance	Parameter	Value	Test material	Sampling time
108-88-3	Toluene	Toluene	0.02 mg/L		Prior to last shift of workweek
67-56-1	Methanol	Methanol	15 mg/L	Urine	End of shift



according to Regulation (EC) No 1907/2006

Sodium methanolate 0.1 mol/l

Revision: 15.09.2025 Product code: AC15.00958 Page 7 of 17

DNEL/DMEL values

CAS No Substance			
DNEL type	Exposure route	Effect	Value
108-88-3 toluene			
Worker DNEL, long-term	inhalation	systemic	192 mg/m³
Worker DNEL, acute	inhalation	systemic	384 mg/m³
Worker DNEL, long-term	inhalation	local	192 mg/m³
Worker DNEL, acute	inhalation	local	384 mg/m³
Worker DNEL, long-term	dermal	systemic	384 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	56,5 mg/m³
Consumer DNEL, acute	inhalation	systemic	226 mg/m³
Consumer DNEL, long-term	inhalation	local	56,5 mg/m³
Consumer DNEL, acute	inhalation	local	226 mg/m³
Consumer DNEL, long-term	dermal	systemic	226 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	8,13 mg/kg bw/day
67-56-1 methanol			
Consumer DNEL, acute	inhalation	systemic	50 mg/m³
Worker DNEL, long-term	inhalation	systemic	260 mg/m³
Worker DNEL, acute	inhalation	systemic	260 mg/m³
Worker DNEL, long-term	inhalation	local	260 mg/m³
Worker DNEL, acute	inhalation	local	260 mg/m³
Worker DNEL, long-term	dermal	systemic	40 mg/kg bw/day
Worker DNEL, acute	dermal	systemic	40 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	50 mg/m³
		l	
Consumer DNEL, long-term	inhalation	local	50 mg/m³
Consumer DNEL, long-term Consumer DNEL, acute	inhalation inhalation	local	50 mg/m³ 50 mg/m³
			
Consumer DNEL, acute	inhalation	local	50 mg/m³
Consumer DNEL, acute Consumer DNEL, long-term	inhalation dermal	local systemic	50 mg/m³ 8 mg/kg bw/day



according to Regulation (EC) No 1907/2006

Sodium methanolate 0.1 mol/l

Revision: 15.09.2025 Product code: AC15.00958 Page 8 of 17

PNEC values

CAS No	Substance		
Environmenta	l compartment	Value	
108-88-3 toluene			
Freshwater			
Freshwater (in	ntermittent releases)	0,68 mg/l	
Marine water		0,68 mg/l	
Freshwater se	ediment	16,39 mg/kg	
Marine sedim	16,39 mg/kg		
Micro-organisms in sewage treatment plants (STP)		13,61 mg/l	
Soil		2,89 mg/kg	
67-56-1	methanol		
Freshwater		20,8 mg/l	
Freshwater (ir	ntermittent releases)	1540 mg/l	
Marine water		2,08 mg/l	
Freshwater sediment		77 mg/kg	
Marine sediment 7,7 mg			
Micro-organis	ms in sewage treatment plants (STP)	100 mg/l	
Soil		100 mg/kg	

8.2. Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment

Eye/face protection

goggles

Face protection umbrella

Hand protection

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact: No data available

By short-term hand contact

Trade name/designation: KCL 890 Vitoject® Suitable material: FKM (fluoro rubber) 0,7 mm

Wearing time with occasional contact (splashes): > 120 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).



according to Regulation (EC) No 1907/2006

Sodium methanolate 0.1 mol/l

Revision: 15.09.2025 Product code: AC15.00958 Page 9 of 17

Skin protection

Take off immediately all contaminated clothing and wash it before reuse.

Wear fire resistant or flame retardant clothing.

Wash hands and face before breaks and after work and take a shower if necessary.

Respiratory protection

Respiratory protection necessary at: aerosol or mist formation

The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Environmental exposure controls

Do not allow to enter into surface water or drains.

Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.

Danger of explosion

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid Colour: clear

Odour: like: Hydrocarbons, aromatic

Odour threshold: No data available

Melting point/freezing point:

Boiling point or initial boiling point and

No data available

>35 °C

boiling range:

No data available Flammability: No data available Lower explosion limits: No data available Upper explosion limits: ~6°C Flash point: No data available Auto-ignition temperature: No data available Decomposition temperature: No data available pH-Value: No data available Viscosity / kinematic: No data available Water solubility:

Solubility in other solvents

No data available

Dissolution rate:

Partition coefficient n-octanol/water:

Dispersion stability:

Vapour pressure:

Vapour pressure:

No data available

Relative density:

Relative density:

No data available

Bulk density:

No data available

Relative vapour density:

No data available

Particle characteristics:

No data available

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Sustained combustibility: Sustained combustibility

Self-ignition temperature

Solid: No data available



according to Regulation (EC) No 1907/2006

Sodium methanolate 0.1 mol/l

Revision: 15.09.2025 Product code: AC15.00958 Page 10 of 17

Gas: No data available

Oxidizing properties

No data available

Other safety characteristics

No data available Evaporation rate: Solvent separation test: No data available No data available Solvent content: No data available Solid content: No data available Sublimation point: No data available Softening point: Pour point: No data available No data available No data available Viscosity / dynamic: No data available Flow time:

Further Information
No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

Vapours may form explosive mixtures with air.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Oxidising agent

Nitric acid

Acetic acid

Strong acid

silver

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

Plastic articles

Rubber articles

10.6. Hazardous decomposition products

SECTION 5: Firefighting measures

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicocinetics, metabolism and distribution

Avoid exposure - obtain special instructions before use.



according to Regulation (EC) No 1907/2006

Sodium methanolate 0.1 mol/l

Revision: 15.09.2025 Product code: AC15.00958 Page 11 of 17

Acute toxicity

Harmful if inhaled.

Harmful in contact with skin.

Harmful if swallowed.

Irritation to respiratory tract

Resorption (by inhalation)

Resorption (dermal)

ATEmix calculated

ATE (oral) 620,7 mg/kg; ATE (dermal) 1862 mg/kg; ATE (inhalation vapour) 18,62 mg/l; ATE (inhalation dust/mist) 3,104 mg/l

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
108-88-3	toluene					
	oral	LD50 mg/kg	5580	Rat	Toxicology 4, 5-15 (1975)	EU Method B.1
	dermal	LD50 mg/kg	> 5000	Rabbit	American Industrial Hygiene Association	Study investigated mortality in groups o
	inhalation (4 h) vapour	LC50	28,1 mg/l	Rat	Study report (1980)	OECD Guideline 403
67-56-1	methanol					
	oral	LD50 mg/kg	6000	Monkey	Amer J Ophthalmol 40: 76-83 (cited in DG	Determination of the acute toxicity of t
	dermal	ATE mg/kg	300			
	inhalation (4 h) vapour	LC50 mg/l	128,2	Rat	Study report (1980)	Study performed according to internal co
	inhalation dust/mist	ATE	0,5 mg/l			

Irritation and corrosivity

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of damaging the unborn child. (toluene)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Causes damage to organs. (methanol)

May cause drowsiness or dizziness. (toluene)

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (toluene)

Aspiration hazard

May be fatal if swallowed and enters airways.

Information on likely routes of exposure

There are no data available on the mixture itself.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Sodium methanolate 0.1 mol/l

Revision: 15.09.2025 Product code: AC15.00958 Page 12 of 17

Specific effects in experiment on an animal

There are no data available on the mixture itself.

Additional information on tests

There are no data available on the mixture itself.

Practical experience

There are no data available on the mixture itself.

11.2. Information on other hazards

Endocrine disrupting properties

There are no data available on the mixture itself.

Other information

Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).

Further information

Irritant, Headache
Dizziness, Dizziness
Vomiting, Inebriation
Spasms, Circulatory collapse
Respiratory complaints, Dyspnoea
Unconsciousness

SECTION 12: Ecological information

12.1. Toxicity

Harmful to aquatic life with long lasting effects.



according to Regulation (EC) No 1907/2006

Sodium methanolate 0.1 mol/l

Revision: 15.09.2025 Product code: AC15.00958 Page 13 of 17

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method
108-88-3	toluene						
	Acute fish toxicity	LC50	5,5 mg/l	96 h	Oncorhynchus kisutch	Transactions A. Fish. Soc. 110, 430-436.	Fry were exposed to toluene in a flow th
	Acute algae toxicity	ErC50 mg/l	> 433	96 h	Pseudokirchneriella subcapitata	REACh Registration Dossier	Method: other
	Acute crustacea toxicity	EC50	11,5 mg/l	48 h	Daphnia magna	REACh Registration Dossier	Method: other
	Fish toxicity	NOEC mg/l	1,39	40 d	Oncorhynchus kisutch	Transactions A. Fish. Soc. 110, 430-436.	Fry were exposed to toluene in a flow th
	Algae toxicity	NOEC mg/l	> 400	7 d	Scenedesmus quadricauda	REACh Registration Dossier	Method: other
	Crustacea toxicity	NOEC mg/l	0,74	7 d	Ceriodaphnia dubia	Ecotoxicol. Environ. Saf. 39, 136-146. (other: US EPA 600/4-91-003
67-56-1	methanol	•					
	Acute fish toxicity	LC50 mg/l	15400	96 h	Lepomis macrochirus	Bulletin of Environmental Contamination	other: EPA-660/3-75-00 9, 1975
	Acute algae toxicity	ErC50 22000 mg/l	ca.	96 h	Pseudokirchneriella subcapitata	Ecotoxicology and Environmental Safety 7	OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	> 10000	48 h	Daphnia magna	Water Research 23(4): 495-499 (1989)	other: DIN 38412 Teil 11
	Fish toxicity	NOEC mg/l	446,7	28 d	Pimephales promelas	SAR and QSAR in Environmental Research,	Calculation performed with ECOSAR
	Crustacea toxicity	NOEC	208 mg/l	21 d	Daphnia magna	OECD QSAR Toolbox Report (2013)	Toxicity of the target chemical is predi

12.2. Persistence and degradability

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
108-88-3	toluene	2,73
67-56-1	methanol	-0,77



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Sodium methanolate 0.1 mol/l Product code: AC15.00958 Page 14 of 17

BCF

CAS No	Chemical name	BCF	Species	Source
108-88-3	toluene	90	Leuciscus idus melanotus	Chemosphere 14 (10).
67-56-1	methanol	1	Cyprinus carpio	Comparative Biochemi

12.4. Mobility in soil

Revision: 15.09.2025

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Do not allow to enter into surface water or drains.

Further information

Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations.

Do not empty into drains.

Do not mix with other wastes.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 1992

14.2. UN proper shipping name: FLAMMABLE LIQUID, TOXIC, N.O.S. (toluene, methanol)

14.3. Transport hazard class(es): Ш 14.4. Packing group: Hazard label: 3+6.1 Classification code: FT1 274 Special Provisions: 1 I Limited quantity: F2 Excepted quantity: 2 Transport category: 336 Hazard No: Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1992

14.2. UN proper shipping name: FLAMMABLE LIQUID, TOXIC, N.O.S. (toluene, methanol)

 14.3. Transport hazard class(es):
 3

 14.4. Packing group:
 II

 Hazard label:
 3+6.1



according to Regulation (EC) No 1907/2006

	Sodium methano		
Revision: 15.09.2025	Product code:	AC15.00958	Page 15 of 17
Classification code:	FT1		
Special Provisions:	274 802		
Limited quantity:	1 L		
Excepted quantity:	E2		
Marine transport (IMDG)			
14.1. UN number or ID number:	UN 1992		
14.2. UN proper shipping name:	FLAMMABLE LIQUID	D, TOXIC, N.O.S. (toluene, methanol)	
14.3. Transport hazard class(es):	3		
14.4. Packing group:	II		
Hazard label:	3+6.1		
Special Provisions:	274		
Limited quantity:	1 L		
Excepted quantity:	E2		
EmS:	F-E, S-D		
Air transport (ICAO-TI/IATA-DGR)			
14.1. UN number or ID number:	UN 1992		
14.2. UN proper shipping name:	FLAMMABLE LIQUID	D, TOXIC, N.O.S. (toluene, methanol)	
14.3. Transport hazard class(es):	3		
14.4. Packing group:	II		
Hazard label:	3+6.1		
Special Provisions:	A3		
Limited quantity Passenger:	1 L		
Passenger LQ:	Y341		
Excepted quantity:	E2		
IATA-packing instructions - Passenger:		352	
IATA-max. quantity - Passenger:		1 L	
IATA-packing instructions - Cargo:		364	
IATA-max. quantity - Cargo:		60 L	
14.5. Environmental hazards			

SECTION 15: Regulatory information

ENVIRONMENTALLY HAZARDOUS:

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

No

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 48, Entry 69, Entry 75

Information according to Directive

H3 STOT SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE

2012/18/EU (SEVESO III):

Additional information: P5c

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe employment restrictions for women of

child-bearing age.

Water hazard class (D): 3 - highly hazardous to water

SECTION 16: Other information



according to Regulation (EC) No 1907/2006

Sodium methanolate 0.1 mol/l

Revision: 15.09.2025 Product code: AC15.00958 Page 16 of 17

Abbreviations and acronyms

Flam. Liq. 2: Flammable liquids, hazard category 2 Acute Tox. 3: Acute toxicity, hazard category 3 Asp. Tox. 1: Aspiration hazard, hazard category 1 Skin Irrit. 2: Skin irritation, hazard category 2 Repr. 2: Reproductive toxicity, hazard category 2

STOT SE 1: Specific target organ toxicity - single exposure, hazard category 1 STOT RE 2: Specific target organ toxicity - repeated exposure, hazard category 2

Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard category: Chronic 3

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Repr. 2; H361d	Calculation method
Acute Tox. 4; H332	Calculation method
Acute Tox. 4; H312	Calculation method
Acute Tox. 4; H302	Calculation method
Skin Irrit. 2; H315	Calculation method
STOT SE 1; H370	Calculation method
STOT SE 3; H336	Calculation method
STOT RE 2; H373	Calculation method
Asp. Tox. 1; H304	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.

H301 Toxic if swallowed.
H302 Harmful if swallowed.

H302+H312+H332 Harmful if swallowed, in contact with skin or if inhaled.

H304 May be fatal if swallowed and enters airways.

H311 Toxic in contact with skin.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H331 Toxic if inhaled.
H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.H361d Suspected of damaging the unborn child.

H370 Causes damage to organs (eyes, central nervous system).

H370 Causes damage to organs.

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

Further Information

Provide appropriate information, instructions and training to users

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Sodium methanolate 0.1 mol/l

Revision: 15.09.2025 Product code: AC15.00958 Page 17 of 17

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)