

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Etching solution Vilella

Revision: 18.02.2026

Product code: AC15.03890

Page 1 of 14

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Etching solution Vilella

UFI: QN8J-T5JS-TEHK-KYP9

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Reagents and laboratory chemicals
Only for laboratory and analysis purposes.

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet**Details of the supplier of the safety data sheet**

Company name: AnalytiChem Services, Unipessoal, Lda
Street: Rua de Júlio Dinis 676 7º
Place: N-4050-320 Porto
Telephone: +351 226002917
E-mail: info@analytichem.com
Contact person: SDS service department
E-mail: SDS@analytichem.com
Internet: www.analytichem.com
Responsible Department: SDS service department

Supplier or manufacturer details

Company name: AnalytiChem Belgium NV
Street: Industriezone "De Arend" 2
Place: B-8210 Zedelgem
Telephone: +32 50 28 83 20
E-mail: info.be@analytichem.com
Contact person: SDS service department
E-mail: SDS@analytichem.com
Responsible Department: AnalytiChem:
EU-Belgium: AnalytiChem Belgium, Industriezone "De Arend" 2, 8210 Zedelgem, Belgium, +32 50 28 83 20
EU-Germany: AnalytiChem Germany, Stempelstrasse 6, 47167 Duisburg, Germany, +49 203 51 94 – 200
EU-Netherlands: AnalytiChem Netherlands, Communicatieweg 7, 3641 SG Mijdrecht, The Netherlands, +31 297 286848
UK: AnalytiChem UK, Unit 7 Launton Business Center, Murdock Road, Bicester, OX26 4XB, England, +44 1869 355 500
USA: AnalytiChem USA, 227 China Road, Winslow, Maine, 04901, United States, +1 800-244-8378
Canada: AnalytiChem Canada, 21800 Clark Graham Avenue, Baie d'Urfe, H9X 4B6, Canada, +1 514-457-0701
Australia: ORE Research & Exploration Pty Ltd, 37A Hosie Street, Bayswater North, 3153, Australia, +61 3 9729 0333
+353 1 901 4670 (CHEMTREC)

1.4. Emergency telephone number:**Further Information**

This product is a mixture. REACH Registration Number see section 3.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Etching solution Vilella

Revision: 18.02.2026

Product code: AC15.03890

Page 2 of 14

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture**Regulation (EC) No 1272/2008**

Flam. Liq. 2; H225
Met. Corr. 1; H290
Eye Irrit. 2; H319

Full text of hazard statements: see SECTION 16.

2.2. Label elements**Regulation (EC) No 1272/2008**

Signal word: Danger

Pictograms:

**Hazard statements**

H225 Highly flammable liquid and vapour.
H290 May be corrosive to metals.
H319 Causes serious eye irritation.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P390 Absorb spillage to prevent material damage.
P403+P235 Store in a well-ventilated place. Keep cool.
P501 Dispose of contents/container to an appropriate recycling or disposal facility.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures**Relevant ingredients**

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
64-17-5	ethanol			90 - < 95 %
	200-578-6	603-002-00-5	01-2119457610-43	
	Flam. Liq. 2, Eye Irrit. 2; H225 H319			
7647-01-0	Hydrochloric acid			1 - < 5 %
	231-595-7	017-002-01-X	01-2119484862-27	
	Met. Corr. 1, Skin Corr. 1B, Eye Dam. 1, STOT SE 3; H290 H314 H318 H335			
88-89-1	"2,4,6-trinitrophenol; picric acid"			1 - < 5 %
	201-865-9	609-009-00-X		
	Expl. 1.1, Acute Tox. 3, Acute Tox. 3, Acute Tox. 3; H201 H331 H311 H301			

Full text of H and EUH statements: see section 16.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Etching solution Vilella

Revision: 18.02.2026

Product code: AC15.03890

Page 3 of 14

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
64-17-5	200-578-6	ethanol	90 - < 95 %
		inhalation: LC50 = 124,7 mg/l (vapours); oral: LD50 = 10470 mg/kg Eye Irrit. 2; H319: >= 50 - 100	
7647-01-0	231-595-7	Hydrochloric acid	1 - < 5 %
		Skin Corr. 1B; H314: >= 25 - 100 Skin Irrit. 2; H315: >= 10 - < 25 Eye Irrit. 2; H319: >= 10 - < 25 STOT SE 3; H335: >= 10 - 100	
88-89-1	201-865-9	"2,4,6-trinitrophenol; picric acid"	1 - < 5 %
		inhalation: ATE = 3 mg/l (vapours); inhalation: ATE = 0,5 mg/l (dusts or mists); dermal: ATE = 300 mg/kg; oral: ATE = 100 mg/kg	

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

No data available

After inhalation

Provide fresh air.

Call a physician immediately.

After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

Call a physician immediately.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Remove contact lenses, if present and easy to do. Continue rinsing.

Protect uninjured eye.

After ingestion

Rinse mouth immediately and drink plenty of water.

Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Irritant

Cough

Dyspnoea

Dizziness

The product causes narcotic-like effects.

Inebriation

Vomiting

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Etching solution Vilella

Revision: 18.02.2026

Product code: AC15.03890

Page 4 of 14

Suitable extinguishing mediaWater spray jet, Carbon dioxide (CO₂), Foam, Extinguishing powder.**Unsuitable extinguishing media**

no restriction

5.2. Special hazards arising from the substance or mixture

Picrates, in a dry state, are extremely shock-sensitive and heat-sensitive (danger of explosion).

Combustible liquid.

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Hazardous combustion products

In case of fire may be liberated:

Hydrogen chloride (HCl)

Carbon dioxide (CO₂), Carbon monoxide

Beware of reignition.

5.3. Advice for firefighters

Remove persons to safety. Do not inhale explosion and combustion gases.

Avoid contact with skin, eyes and clothes.

In case of fire: Wear self-contained breathing apparatus.

Use water spray jet to protect personnel and to cool endangered containers.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Suppress gases/vapours/mists with water spray jet.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Picrates, in a dry state, are extremely shock-sensitive and heat-sensitive (danger of explosion).

Keep away from sources of ignition - No smoking.

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

Take action to prevent static discharges.

Corrosive to metals.

For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Consult an expert

Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Danger of explosion

6.3. Methods and material for containment and cleaning up

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Etching solution Vilella

Revision: 18.02.2026

Product code: AC15.03890

Page 5 of 14

For containment

- Cover drains.
- Prevent spread over a wide area (e.g. by containment or oil barriers).
- Collect in closed and suitable containers for disposal.
- Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

- Clean contaminated articles and floor according to the environmental legislation.

Other information

- Provide adequate ventilation.
- Do not breathe dust/fume/gas/mist/vapours/spray.
- Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

- Safe handling: see section 7
- Personal protection equipment: see section 8
- Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

- Do not dry up the product.
- Picrates, in a dry state, are extremely shock-sensitive and heat-sensitive (danger of explosion).
- Read label before use. Handle and open container with care.
- When using do not eat, drink, smoke, sniff. Keep container tightly closed.
- Use personal protection equipment. Use extractor hood (laboratory).
- Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation.

Advice on protection against fire and explosion

- Take action to prevent static discharges. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- Vapours may form explosive mixtures with air.

Advice on general occupational hygiene

- Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.
- The choice of body protection depends on the concentration and quantity of hazardous substances. The chemical resistance of protective agents must be clarified with their suppliers.

Further information on handling

- Take off immediately all contaminated clothing and wash it before reuse.
- If handled uncovered, arrangements with local exhaust ventilation have to be used.
- Draw up and observe skin protection programme.
- Wash hands and face before breaks and after work and take a shower if necessary.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

- Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- Do not dry up the product.
- Picrates, in a dry state, are extremely shock-sensitive and heat-sensitive (danger of explosion).

Hints on joint storage

- Do not store together with: Oxidising agent. Pyrophoric or self-heating substances.
- Take national regulations into account.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Etching solution Vilella

Revision: 18.02.2026

Product code: AC15.03890

Page 6 of 14

Further information on storage conditions

Corrosive to metals.
Unsuitable container/equipment material: Metal

7.3. Specific end use(s)

Laboratory use Laboratory chemical

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
64-17-5	Ethyl alcohol	1000	-		STEL (15 min)	
7647-01-0	Hydrogen chloride	5	8		TWA (8 h)	
		10	15		STEL (15 min)	
88-89-1	Picric acid	-	0.1		TWA (8 h)	
		-	0.3		STEL (15 min)	

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
64-17-5	ethanol			
	Worker DNEL, long-term	inhalation	systemic	950 mg/m ³
	Worker DNEL, long-term	dermal	systemic	343 mg/kg bw/day
	Consumer DNEL, long-term	inhalation	systemic	114 mg/m ³
	Consumer DNEL, long-term	dermal	systemic	206 mg/kg bw/day
	Consumer DNEL, long-term	oral	systemic	87 mg/kg bw/day
7647-01-0	Hydrochloric acid			
	Worker DNEL, long-term	inhalation	local	8 mg/m ³
	Worker DNEL, acute	inhalation	local	15 mg/m ³
	Consumer DNEL, long-term	inhalation	local	8 mg/m ³
	Consumer DNEL, acute	inhalation	local	15 mg/m ³

PNEC values

CAS No	Substance	Value
	Environmental compartment	
64-17-5	ethanol	
	Freshwater	0,96 mg/l
	Freshwater (intermittent releases)	2,75 mg/l
	Marine water	0,79 mg/l
	Freshwater sediment	3,6 mg/kg
	Marine sediment	2,9 mg/kg
	Secondary poisoning	380 mg/kg
	Microorganisms in sewage treatment plants (STP)	580 mg/l
	Soil	0,63 mg/kg

8.2. Exposure controls

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Etching solution Vilella

Revision: 18.02.2026

Product code: AC15.03890

Page 7 of 14

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Suitable eye protection: goggles.

Hand protection

Tested protective gloves must be worn. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing

Material, acid-resistant

Respiratory protection

Respiratory protection necessary at: aerosol or mist formation

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Thermal hazards

No data available

Environmental exposure controls

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Danger of explosion

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	yellow
Odour:	like: Ethanol
Odour threshold:	No data available
Melting point/freezing point:	-117 °C
Boiling point or initial boiling point and boiling range:	78 °C
Flammability:	not applicable
Lower explosion limits:	No data available
Upper explosion limits:	No data available
Flash point:	12 °C
Auto-ignition temperature:	No data available
Decomposition temperature:	No data available
pH-Value:	acidic
Viscosity / kinematic:	No data available
Water solubility:	No data available
Solubility in other solvents	
not determined	
Dissolution rate:	No data available
Partition coefficient n-octanol/water:	No data available
Dispersion stability:	No data available

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Etching solution Vilella

Revision: 18.02.2026

Product code: AC15.03890

Page 8 of 14

Vapour pressure:	No data available
Vapour pressure:	No data available
Density:	0,82 g/cm ³
Relative density:	No data available
Bulk density:	No data available
Relative vapour density:	No data available
Particle characteristics:	No data available

9.2. Other information**Information with regard to physical hazard classes****Explosive properties**

Vapours can form explosive mixtures with air.

Do not dry up the product.

Picrates, in a dry state, are extremely shock-sensitive and heat-sensitive (danger of explosion).

Sustained combustibility: Sustained combustibility

Self-ignition temperature

Solid: not applicable

Gas: not applicable

Oxidizing properties

Not oxidising.

Other safety characteristics

Evaporation rate: No data available

Solvent separation test: No data available

Solvent content: No data available

Solid content: No data available

Sublimation point: No data available

Softening point: No data available

Pour point: No data available

No data available:

Viscosity / dynamic: No data available

Flow time: No data available

Further Information

Corrosive to metals.

SECTION 10: Stability and reactivity**10.1. Reactivity**

Highly flammable.

Vapours can form explosive mixtures with air.

Do not dry up the product.

Picrates, in a dry state, are extremely shock-sensitive and heat-sensitive (danger of explosion).

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Oxidising agent

Alkali (lye)

(for ethanol) Risk of explosion / exothermic reaction with: hydrogen peroxide, perchlorates, perchloric acid, nitric acid, mercury(II) nitrate, permanganic acid, nitriles, peroxy compounds, strong oxidizing agents, nitrosyl compounds, peroxides, sodium, potassium, halogen oxides, calcium hypochlorite, nitrogen dioxide, metal oxides, uranium hexafluoride, iodides, chlorine, alkali metals, alkaline earth metals, alkali oxides, ethylene oxide, silver, with nitric acid, silver compounds, with ammonia, potassium permanganate, with concentrated sulfuric

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Etching solution Vilella

Revision: 18.02.2026

Product code: AC15.03890

Page 9 of 14

acid. Fire hazard or formation of flammable gases or vapors with: halogen-halogen compounds, chromium(VI) oxide, chromyl chloride, fluorine, hydrides, phosphorus oxides, platinum, nitric acid, with potassium permanganate.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

10.5. Incompatible materials

Metal
Plastic articles
Rubber articles

10.6. Hazardous decomposition products

In case of fire may be liberated:
SECTION 5: Firefighting measures

Further information

No data available

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008****Toxicokinetics, metabolism and distribution**

There are no data available on the mixture itself.

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 5000 mg/kg; ATE (dermal) > 5000 mg/kg

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64-17-5	ethanol				
	oral	LD50 mg/kg	10470	Rat	Study report (1976) OECD Guideline 401
	inhalation (4 h) vapour	LC50 mg/l	124,7	Rat	Study report (1980) OECD Guideline 403
88-89-1	"2,4,6-trinitrophenol; picric acid"				
	oral	ATE mg/kg	100		
	dermal	ATE mg/kg	300		
	inhalation vapour	ATE	3 mg/l		
	inhalation dust/mist	ATE	0,5 mg/l		

Irritation and corrosivity

Serious eye damage/eye irritation: Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Etching solution Vilella

Revision: 18.02.2026

Product code: AC15.03890

Page 10 of 14

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

There are no data available on the mixture itself.

Specific effects in experiment on an animal

There are no data available on the mixture itself.

Additional information on tests

There are no data available on the mixture itself.

Practical experience

There are no data available on the mixture itself.

11.2. Information on other hazards**Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

Other information

Irritant

Cough

Dyspnoea

Dizziness

The product causes narcotic-like effects.

Inebriation

Vomiting

Further information

Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).

SECTION 12: Ecological information**12.1. Toxicity**

Based on available data, the classification criteria are not met.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Etching solution Vilella

Revision: 18.02.2026

Product code: AC15.03890

Page 11 of 14

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
64-17-5	ethanol					
	Acute fish toxicity	LC50 15400 mg/l	96 h	Lepomis macrochirus	Bulletin of Environmental Contamination	other: EPA-660/3-75-009, 1975
	Acute algae toxicity	ErC50 ca. 22000 mg/l	96 h	Pseudokirchneriella subcapitata	Ecotoxicology and Environmental Safety 7	OECD Guideline 201
	Acute crustacea toxicity	EC50 > 10000 mg/l	48 h	Daphnia magna	Water Research 23(4): 495-499 (1989)	other: DIN 38412 Teil 11
	Algae toxicity	NOEC 5400 mg/l	5 d	Skeletonema costatum	Environ Toxicol Chem 8(5):451-455. (1989)	Study to determine the sensitivity of a
	Crustacea toxicity	NOEC 2 mg/l	10 d	Ceriodaphnia dubia	Arch Environ Contam Toxicol 20(2):211-21	Follows the basic methodology for the th
7647-01-0	Hydrochloric acid					
	Acute fish toxicity	LC50 862 mg/l	96 h	Leuciscus idus		

12.2. Persistence and degradability

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
64-17-5	ethanol	-0,77

BCF

CAS No	Chemical name	BCF	Species	Source
64-17-5	ethanol	1	Cyprinus carpio	Comparative Biochemi

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Discharge into the environment must be avoided.

Harmful effect due to pH shift.

Forms corrosive mixtures with water even if diluted.

Further information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations**13.1. Waste treatment methods**

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Etching solution Vilella

Revision: 18.02.2026

Product code: AC15.03890

Page 12 of 14

Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.
Send to a physico-chemical treatment facility under observation of official regulations.
Do not empty into drains.

Contaminated packaging

Waste codes/waste designations according to EWC/AVV
Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number or ID number:	UN 2924
14.2. UN proper shipping name:	FLAMMABLE LIQUID, CORROSIVE, N.O.S. (ethanol, Hydrochloric acid)
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3+8
Classification code:	FC
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	338
Tunnel restriction code:	D/E

Inland waterways transport (ADN)

14.1. UN number or ID number:	UN 2924
14.2. UN proper shipping name:	FLAMMABLE LIQUID, CORROSIVE, N.O.S. (ethanol, Hydrochloric acid)
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3+8
Classification code:	FC
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2

Marine transport (IMDG)

14.1. UN number or ID number:	UN 2924
14.2. UN proper shipping name:	FLAMMABLE LIQUID, CORROSIVE, N.O.S. (ethanol, Hydrochloric acid)
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3+8
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2
EmS:	F-E, S-C

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:	UN 2924
14.2. UN proper shipping name:	FLAMMABLE LIQUID, CORROSIVE, N.O.S. (ethanol, Hydrochloric acid)
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3+8
Special Provisions:	A3
Limited quantity Passenger:	0.5 L
Passenger LQ:	Y340

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Etching solution Vilella

Revision: 18.02.2026

Product code: AC15.03890

Page 13 of 14

Excepted quantity:	E2	
IATA-packing instructions - Passenger:		352
IATA-max. quantity - Passenger:		1 L
IATA-packing instructions - Cargo:		363
IATA-max. quantity - Cargo:		5 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: Combustible liquid.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Information according to Directive 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

Additional information

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

SECTION 16: Other information**Abbreviations and acronyms**

Expl. 1.1: Explosives, division 1.1

Met. Corr. 1: Corrosive to metals, hazard category 1

Flam. Liq. 2: Flammable liquids, hazard category 2

Acute Tox. 3: Acute toxicity, hazard category 3

Skin Corr. 1B: Skin corrosion, sub-category 1B

Eye Dam. 1: Serious eye damage, hazard category 1

Eye Irrit. 2: Eye irritation, hazard category 2

STOT SE 3: Specific target organ toxicity - single exposure, hazard category 3

ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Etching solution Vilella

Revision: 18.02.2026

Product code: AC15.03890

Page 14 of 14

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Met. Corr. 1; H290	On basis of test data
Eye Irrit. 2; H319	Calculation method

Relevant H and EUH statements (number and full text)

H201	Explosive; mass explosion hazard.
H225	Highly flammable liquid and vapour.
H290	May be corrosive to metals.
H301	Toxic if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

Provide appropriate information, instructions and training to users

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)