

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Ethylenediamine 20%

Revision: 19.09.2025

Product code: AC15.04175

Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Ethylenediamine 20%

UFI: UKQ2-S3DJ-400N-5VF6

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Reagents and laboratory chemicals
Only for laboratory and analysis purposes.

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Details of the supplier of the safety data sheet

Company name: AnalytiChem Services, Unipessoal, Lda
Street: Rua de Júlio Dinis 676 7º
Place: P-4050-320 Porto
Telephone: +351 226002917
E-mail: info@analytichem.com
Contact person: SDS service department
E-mail: SDS@analytichem.com
Internet: www.analytichem.com
Responsible Department: SDS service department

Supplier or manufacturer details

Company name: AnalytiChem GmbH
Street: Stempelstraße 6
Place: D-47167 Duisburg
Telephone: 0203/5194-0
E-mail: info@analytichem.de
Contact person: SDS service department
E-mail: SDS@analytichem.com
Internet: www.analytichem.de
Responsible Department: AnalytiChem:
EU-Belgium: AnalytiChem Belgium, Industriezone "De Arend" 2, 8210 Zedelgem, Belgium, +32 50 28 83 20
EU-Germany: AnalytiChem Germany, Stempelstrasse 6, 47167 Duisburg, Germany, +49 203 51 94 – 200
EU-Netherlands: AnalytiChem Netherlands, Communicatieweg 7, 3641 SG Mijdrecht, The Netherlands, +31 297 286848
UK: AnalytiChem UK, Unit 7 Launton Business Center, Murdock Road, Bicester, OX26 4XB, England, +44 1869 355 500
USA: AnalytiChem USA, 227 China Road, Winslow, Maine, 04901, United States, +1 800-244-8378
Canada: AnalytiChem Canada, 21800 Clark Graham Avenue, Baie d'Urfe, H9X 4B6, Canada, +1 514-457-0701
Australia: ORE Research & Exploration Pty Ltd, 37A Hosie Street, Bayswater North, 3153, Australia, +61 3 9729 0333
+353 1 901 4670 (CHEMTREC)

Telefax: 0203/5194-290

1.4. Emergency telephone number:

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Ethylenediamine 20%

Revision: 19.09.2025

Product code: AC15.04175

Page 2 of 13

Further Information

This product is a mixture. REACH Registration Number see section 3.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Skin Corr. 1B; H314
Eye Dam. 1; H318
Resp. Sens. 1; H334
Skin Sens. 1; H317

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling
ethylenediamine

Signal word: Danger

Pictograms:



Hazard statements

H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P280 Wear protective gloves/protective clothing and eye protection/face protection.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER/doctor.

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixtures in aqueous solution

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Ethylenediamine 20%

Revision: 19.09.2025

Product code: AC15.04175

Page 3 of 13

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
107-15-3	ethylenediamine			20 - < 25 %
	203-468-6	612-006-00-6	01-2119480383-37	
	Flam. Liq. 3, Acute Tox. 3, Acute Tox. 4, Acute Tox. 4, Acute Tox. 4, Skin Corr. 1B, Resp. Sens. 1, Skin Sens. 1, Aquatic Chronic 3; H226 H311 H332 H312 H302 H314 H334 H317 H412			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
107-15-3	203-468-6	ethylenediamine	20 - < 25 %
	inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = 560 mg/kg; oral: LD50 = 866 mg/kg		

Further Information

No data available

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Self-protection of the first aider

After inhalation

Provide fresh air.

If breathing is irregular or stopped, administer artificial respiration.

Call a physician immediately.

After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

Call a physician immediately.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Remove contact lenses, if present and easy to do. Continue rinsing. Protect uninjured eye.

After ingestion

Rinse mouth immediately and drink plenty of water.

Do not allow a neutralisation agent to be drunk. Do NOT induce vomiting.

Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Irritant

corrosive

Dyspnoea

Risk of serious damage to eyes.

Allergic reactions

Cough

Dyspnoea

4.3. Indication of any immediate medical attention and special treatment needed

No data available

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Ethylenediamine 20%

Revision: 19.09.2025

Product code: AC15.04175

Page 4 of 13

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Foam
Carbon dioxide (CO₂)
Extinguishing powder
Water

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products
In case of fire may be liberated:
Nitrogen oxides (NO_x)
Carbon dioxide (CO₂), Carbon monoxide
In case of warming: Vapours are heavier than air, spread along floors and form explosive mixtures with air.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.
In case of fire and/or explosion do not breathe fumes.
Avoid contact with skin, eyes and clothes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.
Move undamaged containers from immediate hazard area if it can be done safely.
Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Do not breathe vapour/aerosol.

For non-emergency personnel

Provide adequate ventilation.
Use personal protection equipment.
Avoid contact with skin, eyes and clothes.
Remove persons to safety.
Emergency procedures
Consult an expert
Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up**For containment**

Cover drains.
Prevent spread over a wide area (e.g. by containment or oil barriers).
Collect in closed and suitable containers for disposal.
Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Ethylenediamine 20%

Revision: 19.09.2025

Product code: AC15.04175

Page 5 of 13

Other information

Provide adequate ventilation.
Do not breathe dust/fume/gas/mist/vapours/spray.
Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7
Personal protection equipment: see section 8
Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Read label before use. Handle and open container with care.
When using do not eat, drink, smoke, sniff. Keep container tightly closed.
Use personal protection equipment. Use extractor hood (laboratory).
Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation.

Advice on protection against fire and explosion

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs.
The choice of body protection depends on the concentration and quantity of hazardous substances. The chemical resistance of protective agents must be clarified with their suppliers.

Further information on handling

Take off immediately all contaminated clothing and wash it before reuse.
Draw up and observe skin protection programme.
Wash hands and face before breaks and after work and take a shower if necessary.
If handled uncovered, arrangements with local exhaust ventilation have to be used.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep in a cool, well-ventilated place.
Keep container tightly closed and dry.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Unsuitable container/equipment material:
Light metal

Hints on joint storage

national regulations

Further information on storage conditions

Keep cool. Protect from sunlight.

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational exposure limits**

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
107-15-3	Ethylenediamine	10	25		TWA (8 h)	

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Ethylenediamine 20%

Revision: 19.09.2025

Product code: AC15.04175

Page 6 of 13

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
107-15-3	ethylenediamine			
Worker DNEL, long-term		inhalation	systemic	25 mg/m³
Worker DNEL, long-term		dermal	systemic	3,6 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	12,5 mg/m³
Consumer DNEL, long-term		oral	systemic	0,275 mg/kg bw/day

PNEC values

CAS No	Substance	
Environmental compartment	Value	
107-15-3	ethylenediamine	
Freshwater	0,016 mg/l	
Freshwater (intermittent releases)	0,167 mg/l	
Marine water	0,002 mg/l	
Freshwater sediment	7,68 mg/kg	
Marine sediment	0,768 mg/kg	
Secondary poisoning	4,9 mg/kg	
Micro-organisms in sewage treatment plants (STP)	0,5 mg/l	
Soil	4,36 mg/kg	

8.2. Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment

Eye/face protection

goggles

Face protection umbrella

Hand protection

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact

Trade name/designation KCL 897 Butoject®

Recommended material: Butyl caoutchouc (butyl rubber) 0,3 mm

Wearing time with permanent contact > 480 min

By short-term hand contact

Trade name/designation KCL 720 Camapren®

Recommended material: CR (polychloroprene, chloroprene rubber) 0,65 mm

Wearing time with occasional contact (splashes): > 110 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet (>, <) supplied by us and for the designated use. When dissolving in or mixing with other substances and

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Ethylenediamine 20%

Revision: 19.09.2025

Product code: AC15.04175

Page 7 of 13

under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Take off immediately all contaminated clothing and wash it before reuse.
Wash hands and face before breaks and after work and take a shower if necessary.
Draw up and observe skin protection programme.

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.
The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Thermal hazards

No data available

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid	
Colour:	colourless	
Odour:	like: Amines	
Odour threshold:	No data available	
Melting point/freezing point:		No data available
Boiling point or initial boiling point and boiling range:		No data available
Flammability:		No data available
Lower explosion limits:		No data available
Upper explosion limits:		No data available
Flash point:		No data available
Auto-ignition temperature:		No data available
Decomposition temperature:		No data available
pH-Value:		8-10
Viscosity / kinematic:		No data available
Water solubility:		Soluble in: Water
Solubility in other solvents		
No data available		
Dissolution rate:		No data available
Partition coefficient n-octanol/water:		No data available
Dispersion stability:		No data available
Vapour pressure:		No data available
Vapour pressure:		No data available
Density:		No data available
Relative density:		No data available
Bulk density:		No data available
Relative vapour density:		No data available
Particle characteristics:		No data available

9.2. Other information**Information with regard to physical hazard classes****Explosive properties**

In case of warming: Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Sustained combustibility: No data available

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Ethylenediamine 20%

Revision: 19.09.2025

Product code: AC15.04175

Page 8 of 13

Self-ignition temperature

Solid:

No data available

Gas:

No data available

Oxidizing properties

No data available

Other safety characteristics

Evaporation rate:

No data available

Solvent separation test:

No data available

Solvent content:

No data available

Solid content:

No data available

Sublimation point:

No data available

Softening point:

No data available

Pour point:

No data available

Viscosity / dynamic:

No data available

Flow time:

No data available

Further Information

No data available

SECTION 10: Stability and reactivity**10.1. Reactivity**

In case of warming: Vapours are heavier than air, spread along floors and form explosive mixtures with air.

10.2. Chemical stability

Protect against: Air

10.3. Possibility of hazardous reactions

Acid halides

Acrolein

Acid chlorides, inorganic

Alcohols

aldehydes

Acetic acid

Acetic anhydride

Oxidising agent

Acids

Nitric acid

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

Aluminium

Lead

Zinc

copper

Copper alloys

Iron.

Brass

bronze

10.6. Hazardous decomposition products

SECTION 5: Firefighting measures

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Ethylenediamine 20%

Revision: 19.09.2025

Product code: AC15.04175

Page 9 of 13

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects).

Pulmonary oedema

Mucous membrane irritation in the mouth, throat, esophagus and gastrointestinal tract.

Inhalation effect: Damage to the respiratory tract.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 50 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
107-15-3	ethylenediamine				
	oral	LD50 866 mg/kg	Rat	Study report (1979)	OECD Guideline 401
	dermal	LD50 560 mg/kg	Rabbit	Study report (1948)	Concentrated and 10% water solution was
	inhalation vapour	ATE 11 mg/l			
	inhalation dust/mist	ATE 1,5 mg/l			

Irritation and corrosivity

Skin corrosion/irritation: Causes severe skin burns and eye damage.

Serious eye damage/eye irritation: Causes serious eye damage.

Sensitising effects

May cause allergy or asthma symptoms or breathing difficulties if inhaled. (ethylenediamine)

May cause an allergic skin reaction. (ethylenediamine)

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

No data available

Specific effects in experiment on an animal

No data available

Additional information on tests

No data available

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Ethylenediamine 20%

Revision: 19.09.2025

Product code: AC15.04175

Page 10 of 13

Practical experience

No data available

11.2. Information on other hazards**Endocrine disrupting properties**

No data available

Other information

Causes damage to organs.

Organs affected:

Liver and kidney damage

Further information

Irritant

corrosive

Dyspnoea

Risk of serious damage to eyes.

Pulmonary oedema

Gastrointestinal complaints

Vomiting

SECTION 12: Ecological information**12.1. Toxicity**

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
107-15-3	ethylenediamine					
	Acute fish toxicity	LC50 640 mg/l	96 h	Poecilia reticulata	Study report (1989)	EU Method C.1
	Acute algae toxicity	ErC50 71 mg/l	72 h	Pseudokirchneriella subcapitata	Study report (1990)	EU Method C.3
	Acute crustacea toxicity	EC50 16,7 mg/l	48 h	Daphnia magna	Study report (1989)	EU Method C.2
	Fish toxicity	NOEC > 10 mg/l	28 d	Gasterosteus aculeatus	Study report (1992)	OECD Guideline 210
	Crustacea toxicity	NOEC 0,16 mg/l	21 d	Daphnia magna	Wat. Res. Vol 23, No. 4, 501-510, 1989 (1)	other: Provisional Procedure: Extended t
	Acute bacteria toxicity	EC50 1600 mg/l ()	0,5 h	activated sludge of a predominantly domestic sewage	Study report (1989)	other: EC protocol as published O.J. 30

12.2. Persistence and degradability

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
107-15-3	ethylenediamine	-1,62

12.4. Mobility in soil

There are no data available on the mixture itself.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Ethylenediamine 20%

Revision: 19.09.2025

Product code: AC15.04175

Page 11 of 13

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Do not allow to enter into surface water or drains.

Further information

Avoid release to the environment.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations.

Do not empty into drains.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number or ID number:	UN 2735
14.2. UN proper shipping name:	AMINES, LIQUID, CORROSIVE, N.O.S. (ethylenediamine)
14.3. Transport hazard class(es):	8
14.4. Packing group:	II
Hazard label:	8
Classification code:	C7
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	80
Tunnel restriction code:	E

Inland waterways transport (ADN)

14.1. UN number or ID number:	UN 2735
14.2. UN proper shipping name:	AMINES, LIQUID, CORROSIVE, N.O.S. (ethylenediamine)
14.3. Transport hazard class(es):	8
14.4. Packing group:	II
Hazard label:	8
Classification code:	C7
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2

Marine transport (IMDG)

14.1. UN number or ID number:	UN 2735
14.2. UN proper shipping name:	AMINES, LIQUID, CORROSIVE, N.O.S. (ethylenediamine)
14.3. Transport hazard class(es):	8

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Ethylenediamine 20%

Revision: 19.09.2025

Product code: AC15.04175

Page 12 of 13

14.4. Packing group:

Hazard label:	II
Special Provisions:	8
Limited quantity:	274
Excepted quantity:	1 L
EmS:	E2
Segregation group:	F-A, S-B
	18 - alkalis

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:	UN 2735
14.2. UN proper shipping name:	AMINES, LIQUID, CORROSIVE, N.O.S. (ethylenediamine)
14.3. Transport hazard class(es):	8
14.4. Packing group:	II
Hazard label:	8
Special Provisions:	A3 A803
Limited quantity Passenger:	0.5 L
Passenger LQ:	Y840
Excepted quantity:	E2
IATA-packing instructions - Passenger:	851
IATA-max. quantity - Passenger:	1 L
IATA-packing instructions - Cargo:	855
IATA-max. quantity - Cargo:	30 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No dangerous good in sense of this transport regulation.

14.7. Maritime transport in bulk according to IMO instruments

No dangerous good in sense of this transport regulation.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Authorisations (REACH, annex XIV):

Substances of very high concern, SVHC (REACH, article 59):

ethylenediamine

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Directive 2004/42/EC on VOC in paints and varnishes: 20 %

Information according to Directive 2012/18/EU (SEVESO III): Not subject to 2012/18/EU (SEVESO III)

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 1,7,8,15.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Ethylenediamine 20%

Revision: 19.09.2025

Product code: AC15.04175

Page 13 of 13

Abbreviations and acronyms

Flam. Liq. 3: Flammable liquids, hazard category 3

Acute Tox. 3: Acute toxicity, hazard category 3

Skin Corr. 1B: Skin corrosion, sub-category 1B

Eye Dam. 1: Serious eye damage, hazard category 1

Resp. Sens. 1: Respiratory sensitisation, hazard category 1

Skin Sens. 1: Skin sensitisation, hazard category 1

Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard category: Chronic 3

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Skin Corr. 1B; H314	Calculation method
Eye Dam. 1; H318	Calculation method
Resp. Sens. 1; H334	Calculation method
Skin Sens. 1; H317	Calculation method

Relevant H and EUH statements (number and full text)

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H412	Harmful to aquatic life with long lasting effects.

Further Information

Provide appropriate information, instructions and training to users

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)