

Safety Data Sheet

according to 29 CFR 1910.1200(g)

Conostan Single-Element Standard, Nickel 5000 ppm (Ni)

Revision date: 09/09/2025

Product code: AC18.05879

Page 2 of 10

2. Hazard(s) identification

Classification of the chemical

29 CFR Part 1910.1200

- Carcinogenicity: Category 2
- Respiratory or skin sensitization: Skin sensitization, category 1
- Aspiration hazard: Category 1

Label elements

29 CFR Part 1910.1200

Signal word: Danger

Pictograms:



Hazard statements

- May be fatal if swallowed and enters airways
- May cause an allergic skin reaction
- Suspected of causing cancer

Precautionary statements

- Obtain special instructions before use.
- Do not handle until all safety precautions have been read and understood.
- Avoid breathing dust/fume/gas/mist/vapors/spray.
- Contaminated work clothing must not be allowed out of the workplace.
- Wear protective gloves/protective clothing/eye protection/face protection.
- If swallowed: Immediately call a poison center/doctor.
- Do NOT induce vomiting.
- Wash contaminated clothing before reuse.
- If exposed or concerned: Get medical advice/attention.
- Store locked up.
- Dispose of contents/container to an appropriate recycling or disposal facility.

Hazards not otherwise classified

No data available

3. Composition/information on ingredients

Mixtures

Relevant ingredients

CAS No	Components	Quantity
8042-47-5	White mineral oil, petroleum	99.5 %
7440-02-0	nickel	0.5 %

Further Information

No data available

4. First-aid measures

Description of first aid measures

General information

No data available

Safety Data Sheet

according to 29 CFR 1910.1200(g)

Conostan Single-Element Standard, Nickel 5000 ppm (Ni)

Revision date: 09/09/2025

Product code: AC18.05879

Page 3 of 10

After inhalation

Provide fresh air.
Call a doctor if you feel unwell.

After contact with skin

Wash immediately with: Water, Soap
Take off immediately all contaminated clothing and wash it before reuse.
In case of skin irritation, consult a physician.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water.
Remove contact lenses, if present and easy to do. Continue rinsing.
In case of eye irritation consult an ophthalmologist.

After ingestion

Rinse mouth.
Do NOT induce vomiting.
Observe risk of aspiration if vomiting occurs.
Call a physician immediately.

Most important symptoms and effects, both acute and delayed

Gastrointestinal complaints
Pneumonia
Vapors may cause drowsiness and dizziness.
Dizziness

Indication of any immediate medical attention and special treatment needed

Aspiration hazard

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media

Foam
Carbon dioxide (CO₂)
Extinguishing powder
Water

Unsuitable extinguishing media

No data available

Specific hazards arising from the chemical

Combustible liquids
Hazardous combustion products
In case of fire may be liberated:
Carbon dioxide (CO₂)

Special protective equipment and precautions for fire-fighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.
Use water spray jet to protect personnel and to cool endangered containers.
Move undamaged containers from immediate hazard area if it can be done safely.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

General advice

In case of warming:

Safety Data Sheet

according to 29 CFR 1910.1200(g)

Conostan Single-Element Standard, Nickel 5000 ppm (Ni)

Revision date: 09/09/2025

Product code: AC18.05879

Page 4 of 10

Vapors are heavier than air, spread along floors and form explosive mixtures with air.

Take precautionary measures against static discharges.

For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

For emergency responders

Precautionary statements For emergency responders : Personal protection equipment (PPE): see section 8

Environmental precautions

Do not allow to enter into surface water or drains.

Methods and material for containment and cleaning up

For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Collect in closed and suitable containers for disposal.

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wear breathing apparatus if exposed to vapors/dusts/aerosols.

Reference to other sections

Safe handling: see section 7

Personal protection equipment (PPE): see section 8

Disposal: see section 13

7. Handling and storage

Precautions for safe handling

Advice on safe handling

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Keep container tightly closed.

Use personal protection equipment. Use extractor hood (laboratory).

Do not breathe vapor or spray.

Advice on protection against fire and explosion

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Take precautionary measures against static discharges.

In case of warming:

Vapors are heavier than air, spread along floors and form explosive mixtures with air.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs.

The choice of body protection depends on the concentration and quantity of hazardous substances. The

chemical resistance of the protective agents should be clarified with their suppliers.

Further information on handling

Take off immediately all contaminated clothing and wash it before reuse.

Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary.

Conditions for safe storage, including any incompatibilities

Safety Data Sheet

according to 29 CFR 1910.1200(g)

Conostan Single-Element Standard, Nickel 5000 ppm (Ni)

Revision date: 09/09/2025

Product code: AC18.05879

Page 5 of 10

Requirements for storage rooms and vessels

Keep container tightly closed.

Hints on joint storage

National regulations

Further information on storage conditions

Keep cool. Protect from sunlight.

8. Exposure controls/personal protection
Control parameters
Exposure limits

CAS No	Substance	ppm	mg/m ³	Category	Origin
-	Mineral oil, excluding metal working fluids (inhalable fraction); Pure, highly and severely refined		5	TWA (8 h)	ACGIH-2025
7440-02-0	Nickel elemental (inhalable fraction)		1.5	TWA (8 h)	ACGIH-2025
7440-02-0	Nickel metal and other compounds (as Ni)	0.015	-	TWA (8 h)	REL
7440-02-0	Nickel, metal and insoluble compounds (as Ni)	-	1	TWA (8 h)	PEL
7440-02-0	Nickel, soluble compounds (as Ni)	-	1	TWA (8 h)	PEL

Biological Exposure Indices (BEI-ACGIH)

CAS No	Substance	Determinant	Value	Test material	Sampling time
7440-02-0	NICKEL	Nickel	5 µg/L	urine	Post-shift at end of workweek

Additional advice on limit values

Observe in addition any national regulations!

Exposure controls
Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment
Eye/face protection

goggles

Face protection umbrella

Hand protection

Tested protective gloves must be worn

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Take off immediately all contaminated clothing and wash it before reuse.

Wash hands and face before breaks and after work and take a shower if necessary.

Draw up and observe skin protection programme.

Safety Data Sheet

according to 29 CFR 1910.1200(g)

Conostan Single-Element Standard, Nickel 5000 ppm (Ni)

Revision date: 09/09/2025

Product code: AC18.05879

Page 6 of 10

Respiratory protection

Respiratory protection necessary at: aerosol or mist formation

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented. A respiratory protection program that meets OSHA's 29 CFR 1910.134 requirements must be followed whenever workplace conditions warrant a respirator's use.

Thermal hazards

No data available

Environmental exposure controls

Do not allow to enter into surface water or drains.

9. Physical and chemical properties

Information on basic physical and chemical properties

Physical state:	Liquid
Color:	clear, colorless
Odor:	like: Hydrocarbons
Odour threshold:	No data available
Melting point/freezing point:	No data available
Boiling point or initial boiling point and boiling range:	218-800 (424.4-1472°F) °C
Flammability:	No data available
Lower explosion limits:	No data available
Upper explosion limits:	No data available
Flash point:	No data available
Auto-ignition temperature:	No data available
Decomposition temperature:	No data available
pH-Value:	No data available
Viscosity / kinematic:	No data available
Water solubility:	No data available
Solubility in other solvents	No data available
No data available	
Dissolution rate:	No data available
Partition coefficient n-octanol/water:	No data available
Dispersion stability:	No data available
Vapor pressure:	No data available
Vapor pressure:	No data available
Density:	No data available
Relative density:	No data available
Bulk density:	No data available
Relative vapour density:	No data available
Particle characteristics:	No data available

Other information

Information with regard to physical hazard classes

Explosive properties

In case of warming:

Vapors are heavier than air, spread along floors and form explosive mixtures with air.

Self-ignition temperature

Solid:

No data available

Gas:

No data available

Safety Data Sheet

according to 29 CFR 1910.1200(g)

Conostan Single-Element Standard, Nickel 5000 ppm (Ni)

Revision date: 09/09/2025

Product code: AC18.05879

Page 7 of 10

Oxidizing properties
No data available

Other safety characteristics

Evaporation rate:	No data available
Solvent separation test:	No data available
Solvent content:	No data available
Solid content:	No data available
Sublimation point:	No data available
Softening point:	No data available
Pour point:	No data available
	No data available
Viscosity / dynamic:	No data available
Flow time:	No data available

Further Information

No data available

10. Stability and reactivity

Reactivity

In case of warming:
Vapours may form explosive mixtures with air.

Chemical stability

The product is stable under storage at normal ambient temperatures.

Possibility of hazardous reactions

Oxidising agent

Conditions to avoid

Heat
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Incompatible materials

No data available

Hazardous decomposition products

in case of fire, see:
SECTION 5: Fire fighting measures

Further information

No data available

11. Toxicological information

Route(s) of Entry

No data available

Information on toxicological effects

Toxicokinetics, metabolism and distribution

No data available

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

Safety Data Sheet

according to 29 CFR 1910.1200(g)

Conostan Single-Element Standard, Nickel 5000 ppm (Ni)

Revision date: 09/09/2025

Product code: AC18.05879

Page 8 of 10

CAS No	Components				
	Exposure route	Dose	Species	Source	Method
8042-47-5	White mineral oil, petroleum				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1987)	OECD Guideline 401
	dermal	LD50 > 2000 mg/kg	Rabbit	Study report (1987)	OECD Guideline 402

Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitizing effects

May cause an allergic skin reaction (nickel)

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of causing cancer (nickel)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

Specific target organ toxicity (STOT) - single exposure

Based on available data, the classification criteria are not met.

Specific target organ toxicity (STOT) - repeated exposure

Based on available data, the classification criteria are not met.

Carcinogenicity (OSHA): No ingredient of this mixture is listed.

Carcinogenicity (IARC): Metallic Nickel (CAS 7440-02-0) is listed in group 2B.

Carcinogenicity (NTP): Metallic Nickel (CAS 7440-02-0) is listed in group RAHC.

Aspiration hazard

May be fatal if swallowed and enters airways

Specific effects in experiment on an animal

No data available

Additional information on tests

No data available

Practical experience

No data available

Information on other hazards
Endocrine disrupting properties

No data available

Other information

No data available

Further information

Gastrointestinal complaints

Pneumonia

Vapors may cause drowsiness and dizziness.

Dizziness

12. Ecological information
Persistence and degradability

No data available

Bioaccumulative potential

No data available

Safety Data Sheet

according to 29 CFR 1910.1200(g)

Conostan Single-Element Standard, Nickel 5000 ppm (Ni)

Revision date: 09/09/2025

Product code: AC18.05879

Page 9 of 10

Mobility in soil

No data available

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

Other adverse effects

Do not allow to enter into surface water or drains.

Further information

Avoid release to the environment.

13. Disposal considerations

Waste treatment methods

Disposal recommendations

Send to a physico-chemical treatment facility under observation of official regulations .

Do not allow to enter into surface water or drains.

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

14. Transport information

U.S. DOT 49 CFR 172.101

Proper shipping name:

No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

UN number or ID number:

No dangerous good in sense of this transport regulation.

UN proper shipping name:

No dangerous good in sense of this transport regulation.

Transport hazard class(es):

No dangerous good in sense of this transport regulation.

Packing group:

No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

UN number or ID number:

No dangerous good in sense of this transport regulation.

UN proper shipping name:

No dangerous good in sense of this transport regulation.

Transport hazard class(es):

No dangerous good in sense of this transport regulation.

Packing group:

No dangerous good in sense of this transport regulation.

Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

Special precautions for user

No dangerous good in sense of this transport regulation.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No dangerous good in sense of this transport regulation.

15. Regulatory information

U.S. Regulations

National regulatory information

SARA Section 304 CERCLA:

Nickel (7440-02-0): Reportable quantity = 100 (45.4) lbs. (kg)

SARA Section 311/312 Hazards:

Nickel (7440-02-0): Fire hazard, Delayed (chronic) health hazard, Immediate (acute) health hazard

SARA Section 313 Toxic release inventory:

Nickel (7440-02-0): De minimis limit = 0.1 %, Reportable threshold = Standard

Safety Data Sheet

according to 29 CFR 1910.1200(g)

Conostan Single-Element Standard, Nickel 5000 ppm (Ni)

Revision date: 09/09/2025

Product code: AC18.05879

Page 10 of 10

Clean Air Act Section 112(b):
Nickel (7440-02-0)

State Regulations**Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65, State of California)**

WARNING: This product can expose you to chemicals including Nickel (Metallic) (cancer), which are known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

16. Other information

Revision date: 09/09/2025

Revision No: 1,01

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)