

Safety Data Sheet

according to Regulation (EC) No 1907/2006

CONOSTAN FTIR BR 1.0 Test Standard (150-702-001)

Revision: 15.01.2026

Product code: AC18.06094

Page 2 of 12

Further Information

No data available

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

- Acute Tox. 4; H302
- Skin Corr. 1; H314
- Eye Dam. 1; H318
- STOT RE 1; H372
- Asp. Tox. 1; H304
- Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

2.2. Label elements


Regulation (EC) No 1272/2008

Hazard components for labelling

- Sulfonate Mixture
- White mineral oil, petroleum

Signal word: Danger

Pictograms:



Hazard statements

- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H314 Causes severe skin burns and eye damage.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

- P260 Do not breathe dust/fume/gas/mist/vapours/spray.
- P280 Wear protective gloves/protective clothing and eye protection/face protection.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P310 Immediately call a POISON CENTER/doctor.

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Safety Data Sheet

according to Regulation (EC) No 1907/2006

CONOSTAN FTIR BR 1.0 Test Standard (150-702-001)

Revision: 15.01.2026

Product code: AC18.06094

Page 3 of 12

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
-	Sulfonate Mixture			65 - < 70 %
	Acute Tox. 4, Skin Corr. 1, Eye Dam. 1, STOT RE 1, Asp. Tox. 1, Aquatic Chronic 2; H302 H314 H318 H372 H304 H411			
8042-47-5	White mineral oil, petroleum			30 - < 35 %
	232-455-8			
	Asp. Tox. 1; H304			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
-		Sulfonate Mixture	65 - < 70 %
		oral: ATE = 500 mg/kg	
8042-47-5	232-455-8	White mineral oil, petroleum	30 - < 35 %
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg	

Further Information

No data available

SECTION 4: First aid measures
4.1. Description of first aid measures
General information

No data available

After inhalation

Provide fresh air.
Call a doctor if you feel unwell.

After contact with skin

Wash immediately with: Water, Soap
Take off immediately all contaminated clothing and wash it before reuse.
In case of skin irritation, consult a physician.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water.
Remove contact lenses, if present and easy to do. Continue rinsing.
In case of eye irritation consult an ophthalmologist.

After ingestion

Observe risk of aspiration if vomiting occurs.
Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Gastrointestinal complaints
Pneumonia
Vapours may cause drowsiness and dizziness.
Dizziness
Depression of central nervous system
Headache

4.3. Indication of any immediate medical attention and special treatment needed

Safety Data Sheet

according to Regulation (EC) No 1907/2006

CONOSTAN FTIR BR 1.0 Test Standard (150-702-001)

Revision: 15.01.2026

Product code: AC18.06094

Page 4 of 12

Aspiration hazard

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam
Carbon dioxide (CO₂)
Extinguishing powder
Water

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Combustible liquids
Hazardous combustion products
In case of fire may be liberated:
Carbon dioxide (CO₂)
Carbon monoxide
In case of warming:
Vapours are heavier than air, spread along floors and form explosive mixtures with air.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.
Use water spray jet to protect personnel and to cool endangered containers.
Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

In case of warming:
Vapours are heavier than air, spread along floors and form explosive mixtures with air.
Take precautionary measures against static discharges.

For non-emergency personnel

Provide adequate ventilation.
Use personal protection equipment.
Avoid contact with skin, eyes and clothes.
Remove persons to safety.
Emergency procedures
Consult an expert
Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For containment

Cover drains.
Prevent spread over a wide area (e.g. by containment or oil barriers).
Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Safety Data Sheet

according to Regulation (EC) No 1907/2006

CONOSTAN FTIR BR 1.0 Test Standard (150-702-001)

Revision: 15.01.2026

Product code: AC18.06094

Page 5 of 12

Collect in closed and suitable containers for disposal.

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Keep container tightly closed.

Use personal protection equipment.

Do not breathe vapour/aerosol.

Provide adequate ventilation.

Advice on protection against fire and explosion

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Take precautionary measures against static discharges.

In case of warming:

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs.

The choice of body protection depends on the concentration and quantity of hazardous substances. The chemical resistance of protective agents must be clarified with their suppliers.

Further information on handling

Take off immediately all contaminated clothing and wash it before reuse.

Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed.

Hints on joint storage

National regulations

Further information on storage conditions

Keep cool. Protect from sunlight.

7.3. Specific end use(s)

Laboratory chemicals

Only for laboratory and analysis purposes.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Safety Data Sheet

according to Regulation (EC) No 1907/2006

CONOSTAN FTIR BR 1.0 Test Standard (150-702-001)

Revision: 15.01.2026

Product code: AC18.06094

Page 6 of 12

DNEL/DMEL values

CAS No	Substance			
DNEL type	Exposure route	Effect	Value	
8042-47-5	White mineral oil, petroleum			
Worker DNEL, long-term	inhalation	systemic	160 mg/m ³	
Worker DNEL, long-term	dermal	systemic	220 mg/kg bw/day	
Consumer DNEL, long-term	inhalation	systemic	35 mg/m ³	
Consumer DNEL, long-term	dermal	systemic	93 mg/kg bw/day	
Consumer DNEL, long-term	oral	systemic	40 mg/kg bw/day	

Additional advice on limit values

Observe in addition any national regulations!

8.2. Exposure controls
Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment
Eye/face protection

goggles

Face protection umbrella

Hand protection

Tested protective gloves must be worn

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Take off immediately all contaminated clothing and wash it before reuse.

Wash hands and face before breaks and after work and take a shower if necessary.

Draw up and observe skin protection programme.

Respiratory protection

Respiratory protection necessary at: aerosol or mist formation

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Thermal hazards

No data available

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties
9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	No data available
Odour:	No data available
Odour threshold:	No data available
Melting point/freezing point:	No data available

Safety Data Sheet

according to Regulation (EC) No 1907/2006

CONOSTAN FTIR BR 1.0 Test Standard (150-702-001)

Revision: 15.01.2026

Product code: AC18.06094

Page 7 of 12

Boiling point or initial boiling point and boiling range:	No data available
Flammability:	No data available
Lower explosion limits:	No data available
Upper explosion limits:	No data available
Flash point:	No data available
Auto-ignition temperature:	No data available
Decomposition temperature:	No data available
pH-Value:	No data available
Viscosity / kinematic:	No data available
Water solubility:	No data available
Solubility in other solvents	
No data available	
Dissolution rate:	No data available
Partition coefficient n-octanol/water:	No data available
Dispersion stability:	No data available
Vapour pressure:	No data available
Vapour pressure:	No data available
Density:	No data available
Relative density:	No data available
Bulk density:	No data available
Relative vapour density:	No data available
Particle characteristics:	No data available

9.2. Other information
Information with regard to physical hazard classes
Explosive properties

In case of warming:

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Sustained combustibility:

No data available

Self-ignition temperature

Solid:

No data available

Gas:

No data available

Oxidizing properties

No data available

Other safety characteristics

Evaporation rate:

No data available

Solvent separation test:

No data available

Solvent content:

No data available

Solid content:

No data available

Sublimation point:

No data available

Softening point:

No data available

Pour point:

No data available

No data available

Viscosity / dynamic:

No data available

Flow time:

No data available

Further Information

No data available

SECTION 10: Stability and reactivity

Safety Data Sheet

according to Regulation (EC) No 1907/2006

CONOSTAN FTIR BR 1.0 Test Standard (150-702-001)

Revision: 15.01.2026

Product code: AC18.06094

Page 8 of 12

10.1. Reactivity

In case of warming:
Vapours may form explosive mixtures with air.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Oxidising agent

10.4. Conditions to avoid

Heat
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

No data available

10.6. Hazardous decomposition products

in case of fire, see:
SECTION 5: Firefighting measures

Further information

No data available

SECTION 11: Toxicological information
11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008
Toxicokinetics, metabolism and distribution

No data available

Acute toxicity

Harmful if swallowed.

ATEmix calculated

ATE (oral) 746,3 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
-	Sulfonate Mixture				
	oral	ATE 500 mg/kg			
8042-47-5	White mineral oil, petroleum				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1987)	OECD Guideline 401
	dermal	LD50 > 2000 mg/kg	Rabbit	Study report (1987)	OECD Guideline 402

Irritation and corrosivity

Skin corrosion/irritation: Causes severe skin burns and eye damage.
Serious eye damage/eye irritation: Causes serious eye damage.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.
Carcinogenicity: Based on available data, the classification criteria are not met.
Reproductive toxicity: Based on available data, the classification criteria are not met.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

CONOSTAN FTIR BR 1.0 Test Standard (150-702-001)

Revision: 15.01.2026

Product code: AC18.06094

Page 9 of 12

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Causes damage to organs through prolonged or repeated exposure. (Sulfonate Mixture)

Aspiration hazard

May be fatal if swallowed and enters airways.

Information on likely routes of exposure

No data available

Specific effects in experiment on an animal

No data available

Additional information on tests

No data available

Practical experience

No data available

11.2. Information on other hazards
Endocrine disrupting properties

No data available

Other information

No data available

Further information

Gastrointestinal complaints

Pneumonia

Vapours may cause drowsiness and dizziness.

Dizziness

Depression of central nervous system

Headache

SECTION 12: Ecological information
12.1. Toxicity

Toxic to aquatic life with long lasting effects.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
8042-47-5	White mineral oil, petroleum					
	Acute fish toxicity	LC50 mg/l	> 10000	96 h	Lepomis macrochirus	REACH Registration Dossier
	Acute crustacea toxicity	EC50 mg/l	> 100	48 h	Daphnia magna	Study report (2008)
						Method: other: procedure as detailed in OECD Guideline 202

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential
Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
8042-47-5	White mineral oil, petroleum	> 6

12.4. Mobility in soil

No data available

Safety Data Sheet

according to Regulation (EC) No 1907/2006

CONOSTAN FTIR BR 1.0 Test Standard (150-702-001)

Revision: 15.01.2026

Product code: AC18.06094

Page 10 of 12

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Do not allow to enter into surface water or drains.

Further information

Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Send to a physico-chemical treatment facility under observation of official regulations.

Do not allow to enter into surface water or drains.

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

<u>14.1. UN number or ID number:</u>	UN 3265
<u>14.2. UN proper shipping name:</u>	CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S.(Sulfonate Mixture)
<u>14.3. Transport hazard class(es):</u>	8
<u>14.4. Packing group:</u>	II
Hazard label:	8
Classification code:	C3
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	80
Tunnel restriction code:	E

Inland waterways transport (ADN)

<u>14.1. UN number or ID number:</u>	UN 3265
<u>14.2. UN proper shipping name:</u>	CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S.(Sulfonate Mixture)
<u>14.3. Transport hazard class(es):</u>	8
<u>14.4. Packing group:</u>	II
Hazard label:	8
Classification code:	C3
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2

Marine transport (IMDG)

<u>14.1. UN number or ID number:</u>	UN 3265
<u>14.2. UN proper shipping name:</u>	CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S.(Sulfonate Mixture)
<u>14.3. Transport hazard class(es):</u>	8
<u>14.4. Packing group:</u>	II
Hazard label:	8

Safety Data Sheet

according to Regulation (EC) No 1907/2006

CONOSTAN FTIR BR 1.0 Test Standard (150-702-001)

Revision: 15.01.2026

Product code: AC18.06094

Page 11 of 12

Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2
EmS:	F-A, S-B
Segregation group:	1 - acids

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:	UN 3265
14.2. UN proper shipping name:	CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S.(Sulfonate Mixture)
14.3. Transport hazard class(es):	8
14.4. Packing group:	II
Hazard label:	8
Special Provisions:	A3 A803
Limited quantity Passenger:	0.5 L
Passenger LQ:	Y840
Excepted quantity:	E2
IATA-packing instructions - Passenger:	851
IATA-max. quantity - Passenger:	1 L
IATA-packing instructions - Cargo:	855
IATA-max. quantity - Cargo:	30 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS:	Yes
Danger releasing substance:	Sulfonate Mixture

SECTION 15: Regulatory information
15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture
EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3

Information according to Directive 2012/18/EU (SEVESO III):	E2 Hazardous to the Aquatic Environment
---	---

Additional information

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

National regulatory information
SECTION 16: Other information
Changes

This data sheet contains changes from the previous version in section(s): 1,2,9,11,14,15.

Abbreviations and acronyms

Acute Tox. 4: Acute toxicity, hazard category 4

Asp. Tox. 1: Aspiration hazard, hazard category 1

Skin Corr. 1: Skin corrosion, hazard category 1

Eye Dam. 1: Serious eye damage, hazard category 1

STOT RE 1: Specific target organ toxicity - repeated exposure, hazard category 1

Aquatic Chronic 2: Hazardous to the aquatic environment, long-term hazard category: Chronic 2

Safety Data Sheet

according to Regulation (EC) No 1907/2006

CONOSTAN FTIR BR 1.0 Test Standard (150-702-001)

Revision: 15.01.2026

Product code: AC18.06094

Page 12 of 12

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Acute Tox. 4; H302	Calculation method
Skin Corr. 1; H314	Calculation method
Eye Dam. 1; H318	Calculation method
STOT RE 1; H372	Calculation method
Asp. Tox. 1; H304	Calculation method
Aquatic Chronic 2; H411	Calculation method

Relevant H and EUH statements (number and full text)

H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H372	Causes damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

Provide appropriate information, instructions and training to users

Identified uses

No	Short title	LCS	SU	PC	PROC	ERC	AC	TF	Specification
1	PC21	-	-	21	15	-	-	-	
2	PROC15	-	-	-	15	-	-	-	

LCS: Life cycle stages

PC: Product categories

ERC: Environmental release categories

TF: Technical functions

SU: Sectors of use

PROC: Process categories

AC: Article categories

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)